



시험 성적서

TEST REPORT

페이지(page) : (1) / (총(Total) 6)

성적서 번호 Report No.		ICRT-TR-E210867-0A	
신청자 Client	기관명 Name	TRUEN Co., Ltd.	
	주소 Address	1309, Woolim e-BIZ Center 1, 28, Digital-ro 33-gil, Guro-gu, Seoul, Republic of Korea	
시험대상품목 Sample description		Wireless Home Camera	
모델명 Type designation		TSC-221S	
정격 Ratings		DC 5.0 V (Used AC/DC adapter).	
시험장소 Place of test		<input checked="" type="checkbox"/> 고정시험(Inside test) <input type="checkbox"/> 현장시험(Field test) 주소지(Address): 112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea	
시험기간 Date of test		04. Mar. 2021 ~ 05. Mar. 2021	
시험방법/항목 Test Method/Item		FCC rule §1.1310	
시험결과 Test Results		Refer to 3. Maximum Permissible Exposure	
확인 Affirmation	작성자 Tested by	기술책임자 Technical Manager	
	성명 Name In-Jung, Kim (Signature)	성명 Name Hong-Kyu, Lee (Signature)	
<input type="checkbox"/> 위 성적서는 고객이 제공한 시료에 대한 시험결과입니다. This is certified that the above mentioned products have been tested for the sample			
<input type="checkbox"/> 위 성적서는 KS Q ISO/IEC 17025 및 한국인정기구(KOLAS)인정과 관련이 없습니다. The above test report is not related to accreditation by KS Q ISO/IEC 17025 and Korea Laboratory Accreditation scheme.			
<input type="checkbox"/> 위 성적서는 주식회사 아이씨알의 승인 없이는 일부 복제에 대해 금지됩니다. The test report is prohibited for some reproduction without the approval of the ICR.			
2021. 04. 15			
주식회사 아이씨알 대표이사 The head of INTERNATIONAL CERTIFICATION REGISTRAR			
			

본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

The authenticity of the test report can be checked on the G4B or ICR website.

경기도 김포시 양촌읍 황금3로7번길 112 / Tel: 02-6351-9001 ~ 6



Contents

- 1. Applicant & Manufacturer & Test Laboratory Information..... 3
 - 1.1 Applicant information..... 3
 - 1.2 Manufacturer Information 3
 - 1.3 Test Laboratory Information 3
- 2. Equipment under Test(EUT) Information 4
 - 2.1 General Information..... 4
 - 2.2 Additional Information 4
 - 2.3 Mode of operation during the test 4
 - 2.4 Modifications of EUT 4
 - 2.5 Reason of Additional Model Name..... 4
- 3. Maximum Permissible Exposure 5
 - 3.1 RF Exposure calculation..... 5
 - 3.2 EUT Description..... 5
 - 3.3 Result 6

Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E210867-0A	15-Apr-2021	Initial Issue	All



1. Applicant & Manufacturer & Test Laboratory Information

1.1 Applicant information

Applicant	TRUEN Co., Ltd.
Address	1309, Woolim e-BIZ Center 1, 28, Digital-ro 33-gil, Guro-gu, Seoul, Republic of Korea
Contact Person	JunHo Kang
Telephone No.	+82-70-8677-6000
Fax No.	+82-2-2108-1595
E-mail	jhkang@truen.co.kr

1.2 Manufacturer Information

Manufacturer 1	TRUEN Co., Ltd.
Address	1309, Woolim e-BIZ Center 1, 28, Digital-ro 33-gil, Guro-gu, Seoul, Republic of Korea
Manufacturer 2	FENGTAIDA
Address	4/F BLDG G,NO. 4010 BANXUEGANG ROAD, BANTIAN LOGGANG DISTRICT, SHENZHEN,CHINA

1.3 Test Laboratory Information

Conducted tests were performed at	
Laboratory	ICR Co., Ltd.
Address	112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea
Telephone No.	+82-2-6351-9002
Fax No.	+82-2-6351-9007
RRA No.	KR0165
KOLAS No.	KT652
Test Firm Registration Number	490614



2. Equipment under Test(EUT) Information

2.1 General Information

Product Name	Wireless Home Camera
Brand Name	-
Model Name	TSC-221S
Additional Model Name	TSC-221U, TSC-221V
FCC ID	2AZK3-TSC-221S
Power Supply	DC 5.0 V(Used AC/DC adapter).

2.2 Additional Information

Equipment Class	DTS-Digital Transmission System
Device Type	Stand-alone
Operating Frequency	2 412 MHz ~ 2 462 MHz
RF Output Power	16.34 dBm
Number of Channel	11
Modulation Type	802.11b: DSSS Modulation 802.11g/n(HT20): OFDM Modulation
Antenna Type	FPCB Antenna
Antenna Gain	3.51 dBi
Antenna Operating Mode	Single Antenna Equipment with only one antenna
List of Each Oscillator or Crystal Frequency	32.768 MHz

2.3 Mode of operation during the test

- The EUT is continuous transmission mode during the test with set to each of the Low Channel, Middle Channel, and High Channel at the worst case data rate. The worst case data rate for each modulation is determined 1 Mbps for IEEE 802.11b, 6 Mbps for IEEE 802.11g, 6.5 Mbps for HT20.

2.4 Modifications of EUT

- None

2.5 Reason of Additional Model Name

NO	Family model name	Differential point
1	TSC-221U	Basic model and electric performance, structure and circuit are the same, but simple derivative model name is added according to buyer request
2	TSC-221V	



3. Maximum Permissible Exposure

3.1 RF Exposure calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500 \text{ mW/cm}^2$ for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm^2 for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm^2 exposure is calculated as follows:

$$E = \sqrt{(30 * P * G)} / d, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm^2 , Z = Impedance of free space, 377Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using $P (\text{mW}) = P (\text{W}) / 1 000$, $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm^2

3.2 EUT Description

Kind of EUT	Wireless Home Camera
Operating Frequency Band	<ul style="list-style-type: none"> ■ WLAN(802.11b/g/n(HT20)): 2 412 MHz ~ 2 462 MHz □ WLAN(802.11n(HT40)): 2 422 MHz ~ 2 452 MHz □ WLAN: 5 180 MHz ~ 5 320 MHz / 5 500 MHz ~ 5 700 MHz □ WLAN: 5 745 MHz ~ 5 825 MHz □ Bluetooth: 2 402 MHz ~ 2 480 MHz
Max. Output Power	16.34 dBm
Exposure Evaluation Applied	<ul style="list-style-type: none"> ■ MPE □ SAR □ N/A



3.3 Result

According to above equation, the following result was obtained.

Operating Mode	Target Power W / tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(mW)	Log	Linear			
802.11b	16.34 ± 1.0	17.34	54.20	1	1.26	2.35	0.014	1.00
802.11g	16.19 ± 1.0	17.19	52.36			2.31	0.013	
802.11n(HT20)	16.15 ± 1.0	17.15	51.88			2.29	0.013	

According to above table, for Band(802.11b), safe distance,

$$D = 0.282 * \sqrt{(54.20 * 1.26)/1.00} = 2.35 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 54.20 * 1.26 / (4 * \pi * 20^2) = 0.014$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

- END OF REPORT.