

RF Exposure Evaluation

Client Information:

Applicant: Yuwei Technology (Dongguan) Co., Ltd.
Applicant add.: Room 301, No.15 Longjing Road, Guanjingtou, Fenggang Town, Dongguan City, Guangdong Province, China
Manufacturer: Yuwei Technology (Dongguan) Co., Ltd.
Manufacturer add.: Room 301, No.15 Longjing Road, Guanjingtou, Fenggang Town, Dongguan City, Guangdong Province, China

Product Information:

Product Name: Solar Power Bank
Model No.: T11PWX
Brand Name: N/A

FCC ID: 2AZK8-T11PWX

Applicable standards: FCC CFR 47 PART 1, § 1.1310
KDB 680106 D01 Wireless Power Transfer v04

Prepared By:

Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

Date of Receipt: May 23, 2024

Date of Test: May 23, 2024~ Jun. 03, 2024

Date of Issue: Jun. 03, 2024

Test Result: Pass

This device described above has been tested by Guangdong Asia Hongke Test Technology Limited and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Note: This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited, this document may be altered or revised by Guangdong Asia Hongke Test Technology Limited, personal only, and shall be noted in the revision of the document. This test report must not be used by the client to claim product endorsement

Leon Yi

Reviewed by: _____

Leon.yi

Sean She

Approved by: _____

Sean She



TABLE OF CONTENTS

1	TEST FACILITY	4
1.1	Deviation from standard	4
1.2	Abnormalities from standard conditions	4
1.3	Test Location	4
2	GENERAL INFORMATION	5
3	TEST METHODOLOGY	6
3.1	Measuring Standard	6
3.2	Test Setup	7
3.3	Test Procedure	7
4	Equipment Approval Considerations	8
4.1	Description of the test mode	9
4.2	Peripheral List	9
4.3	Test Instruments list	9
4.4	Duty Cycle:	10
4.5	Compliance Location: Center vs Tip-Surface of the Probe	11
4.6	Test Result	13
5	Test Setup photo	24



Revision History

Revision	Issue Date	Revisions	Revised By
00	Jun. 03, 2024	Initial Issue	Sean She

1 TEST FACILITY

The test facility is recognized, certified or accredited by the following organizations:

FCC-Registration No.: 251906 Designation Number: CN1376

Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC —Registration No.: 31737 CAB identifier: CN0165

The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

A2LA-Lab Cert. No.: 7133.01

Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

1.1 Deviation from standard

None

1.2 Abnormalities from standard conditions

None

1.3 Test Location

Guangdong Asia Hongke Test Technology Limited

Address: B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

2 GENERAL INFORMATION

EUT Name:	Solar Power Bank
Model No:	T11PWX
Serial Model:	N/A
Test sample(s) ID:	AITSZ24052212001
Sample(s) Status:	Engineer sample
Operation frequency:	110kHz-205kHz
Modulation Technology:	ASK
Antenna Type:	loop coil Antenna
Antenna gain:	0dBi
Hardware version.:	N/A
Software version.:	N/A
Power supply:	Input: IN1/IN2:5V=3A 9V=2A 12V=1.5A OUT1:5V=3A 9V=2.22A 12V=1.67A OUT2:5V=3A OUT3:5V=3A 9V=2A 12V=1.5A 5V=4.5A 4.5V=5A OUT4:5V2.4A OUT5:5V=3A 9V=2.22A 12V=1.67A Wireless Charger:15W(Max)
Model different:	N/A
Note:	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

3 TEST METHODOLOGY

3.1 Measuring Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. According to §1.1310 and §2.1091 RF exposure is calculated. According KDB680106 D01: KDB 680106 D01 Wireless Power Transfer v04.

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
F=frequency in MHz *=Plane-wave equivalent power density RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).				

Note 1: f = frequency in MHz; *Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03

Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

3.2 Test Setup



3.3 Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (2cm increments from 0 ~ 20 cm for all sides) which is between the edge of the charger and the geometric edge of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

Remark: The EUT's test position A, B, C, D, E and F is valid for the E and H field measurements.

4 Equipment Approval Considerations

The EUT does comply with KDB 680106 D01 as follow table.

Requirements of section 5 of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operated in the frequency range 110-205KHz.
Output power from each primary coil is less than or equal to 15 watts	Yes	The maximum output power of the primary coil is 15W.
The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time	Yes	The transfer system includes 1 primary coils.
Client device is placed directly in contact with the transmitter	Yes	Client device is placed directly in contact with the transmitter
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion)	No	EUT is a portable power bank
The aggregate E-field and H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	No	H-field and E-field measurement taken every 2 cm (starting as close to 20 cm as possible) on each edge/top surface of the host/client pair were also evaluated for portable use conditions.

4.1 Description of the test mode

Equipment under test was operated during the measurement under the following conditions:

Test Mode	Description	
Mode 1	Adapter + EUT + phone+(15W MAX) full load	Pre-tested
Mode 2	Adapter + EUT + phone+(15W MAX) half load	Pre-tested
Mode 3	Adapter + EUT + phone+(15W MAX) no load	Pre-tested
Mode 4	EUT + phone+(15W MAX) full load	Record
Mode 5	EUT + phone+(15W MAX) half load	Pre-tested
Mode 6	EUT + phone+(15W MAX) no load	Pre-tested
Mode 7	Test the EUT in idle mode.	Pre-tested

Note: All test modes were pre-tested, but we only recorded the worst case in this report.

4.2 Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	phone	OSCAL	PILOT2	N/A	N/A	N/A


4.3 Test Instruments list

Test Equipment	Manufacturer	Model No.	SN.	Cal. Date (cm-dd-yy)	Cal. Due date (cm-dd-yy)
Magnetic Amplitude and Gradient Probe System	SPEAG	MAGPy-8H3D+E3D V2 & MAGPy-DAS V2	3107 & 3097	03.15.2024	03.14.2025

Parameter	Specs
PROBE DESIGN	
Diameter	60 mm
8 isotropic <i>H</i> -field sensors	concentric loops of 1 cm ² arranged at the corner of a cube of 22 mm side length
1 isotropic <i>E</i> -field sensor	orthogonal dipole/monopole (arm length: 50 mm)
Measurement center	18.5 mm from the probe tip
Temperature range	0–40 °C
Dimensions	110 × 635 × 35 mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)
<i>H</i>-FIELD SPECIFICATION	
Frequency range	3 kHz–10 MHz
Measurement range	0.1–3200 A/m, 0.12 μT–4 mT
Gradient range	0–80 T/m/T
<i>E</i>-FIELD SPECIFICATION	
Frequency range	3 kHz–10 MHz
Measurement range	0.08–2000 V/m

4.4 Duty Cycle:

Mode	ON Time(ms)	Period(ms)	Duty Cycle(%)
Operating(110kHz-205kHz)	/	/	100



4.5 Compliance Location: Center vs Tip-Surface of the Probe

The following information is from the equipment manual:




Figure 2.1: MAGPy-8H3D+E3D V2 probe, without the casing

In the MAGPy V2.0 implementation, the H -field is evaluated at the center of the probe (which is 18.5mm above the surface of its tip) and also at the surface of its tip.

In the MAGPy V2.0 implementation, the H -field is evaluated at the center of the probe (which is 18.5 mm above the surface of its tip) and also at the surface of its tip.




Figure 2.5: Extrapolation of the total H -field at the probe surface is made at each pair of sensors (i.e., bottom and top sensors) around the sensor cube

The total H -field at the tip-surface $H_{tip-surface}$ can be extrapolated using the total H -field measured at the top and bottom sensors (Figure 2.5), H_{top} and H_{bottom} , as well as the normalized H -field gradient G_n . The field extrapolation formula is a polynomial function of G_n ($\Delta d = 18.5$ mm) [7].

$$H_{tip-surface} = \frac{H_{bottom} + H_{top}}{2} \sum_{i=0}^7 c_i (G_n \Delta d)^i \quad (1.6)$$

The polynomial coefficients c_i are given in Table 2.2. They have been determined from simulations of 70 coils covering normalized gradients up to 80 for the 97.5th percentile (Figure 2.6). This provides a conservative estimate of the total H -field at the tip-surface without large overestimation.




Figure 2.6: Extrapolation factors (i.e., ratios between the simulated results of $H_{tip-surface}$ and $\frac{H_{bottom} + H_{top}}{2}$) plotted as a function of the normalized H -field gradient. The data are from simulations of 70 coils with varying outer diameters D_o and filling ratios (0.1–0.9). The prediction of the polynomial function $\sum_{i=0}^7 c_i (G_n \Delta d)^i$ with coefficients fitted for 97.5th percentile (i.e., the red dashed line) is also shown.

Coefficient	Value
c_0	1.00
c_1	1.00
c_2	-1.01
c_3	15.9
c_4	-50.8
c_5	74.7
c_6	-51.4
c_7	13.7

Table 2.2: Coefficients of the polynomial function for the H -field extrapolation to the tip-surface of the probe, determined with 0.975 quantile regression (i.e., the 97.5th percentile)

4.6 Test Result

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
0cm	< 1%	Top	15.97	1.35
0cm	< 1%	Bottom	15.94	1.33
0cm	< 1%	Left	15.78	1.28
0cm	< 1%	Right	15.88	1.27
0cm	< 1%	Front	15.85	1.29
0cm	< 1%	Rear	15.80	1.33
Limit			614	1.63
Margin Limit (%)			2.60%	82.82%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
0cm	< 50%	Top	15.95	1.28
0cm	< 50%	Bottom	15.90	1.31
0cm	< 50%	Left	15.72	1.18
0cm	< 50%	Right	15.81	1.27
0cm	< 50%	Front	15.80	1.20
0cm	< 50%	Rear	15.76	1.25
Limit			614	1.63
Margin Limit (%)			2.60%	80.37%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
0cm	< 99%	Top	15.93	1.25
0cm	< 99%	Bottom	15.81	1.27
0cm	< 99%	Left	15.71	1.16
0cm	< 99%	Right	15.74	1.17
0cm	< 99%	Front	15.80	1.16
0cm	< 99%	Rear	15.67	1.19
Limit			614	1.63
Margin Limit (%)			2.59%	77.91%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
2cm	< 1%	Top	14.43	1.26
2cm	< 1%	Bottom	14.52	1.26
2cm	< 1%	Left	14.32	1.24
2cm	< 1%	Right	14.40	1.17
2cm	< 1%	Front	14.37	1.22
2cm	< 1%	Rear	14.38	1.25
Limit			614	1.63
Margin Limit (%)			2.36%	77.30%

614

1.63

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
2cm	< 50%	Top	14.41	1.23
2cm	< 50%	Bottom	14.48	1.20
2cm	< 50%	Left	14.25	1.20
2cm	< 50%	Right	14.30	1.11
2cm	< 50%	Front	14.33	1.21
2cm	< 50%	Rear	14.30	1.18
Limit			614	1.63
Margin Limit (%)			2.36%	75.46%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
2cm	< 99%	Top	14.31	1.16
2cm	< 99%	Bottom	14.40	1.16
2cm	< 99%	Left	14.20	1.16
2cm	< 99%	Right	14.25	1.04
2cm	< 99%	Front	14.30	1.11
2cm	< 99%	Rear	14.27	1.18
Limit			614	1.63
Margin Limit (%)			2.35%	72.39%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
4cm	< 1%	Top	13.86	1.12
4cm	< 1%	Bottom	13.80	1.14
4cm	< 1%	Left	13.68	1.09
4cm	< 1%	Right	13.77	1.10
4cm	< 1%	Front	13.70	1.07
4cm	< 1%	Rear	13.80	1.02
Limit			614	1.63
Margin Limit (%)			2.26%	69.94%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
4cm	< 50%	Top	13.79	1.04
4cm	< 50%	Bottom	13.71	1.11
4cm	< 50%	Left	13.64	1.04
4cm	< 50%	Right	13.73	1.01
4cm	< 50%	Front	13.66	1.06
4cm	< 50%	Rear	13.74	0.99
Limit			614	1.63
Margin Limit (%)			2.25%	68.10%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
4cm	< 99%	Top	13.73	1.03
4cm	< 99%	Bottom	13.65	1.09
4cm	< 99%	Left	13.55	0.99
4cm	< 99%	Right	13.66	0.95
4cm	< 99%	Front	13.65	1.03
4cm	< 99%	Rear	13.65	0.92
Limit			614	1.63
Margin Limit (%)			2.24%	66.87%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
6cm	< 1%	Top	13.17	0.95
6cm	< 1%	Bottom	13.14	0.88
6cm	< 1%	Left	13.05	0.90
6cm	< 1%	Right	12.99	0.90
6cm	< 1%	Front	13.03	0.88
6cm	< 1%	Rear	13.07	0.91
Limit			614	1.63
Margin Limit (%)			2.14%	58.28%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
6cm	< 50%	Top	13.12	0.88
6cm	< 50%	Bottom	13.12	0.88
6cm	< 50%	Left	13.03	0.83
6cm	< 50%	Right	12.96	0.83
6cm	< 50%	Front	12.94	0.81
6cm	< 50%	Rear	12.97	0.90
Limit			614	1.63
Margin Limit (%)			2.14%	55.21%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
6cm	< 99%	Top	13.06	0.82
6cm	< 99%	Bottom	13.10	0.78
6cm	< 99%	Left	12.98	0.80
6cm	< 99%	Right	12.89	0.82
6cm	< 99%	Front	12.94	0.74
6cm	< 99%	Rear	12.92	0.89
Limit			614	1.63
Margin Limit (%)			2.13%	54.60%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
8cm	< 1%	Top	12.59	0.88
8cm	< 1%	Bottom	12.46	0.88
8cm	< 1%	Left	12.51	0.89
8cm	< 1%	Right	12.54	0.85
8cm	< 1%	Front	12.50	0.78
8cm	< 1%	Rear	12.37	0.78
Limit			614	1.63
Margin Limit (%)			2.05%	54.60%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
8cm	< 50%	Top	12.55	0.80
8cm	< 50%	Bottom	12.44	0.80
8cm	< 50%	Left	12.46	0.79
8cm	< 50%	Right	12.46	0.85
8cm	< 50%	Front	12.40	0.71
8cm	< 50%	Rear	12.36	0.77
Limit			614	1.63
Margin Limit (%)			2.04%	52.15%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
8cm	< 99%	Top	12.47	0.71
8cm	< 99%	Bottom	12.40	0.70
8cm	< 99%	Left	12.39	0.71
8cm	< 99%	Right	12.37	0.75
8cm	< 99%	Front	12.33	0.62
8cm	< 99%	Rear	12.32	0.70
Limit			614	1.63
Margin Limit (%)			2.03%	46.01%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
10cm	< 1%	Top	11.84	0.72
10cm	< 1%	Bottom	11.86	0.78
10cm	< 1%	Left	11.83	0.68
10cm	< 1%	Right	11.78	0.72
10cm	< 1%	Front	11.78	0.65
10cm	< 1%	Rear	11.80	0.65
Limit			614	1.63
Margin Limit (%)			1.93%	47.85%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
10cm	< 50%	Top	11.84	0.70
10cm	< 50%	Bottom	11.81	0.70
10cm	< 50%	Left	11.75	0.60
10cm	< 50%	Right	11.71	0.63
10cm	< 50%	Front	11.74	0.60
10cm	< 50%	Rear	11.79	0.65
Limit			614	1.63
Margin Limit (%)			1.93%	42.94%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
10cm	< 99%	Top	11.75	0.69
10cm	< 99%	Bottom	11.75	0.64
10cm	< 99%	Left	11.66	0.57
10cm	< 99%	Right	11.68	0.55
10cm	< 99%	Front	11.71	0.51
10cm	< 99%	Rear	11.77	0.59
Limit			614	1.63
Margin Limit (%)			1.92%	42.33%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
12cm	< 1%	Top	11.05	0.67
12cm	< 1%	Bottom	11.07	0.71
12cm	< 1%	Left	10.94	0.66
12cm	< 1%	Right	11.02	0.65
12cm	< 1%	Front	10.94	0.67
12cm	< 1%	Rear	10.98	0.61
Limit			614	1.63
Margin Limit (%)			1.80%	43.34%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
12cm	< 50%	Top	11.01	0.66
12cm	< 50%	Bottom	11.04	0.64
12cm	< 50%	Left	10.88	0.57
12cm	< 50%	Right	10.97	0.64
12cm	< 50%	Front	10.85	0.64
12cm	< 50%	Rear	10.95	0.61
Limit			614	1.63
Margin Limit (%)			1.80%	40.77%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
12cm	< 99%	Top	10.95	0.58
12cm	< 99%	Bottom	11.01	0.64
12cm	< 99%	Left	10.84	0.53
12cm	< 99%	Right	10.95	0.57
12cm	< 99%	Front	10.77	0.61
12cm	< 99%	Rear	10.88	0.52
Limit			614	1.63
Margin Limit (%)			1.79%	39.20%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
14cm	< 1%	Top	10.66	0.59
14cm	< 1%	Bottom	10.52	0.56
14cm	< 1%	Left	10.59	0.59
14cm	< 1%	Right	10.56	0.56
14cm	< 1%	Front	10.54	0.55
14cm	< 1%	Rear	10.55	0.51
Limit			614	1.63
Margin Limit (%)			1.74%	36.20%

614

1.63

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
14cm	< 50%	Top	10.60	0.53
14cm	< 50%	Bottom	10.45	0.56
14cm	< 50%	Left	10.59	0.49
14cm	< 50%	Right	10.56	0.48
14cm	< 50%	Front	10.45	0.49
14cm	< 50%	Rear	10.46	0.48
Limit			614	1.63
Margin Limit (%)			1.73%	34.36%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
14cm	< 99%	Top	10.55	0.49
14cm	< 99%	Bottom	10.41	0.50
14cm	< 99%	Left	10.57	0.48
14cm	< 99%	Right	10.46	0.40
14cm	< 99%	Front	10.37	0.47
14cm	< 99%	Rear	10.41	0.41
Limit			614	1.63
Margin Limit (%)			1.72%	30.67%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
18cm	< 1%	Top	9.09	0.37
18cm	< 1%	Bottom	9.16	0.35
18cm	< 1%	Left	9.03	0.28
18cm	< 1%	Right	9.05	0.28
18cm	< 1%	Front	9.02	0.31
18cm	< 1%	Rear	9.00	0.28
Limit			614	1.63
Margin Limit (%)			1.49%	22.70%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
18cm	< 50%	Top	9.01	0.28
18cm	< 50%	Bottom	9.12	0.29
18cm	< 50%	Left	8.99	0.25
18cm	< 50%	Right	8.99	0.21
18cm	< 50%	Front	8.99	0.29
18cm	< 50%	Rear	8.96	0.22
Limit			614	1.63
Margin Limit (%)			1.49%	17.79%

614 1.63

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
18cm	< 99%	Top	8.92	0.27
18cm	< 99%	Bottom	9.08	0.23
18cm	< 99%	Left	8.90	0.18
18cm	< 99%	Right	8.91	0.19
18cm	< 99%	Front	8.93	0.27
18cm	< 99%	Rear	8.90	0.13
Limit			614	1.63
Margin Limit (%)			1.48%	16.56%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 1%	Top	8.11	0.24
20cm	< 1%	Bottom	8.20	0.24
20cm	< 1%	Left	7.97	0.23
20cm	< 1%	Right	7.98	0.21
20cm	< 1%	Front	7.94	0.19
20cm	< 1%	Rear	8.08	0.15
Limit			614	1.63
Margin Limit (%)			1.34%	14.72%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 50%	Top	8.10	0.22
20cm	< 50%	Bottom	8.12	0.22
20cm	< 50%	Left	7.89	0.11
20cm	< 50%	Right	7.91	0.08
20cm	< 50%	Front	7.86	0.07
20cm	< 50%	Rear	8.01	0.16
Limit			614	1.63
Margin Limit (%)			1.32%	13.50%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 99%	Top	8.08	0.11
20cm	< 99%	Bottom	8.04	0.18
20cm	< 99%	Left	7.86	0.11
20cm	< 99%	Right	7.83	0.22
20cm	< 99%	Front	7.80	0.11
20cm	< 99%	Rear	7.94	0.10
Limit			614	1.63
Margin Limit (%)			1.32%	13.50%

5 Test Setup photo

. 0cm-Botton



. 0cm-Front



0cm-Left



0cm-Rear



0cm-Right



0cm-Top



End of report