

EUT Description: Garage door smart switch

ModelNo.:SGDS-02WX,SGDS-01CKM,SC-GO-1A,SGDS-03WX,SGDS-02XL,SGDS-03XL FCC ID: 2AZKM-SGDS02WX Equipment type: fixed equipment

Page 1 of 2

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0	614	1.63	*(100)	6			
3.0–30	1842/f	4.89/f	*(900/f ²)	6			
30–300	61.4	0.163	1.0	6			
300-1500			f/300	6			
1500-100,000			5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f ²)	30			
30–300	27.5	0.073	0.2	30			
300–1500			f/1500	30			
1500-100,000			1.0	30			

Limits for Maximum Permissible Exposure (MPE)

F = frequency in MHz

Formula: $Pd = (Pout^{*}G)/(4^{*} \pi * r^{2})$

Where :

 $Pd = power density in mW/cm^2$,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

π = 3.14;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



3. Test Result of RF Exposure Evaluation

	Output power	Antenna	Power Density	Limit	Result
	(dBm/ mW)	Gain(dBi)	at R=20cm	(mW/cm ²)	
			(mW/cm²)		
802.11b	17.43/55.3350	1.0	0.01386	1.0	Pass
802.11g	20.44/110.6623	1.0	0.02773	1.0	Pass
802.11n(20MHz)	20.37/108.8930	1.0	0.02728	1.0	Pass
802.11n(40MHz)	19.33/85.7038	1.0	0.02147	1.0	Pass

Turn-up power			
Mode	Peak power range(dBm)		
WIFI	17.00-21.00		

	Output power	Antenna	Power Density	Limit	Result
WIFI	(dBm/ mW)	Gain(dBi)	at R=20cm	(mW/cm²)	
			(mW/cm²)		
	21.00/125.8925	1.0	0.03154	1.0	Pass

Conclusion: No SAR is required