



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 17159
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

Dates of Tests: June 17, 2021 ~ July 14, 2021
 Test Report S/N: LR500112107G
 Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.	2AZKWREBE-TZ42C
APPLICANT	ATEC IoT CO., LTD.

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	Electronic Shelf Label
Manufacturer	:	SUZHOU NIHONE Electronics Technology Co., LTD
Model name	:	REBE-TZ42C
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C63.10 - 2013
Frequency Range	:	Zigbee 2405 ~ 2480 MHz
Max. Output Power	:	Max 1.47 dBm - Conducted
Data of issue	:	July 15, 2021

This test report is issued under the authority of:

JaBeom.Koo

Ja-Beom Koo, Manager

The test was supervised by:

延

Jae-Huem, Yun, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB Code.: 200723-0

TAZigbee OF CONTENTS

1. GENERAL INFORMATION ----- 3

2. INFORMATION ABOUT TEST ITEM ----- 4

3. TEST REPORT ----- 5

 3.1 SUMMARY OF TESTS ----- 5

 3.2 TECHNICAL CHARACTERISTICS TEST ----- 6

 3.2.1 6 dB BANDWIDTH ----- 6

 3.2.2 PEAK OUTPUT POWER ----- 9

 3.2.3 POWER SPECTRAL DENSITY ----- 12

 3.2.4 BAND EDGE ----- 15

 3.2.5 CONDUCTED SPURIOUS EMISSIONS ----- 17

 3.2.6 RADIATED SPURIOUS EMISSIONS ----- 20

 3.2.7 AC CONDUCTED EMISSIONS ----- 32

APPENDIX

 APPENDIX TEST EQUIPMENT USED FOR TESTS ----- 33

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 17159
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2021-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2023-01-15	FCC CAB
VCCI	JAPAN	C-4948,	2023-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2023-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2023-08-15	VCCI registration
VCCI	JAPAN	G-847	2021-12-13	VCCI registration
IC	CANADA	5799A-1	2022-10-18	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

2. Information about test item

2-1 Client & Manufacturer

Client Company name : ATEC IoT CO., LTD.
 Address : 289, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13488, South Korea
 Tel / Fax : +82-10-5790-6171 / +82-31-696-1534
 Manufacturer : SUZHOU NIHONE Electronics Technology Co., LTD
 Address : No. 185, Xiaoxiang Road, Suzhou New District, Suzhou City, Jiangsu Province, P.R. China
 Tel / Fax : +82-10-5790-6171 / +82-31-696-1534

2-2 Equipment Under Test (EUT)

Model name : ATEC IoT CO., LTD.
 Serial number : Identical prototype
 Date of receipt : June 17, 2021
 EUT condition : Pre-production, not damaged
 Antenna type : FPCB Antenna (Max Gain : -5.84 dBi)
 Frequency Range : Zigbee 2405 ~ 2480 MHz
 RF output power : Max 1.47 dBm – Conducted
 Type of Modulation : Pi/4 DQPSK, 8DPSK
 Power Source : DC 3.0 V

2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz) Zigbee	2405	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	-	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	Conducted	C
15.247(b)	Transmitter Peak Output Power		C
15.247(e)	Transmitter Power Spectral Density		C
15.247(d)	Band Edge & Conducted Spurious emission		C
15.209	Transmitter emission	Radiated	C
15.207	AC Conducted Emissions	Conducted	N/A
15.203	Antenna requirement	-	C

N/A : This product is battery-enabled and excludes the test.

The above equipment was tested by LTA Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247 The test results of this report relate only to the tested sample identified in this report.

The tests were performed according to the method of measurements prescribed in KDB No.558074.

→ Antenna Requirement

A TEC IoT CO., LTD. FCC ID: 2AU8YREBE-TZ42C unit complies with the requirement of §15.203.

The antenna type is PCB Antenna

3.2 Technical Characteristics Test

3.2.1 6 dB Bandwidth

Procedure:

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

Span = 3 X RBW

VBW = 3 X RBW

Sweep = auto

Trace = max hold

Detector function = peak

Measurement Data : Complies

Zigbee Mode

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2405	1.780	Complies
2440	1.780	Complies
2480	1.708	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

6 dB Bandwidth ≥ 500 kHz

Measurement Setup






Figure 1: Measurement setup for the carrier frequency separation

Low Channel




Date: 26.MAY.2021 17:02:22

Middle Channel



Date: 26.MAY.2021 17:06:59

High Channel



Date: 26.MAY.2021 17:07:13

3.2.2 Peak Output Power Measurement

Procedure:

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth :

The spectrum analyzer is set to:

- Center frequency = the highest, middle and the lowest channels
- RBW ≥ DTS Bandwidth Span ≥ 3 X RBW
- VBW = 3 X RBW Sweep = auto
- Detector function = peak

Measurement Data : Complies

Zigbee Mode

Frequency (MHz)	Test Results	
	Measured data (dBm)	Result
2405	0.91	Complies
2440	1.04	Complies
2480	1.47	Complies

- See next pages for actual measured spectrum plots.


Minimum Standard:

Peak output power	≤ 1 W(30 dBm)
-------------------	---------------

Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

Low Zigbee




Date: 26.MAY.2021 17:13:52

Middle Zigbee



Date: 26.MAY.2021 17:14:01

High Zigbee



Date: 26.MAY.2021 17:14:09

3.2.3 Power Spectral Density

Procedure:

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

The spectrum analyzer is set to:

- RBW = 3 kHz (3 kHz ≤ RBW ≤ 100 kHz) Span ≥ 1.5 times the DTS bandwidth
- VBW = 3 X RBW Sweep = auto
- Detector function = peak Trace = max hold

Measurement Data : Complies

Zigbee Mode-Ant 1

Frequency (MHz)	Test Results	
	dBm / 3 kHz BW	Result
2405	-13.33	Complies
2440	-14.78	Complies
2480	-13.42	Complies

- See next pages for actual measured spectrum plots.


Minimum Standard:

Power Spectral Density	≤ 8 dBm @ 3 kHz BW
------------------------	--------------------

Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

Low Zigbee




Date: 26.MAY.2021 17:15:37

Middle Zigbee




Date: 26.MAY.2021 17:15:49

High Zigbee




Date: 26.MAY.2021 17:16:00

Lower edge



Date: 26.MAY.2021 17:16:34

Upper edge



Date: 26.MAY.2021 17:17:05

3.2.5 Conducted Spurious Emissions

Procedure:

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz

Sweep = auto

VBW = 100 kHz

Detector function = peak

Trace = max hold

Measurement Data: Complies


- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

Minimum Standard:	≥ 20 dBc
--------------------------	---------------

Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

Unwanted Emission – Low Channel
Frequency Range = 30 MHz ~ 26.5 GHz



Date: 26.MAY.2021 17:18:40


Unwanted Emission – Middle Channel
Frequency Range = 30 MHz ~ 26.5 GHz



Date: 26.MAY.2021 17:19:51


Unwanted Emission – High Channel

\Frequency Range = 30 MHz ~ 26.5 GHz




Date: 26.MAY.2021 17:20:04

below 1 GHz (30 MHz to 1 GHz)



above 1 GHz



Measurement Data: **Complies**


- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30MHz.
- The test results for the worst of the various operating modes are presented in accordance with 6.3.4 of ANSI C63.10.
- Checked with a red circle is the fundamental frequency.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	2400/F(kHz) (@ 30 m)
0.490 ~ 1.705	24000/F(kHz) (@ 30 m)
1.705 ~ 30	30(@ 30 m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.


Radiated Emissions – Zigbee(Low)



Date: 2021-06-28

No.	Freq MHz	Reading dB μ V	C.F dB	Result QP dB μ V/m	Limit dB μ V/m	Margin dB	Height cm	Angle deg	Polarity
1.	264.01	54.28	-16.93	37.35	46.00	8.65	100	355	horizontal
2.	312.03	52.56	-15.06	37.50	46.00	8.50	108	0	horizontal
3.	768.05	41.53	-4.87	36.66	46.00	9.34	100	115	horizontal


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



Date: 2021-06-28


No.	Freq MHz	Reading dB μ V	C.F dB	Result QP dB μ V/m	Limit dB μ V/m	Margin dB	Height cm	Angle deg	Polarity
1.	81.05	48.61	-21.09	27.52	40.00	12.48	100	99	vertical
2.	81.53	48.60	-21.24	27.36	40.00	12.64	100	114	vertical
3.	796.91	37.76	-4.29	33.47	46.00	12.53	156	0	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1792.63	48.45	-10.48	37.97	74.00	36.03	321	328	horizontal
2.	14551.13	33.61	10.23	43.84	74.00	30.16	101	107	horizontal
3.	17997.88	33.55	15.04	48.59	74.00	25.41	8	13	horizontal


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1996.63	48.77	-9.33	39.44	74.00	34.56	165	157	vertical
2.	2453.50	47.42	-7.66	39.76	74.00	34.24	360	360	vertical
3.	17985.13	34.63	14.96	49.59	74.00	24.41	360	360	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain


Date: 2021-07-05



No.	Freq MHz	RD PK dBμV	RD AV dBμV	C.F dB	Result PK dBμV	Result AV dBμV	Limit PK dBμV	Limit AV dBμV	Margin PK dB	Margin AV dB	Height cm	Angle deg	Polarity
2.	18000.00	38.08	34.31	17.07	55.15	51.38	74.00	54.00	18.85	2.62	320	314	horizontal
4.	19237.81	38.48	34.73	16.42	54.90	51.15	74.00	54.00	19.10	2.85	129	123	horizontal
6.	19270.75	38.83	33.96	16.39	55.22	50.35	74.00	54.00	18.78	3.65	66	57	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain


Date: 2021-07-05



No.	Freq MHz	RD PK dBμV	RD AV dBμV	C.F dB	Result PK dBμV	Result AV dBμV	Limit PK dBμV	Limit AV dBμV	Margin PK dB	Margin AV dB	Height cm	Angle deg	Polarity
2.	19143.25	38.87	34.57	16.45	55.32	51.02	74.00	54.00	18.68	2.98	215	221	vertical
4.	19314.31	39.18	35.81	16.34	55.52	52.15	74.00	54.00	18.48	1.85	343	348	vertical
6.	19452.44	40.47	34.27	16.16	56.63	50.43	74.00	54.00	17.37	3.57	165	172	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain


Radiated Emissions – Zigbee(Middle)



Date: 2021-06-28

No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	264.01	54.48	-16.93	37.55	46.00	8.45	100	357	horizontal
2.	312.03	52.89	-15.06	37.83	46.00	8.17	100	0	horizontal
3.	768.05	42.43	-4.87	37.56	46.00	8.44	100	113	horizontal


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



Date: 2021-06-28


No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	80.08	48.44	-20.81	27.63	40.00	12.37	100	98	vertical
2.	80.32	48.73	-20.89	27.84	40.00	12.16	100	98	vertical
3.	81.05	48.64	-21.09	27.55	40.00	12.45	100	134	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1790.50	52.00	-10.49	41.51	74.00	32.49	180	186	horizontal
2.	14578.75	34.60	10.14	44.74	74.00	29.26	134	140	horizontal
3.	17938.38	34.18	14.69	48.87	74.00	25.13	292	299	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1790.50	48.35	-10.49	37.86	74.00	36.14	160	154	vertical
2.	14464.00	33.84	10.29	44.13	74.00	29.87	360	360	vertical
3.	17957.50	34.62	14.80	49.42	74.00	24.58	360	360	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq MHz	RD PK dBμV	RD AV dBμV	C.F dB	Result PK dBμV	Result AV dBμV	Limit PK dBμV	Limit AV dBμV	Margin PK dB	Margin AV dB	Height cm	Angle deg	Polarity
2.	18793.69	38.26	34.76	16.73	54.99	51.49	74.00	54.00	19.01	2.51	213	206	horizontal
4.	19207.00	39.07	35.03	16.45	55.52	51.48	74.00	54.00	18.48	2.52	0	0	horizontal
6.	19931.63	39.53	35.09	15.61	55.14	50.70	74.00	54.00	18.86	3.30	135	126	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	RD PK dBμV	RD AV dBμV	C.F dB	Result PK dBμV	Result AV dBμV	Limit PK dBμV	Limit AV dBμV	Margin PK dB	Margin AV dB	Height cm	Angle deg	Polarity
2.	18688.50	38.00	34.58	16.85	54.85	51.43	74.00	54.00	19.15	2.57	87	94	vertical
4.	19811.56	39.20	34.81	15.70	54.90	50.51	74.00	54.00	19.10	3.49	182	189	vertical
6.	19986.88	39.97	33.96	15.49	55.46	49.45	74.00	54.00	18.54	4.55	324	329	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain


Radiated Emissions – Zigbee(High)

Date: 2021-06-28




No.	Freq MHz	Reading dB μ V	C.F dB	Result QP dB μ V/m	Limit dB μ V/m	Margin dB	Height cm	Angle deg	Polarity
1.	264.01	54.61	-16.93	37.68	46.00	8.32	100	0	horizontal
2.	312.03	52.56	-15.06	37.50	46.00	8.50	100	0	horizontal
3.	768.05	42.22	-4.87	37.35	46.00	8.65	100	113	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dB μ V	C.F dB	Result QP dB μ V/m	Limit dB μ V/m	Margin dB	Height cm	Angle deg	Polarity
1.	80.68	49.82	-20.98	28.84	40.00	11.16	100	116	vertical
2.	796.66	38.81	-4.30	34.51	46.00	11.49	161	0	vertical
3.	799.82	37.80	-4.17	33.63	46.00	12.37	161	0	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1805.38	46.81	-10.41	36.40	74.00	37.60	179	186	horizontal
2.	14459.75	33.33	10.28	43.61	74.00	30.39	22	29	horizontal
3.	17983.00	33.21	14.95	48.16	74.00	25.84	85	92	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1983.88	45.06	-9.41	35.65	74.00	38.35	181	174	vertical
2.	14540.50	33.52	10.27	43.79	74.00	30.21	0	0	vertical
3.	17638.75	32.75	12.93	45.68	74.00	28.32	360	360	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq MHz	RD PK dB μ V	RD AV dB μ V	C.F dB	Result PK dB μ V	Result AV dB μ V	Limit PK dB μ V	Limit AV dB μ V	Margin PK dB	Margin AV dB	Height cm	Angle deg	Polarity
2.	18587.56	37.95	33.98	16.90	54.85	50.88	74.00	54.00	19.15	3.12	147	140	horizontal
4.	18670.44	37.99	34.40	16.86	54.85	51.26	74.00	54.00	19.15	2.74	0	0	horizontal
6.	20059.13	39.67	34.12	15.39	55.06	49.51	74.00	54.00	18.94	4.49	164	159	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq MHz	RD PK dB μ V	RD AV dB μ V	C.F dB	Result PK dB μ V	Result AV dB μ V	Limit PK dB μ V	Limit AV dB μ V	Margin PK dB	Margin AV dB	Height cm	Angle deg	Polarity
2.	18757.56	38.31	34.55	16.78	55.09	51.33	74.00	54.00	18.91	2.67	0	0	vertical
4.	18925.44	38.74	34.63	16.58	55.32	51.21	74.00	54.00	18.68	2.79	149	156	vertical
6.	20010.25	39.75	34.70	15.44	55.19	50.14	74.00	54.00	18.81	3.86	0	0	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

3.2.7 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Minimum Standard: FCC Part 15.207(a)

Measurement Data: N/A

Class B

Frequency Range	quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

APPENDIX
TEST EQUIPMENT USED FOR TESTS

	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Next Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2021-09-06
2	■	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2022-03-16
3		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2022-03-16
4		Attenuator (3 dB)	8491A	37822	HP	1 year	2021-09-06
5		Attenuator (10 dB)	8491A	63196	HP	1 year	2021-09-06
6	■	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2021-09-06
7		RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2021-09-06
8		RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2022-03-16
9	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2022-09-06
10	■	DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2022-03-18
11		DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2022-03-18
12	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2023-03-20
13		Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2022-03-16
14		Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
15	■	DC Power Supply	6674A	3637A01657	Agilent	-	-
17	■	Power Meter	EPM-441A	GB32481702	HP	1 year	2022-03-16
18	■	Power Sensor	8481A	3318A94972	HP	1 year	2021-09-06
19		Audio Analyzer	8903B	3729A18901	HP	1 year	2021-09-06
20		Modulation Analyzer	8901B	3749A05878	HP	1 year	2021-09-06
21		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2021-09-06
22		Stop Watch	HS-3	812Q08R	CASIO	2 year	2022-03-18
23		LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2021-09-06
24		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2022-03-16
25		UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2022-03-16
26		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2022-03-16
27		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2022-03-16
28		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2022-03-16
29		Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2022-03-16
30		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2022-03-16
31	■	Active Loop Antenna	FMZB 1519	1519-031	SCHWARZBECK	2 year	2023-02-26