

# TEST REPORT

Product Name : LED LAMP  
Model Number : LED2100-QI, LED2100-QI-FLT,  
LED-QI2100-BKG-AMZ, LED2200-QI-BK  
FCC ID : 2AZLV-LED2100-QI10W

Prepared for : Goods iQ  
Address : 50 Romano Vineyard Way North Kingstown, RI 02852


Prepared by : EMTEK (DONGGUAN) CO., LTD.  
Address : -1&2F., Building 2, Zone A, Zhongda Marine Biotechnology  
Research and Development Base, No. 9, Xincheng Avenue,  
Songshanhu High-technology Industrial Development Zone,  
Dongguan, Guangdong, China

Tel : +86-0769-22807078  
Fax: +86-0769-22807079

Report Number : EDG2208310038E00702R  
Date(s) of Tests : August 31, 2022 to January 09, 2023  
Date of Issue : January 10, 2023

## TABLE OF CONTENT

Test Report Description	Page
<b>1. SUMMARY OF TEST RESULT .....</b>	<b>3</b>
<b>2. GENERAL INFORMATION.....</b>	<b>5</b>
2.1. DESCRIPTION OF DEVICE (EUT) .....	5
2.2. DESCRIPTION OF TEST FACILITY.....	5
2.3. MEASUREMENT UNCERTAINTY .....	6
<b>3. MEASURING DEVICE AND TEST EQUIPMENT .....</b>	<b>7</b>
3.1. FOR MPE MEASUREMENT .....	7
<b>4. RF EXPOSURE.....</b>	<b>8</b>
4.1. MEASURING STANDARD .....	8
4.2. REQUIMENTS .....	8
4.3. TEST CONFIGURATION .....	9
4.4. LIMITS .....	10
4.5. MEASURING RESULTS .....	11



## TEST REPORT DESCRIPTION

Applicant : Goods iQ  
Address : 50 Romano Vineyard Way North Kingstown, RI 02852  
Manufacturer : Ningbo Chinyo Lighting Appliance Co., Ltd  
Address : No. 7, Ketai Road, Wangchun Industrial Zone Haishu District, Ningbo, Zhejiang  
Province, China.  
EUT : LED LAMP  
Model Name : LED2100-QI, LED2100-QI-FLT, LED-QI2100-BKG-AMZ, LED2200-QI-BK  
Trademark : BLACK+DECKER

### Measurement Procedure Used:

FCC Part 1(1.1310) and Part 2(2.1091)  
KDB 680106 D01 RF Exposure Wireless Charging App v03

The device described above is tested by EMTEK (DONGGUAN) CO., LTD. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and EMTEK (DONGGUAN) CO., LTD. is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of EMTEK (DONGGUAN) CO., LTD.

Date of Test : August 31, 2022 to January 09, 2023

Prepared by : Warren Deng  
Warren deng /Engineer

Reviewer : Tim Dong  
Tim Dong /Supervisor

Approved & Authorized Signer : Sam Lv  
Sam Lv /Manager



## 1. SUMMARY OF TEST RESULT

EMISSION		
Description of Test Item	Standard & Limits	Results
MPE	FCC Part 1(1.1310) and Part 2(2.1091) KDB 680106 D01 RF Exposure Wireless Charging App v03	Pass
Note: N/A is an abbreviation for Not Applicable.		



## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Product:	LED LAMP
Model Number:	LED2100-QI, LED2100-QI-FLT, LED-QI2100-BKG-AMZ, LED2200-QI-BK
Sample Number:	1#
Power Supply:	DC 12V from adapter
Adapter:	Model: RSS1006-240120-W2-J-P Input: 100-240V 50/60Hz 1.4A Output: 12V 2A
Wireless specification	10W(MAX)
Modulation:	Ask
Maximum Power Rate:	70.67 dBuV/m
Frequency Range:	110 kHz~205 KHz
Antenna Type:	Integral Antenna(Induction coil)
Antenna Gain:	0 dBi
Operating Temperature	0°C ~ +50°C
Date of Received:	August 31, 2022

## 2.2. Description of Test Facility

### Site Description

EMC Lab. : Accredited by CNAS, 2020.08.27  
The certificate is valid until 2024.07.05  
The Laboratory has been assessed and proved to be in compliance with  
CNAS/CL01:2018  
The Certificate Registration Number is L3150

Accredited by FCC  
Designation Number: CN1300  
Test Firm Registration Number: 945551

Accredited by A2LA, April 05, 2021  
The Certificate Registration Number is 4321.02

Accredited by Industry Canada  
The Certificate Registration Number is CN0113

Name of Firm : EMTEK (Dongguan) Co., Ltd.  
Site Location : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology Research and  
Development Base, N.9, Xincheng Avenue, Songshanhu High-technology  
Industrial Development Zone, Dongguan, Guangdong, China

## 2.3. Measurement Uncertainty

MPE :  $\pm 2\%$

### 3. MEASURING DEVICE AND TEST EQUIPMENT

#### 3.1. For MPE Measurement

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
<input checked="" type="checkbox"/>	E-Field Probe(100kHz-3GHz)	Narda	EF0391	2304/03	July 08, 2022	1 Year
<input checked="" type="checkbox"/>	Broadband Field Meter	Narda	NBM-550	232421	July 08, 2022	1 Year
<input checked="" type="checkbox"/>	Exposure Level Tester(1Hz-400KHz)	Narda	ELT-400	C-0012	July 08, 2022	1 Year

## 4. RF EXPOSURE

### 4.1. Measuring Standard

FCC Part 1(1.1310) and Part 2(2.1091)

### 4.2. Requirments

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- o Fixed Installations: fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- o Mobile Devices: a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- o Portable Devices: a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093). The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows: Occupational/Controlled Exposure: In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks. General Population/Uncontrolled Exposure: The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.



### 4.3. Test configuration

- 1, The field strength of both E-field and H-field was measured at 15cm(the 15 cm measured from the center of the probe(s) to the edge of the device) using the equipment list above for determining compliance with the MPE requirements of FCC Part 1.1310.
- 2, The RF power density was measured at 3 different charge conditions: min load, mid load, max load.
- 3, Maximum E-field and H-field measurements were made at 20cm from the top and 15cm from the edge of EUT. Along the side of the EUT and still 15cm away from the edge of the EUT, the field probes were positioned at the location where there is maximum field strength. The maximum E-field and H-field is reported below.
- 4, This device uses a wireless charging circuit for power transfer operating at the frequency of 110 – 205kHz. Thus, the 300kHz limits were used: E-field Limit = 614 (V/m); H-field limit = 1.63 (A/m).



#### 4.4. Limits

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density



Test Mode	Description	Remark
Mode A Charging(10W)	100% Load	With resistor
	50% Load	With resistor
	10% Load	With resistor

#### 4.5. Measuring Results

*Test Mode: Mode A(100% Load)*

Electric Field Emissions		
Test Position	Measure Value (V/m)	50% Limit(V/m)
Top	7.71	307
Left	5.34	307
Right	4.92	307
Rear	5.16	307
Front	5.78	307
Bottom	4.99	307
Magnetic Field Emissions		
Test Position	Measure Value (A/m)	50% Limit(V/m)
Top	0.278	0.815
Left	0.223	0.815
Right	0.215	0.815
Rear	0.213	0.815
Front	0.217	0.815
Bottom	0.214	0.815

*Test Mode: Mode A(50% Load)*

Electric Field Emissions		
Test Position	Measure Value (V/m)	50% Limit(V/m)
Top	7.45	307
Left	5.61	307
Right	4.96	307
Rear	4.32	307
Front	4.87	307
Bottom	4.34	307
Magnetic Field Emissions		
Test Position	Measure Value (A/m)	50% Limit(V/m)
Top	0.217	0.815
Left	0.213	0.815
Right	0.211	0.815
Rear	0.209	0.815
Front	0.209	0.815
Bottom	0.207	0.815

*Test Mode: Mode A(10% Load)*

Electric Field Emissions		
Test Position	Measure Value (V/m)	50% Limit(V/m)
Top	6.97	307
Left	4.14	307
Right	4.03	307
Rear	4.01	307
Front	4.12	307
Bottom	4.04	307
Magnetic Field Emissions		
Test Position	Measure Value (A/m)	50% Limit(V/m)
Top	0.205	0.815
Left	0.202	0.815
Right	0.202	0.815
Rear	0.203	0.815
Front	0.201	0.815
Bottom	0.201	0.815

Remark: The device meets the mobile RF exposure limit at 20cm from the top and 15cm from the edge of EUT separation distance as specified in §2.1091 of the FCC Rules. The maximum leakage fields at 20cm from the top and 15cm from the edge of EUT surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

**Requirement for KDB Publication 680106 D01**

Condition Requirement	Answers
Power transfer frequency is less than 1 MHz.	The power transfer frequency is 110KHz-205KHz.
Output power from each primary coil is less than or equal to 15 watts.	The maximum output power is 10W
The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	The transfer system includes only single primary.
Client device is placed directly in contact with the transmitter.	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Mobile exposure conditions only
The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Please refer to the result of Electric Field Emissions and Magnetic Field Emissions.

\*\*\* End of Report \*\*\*

# 声明 Statement

1. 本报告无授权批准人签字及“检验报告专用章”无效;  
This report will be void without authorized signature or special seal for testing report.
2. 未经许可本报告不得部分复制;  
This report shall not be copied partly without authorization.
3. 本报告的检测结果仅对送测样品有效, 委托方对样品的代表性和资料的真实性负责;  
The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.
4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内, 仅作为客户委托、科研、教学或内部质量控制等目的使用;  
The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
5. 本检测报告以实测值进行符合性判定, 未考虑不确定度所带来的风险, 本实验室不承担相关责任, 特别约定、标准或规范中有明确规定的除外;  
The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.
6. 对本检测报告若有异议, 请于收到报告之日起 20 日内提出;  
Objections shall be raised within 20 days from the date receiving the report.