



9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d), 15.205, 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02
According to IC RSS-Gen and RSS-247

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V}/\text{m}$)	300
0.490-1.705	24000/F(KHz)	20 log ($\mu\text{V}/\text{m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	22° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

All the antenna(Antenna 1&2) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1&2, GFSK) result recorded was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
11143.53	V	54.67	36.20	74.00	54.00	-19.33	-17.80
14863.14	V	56.88	37.30	74.00	54.00	-17.12	-16.70
17971.40	V	64.23	46.80	74.00	54.00	-9.77	-7.20
12079.38	H	53.84	35.20	74.00	54.00	-20.16	-18.80
14852.40	H	55.50	36.60	74.00	54.00	-18.50	-17.40
17976.60	H	62.34	47.50	74.00	54.00	-11.66	-6.50

Test mode: GFSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
11911.23	V	53.49	35.20	74.00	54.00	-20.51	-18.80
14715.66	V	56.16	37.20	74.00	54.00	-17.84	-16.80
17976.60	V	62.85	46.50	74.00	54.00	-11.15	-7.50
11980.29	H	54.46	36.80	74.00	54.00	-19.54	-17.20
14850.26	H	55.32	37.40	74.00	54.00	-18.68	-16.60
17911.77	H	63.56	46.70	74.00	54.00	-10.44	-7.30

Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
11892.31	V	54.22	36.40	74.00	54.00	-19.78	-17.60
14713.54	V	55.36	37.20	74.00	54.00	-18.64	-16.80
17976.60	V	63.79	46.70	74.00	54.00	-10.21	-7.30
11882.00	H	53.84	35.60	74.00	54.00	-20.16	-18.40
14601.27	H	55.18	36.40	74.00	54.00	-18.82	-17.60
17945.45	H	63.32	47.20	74.00	54.00	-10.68	-6.80

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All the antenna(Antenna 1&2) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK, Hopping) mode have been tested, and the worst(Antenna 1&2, GFSK, Hopping) result recorded was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2387.540	H	49.26	74.00	31.40	54.00
2388.388	V	49.21	74.00	31.60	54.00

Test mode: GFSK Frequency: Channel 78: 2480MHz


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2484.007	H	49.08	74.00	32.60	54.00
2483.847	V	49.55	74.00	33.70	54.00

Test mode: GFSK Frequency: Hopping


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2400.0	H	48.26	74.00	32.50	54.00
2483.5	H	50.47	74.00	33.70	54.00
2400.0	V	48.72	74.00	31.50	54.00
2483.5	V	50.16	74.00	33.40	54.00

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model	Spurious Emission in Restricted Band 2310-2390MHz Channel 0: 2402MHz	GFSK	V
------------	---	------	---



Test Model	Spurious Emission in Restricted Band 2310-2390MHz Channel 0: 2402MHz	GFSK	H
------------	---	------	---




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz	Channel 78: 2480MHz	GFSK	V
------------	---	---------------------	------	---




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C

Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz	Channel 78: 2480MHz	GFSK	H
------------	---	---------------------	------	---




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C

Test Model	Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz Hopping	GFSK	V
------------	--	------	---




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C

Test Model	Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz Hopping	GFSK	H
------------	--	------	---



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C

- Spurious Emission below 1GHz (30MHz to 1GHz)
- All the antenna(Antenna 1&2) and modes(GFSK, $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1&2, GFSK) result recorded was report as below:



Site 3m Chamber #3


Polarization: *Vertical*

Temperature: 25.7 C

Mode:BT 2402

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		58.8185	46.88	-14.74	32.14	40.00	-7.86	QP		
2		119.8556	50.44	-17.46	32.98	43.50	-10.52	QP		
3	*	209.3130	54.60	-16.91	37.69	43.50	-5.81	QP		
4		260.1444	47.95	-14.54	33.41	46.00	-12.59	QP		
5		620.7096	39.57	-4.62	34.95	46.00	-11.05	QP		
6		1000.000	41.67	-1.40	40.27	54.00	-13.73	QP		



Site 3m Chamber #3


Polarization: **Horizontal**

Temperature: 25.7 C

Mode: BT 2402

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		99.8777	53.32	-17.67	35.65	43.50	-7.85	QP		
2		139.8508	54.81	-17.71	37.10	43.50	-6.40	QP		
3	*	181.9202	55.50	-17.32	38.18	43.50	-5.32	QP		
4		323.3204	46.74	-12.36	34.38	46.00	-11.62	QP		
5		501.1790	43.37	-7.22	36.15	46.00	-9.85	QP		
6		869.1302	34.97	0.07	35.04	46.00	-10.96	QP		



Site 3m Chamber #3


Polarization: *Horizontal*

Temperature: 25.7 C

Mode: BT 2441

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		84.1100	50.17	-18.22	31.95	40.00	-8.05			QP
2		119.8556	54.81	-17.46	37.35	43.50	-6.15			QP
3	*	183.2005	55.23	-17.20	38.03	43.50	-5.47			QP
4		260.1444	47.54	-14.54	33.00	46.00	-13.00			QP
5		501.1790	43.94	-7.22	36.72	46.00	-9.28			QP
6		860.0352	33.99	0.28	34.27	46.00	-11.73			QP



Site 3m Chamber #3


Polarization: *Vertical*

Temperature: 25.7 C

Mode: BT 2441

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		59.0251	46.79	-14.73	32.06	40.00	-7.94	QP		
2		119.8556	50.60	-17.46	33.14	43.50	-10.36	QP		
3	*	204.9551	53.37	-17.10	36.27	43.50	-7.23	QP		
4		260.1444	48.09	-14.54	33.55	46.00	-12.45	QP		
5		501.1790	42.14	-7.22	34.92	46.00	-11.08	QP		
6		993.0114	41.28	-1.61	39.67	54.00	-14.33	QP		



Site 3m Chamber #3


Polarization: *Horizontal*

Temperature: 25.7 C

Mode:BT 2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		83.8156	49.89	-18.19	31.70	40.00	-8.30	QP		
2	!	119.8556	55.45	-17.46	37.99	43.50	-5.51	QP		
3	*	183.8440	55.84	-17.14	38.70	43.50	-4.80	QP		
4		300.3672	47.53	-12.82	34.71	46.00	-11.29	QP		
5		580.7026	41.81	-5.77	36.04	46.00	-9.96	QP		
6		869.1302	35.22	0.07	35.29	46.00	-10.71	QP		



Site 3m Chamber #3

Polarization: **Vertical**

Temperature: 25.7 C

Mode: BT 2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		57.5940	46.25	-14.77	31.48	40.00	-8.52			QP
2		119.8556	50.09	-17.46	32.63	43.50	-10.87			QP
3	*	215.2678	52.59	-16.74	35.85	43.50	-7.65			QP
4		260.1444	48.07	-14.54	33.53	46.00	-12.47			QP
5		620.7096	40.18	-4.62	35.56	46.00	-10.44			QP
6		1000.000	41.56	-1.40	40.16	54.00	-13.84			QP

9.8 CONDUCTED EMISSION TEST

9.8.1 Applicable Standard

According to FCC Part 15.207

According to IC RSS-Gen 8.8

9.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


9.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results

Pass

The AC120V &240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #2

Phase: **N**

Temperature: 25.1

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 45 %

Mode: BT mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1980	36.85	10.43	47.28	63.63	-16.35	QP	
2		0.1980	29.96	10.43	40.39	53.69	-13.30	AVG	
3		0.2940	34.41	10.39	44.80	60.37	-15.57	QP	
4		0.2940	29.46	10.39	39.85	50.41	-10.56	AVG	
5		0.5060	33.42	10.32	43.74	56.00	-12.26	QP	
6		0.5060	25.89	10.32	36.21	46.00	-9.79	AVG	
7		0.9100	32.81	10.36	43.17	56.00	-12.83	QP	
8		0.9100	22.05	10.36	32.41	46.00	-13.59	AVG	
9		1.3140	32.42	10.36	42.78	56.00	-13.22	QP	
10		1.3140	17.21	10.36	27.57	46.00	-18.43	AVG	
11	*	15.4060	42.61	10.64	53.25	60.00	-6.75	QP	
12		15.4060	32.57	10.64	43.21	50.00	-6.79	AVG	



Site Conduction #2

Phase: **L1**

Temperature: 25.1

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 45 %

Mode: BT mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1980	36.52	10.43	46.95	63.63	-16.68	QP	
2		0.1980	28.80	10.43	39.23	53.69	-14.46	AVG	
3		0.3020	30.52	10.39	40.91	60.15	-19.24	QP	
4		0.3020	25.20	10.39	35.59	50.19	-14.60	AVG	
5		0.5060	30.75	10.32	41.07	56.00	-14.93	QP	
6		0.5060	22.82	10.32	33.14	46.00	-12.86	AVG	
7		0.7060	30.64	10.30	40.94	56.00	-15.06	QP	
8		0.7060	21.43	10.30	31.73	46.00	-14.27	AVG	
9		1.2540	30.83	10.37	41.20	56.00	-14.80	QP	
10		1.2540	18.16	10.37	28.53	46.00	-17.47	AVG	
11		15.0780	39.56	10.64	50.20	60.00	-9.80	QP	
12	*	15.0780	33.34	10.64	43.98	50.00	-6.02	AVG	

9.9 ANTENNA APPLICATION

9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
FCC 47 CFR Part 15.247 (b)	If transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.
RSS-Gen Section 6.8	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.
RSS-247 Section 5.4	If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

9.9.2 Result

PASS.

- Note:
- Antenna use a permanently attached antenna which is not replaceable.
 - Not using a standard antenna jack or electrical connector for antenna replacement
 - The antenna has to be professionally installed (please provide method of installation)

Please refer to the attached document Internal Photos to show the antenna connector.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

*** End of Report ***