





11N40SISO_Ant1_2422




11N40SISO_Ant2_2422










11N40SISO_Ant2_2452




11AX20SISO_Ant1_2412










11AX20SISO_Ant1_2462




11AX20SISO_Ant2_2462









11AX40SISO_Ant2_2437



11AX40SISO_Ant1_2452





8.4 MAXIMUM POWER SPECTRAL DENSITY

8.4.1 Applicable Standard

According to FCC Part15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02

According to RSS-247 5.2(b) and RSS-Gen 6.12

8.4.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

8.4.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

8.4.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.


Use the peak marker function to determine the maximum amplitude level within the RBW.

8.4.5 Test Results

Temperature:	25 °C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A

TestMode	Antenna	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-16.46	≤8.00	PASS
	Ant2	2412	-16.58	≤8.00	PASS
	Ant1	2437	-17.04	≤8.00	PASS
	Ant2	2437	-17.16	≤8.00	PASS
	Ant1	2462	-16.88	≤8.00	PASS
	Ant2	2462	-16.57	≤8.00	PASS
11G	Ant1	2412	-18.44	≤8.00	PASS
	Ant2	2412	-19.87	≤8.00	PASS
	Ant1	2437	-18.73	≤8.00	PASS
	Ant2	2437	-20.12	≤8.00	PASS
	Ant1	2462	-18.83	≤8.00	PASS
	Ant2	2462	-20.44	≤8.00	PASS
11N20SISO	Ant1	2412	-18.89	≤8.00	PASS
	Ant2	2412	-20.02	≤8.00	PASS
	Ant1	2437	-18.87	≤8.00	PASS
	Ant2	2437	-19.99	≤8.00	PASS
	Ant1	2462	-19.02	≤8.00	PASS
	Ant2	2462	-20.29	≤8.00	PASS
11N40SISO	Ant1	2422	-21.52	≤8.00	PASS
	Ant2	2422	-22.99	≤8.00	PASS
	Ant1	2437	-21.58	≤8.00	PASS
	Ant2	2437	-22.99	≤8.00	PASS
	Ant1	2452	-18.95	≤8.00	PASS
	Ant2	2452	-26.14	≤8.00	PASS
11AX20SISO	Ant1	2412	-20.02	≤8.00	PASS
	Ant2	2412	-21.20	≤8.00	PASS
	Ant1	2437	-20.46	≤8.00	PASS
	Ant2	2437	-21.47	≤8.00	PASS
	Ant1	2462	-20.33	≤8.00	PASS
	Ant2	2462	-21.48	≤8.00	PASS
11AX40SISO	Ant1	2422	-20.30	≤8.00	PASS
	Ant2	2422	-27.28	≤8.00	PASS
	Ant1	2437	-23.28	≤8.00	PASS
	Ant2	2437	-24.39	≤8.00	PASS
	Ant1	2452	-26.11	≤8.00	PASS
	Ant2	2452	-27.47	≤8.00	PASS
11N20MIMO		2422	-10.44	≤8.00	PASS
		2437	-10.41	≤8.00	PASS
		2452	-10.63	≤8.00	PASS
11N40MIMO		2422	-13.21	≤8.00	PASS
		2437	-13.25	≤8.00	PASS
		2452	-12.22	≤8.00	PASS
11AX20MIMO		2422	-11.59	≤8.00	PASS
		2437	-11.96	≤8.00	PASS
		2452	-11.89	≤8.00	PASS
11AX40MIMO		2422	-13.54	≤8.00	PASS
		2437	-14.82	≤8.00	PASS
		2452	-17.76	≤8.00	PASS








11B_Ant2_2437





11B_Ant1_2462















11N20SISO_Ant2_2412



11N20SISO_Ant1_2437







11N40SISO_Ant1_2422



11N40SISO_Ant2_2422

