

FCC ID : 2AZNP-L206FGN

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic	Power	Average	
Range(MHz)	Strength(V/m)	Field	Density(mW/cm ²)	Time	
		Strength(A/m)			
	(A) Limits for O	ccupational/Con	trol Exposures		
300-1500			F/300	6	
1500-			5	6	
100000					
(B) Limits for General Population/Uncontrol Exposures					
300-1500			F/1500	6	
1500-			1	30	
100000					

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm², If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.



11.2 Measurement Result

WIFI2.4G and Bluetooth can transmit at the same time

ΒT

Antenna 1 gain: 3.55 dBi Antenna 2 gain: 3.62 dBi

Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
8.03	7.0 to 9.0	9.0	2.3	0.004	1

BLE Antenna 1 gain: 3.55 dBi Antenna 2 gain: 3.62 dBi

Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
6.22	5.0 to 7.0	7.0	2.3	0.002	1

Wifi 2.4G Antenna 1 gain: 2.97 dBi Antenna 2 gain: 2.95 dBi Directional gain: 5.97 dBi

Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
18.00	17.0 to 19.0	19.0	4.0	0.062	1

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn

EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn



Wifi 5G Antenna 1 gain: 4.69 dBi Antenna 2 gain: 4.82 dBi Directional gain: 7.77 dBi

Frequency band	Measure d power (dBm)	Tune-up power (dBm)	Max tune- up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
5150MHz- 5250MHz	15.01	15.0 to 17.0	17.0	6.0	0.060	1
5250MHz- 5350MHz	15.97	15.0 to 17.0	17.0	6.0	0.060	1
5470MHz- 5725MHz	16.40	15.0 to 17.0	17.0	6.0	0.060	1
5725MHz- 5850MHz	15.66	15.0 to 17.0	17.0	6.0	0.060	1

MAX RF EXPOSURE EVALUATION

Wifi 2.4G	ВТ	Summation of Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
0.062	0.004	0.066	<1