

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	IO Wi-Fi 5 2x2 Outdoor Access Point with Integrated Omni Antenna
Model Name	ion4i_w
FCC ID	2AZOIIION4I-W

2. EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47CFR§2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time IEI ² IHI ² or S (Minutes)
0.3--1.34	614	1.63	(100)*	30
1.34--30	824/f	2.19/f	(180/f ²)*	30
30--300	27.5	0.073	0.2	30
300--1500	--	--	f/1500	30
1500--100,000	--	--	1.0	30

*Note:

- f= Frequency in MHz*Plane-wave Equivalent Power Density
- The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. (operated in BT/ WIFI) See 47CFR§§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S = \frac{PG}{4\pi R^2}$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to anisotropic radiator

R=distance to the center of radiation of the antenna

3. CALCULATION

A minimum test separation distance 20cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of §2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated.

Antenna Gain (2.4GHz) = 6dBi (Numeric = 3.981), rr = 3.14

Antenna Gain (5GHz) = 6dBi (Numeric = 3.981), rr = 3.14

Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Power Density (mW/cm ²)	PowerDensity Limit (mW/cm ²)
2462	24.22	264.24087573	0.209	1
5180 (Band 1)	23.27	212.3244462	0.168	1
5825 (Band 4)	23.04	201.37242499	0.159	1

Note: Only the worst case recorded.