

## FCC 22H 24E 27L, §2.1091 – RF Exposure

**FCC ID: 2AZON-B11**

### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

### Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: *f* is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

### Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: *f* = frequency in MHz

\* = Plane-wave equivalent power density

## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

## Test Result of RF Exposure Evaluation

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm <sup>2</sup> )	Limit (mW/ cm <sup>2</sup> )	Result
FDD-LTE BAND 2	23±1	24	251.19	1.0814 (0.34dBi)	0.05407	1	Pass
FDD-LTE BAND 4	22±1	23	199.53	0.9141 (-0.39dBi)	0.0363	1	Pass
FDD-LTE BAND 5	22±1	23	199.53	1.219 (0.86dBi)	0.04841	0.56	Pass
FDD-LTE BAND 12	22±1	23	199.53	0.861 (-0.65dBi)	0.03419	0.47	Pass
FDD-LTE BAND 13	24±1	25	316.23	1.2106 (0.83dBi)	0.0762	0.52	Pass
FDD-LTE BAND 25	24±1	25	316.23	1.0814 (0.34dBi)	0.06807	1	Pass
FDD-LTE BAND 26(824-849)	22±1	23	199.53	1.219 (0.86dBi)	0.04841	0.55	Pass