

Report No.: TBR-C-202302-0022-11  
Page: 1 of 3

# RF Exposure Evaluation

## FCC ID: 2AZPW-M5

### 1. Client Information

Applicant	:	SHENZHEN BOGASING TECHNOLOGY CO., LTD.
Address	:	Enterprise Life Artificial Intelligence Yousong Garden, Longhua District Shenzhen China
Manufacturer	:	SHENZHEN BOGASING TECHNOLOGY CO., LTD.
Address	:	Enterprise Life Artificial Intelligence Yousong Garden, Longhua District Shenzhen China

### 2. General Description of EUT

EUT Name	:	Wireless Speaker	
Model No.	:	M5, S1 Pro, S2 Pro, S3 Pro, S4 Pro, S5Pro, S6 Pro, S7 Pro, S8 Pro, S9 Pro, G1, G2, G3, G4, G5, G6, G7, G8, G9, G10, G7 Pro	
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is different colors, different sales customers.	
Sample ID	:	RW-C-202302-0022-9-1# & RW-C-202302-0022-9-2#	
Product Description	:	Operation Frequency:	Bluetooth 5.3(BDR+EDR): 2402MHz~2480MHz
	:	Number of Channel:	79 channels
	:	Antenna Gain:	1.9dBi PCB Antenna
Power Supply	:	Input: DC 5V/2A DC 3.7V by 6000mAh 22.2Wh Rechargeable Li-ion battery	
Software Version	:	Ver 1.3.1	
Hardware Version	:	Ver 1.3.2	

Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.

Note: More test information about the EUT please refer the RF Test Report.

TB-RF-074-1.0

## The RF Exposure Evaluation for FCC:

### SAR Test Exclusion Calculations

FCC: According to 447498 D04 Interim General RF Exposure Guidance v01.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and  $ERP_{20\text{cm}}$  is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169



**Calculation:**

Test separation: 5mm					
GFSK(1Mbps)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P <sub>th</sub> (mW)
2.402	0.18	0±1	1	1.259	3
2.441	-1.42	-1±1	0	1.000	3
2.480	-3.11	-3±1	-2	0.631	3

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D04, No SAR is required.

Test separation: 5mm					
π/4-DQPSK(2Mbps)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P <sub>th</sub> (mW)
2.402	0.15	0±1	1	1.259	3
2.441	-1.35	-1±1	0	1.000	3
2.480	-2.75	-2±1	-1	0.794	3

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D04, No SAR is required.

Test separation: 5mm					
8-DPSK(3Mbps)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P <sub>th</sub> (mW)
2.402	0.41	0±1	1	1.259	3
2.441	-0.95	0±1	1	1.259	3
2.480	-2.90	-2±1	-1	0.794	3

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D04, No SAR is required.

-----END OF THE REPORT-----



TB-RF-074-1.0