RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AZQV-MSD-003

EUT Specification

EUT	Wifi Digital Photo Frame					
Frequency band (Operating)						
	☐ WLAN: 5.18GHz ~ 5.24GHz					
	☐ WLAN: 5.745GHz ~ 5.825GHz					
	Others: SRD: 915MHz					
Device category	☐ Portable (<20cm separation)					
	☐ Others					
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm2)					
	☐ General Population/Uncontrolled exposure (S=1mW/cm2)					
Antenna diversity	⊠ Single antenna					
	☐ Multiple antennas					
	☐ Tx diversity					
	☐ Rx diversity					
	☐ Tx/Rx diversity					
Antenna gain (Max)	WIFI 2.4G: 3dBi					
	SRD: 2dBi					
Evaluation applied						
	☐ SAR Evaluation					

Limits for Maximum Permissible Exposure(MPE)

Frequency	Electric Field	Magnetic Field	Power	Average				
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm²)	Time				
(A) Limits for Occupational/Control Exposures								
300-1500			F/300	6				
1500-100000			5	6				
(B) Limits for General Population/Uncontrol Exposures								
300-1500			F/1500	6				
1500-100000			1	30				

Friis transmission formula: Pd=(Pout*G)\(4*pi*R2)

Where

Pd= Power density in mW/cm²
Pout=output power to antenna in Mw
G= gain of antenna in linear scale
Pi=3.1416

R= distance between observation point and center of the radiator in cm Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Max Measurement Result

Operating Mode	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits
	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm2)	(mW/cm2)
2.4G WIFI	15.83	15.83 ±1	16.83	3	0.0191	1