



# FCC RF EXPOSURE REPORT

### **CERTIFICATION TEST REPORT**

For

110/160CFM Bath Fan with Bluetooth Speaker

MODEL NUMBER: OL1700501

### REPORT NUMBER: 4790958738-2-RF-2

**ISSUE DATE: September 6, 2023** 

FCC ID: 2AZR9-OL1700501

Prepared for

Syvio Technology CO., LIMITED Room A, 8/F,Kwok Cheung Building, 635-637 Shanghai Street, Mong Kok, Hong Kong China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



### **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	September 6, 2023	Initial Issue	



## TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	.4
2.	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	.5
4.	DESCRIPTION OF EUT	6
5.	REQUIREMENT	7



## **1. ATTESTATION OF TEST RESULTS**

#### Applicant Information

Company Name:	Syvio Technology CO., LIMITED
Address:	Room A, 8/F,Kwok Cheung Building, 635-637 Shanghai Street, Mong Kok, Hong Kong China

#### Manufacturer Information

Company Name:	Linkzone Technology Co., Limited
Address:	4001, Block C, Building 1, Section 1, Chuangzhi Yuncheng,
	Liuxian Avenue, Xili Communityxili Street, Nanshan District

#### **EUT Information**

EUT Name:	110/160CFM Bath Fan with Bluetooth Speaker
Model:	OL1700501
Brand:	OREIN
Sample Received Date:	August 14, 2023
Sample Status:	Normal
Sample ID:	6335010
Date of Tested:	August 14, 2023 to September 6, 2023

APPLICABLE STANDARDS			
STANDARD TEST RESULTS			
FCC 47CFR§2.1091	PASS		

Prepared By:

fammy . Huang

Checked By: Derry Gran

Fanny Huang **Engineer Project Associate** 

Denny Huang Senior Project Engineer

Approved By:

Spoplentino

Stephen Guo Operations Manager



# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB447498D01v06.

# 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<ul> <li>A2LA (Certificate No.: 4102.01)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</li> <li>FCC (FCC Designation No.: CN1187)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules</li> <li>ISED (Company No.: 21320)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</li> <li>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name:</li> </ul>
	· ·
	Shielding Room B , the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



## 4. DESCRIPTION OF EUT

EUT Name:		110/160CFM Bath Fan with Bluetooth Speaker	
Model:		OL1700501	
Product Description	Frequency Range:	2402 MHz to 2480 MHz	
	Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)	
(BT)	Type of Modulation:	GFSK, Π /4DQPSK, 8DPSK	
Normal Test Voltage:		AC 120 V, 60 Hz	



## 5. REQUIREMENT

### LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

### **RF EXPOSURE LIMIT**

### **CALCULATION METHOD**

S=PG/4πR<sup>2</sup> Where: S=power density P=power input to antenna G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna



### CALCULATED RESULTS

Worst Case						
Mode	Max Tune Up Power	Antenna Gain	Power Density	Power Density Limit	Test Result	
	dBm	dBi	mW/cm2	mW/cm2		
BT	3	5.95	0.00156	1.0	Complies	

Note:

1. The Power comes from report operation description.

2. The minimum separation distance of the device is greater than 20 cm, and 20 cm separation distance was set for calculation.

3. Calculate by WORST-CASE mode.

## END OF REPORT