



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20210500592E-02

Applicant: Star Atmosphere Technology (Shenzhen) Co., LTD

Address of Applicant: Room 2706A, Block A, Sunshine TDI Building, Nanshan District, Shenzhen 518000, China

Equipment Under Test (EUT):

EUT Name: WOLONOW Smart Body Fat Scale PRO

Model No.: BFSITO-300

Test Model No.: BFSITO-300

Brand Name: WOLONOW

FCC ID: 2AZSZ-ITO300

Standards: 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2021-05-08

Date of Test: 2021-05-08 to 2021-05-18

Date of Issue: 2021-06-17

Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

lewis zhou

(Lewis Zhou)

Reviewed By:

Sheek , Luo

(Sheek Luo)

Approved By:

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210500592E-02	Rev.01	Initial report	2021-06-17

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Standard Requirement	5
4.1.2 Limits	5
4.1.3 EUT RF Exposure	6

3 General Information

3.1 Client Information

Applicant:	Star Atmosphere Technology (Shenzhen) Co., LTD
Address of Applicant:	Room 2706A, Block A, Sunshine TDI Building, Nanshan District, Shenzhen 518000, China
Manufacturer:	Star Atmosphere Technology (Shenzhen) Co., LTD
Address of Manufacturer:	Room 2706A, Block A, Sunshine TDI Building, Nanshan District, Shenzhen 518000, China
Factory:	Star Atmosphere Technology (Shenzhen) Co., LTD
Address of Factory:	Room 2706A, Block A, Sunshine TDI Building, Nanshan District, Shenzhen 518000, China

3.2 General Description of EUT

Product Name:	WOLONOW Smart Body Fat Scale PRO
Model No.:	BFSITO-300
Test Model No.:	BFSITO-300
Trade Mark:	WOLONOW
Hardware Version:	V1.3
Software Version:	V1.5
Operation Frequency:	2402MHz~2480MHz
Version:	2.4G custom
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	3
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	MacroGiga Test V2.0 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0 dBi
EUT Power Supply:	DC3.7V 50MA

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

1) For BLE

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)		(dBm)
Lowest(2402MHz)	-0.64	0.5±1		1.5
Middle(2440MHz)	-0.03	0±1		1.0
Highest(2480MHz)	-0.13	0±1		1.0

Worst case: GFSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-0.64	0.5±1	1.5	1.413	0.438	3.0
Middle (2440MHz)	-0.03	0±1	1.0	1.259	0.393	
Highest (2480MHz)	-0.13	0±1	1.0	1.259	0.397	

Conclusion: the calculated value ≤3.0, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20210500592E-01