



FCC ID: 2AZUG-WA144

1. Limit for Portable Equipment Exposure

Frequency	1-g SAR
100MHz-6GHz	3.0

For 100 MHz to 6 GHz and test separation distances \leqslant 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leqslant 3.0 \text{ for 1-g SAR, and} \leqslant 7.5 \text{ for 10-g extremity SAR,}$
where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

2. Estimation Result

Frequency (MHz)	PK Output Power(dBm)	Output Power(mW)	Test Separation Distance (mm)	Measurement Result	1-g SAR
433.92	-12.49	0.056	5	0.007	3.0

Note:

- use the maximum E-field strength(84.86dB_V/m) for the RF exposure evaluation
- $E(\text{dB}_V/\text{m}) = \text{EIRP}(\text{dBm}) - 95.2$ for distance 3m
so the $\text{EIRP} = 84.86\text{dB}_V/\text{m} - 95.2 = -10.34\text{dBm}$
- $\text{EIRP}(\text{dBm}) = \text{ERP} + 2.15\text{dBi}$
so the $\text{ERP} = -10.34\text{dBm} - 2.15\text{dBi} = -12.49\text{dBm}$

-----The End-----