

FCC ID: 2AZUR-HI-BOX

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type: PCB Antenna

Antenna Gain: 0.2dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	6.63	4.603	7±1	8.0	6.310	<5	1.95576	3.00	YES
	2.441	7.48	5.598	7±1	8.0	6.310	<5	1.97158	3.00	YES
	2.480	7.02	5.035	7±1	8.0	6.310	<5	1.98727	3.00	YES
π/4-DQPSK	2.402	7.28	5.346	7±1	8.0	6.310	<5	1.95576	3.00	YES
	2.441	7.68	5.861	7±1	8.0	6.310	<5	1.97158	3.00	YES
	2.480	7.46	5.572	7±1	8.0	6.310	<5	1.98727	3.00	YES
8DPSK	2.402	7.51	5.636	7±1	8.0	6.310	<5	1.95576	3.00	YES
	2.441	7.76	5.970	7±1	8.0	6.310	<5	1.97158	3.00	YES
	2.480	7.65	5.821	7±1	8.0	6.310	<5	1.98727	3.00	YES

BLE:

Antenna Type: PCB Antenna

Antenna Gain: 0.2dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
GFSK(1M)	2.402	-2.68	0.540	-2±1	-1.0	0.794	<5	0.24622	3.00	YES
	2.44	-2.26	0.594	-2±1	-1.0	0.794	<5	0.24816	3.00	YES
	2.48	-2.18	0.605	-2±1	-1.0	0.794	<5	0.25018	3.00	YES

Conclusion:

For the max result : $0.49127 \leq 3.0$ for 1-g SAR, No SAR is required.


Signature:**Date:** 2021-11-11**NAME AND TITLE** (Please print or type): Alex /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China