



RF Exposure Evaluation

FCC ID: 2AZWI-3838LEQI

1. Client Information

Applicant	:	Shenzhen Leqi Network Technology Co., LTD
Address	:	Room 101, Building 9 & Room 401, Building 12, Yazhou Industrial Park, Bantian, Longgang, Shenzhen, Guangdong, 518000, China.
Manufacturer	:	Shenzhen Leqi Network Technology Co., LTD
Address	:	Room 101, Building 9 & Room 401, Building 12, Yazhou Industrial Park, Bantian, Longgang, Shenzhen, Guangdong, 518000, China.

2. General Description of EUT

EUT Name	:	Side Handle with Wireless Control for Cellphone
Model(s)	:	SG-20, SG-30 Fold, SG-20 Fold
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is different customers, different model name.
Product Description	Operation Frequency:	Bluetooth 4.2(BLE): 2402MHz~2480MHz
	Number of Channel:	Bluetooth 4.2(BLE): 40 channels
	Antenna Gain:	0dBi PCB Antenna
	Modulation Type:	GFSK
	Bit Rate of Transmitter:	1Mbps
Power Rating	:	Input: DC 5V DC 3.7V by 100mAh Rechargeable Li-ion battery
Software Version	:	V1.1
Hardware Version	:	V1.0
Connecting I/O Port(S)	:	Please refer to the User's Manual

Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0$ for 10-g SAR

2. Calculation:

Test separation: 5mm						
BLE Mode (1Mbps)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	1.858	1±1	2	1.585	0.491	3.0
2.440	1.527	1±1	2	1.585	0.495	3.0
2.480	0.948	0±1	1	1.259	0.397	3.0

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----