




## RF Exposure Evaluation Report

<b>Report Reference No.</b> .....:	MTEB23080162-H	
<b>FCC ID</b> .....:	2AZWZ-T6PRO	
Compiled by ( position+printed name+signature)...	File administrators Alisa Luo	
Supervised by ( position+printed name+signature)...	Test Engineer Sunny Deng	
Approved by ( position+printed name+signature)...	Manager Yvette Zhou	
Date of issue.....:	Aug. 14,2023	
<b>Representative Laboratory Name.:</b>	<b>Shenzhen Most Technology Service Co., Ltd.</b>	
Address .....	East A, 1 floor of New Aolin Factory buiding, Langshan Erlu, North District, Hi-tech Industry Park, Nanshan,Shenzhen,Guangdong,China	
<b>Applicant's name</b> .....:	<b>KAWA ELECTRONICS COMPANY LIMITED</b>	
Address .....	FLAT A 21/F CHEUNG LEE IND BLDG 9 CHEUNG LEE ST CHAI WAN HONG KONG , China	
<b>Test specification/ Standard</b> .....	<b>47 CFR Part 1.1307;47 CFR Part 1.1310 KDB447498D01 General RF Exposure Guidance v06</b>	
TRF Originator.....:	Shenzhen Most Technology Service Co., Ltd.	
<b>Shenzhen Most Technology Service Co., Ltd. All rights reserved.</b>		
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.		
<b>Test item description</b> .....	Security Camera	
Trade Mark .....	KAWA Apical	
Model/Type reference.....:	T6 Pro	
Listed Models .....	T6、 T7、 T7 Pro、 2337C、 2337B、 T601、 T701	
Modulation Type .....	CCK/DSSS/ OFDM	
Operation Frequency.....:	From 2412MHz~2462MHz	
Hardware Version.....	2337C-MAIN-01A	
Software Version .....	Ver 2337C.1.0	
Rating .....	DC 12V (by Adapter) POE power supply(48V 0.35A)	
Result.....:	<b>PASS</b>	

# TEST REPORT

Equipment under Test : Security Camera

Model /Type : T6 Pro

Listed Models : T6、 T7、 T7 Pro、 2337C、 2337B、 T601、 T701

Remark : Inside the lens size difference, the other is the same.

Applicant : **KAWA ELECTRONICS COMPANY LIMITED**

Address : FLAT A 21/F CHEUNG LEE IND BLDG 9 CHEUNG LEE ST  
CHAI WAN HONG KONG , China

Manufacturer : **KAWA ELECTRONICS COMPANY LIMITED**

Address : FLAT A 21/F CHEUNG LEE IND BLDG 9 CHEUNG LEE  
ST CHAI WAN HONG KONG , China

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## 1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2023-08-14	Initial Issue	Alisa Luo

## 2. SAR Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 2.1.2 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$  Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

**2.1.3 EUT RF Exposure**

Antenna Gain: 3.52dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.4 in linear scale. Output Power Into Antenna & RF Exposure Evaluation Distance:

WIFI 2.4G

802.11b			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	17.30	17.30 ± 1	18.3
Middle(2437MHz)	18.18	18.18 ± 1	19.18
Highest(2462MHz)	17.48	17.48 ± 1	18.48

802.11g			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	16.95	16.95 ± 1	17.95
Middle(2437MHz)	17.78	17.78 ± 1	18.78
Highest(2462MHz)	18.00	18.00 ± 1	19

802.11n(H20)			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	16.89	16.89 ± 1	17.89
Middle(2437MHz)	17.68	17.68 ± 1	18.68
Highest(2462MHz)	17.95	17.95 ± 1	18.95

Worst case: 802.11b						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Middle(2437MHz)	19.18	82.79	3.52	0.037	1.0	Pass

Note: 1) Refer to report MTEB23080162-R for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (82.79 * 2.25) / (4 * 3.1416 * 20^2) = 0.037$

.....**THE END OF REPORT**.....