

TEST REPORT

Applicant: ZHONGYEDA TOYS FACTORY

Address of Applicant: CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA

Manufacturer: ZHONGYEDA TOYS FACTORY

Address of Manufacturer: CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA

Equipment Under Test (EUT)

Product Name: Remote control boat

Model No.: See section 5.1

FCC ID: 2AZXK-13790833616

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: October 09, 2021

Date of Test: October 09-15, 2021

Date of report issued: October 15, 2021

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Luo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	October 15, 2021	Original

Prepared By:




Date:

October 15, 2021

Project Engineer

Check By:



Date:

October 15, 2021

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS.....	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY.....	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS.....	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT	10
7.2 RADIATED EMISSION METHOD	11
7.2.1 <i>Field Strength of The Fundamental Signal</i>	13
7.2.2 <i>Spurious emissions</i>	14
7.2.3 <i>Bandedge emissions</i>	26
7.3 20dB OCCUPY BANDWIDTH	30
8 TEST SETUP PHOTO	32
9 EUT CONSTRUCTIONAL DETAILS	32

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10: 2013.
2. Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Remote control boat
Model No.:	T12, T11, T13, T14, T15, T16, T17, T18, T19, T20, T21, T22, T23, T24, T25, T32, T01B, T02B, T03B, T04B, T05B, T06B, T07B, T08B, T09B, T10B, T11B, T12B, T13B, T14B, T15B, T16B, T17B, T18B, T19B, T20B, T21B, T22B, T23B, T24B, T25B, T26B, T27B, T28B, T29B, T30B, T31B, T32B, T33B, T34B, T35B, T36B, T37B, T38B, K01, K02, K03, K04, K05, K06, K07, K08, K09, K10, K11, K12, K13, K14, K15, K16, K17, K18, K19, K20, ZYJH135, ZYJH138, ZYJH121, DE55, YKR088, YKR091
Test Model No.:	T12
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color and model name for commercial purpose.	
Serial No.:	20211010
Test sample(s) ID:	GTS202110000015-1
Sample(s) Status	Engineered sample
Operation Frequency:	2408MHz~2474MHz
Channel numbers:	67
Modulation type:	GFSK
Antenna Type:	Integral antenna
Antenna gain:	0dBi(Declared by applicant)
Power supply:	TX: DC 3.0V (2*1.5V Size "AAA" Battery) RX: D 3.7V, 300mAh, 1.11Wh Li-ion Battery

Note: The report is only for TX device

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2408	21	2428	41	2448	61	2468
2	2409	22	2429	42	2449	62	2469
3	2410	23	2430	43	2450	63	2470
4	2411	24	2431	44	2451	64	2471
5	2412	25	2432	45	2452	65	2472
6	2413	26	2433	46	2453	66	2473
7	2414	27	2434	47	2454	67	2474
8	2415	28	2435	48	2455		
9	2416	29	2436	49	2456		
10	2417	30	2437	50	2457		
11	2418	31	2438	51	2458		
12	2419	32	2439	52	2459		
13	2420	33	2440	53	2460		
14	2421	34	2441	54	2461		
15	2422	35	2442	55	2462		
16	2423	36	2443	56	2463		
17	2424	37	2444	57	2464		
18	2425	38	2445	58	2465		
19	2426	39	2446	59	2466		
20	2427	40	2447	60	2467		

The test frequencies are below:

Channel	Frequency
The lowest channel	2408MHz
The middle channel	2441MHz
The Highest channel	2474MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: New battery is used during all test.	

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	90.46	91.66	89.37

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC—Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. ● IC —Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).
--

5.7 Test Location

All tests were performed at:
<p>Global United Technology Services Co., Ltd. Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960</p>

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 24 2021	June. 23 2022
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 24 2021	June. 23 2022
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 24 2021	June. 23 2022
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 24 2021	June. 23 2022
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 24 2021	June. 23 2022
9	Coaxial Cable	GTS	N/A	GTS211	June. 24 2021	June. 23 2022
10	Coaxial cable	GTS	N/A	GTS210	June. 24 2021	June. 23 2022
11	Coaxial Cable	GTS	N/A	GTS212	June. 24 2021	June. 23 2022
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 24 2021	June. 23 2022
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 24 2021	June. 23 2022
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 24 2021	June. 23 2022
15	Band filter	Amindeon	82346	GTS219	June. 24 2021	June. 23 2022
16	Power Meter	Anritsu	ML2495A	GTS540	June. 24 2021	June. 23 2022
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 24 2021	June. 23 2022
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 24 2021	June. 23 2022
19	Splitter	Agilent	11636B	GTS237	June. 24 2021	June. 23 2022
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 24 2021	June. 23 2022
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 18 2020	Oct. 17 2021
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 18 2020	Oct. 17 2021
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 18 2020	Oct. 17 2021
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 24 2021	June. 23 2022

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 24 2021	June. 23 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 24 2021	June. 23 2022
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 24 2021	June. 23 2022
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 24 2021	June. 23 2022
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 24 2021	June. 23 2022
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 24 2021	June. 23 2022
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 24 2021	June. 23 2022
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 24 2021	June. 23 2022


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 24 2021	June. 23 2022
2	Barometer	ChangChun	DYM3	GTS255	June. 24 2021	June. 23 2022


7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
<i>The antenna is integral antenna, the best case gain of the are antennas 0dBi, reference to the appendix II for details</i>	

7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	2400MHz-2483.5MHz	94.00		Average Value	
		114.00		Peak Value	
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)		Remark	
	0.009MHz-0.490MHz	2400/F(kHz) @300m		Quasi-peak Value	
	0.490MHz-1.705MHz	24000/F(kHz) @30m		Quasi-peak Value	
	1.705MHz-30.0MHz	30 @30m		Quasi-peak Value	
	30MHz-88MHz	100 @3m		Quasi-peak Value	
	88MHz-216MHz	150 @3m		Quasi-peak Value	
	216MHz-960MHz	200 @3m		Quasi-peak Value	
	960MHz-1GHz	500 @3m		Quasi-peak Value	
	Above 1GHz	500 @3m		Average Value	
	5000 @3m		Peak Value		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	<p>For radiated emissions from 9kHz to 30MHz</p>  <p>For radiated emissions from 30MHz to 1GHz</p>				

	 <p>For radiated emissions above 1GHz</p>						
<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 						
<p>Test Instruments:</p>	<p>Refer to section 6.0 for details</p>						
<p>Test mode:</p>	<p>Refer to section 5.2 for details</p>						
<p>Test environment:</p>	<table border="1"> <tr> <td>Temp.:</td> <td>25 °C</td> <td>Humid.:</td> <td>52%</td> <td>Press.:</td> <td>1012mbar</td> </tr> </table>	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar		
<p>Test voltage:</p>	<p>DC 3V</p>						
<p>Test results:</p>	<p>Pass</p>						

Measurement data:

7.2.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2408.00	92.63	27.58	5.39	34.01	91.59	114.00	-22.41	Vertical
2408.00	86.80	27.58	5.39	34.01	85.76	114.00	-28.24	Horizontal
2441.00	92.71	27.48	5.43	33.96	91.66	114.00	-22.34	Vertical
2441.00	86.66	27.48	5.43	33.96	85.61	114.00	-28.39	Horizontal
2474.00	91.31	27.52	5.47	33.92	90.38	114.00	-23.62	Vertical
2474.00	85.43	27.52	5.47	33.92	84.50	114.00	-29.50	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2408.00	82.51	27.58	5.39	34.01	81.47	94.00	-12.53	Vertical
2408.00	77.28	27.58	5.39	34.01	76.24	94.00	-17.76	Horizontal
2441.00	82.92	27.48	5.43	33.96	81.87	94.00	-12.13	Vertical
2441.00	76.12	27.48	5.43	33.96	75.07	94.00	-18.93	Horizontal
2474.00	82.03	27.52	5.47	33.92	81.10	94.00	-12.90	Vertical
2474.00	76.41	27.52	5.47	33.92	75.48	94.00	-18.52	Horizontal

Note: RBW>20dB BW, VBW> RBW, PK detector is for PK value, AV detector is for AV value .


7.2.2 Spurious emissions

■ Below 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

■ Below 1GHz

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
34.760	38.59	12.48	0.61	35.34	16.34	40.00	-23.66	QP
42.302	39.28	13.12	0.69	35.79	17.30	40.00	-22.70	QP
47.326	37.37	13.00	0.74	36.05	15.06	40.00	-24.94	QP
163.755	33.98	12.64	1.65	37.15	11.12	43.50	-32.38	QP
830.400	34.03	22.45	4.58	37.61	23.45	46.00	-22.55	QP
925.756	33.93	23.48	4.95	37.58	24.78	46.00	-21.22	QP

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
34.517	38.72	12.47	0.60	35.32	16.47	40.00	-23.53	QP
40.845	37.80	13.21	0.67	35.71	15.97	40.00	-24.03	QP
55.027	36.36	12.55	0.82	36.25	13.48	40.00	-26.52	QP
148.963	32.83	12.73	1.56	37.07	10.05	43.50	-33.45	QP
714.173	33.00	20.72	4.14	37.63	20.23	46.00	-25.77	QP
854.025	34.07	22.62	4.68	37.61	23.76	46.00	-22.24	QP

Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
36.001	38.22	12.65	0.62	35.42	16.07	40.00	-23.93	QP
41.567	39.80	13.17	0.68	35.75	17.90	40.00	-22.10	QP
47.826	37.77	13.01	0.75	36.08	15.45	40.00	-24.55	QP
54.071	36.44	12.64	0.81	36.24	13.65	40.00	-26.35	QP
737.071	34.96	21.25	4.23	37.63	22.81	46.00	-23.19	QP
881.407	33.11	22.82	4.79	37.60	23.12	46.00	-22.88	QP

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
35.624	38.29	12.59	0.62	35.40	16.10	40.00	-23.90	QP
42.007	38.02	13.14	0.69	35.78	16.07	40.00	-23.93	QP
48.163	37.69	13.01	0.75	36.09	15.36	40.00	-24.64	QP
158.668	33.01	12.77	1.62	37.13	10.27	43.50	-33.23	QP
576.644	33.04	18.66	3.63	37.53	17.80	46.00	-28.20	QP
787.851	34.27	22.07	4.41	37.62	23.13	46.00	-22.87	QP


Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
35.128	38.57	12.52	0.61	35.36	16.34	40.00	-23.66	QP
48.672	37.50	13.02	0.76	36.12	15.16	40.00	-24.84	QP
55.609	36.71	12.52	0.82	36.26	13.79	40.00	-26.21	QP
110.957	36.59	10.08	1.29	36.81	11.15	43.50	-32.35	QP
787.851	34.47	22.07	4.41	37.62	23.33	46.00	-22.67	QP
945.440	32.82	23.89	5.03	37.56	24.18	46.00	-21.82	QP


■ Above 1GHz

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4816.000	43.34	31.22	4.61	37.73	41.44	74.00	-32.56	Peak
7224.000	28.54	36.20	6.50	35.63	35.61	74.00	-38.39	Peak
9632.000	25.98	37.97	7.98	34.95	36.98	74.00	-37.02	Peak

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4816.000	37.05	31.22	4.61	37.73	35.15	74.00	-38.85	Peak
7224.000	28.29	36.20	6.50	35.63	35.36	74.00	-38.64	Peak
9632.000	27.03	37.97	7.98	34.95	38.03	74.00	-35.97	Peak

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBUV/m	Limit level dBUV/m	Over limit dB	Remark
4882.000	44.96	31.33	4.69	37.76	43.22	74.00	-30.78	Peak
7323.000	26.96	36.43	6.63	35.60	34.42	74.00	-39.58	Peak
9764.000	26.39	38.10	8.03	35.03	37.49	74.00	-36.51	Peak

Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	41.33	31.33	4.69	37.76	39.59	74.00	-34.41	Peak
7323.000	30.33	36.43	6.63	35.60	37.79	74.00	-36.21	Peak
9764.000	27.70	38.10	8.03	35.03	38.80	74.00	-35.20	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4948.000	45.25	31.41	4.77	37.78	43.65	74.00	-30.35	Peak
7422.000	28.54	36.62	6.75	35.57	36.34	74.00	-37.66	Peak
9896.000	27.31	38.27	8.08	35.12	38.54	74.00	-35.46	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4948.000	38.25	31.41	4.77	37.78	36.65	74.00	-37.35	Peak
7422.000	26.85	36.62	6.75	35.57	34.65	74.00	-39.35	Peak
9896.000	26.30	38.27	8.08	35.12	37.53	74.00	-36.47	Peak


Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. For above 18GHz, no emission found.

7.2.3 Bandedge emissions


All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.94	27.14	2.81	38.64	20.25	54.00	-33.75	Average
2310.000	39.77	27.14	2.81	38.64	31.08	74.00	-42.92	Peak
2390.000	28.54	27.37	2.91	38.84	19.98	54.00	-34.02	Average
2390.000	39.45	27.37	2.91	38.84	30.89	74.00	-43.11	Peak
2400.000	28.56	27.41	2.91	38.86	20.02	54.00	-33.98	Average
2400.000	40.07	27.41	2.91	38.86	31.53	74.00	-42.47	Peak

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.95	27.14	2.81	38.64	20.26	54.00	-33.74	Average
2310.000	39.36	27.14	2.81	38.64	30.67	74.00	-43.33	Peak
2390.000	28.54	27.37	2.91	38.84	19.98	54.00	-34.02	Average
2390.000	38.69	27.37	2.91	38.84	30.13	74.00	-43.87	Peak
2400.000	28.39	27.41	2.91	38.86	19.85	54.00	-34.15	Average
2400.000	39.48	27.41	2.91	38.86	30.94	74.00	-43.06	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	28.28	27.66	2.99	39.06	19.87	54.00	-34.13	Average
2483.500	45.90	27.66	2.99	39.06	37.49	74.00	-36.51	Peak
2500.000	28.98	27.70	3.01	39.10	20.59	54.00	-33.41	Average
2500.000	41.43	27.70	3.01	39.10	33.04	74.00	-40.96	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	28.35	27.66	2.99	39.06	19.94	54.00	-34.06	Average
2483.500	40.78	27.66	2.99	39.06	32.37	74.00	-41.63	Peak
2500.000	29.04	27.70	3.01	39.10	20.65	54.00	-33.35	Average
2500.000	41.18	27.70	3.01	39.10	32.79	74.00	-41.21	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor


7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	0.829	Pass
Middle	0.814	Pass
Highest	0.806	Pass


Test plot as follows:



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----