

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is a Toy RC Gravity Rover operating at 2.4G Band. The EUT can be powered by DC 3.7V (1 x 3.7V Rechargeable battery). Once use the USB cable charging to the EUT, the wireless function will be disabled. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: 0.0 dBm ( $\pm 3$ dB)

The nominal radiated output power (e.i.r.p) specified: 0.0 dBm ( $\pm 3$ dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 97.8 dB $\mu$ V/m at 3m in the frequency 2445MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = 2.57dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 94.8 dB $\mu$ V/m at 3m in the frequency 2407MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -0.43dBm

which is within the production variation.

The maximum conducted output power specified is 3dBm= 1.995mW

The source- based time-averaging conducted output power

=1.995\* Duty cycle mW <1.995 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$\begin{aligned} P_{th}(\text{mW}) &= ERP_{20\text{cm}} * (d/20\text{cm})^x \quad (X = -\log_{10} \left( \frac{60}{ERP_{20\text{cm}} \sqrt{f}} \right)) \\ &= 3060 * (0.5/20)^{1.9} \text{ mW} \\ &= 2.72 \text{ mW} \end{aligned}$$

Since max. power of the source-based time-averaging conducted output power and effective radiated power (ERP) is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 15.5797ms

Effective period of the cycle = 1.0870ms

DC = 1.0870ms / 15.5797ms = 0.0698 or 6.98%