







Test Mode: Traffic mode PCS1900 (GSM link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode PCS1900 (GPRS 1 link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode PCS1900 (EGPRS 1 link)



Lowest channel




Middle channel





Highest channel


Test Mode: Traffic mode WCDMA Band V (RMC 12.2Kbps link)



Lowest channel





Middle channel





Highest channel

Test Mode: Traffic mode



WCDMA Band II (RMC 12.2Kbps link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode WCDMA Band IV (RMC 12.2Kbps link)



Lowest channel




Middle channel




Highest channel

Band Edge:

Test Mode: Traffic mode GSM850 (GSM link)




Lowest channel




Highest channel

Test Mode: Traffic mode GSM850 (GPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode GSM850 (EGPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode PCS1900 (GSM link)




Lowest channel




Highest channel

Test Mode: Traffic mode PCS1900 (GPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode PCS1900 (EGPRS 1 link)



Lowest channel



Highest channel

Test Mode: Traffic mode WCDMA Band V (RMC 12.2Kbps link)




Lowest channel




Highest channel

Test Mode: Traffic mode WCDMA Band II (RMC 12.2Kbps link)



Lowest channel




Highest channel

Test Mode: Traffic mode WCDMA Band IV (RMC 12.2Kbps link)






Lowest channel



Highest channel

4.8 ERP, EIRP Measurement

<p>Test Requirement:</p>	<p>FCC part22.913(a) and FCC part24.232(b) , Part 27.54(h) RSS-132(5.5), RSS-133 (6.5), RSS-139 (6.6)</p>
<p>Test Method:</p>	<p>FCC part2.1046</p>
<p>Limit:</p>	<p>GSM850, WCDMA Band V: 7W PCS1900, WCDMA Band II: 2W WCDMA Band IV: 1W</p>
<p>Test setup:</p>	<p>Below 1GHz</p>  <p>Above 1GHz</p>  <p>Substituted method:</p> 

Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated. 3. ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated asfollows: $\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$ 4. EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows: $\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GSM link)	Lowest	H	V	29.71	38.45	Pass
			H	28.73		
		E1	V	30.01		
			H	27.27		
		E2	V	29.57		
			H	27.04		
	Middle	H	V	30.63	38.45	Pass
			H	28.01		
		E1	V	29.78		
			H	27.86		
		E2	V	29.77		
			H	27.58		
	Highest	H	V	29.99	38.45	Pass
			H	27.68		
		E1	V	29.87		
			H	27.29		
		E2	V	29.46		
			H	28.05		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GPRS 1 link)	Lowest	H	V	26.83	38.45	Pass
			H	25.19		
		E1	V	27.15		
			H	25.55		
		E2	V	27.51		
			H	26.12		
	Middle	H	V	28.00	38.45	Pass
			H	25.54		
		E1	V	27.19		
			H	25.06		
		E2	V	26.57		
			H	25.39		
	Highest	H	V	27.30	38.45	Pass
			H	25.91		
		E1	V	27.10		
			H	24.95		
		E2	V	27.99		
			H	25.37		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (EGPRS 1 link)	Lowest	H	V	25.20	38.45	Pass
			H	23.21		
		E1	V	25.63		
			H	23.78		
		E2	V	25.47		
			H	24.06		
	Middle	H	V	25.70	38.45	Pass
			H	23.51		
		E1	V	25.60		
			H	23.60		
		E2	V	25.18		
			H	23.28		
	Highest	H	V	25.67	38.45	Pass
			H	23.93		
		E1	V	25.52		
			H	23.23		
		E2	V	26.11		
			H	23.41		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GSM link)	Lowest	H	V	29.34	33.01	Pass
			H	26.09		
		E1	V	29.90		
			H	26.92		
		E2	V	30.11		
			H	26.37		
	Middle	H	V	30.37	33.01	Pass
			H	26.43		
		E1	V	29.58		
			H	26.59		
		E2	V	29.86		
			H	27.16		
	Highest	H	V	29.95	33.01	Pass
			H	26.69		
		E1	V	29.28		
			H	26.98		
		E2	V	29.12		
			H	26.70		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GPRS 1 link)	Lowest	H	V	29.70	33.01	Pass
			H	25.77		
		E1	V	29.78		
			H	26.53		
		E2	V	29.95		
			H	26.60		
	Middle	H	V	30.11	33.01	Pass
			H	27.00		
		E1	V	29.80		
			H	26.78		
		E2	V	29.32		
			H	27.43		
	Highest	H	V	29.99	33.01	Pass
			H	26.26		
		E1	V	29.31		
			H	26.31		
		E2	V	29.51		
			H	26.69		




EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (EGPRS 1 link)	Lowest	H	V	27.17	33.01	Pass
			H	24.02		
		E1	V	27.14		
			H	24.63		
		E2	V	27.49		
			H	24.36		
	Middle	H	V	27.61	33.01	Pass
			H	24.75		
		E1	V	28.01		
			H	24.79		
		E2	V	27.27		
			H	25.12		
	Highest	H	V	27.64	33.01	Pass
			H	24.31		
		E1	V	27.40		
			H	24.23		
		E2	V	26.97		
			H	24.92		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
WCDMA Band V	Lowest	H	V	20.66	38.45	Pass
			H	20.57		
		E1	V	20.25		
			H	20.52		
		E2	V	20.88		
			H	20.56		
	Middle	H	V	20.96	38.45	Pass
			H	20.50		
		E1	V	21.61		
			H	20.29		
		E2	V	21.02		
			H	20.51		
	Highest	H	V	20.99	38.45	Pass
			H	19.67		
		E1	V	20.88		
			H	20.27		
		E2	V	21.09		
			H	20.28		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
WCDMA Band II	Lowest	H	V	21.56	33.01	Pass
			H	20.80		
		E1	V	21.26		
			H	20.32		
		E2	V	21.57		
			H	20.62		
	Middle	H	V	20.62	33.01	Pass
			H	19.85		
		E1	V	20.99		
			H	20.71		
		E2	V	21.15		
			H	20.11		
	Highest	H	V	21.36	33.01	Pass
			H	20.16		
		E1	V	20.92		
			H	20.26		
		E2	V	21.03		
			H	19.68		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
WCDMA Band IV	Lowest	H	V	23.57	33.01	Pass
			H	22.03		
		E1	V	21.93		
			H	21.91		
		E2	V	22.06		
			H	22.60		
	Middle	H	V	22.17	33.01	Pass
			H	21.92		
		E1	V	22.05		
			H	21.74		
		E2	V	21.25		
			H	21.30		
	Highest	H	V	22.14	33.01	Pass
			H	21.30		
		E1	V	22.11		
			H	21.57		
		E2	V	21.46		
			H	22.64		

4.9 Field strength of spurious radiation measurement

<p>Test Requirement:</p>	<p>FCC part22.917(a) and FCC part24.238(a), Part 27.54(h) RSS-132(5.5), RSS-133 (6.5), RSS-139 (6.6)</p>
<p>Test Method:</p>	<p>FCC part2.1053</p>
<p>Limit:</p>	<p>-13dBm</p>
<p>Test setup:</p>	<p>Below 1GHz</p>  <p>Above 1GHz</p>  <p>Substituted method:</p> 

Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. 3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method. 4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $\text{ERP / EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data

Test mode:		GSM850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1648.33	Vertical	-44.12	-13.00	Pass	
2472.35	V	-41.92			
3296.81	V	-39.96			
4120.95	V	-37.72			
4945.03	V	-38.16			
1648.31	Horizontal	-43.79	-13.00	Pass	
2472.48	H	-43.46			
3296.97	H	-39.49			
4121.14	H	-38.98			
4945.28	H	-36.78			
Test mode:		GPRS850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1673.13	Vertical	-44.28	-13.00	Pass	
2509.80	V	-42.22			
3346.30	V	-39.56			
4182.96	V	-38.41			
5019.62	V	-37.57			
1673.12	Horizontal	-45.35	-13.00	Pass	
2509.90	H	-43.62			
3346.48	H	-39.82			
4183.04	H	-38.14			
5019.42	H	-35.88			
Test mode:		EGPRS850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1697.63	Vertical	-44.17	-13.00	Pass	
2546.15	V	-41.36			
3395.40	V	-39.15			
4243.78	V	-38.00			
5092.94	V	-37.18			
1697.48	Horizontal	-45.15	-13.00	Pass	
2546.24	H	-43.36			
3395.25	H	-41.27			
4243.96	H	-39.22			
5092.66	H	-38.63			

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. The above table only shows the worst case channel of each mode.
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:		PCS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3700.49	Vertical	-37.81	-13.00	Pass	
5550.61	V	-35.09			
7400.90	V	-34.49			
9251.15	V	-31.86			
11101.16	V	-29.86			
3700.13	Horizontal	-38.71	-13.00	Pass	
5550.69	H	-36.66			
7400.67	H	-33.67			
9251.07	H	-31.39			
11101.37	H	-30.25			
Test mode:		GPRS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3759.82	Vertical	-37.16	-13.00	Pass	
5639.91	V	-34.45			
7520.13	V	-33.56			
9400.11	V	-30.85			
11279.82	V	-29.59			
3760.09	Horizontal	-38.09	-13.00	Pass	
5639.90	H	-35.50			
7520.16	H	-33.86			
9399.92	H	-30.96			
11280.12	H	-28.56			
Test mode:		EGPRS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3819.58	Vertical	-37.00	-13.00	Pass	
5729.37	V	-35.06			
7639.36	V	-35.08			
9549.15	V	-30.51			
11458.79	V	-30.62			
3819.57	Horizontal	-36.42	-13.00	Pass	
5729.43	H	-35.02			
7639.07	H	-34.96			
9548.95	H	-31.22			
11458.96	H	-29.45			

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. The above table only shows the worst case channel of each mode.
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:		WCDMA Band V		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1652.76	Vertical	-43.90	-13.00	Pass	
2478.95	V	-42.92			
3305.51	V	-40.00			
4131.83	V	-39.84			
4958.28	V	-36.93			
1652.51	Horizontal	-44.87	-13.00	Pass	
2479.10	H	-42.65			
3305.50	H	-41.19			
4131.75	H	-39.34			
4958.33	H	-38.64			
Test mode:		WCDMA Band V		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1672.88	Vertical	-45.20	-13.00	Pass	
2509.33	V	-41.72			
3345.70	V	-39.86			
4182.16	V	-39.73			
5018.54	V	-37.41			
1672.61	Horizontal	-44.79	-13.00	Pass	
2509.19	H	-43.32			
3345.72	H	-40.70			
4181.99	H	-39.51			
5018.49	H	-38.87			
Test mode:		WCDMA Band V		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1693.08	Vertical	-44.06	-13.00	Pass	
2539.51	V	-41.55			
3386.32	V	-41.31			
4233.17	V	-38.44			
5079.67	V	-37.46			
1693.34	Horizontal	-43.76	-13.00	Pass	
2539.71	H	-42.44			
3386.31	H	-40.21			
4232.97	H	-38.86			
5079.57	H	-39.34			

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band II		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3704.73	Vertical	-37.74	-13.00	Pass
5557.31	V	-37.13		
7409.43	V	-34.57		
9261.86	V	-31.80		
11114.21	V	-29.72		
3704.98	Horizontal	-39.07	-13.00	Pass
5557.21	H	-36.09		
7409.56	H	-34.62		
9262.07	H	-31.58		
11114.24	H	-30.70		
Test mode:	WCDMA Band II		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3759.98	Vertical	-38.28	-13.00	Pass
5640.16	V	-35.38		
7520.20	V	-34.86		
9399.74	V	-32.23		
11279.72	V	-30.76		
3760.05	Horizontal	-38.88	-13.00	Pass
5640.05	H	-36.25		
7520.02	H	-34.51		
9400.01	H	-31.96		
11280.11	H	-29.56		
Test mode:	WCDMA Band II		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3815.34	Vertical	-38.14	-13.00	Pass
5722.70	V	-36.61		
7630.16	V	-34.48		
9538.10	V	-32.54		
11445.77	V	-29.28		
3815.19	Horizontal	-39.27	-13.00	Pass
5722.78	H	-36.02		
7630.11	H	-34.53		
9538.04	H	-32.18		
11445.67	H	-28.52		

Remark:


1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:		WCDMA Band IV		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3424.65	Vertical	-38.90	-13.00	Pass	
5137.36	V	-36.08			
10274.18	V	-32.75			
15411.61	V	-29.33			
30823.26	V	--			
3424.78	Horizontal	-38.90	-13.00	Pass	
5137.32	H	-37.27			
10274.54	H	-31.60			
15411.62	H	-28.04			
30822.97	H	--			
Test mode:		WCDMA Band IV		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3480.08	Vertical	-39.98	-13.00	Pass	
5219.92	V	-35.81			
10439.85	V	-30.64			
15659.92	V	-27.85			
31319.95	V	--			
3479.91	Horizontal	-37.95	-13.00	Pass	
5219.80	H	-35.45			
10439.77	H	-32.17			
15660.19	H	-27.70			
31319.80	H	--			
Test mode:		WCDMA Band IV		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3505.29	Vertical	-39.17	-13.00	Pass	
5257.81	V	-35.22			
10515.31	V	-30.60			
15773.54	V	-28.04			
31546.98	V	--			
3505.02	Horizontal	-39.38	-13.00	Pass	
5257.76	H	-36.23			
10515.65	H	-31.13			
15773.54	H	-27.52			
31546.72	H	--			

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

4.10 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part2.1055(a)(1)(b), RSS-132(5.3), RSS-133 (6.3), RSS-139 (6.4)
Test Method:	FCC Part2.1055(a)(1)(b)
Limit:	2.5ppm
Test setup:	 <p style="text-align: center;">Note : Measurement setup for testing on Antenna connector</p>
Test procedure:	<ol style="list-style-type: none"> 1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to –20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass


Measurement Data

Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	20	0.0234	2.5	Pass
	-10	20	0.0243		
	0	15	0.0182		
	10	-8	-0.0090		
	20	8	0.0101		
	30	5	0.0056		
	40	-4	-0.0045		
	50	4	0.0052		
	60	10	0.0114		
Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	16	0.0193	2.5	Pass
	-10	12	0.0146		
	0	10	0.0115		
	10	-12	-0.0144		
	20	14	0.0163		
	30	12	0.0143		
	40	-6	-0.0077		
	50	9	0.0105		
	60	7	0.0083		
Reference Frequency: GSM850 (EGPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	22	0.0267	2.5	Pass
	-10	20	0.0244		
	0	18	0.0209		
	10	-8	-0.0090		
	20	13	0.0159		
	30	10	0.0116		
	40	-5	-0.0058		
	50	3	0.0040		
	60	9	0.0108		

Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
3.8	-20	14	0.0173	2.5	Pass
	-10	18	0.0215		
	0	17	0.0204		
	10	-12	-0.0145		
	20	16	0.0193		
	30	5	0.0056		
	40	1	0.0010		
	50	4	0.0047		
	60	9	0.0113		
Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
3.8	-20	14	0.0171	2.5	Pass
	-10	18	0.0215		
	0	13	0.0160		
	10	-4	-0.0042		
	20	7	0.0085		
	30	10	0.0125		
	40	-5	-0.0055		
	50	1	0.0015		
	60	10	0.0122		
Reference Frequency: PCS1900 (EGPRS 1 link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
3.8	-20	20	0.0239	2.5	Pass
	-10	13	0.0151		
	0	11	0.0133		
	10	-10	-0.0114		
	20	-8	-0.0101		
	30	10	0.0119		
	40	-3	-0.0037		
	50	6	0.0072		
	60	10	0.0114		

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	19	0.0231	2.5	Pass
	-10	20	0.0240		
	0	-8	-0.0091		
	10	2	0.0023		
	20	-8	-0.0099		
	30	11	0.0128		
	40	-7	-0.0085		
	50	9	0.0109		
	60	10	0.0119		
Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880.0MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	18	0.0211	2.5	Pass
	-10	19	0.0222		
	0	-12	-0.0149		
	10	-3	-0.0036		
	20	-5	-0.0064		
	30	6	0.0072		
	40	-12	-0.0143		
	50	5	0.0058		
	60	7	0.0080		
Reference Frequency: WCDMA Band IV Middle channel=1450 channel=1740.0MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	13	0.0156	2.5	Pass
	-10	21	0.0246		
	0	-15	-0.0182		
	10	3	0.0032		
	20	-15	-0.0180		
	30	5	0.0056		
	40	-8	-0.0096		
	50	8	0.0090		
	60	3	0.0030		

4.11 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part2.1055(d)(1)(2), RSS-132(5.3), RSS-133 (6.3), RSS-139 (6.4)
Test Method:	FCC Part2.1055(d)(1)(2)
Limit:	2.5ppm
Test setup:	 <p style="text-align: center;">Temperature Chamber</p> <p style="text-align: center;">Spectrum analyzer</p> <p style="text-align: center;">Att.</p> <p style="text-align: center;">EUT</p> <p style="text-align: center;">Variable Power Supply</p> <p>Note : Measurement setup for testing on Antenna connector</p>
Test procedure:	<ol style="list-style-type: none"> 1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data


Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	15	0.0184	2.5	Pass
	3.8	19	0.0224		
	3.61	-6	-0.0075		
Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	-4	-0.0043	2.5	Pass
	3.8	-9	-0.0110		
	3.61	8	0.0099		
Reference Frequency: GSM850 (EGPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	-7	-0.0089	2.5	Pass
	3.8	0	-0.0005		
	3.61	7	0.0080		

Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	-8	-0.0090	2.5	Pass
	3.8	15	0.0182		
	3.61	-4	-0.0046		
Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	-15	-0.0183	2.5	Pass
	3.8	-6	-0.0078		
	3.61	-11	-0.0128		
Reference Frequency: PCS1900 (EGPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	8	0.0098	2.5	Pass
	3.8	-1	-0.0014		
	3.61	8	0.0093		

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	16	0.0187	2.5	Pass
	3.8	-8	-0.0095		
	3.61	-1	-0.0014		
Reference Frequency: WCDMA Band II Middle channel=940 channel=1880.0MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	7	0.0082	2.5	Pass
	3.8	-16	-0.0194		
	3.61	9	0.0106		
Reference Frequency: WCDMA Band IV Middle channel=1450 channel=1740.0MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.18	9	0.0102	2.5	Pass
	3.8	-10	-0.0115		
	3.61	3	0.0036		

5 Test Setup Photo

Radiated Emission



-----END OF REPORT-----