

Product Number: NB2509-13B-IX060

Product Name: Antenna

Index:

1. Specification / Page 2

2. Characteristics and Reliability Test / Page 3

3. Antenna - S Parameter Test Data / Page 4

4. Antenna - Radiation Pattern Test Data / Page 5 ~ 6

5. Mechanical Drawing / Page 7

Product Number: NB2509-13B-IX060

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency	2400 ~ 2500 MHz 4900 ~ 5900 MHz
S.W.R.	<= 2.0 @ 2400 ~ 2500 MHz <= 2.0 @ 4900 ~ 5900 MHz
Antenna Gain	2 dBi @ 2450MHz // Peak Gain 2 dBi @ 5470MHz // Peak Gain
Polarization	Linear
Impedance	50 Ohm
B. Material & Mechanical Characteristics	
Material of Radiator	FPC
Cable Type	O.D. 1.13 mm // 60mm (BLACK)
Connector Type	Mini Connector
Pull Test	>= 1.0 Kg
C. Environmental	
Operation Temperature	- 40 °C ~ + 85 °C
Storage Temperature	- 40 °C ~ + 85 °C


Product Number: NB2509-13B-IX060

Product Name: Antenna

2. Characteristics and Reliability Test

Test Items		Test Condition and Procedure	Requirements
C1	S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification
C2	Antenna Gain	Set DUT on Antenna Chamber; make individual calibration to test	Directive DUT specification
M1	Vibration	MIL-STD-202G, 201A Amplitude: 0.03 inch (0.76mm); Freq: 10 to 55 Hz 3 directions; 2 hours for each direction	1. No Visual Damage 2. Frequency Tol.<= 5%
M2	Random Drop	Height: 1.5 Meter; 3 directions; 1 time for each direction	1. No parts separated 2. Frequency Tol.<= 5%
M3	Solderability	MIL-STD-202G, 210F, cond. A Solder iron: 350±10°C; Duration: 5 seconds	1. Mounted on PCB 2. No Visual Damage
M4	Terminal-Pull Test	MIL-STD-202G, 211A, cond. A Holding with individual specification; force applied to axis of terminal	1. Directive DUT specification 2. Frequency Tol.<= 5%
M5	Dimension	Inspection of dimension, color, material, package, surface process	Directive DUT specification
E1	Salt Spray	MIL-STD-202G, 101E, cond. B Temp: 35°C; RH: >= 95%; NaCl solution: >= 5%; Time: 48 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E2	Humidity	MIL-STD-202G, 103B, cond. B Temp: 40°C; RH: >= 95%; Time: 48 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E3	Thermal Shock	1 Cycle: - 40°C (30 minutes) to + 80°C (30 minutes) Cycles: 24	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E4	Life (High Temp.)	MIL-STD-202G, 108A, cond. A Temp: 85°C; Time: 96 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
R1	RoHS	With Reference to IEC 62321:2008 with flow chart	Directive RoHS 2002/95/EC
R2	PFOS	With Reference to USA EPA 3540C:1996 by LC/MS	Directive RoHS 2006/122/EC
R3	PFOA	With Reference to USA EPA 3540C:1996 by LC/MS	Directive RoHS 2006/122/EC

3. Antenna - S Parameter Test Data



Product Number: NB2509-13B-IX060

Product Name: Antenna

4. Antenna - Radiation Pattern Test Data

Testing Equipment Specification:

Antenna Anechoic Chamber Dimension: 8 x 4 x 4 m


Quiet Zone: 600mm @1 GHz

Isolation: >100dB @ 1 MHz ~ 10 GHz


Testing Equipment: Agilent 5071B

Received Antenna: 0.7 ~ 6.0 GHz for Gain Calibration


Double Ridged Horn Antenna





H-Plane // 2450MHz



H-Plane // 5470MHz



SIGN		DATE		DESCRIPTION		APPROVER	
ΔΔ							
ΔΔ							
ΔΔ							



Note:
1.Take" * "is the important dimension.
2.Tolerance:Unmarked tolerance refer to

3	NB2509	FPC	25*9mm	1
2	R-CB-113B	Coaxial Cable	SHOWA-O.D. 1.13mm Black	1
1	CI-113	Connector	Mini Connector	1
No.	Part Number	Name	Material	Q'ty

東莞皓諾電子有限公司

Tel:86-0769-89158063
Fax:86-0769-85309196

TITLE: 2.4/5GHz Antenna			
PART NO.: NB2509-13B-IX060		DWG NAME: NB2509-13B-IX060.DWG	
APPROVED BY	CHECKED BY	DESIGNED BY	Tolerance
jeff 2016-09-22	leon 2016-09-22	YD 2016-09-22	UNIT: mm SCALE: 1/1 REVISION: A