Shenzhen Shenlianyu Electronics Co., Ltd

Product specification acknowledgement

| CUSTOMER: Shenzhen Chimele Technology Co., Ltd | | | | | | | | |
|---|--|--|--|--|--|--|--|--|
| Product Name ofCustomer: | | | | | | | | |
| Product Mame ofOurs(Material) Watch-coil tank-shaped magnetic piece KP27*3/16TS/outgoing line 15MM Model: E8-S1C | | | | | | | | |
| APPROVED | | | | | | | | |
| APPROVED Deng Xiang DRAWN Lai Wei DATE 2019/10/16 Address: No. 3, Industrial Road 1, Songgang Xixi Community, Baoan District, Shenzhen City | | | | | | | | |
| Telephone: 15112322462 Fax: 0755-29909524 | | | | | | | | |

pagination 1 of 5

REVISED RECORD

| PEVISON NO | DATE | RE | Change person | |
|------------|------|------------|----------------|--------|
| | | | | |
| REV:01 | | | | |
| REV:02 | | | | |
| REV.UZ | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| ESCRINED | | CHECKED | APPROVED | PACE |
| Lai Wei | | Deng Xiang | Chen Zhanliang | 2 of 5 |

| Specification | | | CISTOMEP/N: | |
|---------------|------------|-------------|---------------------------|------|
| - - | | | PARTNUMBER; | |
| 1.DIMENSION | S: mm | | 8.1MM 13.3MM 27.5MM | |
| APPROVED BY | CHECKED BY | PREPARED BY | DATE | PACE |
| APPROVED BY | | | | FACE |
| | | Lai Wei | 2019/10/17 | |

| Specifcation | | | | | CUSTON | /IERP/N | : | |
|--|--|-----------------------------|------|-----------------------------|---------------------------|---------|---------------------------------------|-----------------|
| | | | | | PARTNUI | MBER: | | |
| 5.WINDI | NG DETA | ILS: | | | | | | |
| Wdy.NO. | Start | Start Finish Turns | | Wire Dia Wdg.TyepeSprad/los | | ad/lose | Wdg.Directio | n Turns/Layer |
| | S | F | 16TS | 0.05*75P | Double layer close around | | Positive and negative around | 2layer/16TS |
| 6.ELECTRICAL CHARACTERISTICS: PARAMETERS UNIN LIMTI | | | | | | | | |
| | PARAME | ETERS | | | | | | |
| | | ETERS | | | JNIN uh | | | LIMTI 2.2±5% |
| Induct | PARAME | TERS | | | | | 12 | |
| Induct | PARAME | TERS 100KH (Hz/1v | z/1v | l | | | 12 | 2 ±5 % |
| Induct | PARAME ance Is@ Q @100K | TERS 100KH (Hz/1v | z/1v | l | uh | | 12 | 2.2±5% 45Min |
| Induct | PARAME ance Is@ Q @100K | TERS 100KH (Hz/1v | z/1v | l | uh | | 12 | 2.2±5% 45Min |
| Induct | PARAME ance Is@ Q @100K R @10 | TERS 100KH KHz/1v OKHz/1 | z/1v | | uh | | 12 | 2.2±5% 45Min |

| MATERIAL | | | | CUST P/N: | OMER | | |
|--------------------|---------------------|------------------|--------------------|--------------|-----------|---------------------|-----------------|
| LIST | | | | PART | NUMBER: | | |
| NO. | Material name | Descrip | tion | Man | ufacturer | | Material |
| 1 | silk-covered wire | 0.05*75P | | | | | |
| 2 | Lead-free tin strip | high temperatu | re | | | | |
| 3 magnetic sheet | | diameter27.5 | diameter27.5MM | | | ferrite. zinc.PC | Manganese 95 |
| 4 | glue | Resin glue | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | I | | | | |
| APPROVED BY 承 认 | | CHECKED BY 审查 | THE PREP 中 中 中 中 中 | | DAT 日期 | | PAGE 页码 |
| | | · - | | i伟 | 2019/1 | | 5 of 5 |