



RF Exposure Evaluation Report

Report Reference No. :	MTEB24060231-H	
FCC ID :	2BAA5-MNRRX	
Compiled by (position+printed name+signature)..:	File administrators Alisa Luo	
Supervised by (position+printed name+signature)..:	Test Engineer Sunny Deng	
Approved by (position+printed name+signature)..:	Manager Yvette Zhou	
Date of issue..... :	Jun. 18,2024	
Representative Laboratory Name. :	Shenzhen Most Technology Service Co., Ltd.	
Address..... :	No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.	
Applicant's name :	AcoustMax International Corporation	
Address..... :	Room 501,Lingyun Building ,HongLang North 2 Road, Baoan District, ShenZhen, China	
Test specification/ Standard :	47 CFR Part 1.1307;47 CFR Part 1.1310 KDB447498D01 General RF Exposure Guidance v06	
TRF Originator..... :	Shenzhen Most Technology Service Co., Ltd.	
Shenzhen Most Technology Service Co., Ltd. All rights reserved.		
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.		
Test item description :	MONSTER ROCKIN ROLLER X	
Trade Mark..... :	Monster	
Model/Type reference..... :	MNRRX	
Listed Models	MNRRX-2,MNRRX Plus,MNRRX-S-2,MNRRX-C	
Modulation Type..... :	GFSK GFSK, $\pi/4$ DQPSK	
Operation Frequency..... :	2402MHz to 2480MHz	
Hardware Version.....	V01	
Software Version.....	V1.0	
Rating..... :	AC 90V~240V 50/60Hz 2A 250W	
Result..... :	PASS	

TEST REPORT

Equipment under Test : MONSTER ROCKIN ROLLER X

Model /Type : MNRRX

Listed Models : MNRRX-2,MNRRX Plus,MNRRX-S-2,MNRRX-C

Remark : Only the model name and Appearance is different.

Applicant : AcoustMax International Corporation

Address : Room 501,Lingyun Building ,HongLang North 2 Road, Baoan District, ShenZhen, China

Manufacturer : AcoustMax International Corporation

Address : Room 501,Lingyun Building ,HongLang North 2 Road, Baoan District, ShenZhen, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2024.06.18	Initial Issue	Alisa Luo

2. SAR Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.1.2 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot R^2)$ Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.1.3 EUT RF Exposure

BLE

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402 MHz)	4.470	4.470 ± 1	5.47
Middle(2440MHz)	4.846	4.846 ± 1	5.846
Highest(2480MHz)	4.878	4.878 ± 1	5.878

BLE

Worst case: GFSK						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest(2480MHz)	5.878	3.87	0	0.00077	1.0	Pass

Note: 1) Refer to report MTEB24060231-R for EUT test Max Conducted average Output Power value.

Note: 2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (3.87 * 1) / (4 * 3.1416 * 20^2) = 0.00077$

BT classic

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	2.317	2.317±1	3.317
Middle(2441MHz)	2.739	2.739±1	3.739
Highest(2480MHz)	5.231	5.231±1	6.231

π /4DQPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	2.325	2.325±1	3.325
Middle(2441MHz)	2.694	2.694±1	3.694
Highest(2480MHz)	5.235	5.235±1	6.235

Worst case: π /4DQPSK						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest(2480MHz)	6.235	4.20	0	0.00084	1.0	Pass

Note: 1) Refer to report MTEB24060231-R1 for EUT test Max Conducted average Output Power value.

Note: 2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (4.20 * 1) / (4 * 3.1416 * 20^2) = 0.00084$

Note: 3) EUT's Bluetooth module is more than 20cm away from the human body.

.....**THE END OF REPORT**.....