# FCC §15.247 (i), §2.1091 - RF Exposure

FCC ID: 2BAARAT-M261

#### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

**Limits for Occupational / Controlled Exposure** 

| Frequency<br>Range (MHz) | Electric Field<br>Strength (E)<br>(V/m) | Magnetic Field<br>Strength (H)<br>(A/m) | Power Density (S)<br>(mW/ cm²) | Averaging Time<br> E  <sup>2</sup> , H  <sup>2</sup> or S<br>(minutes) |  |
|--------------------------|---|---|--------------------------------|--|--|
| 0.3-3.0                  | 614                                     | 1.63                                    | (100)*                         | 6  |  |
| 3.0-30                   | 1842 / f                                | 4.89 / f                                | (900 / f)*                     | 6  |  |
| 30-300                   | 61.4                                    | 0.163                                   | 1.0                            | 6  |  |
| 300-1500                 |   |   | F/300                          | 6  |  |
| 1500-100,000             |   |   | 5                              | 6  |  |

Note: *f* is frequency in MHz

### **Limits for General Population / Uncontrolled Exposure**

| Frequency<br>Range (MHz) | Electric Field<br>Strength (E)<br>(V/m) | Magnetic Field<br>Strength (H)<br>(A/m) | Power Density (S)<br>(mW/ cm²) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|--------------------------|---|---|--------------------------------|--|
| 0.3-1.34                 | 614                                     | 1.63                                    | (100)*                         | 30   |
| 1.34-30                  | 824/f                                   | 2.19/f                                  | (180/f)*                       | 30   |
| 30-300                   | 27.5                                    | 0.073                                   | 0.2                            | 30   |
| 300-1500                 |   |   | F/1500                         | 30   |
| 1500-100,000             |   |   | 1.0                            | 30   |

Note: f = frequency in MHz

<sup>\* =</sup> Power density limit is applicable at frequencies greater than 100 MHz

<sup>\* =</sup> Plane-wave equivalent power density

## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

## Test Result of RF Exposure Evaluation

|              | Modes&<br>Channel<br>Freq.<br>(MHz) | Tune up<br>Produce<br>power | Maximu<br>m peak<br>output<br>power<br>(dBm) | Output<br>power<br>to<br>antenna<br>(mW) | Antenna<br>Gain<br>(numeric) | Power<br>Density<br>(S)<br>(mW/<br>cm2) | Limit<br>(mW<br>/<br>cm2 | Result |
|--------------|-------------------------------------|-----------------------------|--|--|------------------------------|---|--------------------------|--------|
| EDR          | 8DPSK&L<br>CH                       | 4±1                         | 5  | 3.1623                                   | 0.8551<br>(-0.68dBi)         | 0.0005                                  | 1                        | Pass   |
| 2.4G<br>WIFI | 802.11b&2<br>412                    | 15±1                        | 16   | 39.8107                                  | 1.9953<br>(3dBi)             | 0.0158                                  | 1                        | Pass   |
| 5.2GWIFI     | 802.11a20<br>&5240                  | 12±1                        | 13   | 19.9526                                  | 2.2131<br>(3.45dBi)          | 0.0088                                  | 1                        | Pass   |
| 5.8GWIFI     | 802.11ac8<br>0&5775                 | 11±1                        | 12   | 15.8489                                  | 2.2131<br>(3.45dBi)          | 0.0070                                  | 1                        | Pass   |

EDR+2.4GWIFI+5GWIFI supported simultaneous transmission:

EDR+2.4GWIFI+5GWIFI MIMO :  $\sum$ MPE Ratio =0.0005+0.0158+0.0088=0.0251 \le 1, So passed.