



中国认可
国际互认
检测
TESTING
CNAS L6451



Appendix B

Highest Test Plots

Table of Contents

1. 2.4G Body-worn 0mm SAR 3

1. 2.4G Body-worn 0mm SAR

Date: 12.12.2024

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q24112535-2E

DUT: WüM Voice Remote 2; Type: WVR002; Serial: S24112535-007

Communication System: UID 0, Bluetooth (0); Communication System Band: BLE; Frequency: 2402 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005
Medium parameters used (interpolated): $f = 2402\text{ MHz}$; $\sigma = 1.743\text{ S/m}$; $\epsilon_r = 38.571$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ConvF(7.95, 7.95, 7.95) @ 2402 MHz; Calibrated: 29.04.2024
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1197
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Configuration/Front side BLE 1M 2402/Area Scan (6x17x1); Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 0.0475 W/kg

Configuration/Front side BLE 1M 2402/Zoom Scan (7x7x7)/Cube 0; Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 5.091 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.175 W/kg
SAR(1 g) = 0.036 W/kg; SAR(10 g) = 0.013 W/kg
Smallest distance from peaks to all points 3 dB below = 6.5 mm
Ratio of SAR at M2 to SAR at M1 = 40.8%

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 0.115 W/kg

