

# FCC ID: 2BABY6361401USB

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^* [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz ;

Power and distance are rounded to the nearest mW and mm before calculation ;

The result is rounded to one decimal place for comparison ;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

Antenna Gain: 3.24 dBi

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	tune up maximum power(dBm)	Result calculation	1-g SAR
DH5	Ant1	2402	-4.42	0	0.310	3
		2441	-3.25	0	0.312	3
		2480	-2.27	0	0.315	3
2DH5	Ant1	2402	-4.35	0	0.310	3
		2441	-2.86	0	0.312	3
		2480	-1.75	0	0.315	3
3DH5	Ant1	2402	-4.25	0	0.310	3
		2441	-2.72	0	0.312	3
		2480	-1.54	0	0.315	3

## Conclusion:

For the max result :  $0.315 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

Signature:



Date: 2024.3.27

**NAME AND TITLE (Please print or type):** Lisa Wang/Manager

**COMPANY (Please print or type):** Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China