



## Band edge measurements


DH5\_Ant1\_Low\_2402




DH5\_Ant1\_High\_2480




DH5\_Ant1\_Low\_Hop\_2402




### DH5\_Ant1\_High\_Hop\_2480




### 2DH5\_Ant1\_Low\_2402




### 2DH5\_Ant1\_High\_2480



## 3DH5\_Ant1\_Low\_2402




## 3DH5\_Ant1\_High\_2480




### Conducted Spurious Emission


DH5 Ant1 2402 30~1000




DH5 Ant1 2402 1000~26500




DH5 Ant1 2441 30~1000




## DH5\_Ant1\_2441\_1000~26500




## DH5\_Ant1\_2480\_30~1000



## DH5\_Ant1\_2480\_1000~26500




## 2DH5\_Ant1\_2402\_30~1000




## 2DH5\_Ant1\_2402\_1000~26500




## 2DH5\_Ant1\_2441\_30~1000




## 2DH5\_Ant1\_2441\_1000~26500




## 2DH5\_Ant1\_2480\_30~1000




## 2DH5\_Ant1\_2480\_1000~26500




### 3DH5\_Ant1\_2402\_30~1000



### 3DH5\_Ant1\_2402\_1000~26500




### 3DH5\_Ant1\_2441\_30~1000







### 3DH5\_Ant1\_2441\_1000~26500



### 3DH5\_Ant1\_2480\_30~1000



### 3DH5\_Ant1\_2480\_1000~26500



## 9.7 RADIATED SPURIOUS EMISSION

### 9.7.1 Applicable Standard

According to FCC Part 15.247(d), 15.205, 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02  
According to IC RSS-Gen and RSS-247

### 9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

| MHz               | MHz                 | MHz           | GHz         |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110       | 16.42-16.423        | 399.9-410     | 4.5-5.15    |
| 10.495-0.505      | 16.69475-16.69525   | 608-614       | 5.35-5.46   |
| 2.1735-2.1905     | 16.80425-16.80475   | 960-1240      | 7.25-7.75   |
| 4.125-4.128       | 25.5-25.67          | 1300-1427     | 8.025-8.5   |
| 4.17725-4.17775   | 37.5-38.25          | 1435-1626.5   | 9.0-9.2     |
| 4.20725-4.20775   | 73-74.6             | 1645.5-1646.5 | 9.3-9.5     |
| 6.215-6.218       | 74.8-75.2           | 1660-1710     | 10.6-12.7   |
| 6.26775-6.26825   | 123-138             | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 149.9-150.05        | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.7-156.9         | 2690-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 162.0125-167.17     | 3260-3267     | 23.6-24.0   |
| 12.29-12.293      | 167.72-173.2        | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 240-285             | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 322-335.4           | 3600-4400     | (2)         |
| 13.36-13.41       |                     |               |             |

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

| Restricted Frequency(MHz) | Field Strength ( $\mu\text{V}/\text{m}$ ) | Field Strength ( $\text{dB}\mu\text{V}/\text{m}$ ) | Measurement Distance |
|---------------------------|---|--|----------------------|
| 0.009-0.490               | 2400/F(KHz)                               | 20 log ( $\mu\text{V}/\text{m}$ )                  | 300                  |
| 0.490-1.705               | 24000/F(KHz)                              | 20 log ( $\mu\text{V}/\text{m}$ )                  | 30                   |
| 1.705-30                  | 30  | 29.5   | 30                   |
| 30-88                     | 100                                       | 40   | 3                    |
| 88-216                    | 150                                       | 43.5   | 3                    |
| 216-960                   | 200                                       | 46   | 3                    |
| Above 960                 | 500                                       | 54   | 3                    |

### 9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

### 9.7.5 Test Results

#### ■ Spurious Emission below 30MHz(9KHz to 30MHz)

|                    |           |
|--------------------|-----------|
| Temperature:       | 22° C     |
| Relative Humidity: | 45%       |
| ATM Pressure:      | 1011 mbar |

| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission<br>Level(dBuV/m) |    | Limit 3m(dBuV/m) |    | Over(dB) |    |
|----------------|-----------------|---------------------------|----|------------------|----|----------|----|
|                |                 | PK                        | AV | PK               | AV | PK       | AV |
| --             | --              | --                        | -- | --               | -- | --       | -- |

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance}/\text{test distance})$  (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

#### ■ Spurious Emission Above 1GHz(1GHz to 25GHz)

All the antenna(Antenna 1) and modes(GFSK,  $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) result recorded was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV/m) |       | Limit 3m(dBuV/m) |       | Over(dB) |      |
|-------------|-----------|------------------------|-------|------------------|-------|----------|------|
|             | H/V       | PK                     | AV    | PK               | AV    | PK       | AV   |
| 4803.75     | V         | 53.07                  | 49.16 | 74.00            | 54.00 | 20.93    | 4.84 |
| 14553.75    | V         | 63.70                  | 49.91 | 74.00            | 54.00 | 10.30    | 4.09 |
| 17621.25    | V         | 70.37                  | 49.70 | 74.00            | 54.00 | 3.63     | 4.30 |
| 4803.75     | H         | 56.09                  | 51.68 | 74.00            | 54.00 | 17.91    | 2.32 |
| 11506.87    | H         | 62.07                  | 49.64 | 74.00            | 54.00 | 11.93    | 4.36 |
| 17596.87    | H         | 69.80                  | 50.23 | 74.00            | 54.00 | 4.20     | 3.77 |

Test mode: GFSK Frequency: Channel 39: 2441MHz

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV/m) |       | Limit 3m(dBuV/m) |       | Over(dB) |      |
|-------------|-----------|------------------------|-------|------------------|-------|----------|------|
|             | H/V       | PK                     | AV    | PK               | AV    | PK       | AV   |
| 4880.625    | V         | 49.35                  | 46.64 | 74.00            | 54.00 | 24.65    | 7.36 |
| 14675.62    | V         | 65.12                  | 50.25 | 74.00            | 54.00 | 8.88     | 3.75 |
| 17626.87    | V         | 69.64                  | 49.48 | 74.00            | 54.00 | 4.36     | 4.52 |
| 4880.625    | H         | 56.59                  | 50.82 | 74.00            | 54.00 | 17.41    | 3.18 |
| 14662.5     | H         | 64.22                  | 50.20 | 74.00            | 54.00 | 9.78     | 3.80 |
| 17593.12    | H         | 70.51                  | 50.06 | 74.00            | 54.00 | 3.49     | 3.94 |

Test mode: GFSK Frequency: Channel 78: 2480MHz

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV/m) |       | Limit 3m(dBuV/m) |       | Over(dB) |      |
|-------------|-----------|------------------------|-------|------------------|-------|----------|------|
|             | H/V       | PK                     | AV    | PK               | AV    | PK       | AV   |
| 4959.375    | V         | 52.04                  | 50.18 | 74.00            | 54.00 | 21.96    | 3.82 |
| 14671.87    | V         | 64.51                  | 49.99 | 74.00            | 54.00 | 9.49     | 4.01 |
| 17619.37    | V         | 70.20                  | 49.76 | 74.00            | 54.00 | 3.80     | 4.24 |
| 4959.375    | H         | 55.15                  | 51.99 | 74.00            | 54.00 | 18.85    | 2.01 |
| 14596.87    | H         | 64.36                  | 50.35 | 74.00            | 54.00 | 9.64     | 3.65 |
| 17604.37    | H         | 70.86                  | 50.54 | 74.00            | 54.00 | 3.14     | 3.46 |

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All the antenna(Antenna 1) and modes(GFSK,  $\pi/4$ -DQPSK, 8DPSK, Hopping) mode have been tested, and the worst(Antenna 1,GFSK, Hopping) result recorded was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

| Frequency (MHz) | Polarity H/V | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m) |
|-----------------|--------------|-----------------------|-------------------|-----------------------|-------------------|
| 2380.1          | H            | 51.61                 | 74.00             | 42.58                 | 54.00             |
| 2389.14         | V            | 49.93                 | 74.00             | 43.57                 | 54.00             |

Test mode: GFSK Frequency: Channel 78: 2480MHz


| Frequency (MHz) | Polarity H/V | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m) |
|-----------------|--------------|-----------------------|-------------------|-----------------------|-------------------|
| 2483.56         | H            | 56.43                 | 74.00             | 43.23                 | 54.00             |
| 2483.58         | V            | 56.24                 | 74.00             | 42.56                 | 54.00             |

Test mode: GFSK Frequency: Hopping


| Frequency (MHz) | Polarity H/V | PK(dBuV/m) (VBW=3MHz) | Limit 3m (dBuV/m) | AV(dBuV/m) (VBW=10Hz) | Limit 3m (dBuV/m) |
|-----------------|--------------|-----------------------|-------------------|-----------------------|-------------------|
| 2399.68         | H            | 50.03                 | 74.00             | 42.32                 | 54.00             |
| 2483.04         | H            | 47.58                 | 74.00             | 41.23                 | 54.00             |
| 2399.03         | V            | 52.54                 | 74.00             | 41.44                 | 54.00             |
| 2482.09         | V            | 51.89                 | 74.00             | 42.50                 | 54.00             |

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


**Test Model**      **Spurious Emission in Restricted Band 2310-2390MHz**  
**Channel 0: 2402MHz**      **GFSK**      **V**




**Test Model**      **Spurious Emission in Restricted Band 2310-2390MHz**  
**Channel 0: 2402MHz**      **GFSK**      **H**




**Test Model**      **Spurious Emission in Restricted Band 2483.5-2500MHz**  
**Channel 78: 2480MHz**      **GFSK**      **V**




**Test Model**      **Spurious Emission in Restricted Band 2483.5-2500MHz**  
**Channel 78: 2480MHz**      **GFSK**      **H**



**Test Model** Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz Hopping GFSK V




**Test Model** Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz Hopping GFSK H





- Spurious Emission below 1GHz(30MHz to 1GHz)
- All the antenna(Antenna 1) and modes(GFSK,  $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) result recorded was report as below:


|              |                      |
|--------------|----------------------|
| Mode:        | BT 2402              |
| Environment: | Temp: 25°C; Humi:60% |



| Suspected Data List |             |                |               |                |          |                |             |          |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity |
| 1                   | 343.623     | 58.65          | -13.46        | 45.19          | PK       | 46.00          | 0.81        | Vertical |
| 2                   | 393.143     | 48.02          | -11.82        | 36.20          | PK       | 46.00          | 9.80        | Vertical |
| 3                   | 442.662     | 44.41          | -11.17        | 33.24          | PK       | 46.00          | 12.76       | Vertical |
| 4                   | 540.730     | 40.62          | -9.23         | 31.39          | PK       | 46.00          | 14.61       | Vertical |
| 5                   | 638.798     | 46.65          | -6.31         | 40.34          | PK       | 46.00          | 5.66        | Vertical |
| 6                   | 933.974     | 39.33          | -2.55         | 36.78          | PK       | 46.00          | 9.22        | Vertical |

| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 343.6236    | -13.46        | 43.84             | 46.00             | 2.16           |
| 2               | 393.1431    | -11.82        | 34.35             | 46.00             | 11.65          |
| 3               | 442.6627    | -11.17        | 32.23             | 46.00             | 13.77          |
| 4               | 540.7307    | -9.23         | 29.74             | 46.00             | 16.26          |
| 5               | 638.7988    | -6.31         | 38.69             | 46.00             | 7.31           |
| 6               | 933.974     | -2.55         | 35.49             | 46.00             | 10.51          |


|              |                      |
|--------------|----------------------|
| Mode:        | BT 2402              |
| Environment: | Temp: 25°C; Humi:60% |



| Suspected Data List |             |                |               |                |          |                |             |            |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity   |
| 1                   | 343.623     | 58.48          | -13.46        | 45.02          | PK       | 46.00          | 0.98        | Horizontal |
| 2                   | 442.662     | 48.07          | -11.17        | 36.90          | PK       | 46.00          | 9.10        | Horizontal |
| 3                   | 638.798     | 49.97          | -6.31         | 43.66          | PK       | 46.00          | 2.34        | Horizontal |
| 4                   | 688.318     | 38.78          | -6.04         | 32.74          | PK       | 46.00          | 13.26       | Horizontal |
| 5                   | 737.837     | 48.37          | -5.40         | 42.97          | PK       | 46.00          | 3.03        | Horizontal |
| 6                   | 835.905     | 45.78          | -3.96         | 41.82          | PK       | 46.00          | 4.18        | Horizontal |

| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 343.6236    | -13.46        | 43.35             | 46.00             | 2.65           |
| 2               | 442.6627    | -11.17        | 35.66             | 46.00             | 10.34          |
| 3               | 638.7988    | -6.31         | 41.78             | 46.00             | 4.22           |
| 4               | 688.3183    | -6.04         | 31.22             | 46.00             | 14.78          |
| 5               | 737.8378    | -5.40         | 41.29             | 46.00             | 4.71           |
| 6               | 835.9059    | -3.96         | 40.14             | 46.00             | 5.86           |


|              |                      |
|--------------|----------------------|
| Mode:        | BT 2441              |
| Environment: | Temp: 25°C; Humi:60% |



| Suspected Data List |             |                |               |                |          |                |             |          |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity |
| 1                   | 343.623     | 58.14          | -13.46        | 44.68          | PK       | 46.00          | 1.32        | Vertical |
| 2                   | 393.143     | 48.59          | -11.82        | 36.77          | PK       | 46.00          | 9.23        | Vertical |
| 3                   | 442.662     | 44.27          | -11.17        | 33.10          | PK       | 46.00          | 12.90       | Vertical |
| 4                   | 638.798     | 46.25          | -6.31         | 39.94          | PK       | 46.00          | 6.06        | Vertical |
| 5                   | 737.837     | 41.15          | -5.40         | 35.75          | PK       | 46.00          | 10.25       | Vertical |
| 6                   | 933.974     | 38.92          | -2.55         | 36.37          | PK       | 46.00          | 9.63        | Vertical |

| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 343.6236    | -13.46        | 42.71             | 46.00             | 3.29           |
| 2               | 393.1431    | -11.82        | 35.16             | 46.00             | 10.84          |
| 3               | 442.6627    | -11.17        | 31.49             | 46.00             | 14.51          |
| 4               | 638.7988    | -6.31         | 38.33             | 46.00             | 7.67           |
| 5               | 737.8378    | -5.40         | 33.98             | 46.00             | 12.02          |
| 6               | 933.974     | -2.55         | 34.60             | 46.00             | 11.40          |


|              |                      |
|--------------|----------------------|
| Mode:        | BT 2441              |
| Environment: | Temp: 25°C; Humi:60% |



| Suspected Data List |             |                |               |                |          |                |             |            |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity   |
| 1                   | 343.623     | 58.17          | -13.46        | 44.71          | PK       | 46.00          | 1.29        | Horizontal |
| 2                   | 442.662     | 48.32          | -11.17        | 37.15          | PK       | 46.00          | 8.85        | Horizontal |
| 3                   | 638.798     | 49.91          | -6.31         | 43.60          | PK       | 46.00          | 2.40        | Horizontal |
| 4                   | 737.837     | 48.61          | -5.40         | 43.21          | PK       | 46.00          | 2.79        | Horizontal |
| 5                   | 835.905     | 45.99          | -3.96         | 42.03          | PK       | 46.00          | 3.97        | Horizontal |
| 6                   | 933.974     | 40.15          | -2.55         | 37.60          | PK       | 46.00          | 8.40        | Horizontal |

| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 343.6236    | -13.46        | 43.07             | 46.00             | 2.93           |
| 2               | 442.6627    | -11.17        | 35.87             | 46.00             | 10.13          |
| 3               | 638.7988    | -6.31         | 42.16             | 46.00             | 3.84           |
| 4               | 737.8378    | -5.40         | 41.77             | 46.00             | 4.23           |
| 5               | 835.9059    | -3.96         | 40.95             | 46.00             | 5.05           |
| 6               | 933.974     | -2.55         | 36.52             | 46.00             | 9.48           |


|              |                      |
|--------------|----------------------|
| Mode:        | BT 2480              |
| Environment: | Temp: 25°C; Humi:60% |



| Suspected Data List |             |                |               |                |          |                |             |          |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| NO.                 | Freq. [MHz] | Reading [dBµV] | Factor [dB/m] | Level [dBµV/m] | Detector | Limit [dBµV/m] | Margin [dB] | Polarity |
| 1                   | 53.3033     | 54.65          | -17.65        | 37.00          | PK       | 40.00          | 3.00        | Vertical |
| 2                   | 343.623     | 58.48          | -13.46        | 45.02          | PK       | 46.00          | 0.98        | Vertical |
| 3                   | 393.143     | 48.87          | -11.82        | 37.05          | PK       | 46.00          | 8.95        | Vertical |
| 4                   | 540.730     | 40.52          | -9.23         | 31.29          | PK       | 46.00          | 14.71       | Vertical |
| 5                   | 638.798     | 46.35          | -6.31         | 40.04          | PK       | 46.00          | 5.96        | Vertical |
| 6                   | 933.974     | 39.21          | -2.55         | 36.66          | PK       | 46.00          | 9.34        | Vertical |

| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBµV/m] | QP Limit [dBµV/m] | QP Margin [dB] |
| 1               | 53.3033     | -17.65        | 35.77             | 40.00             | 4.23           |
| 2               | 343.6236    | -13.46        | 43.15             | 46.00             | 2.85           |
| 3               | 393.1431    | -11.82        | 35.18             | 46.00             | 10.82          |
| 4               | 540.7307    | -9.23         | 30.26             | 46.00             | 15.74          |
| 5               | 638.7988    | -6.31         | 39.01             | 46.00             | 6.99           |
| 6               | 933.974     | -2.55         | 34.99             | 46.00             | 11.01          |

|              |                      |
|--------------|----------------------|
| Mode:        | BT 2480              |
| Environment: | Temp: 25°C; Humi:60% |


**Suspected Data List**

| NO. | Freq. [MHz] | Reading [dBµV] | Factor [dB/m] | Level [dBµV/m] | Detector | Limit [dBµV/m] | Margin [dB] | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| 1   | 196.036     | 50.14          | -17.38        | 32.76          | PK       | 43.50          | 10.74       | Horizontal |
| 2   | 343.623     | 57.82          | -13.46        | 44.36          | PK       | 46.00          | 1.64        | Horizontal |
| 3   | 442.662     | 48.31          | -11.17        | 37.14          | PK       | 46.00          | 8.86        | Horizontal |
| 4   | 638.798     | 49.69          | -6.31         | 43.38          | PK       | 46.00          | 2.62        | Horizontal |
| 5   | 737.837     | 48.33          | -5.40         | 42.93          | PK       | 46.00          | 3.07        | Horizontal |
| 6   | 835.905     | 45.94          | -3.96         | 41.98          | PK       | 46.00          | 4.02        | Horizontal |

**Final Data List**

| NO. | Freq. [MHz] | Factor [dB/m] | QP Value [dBµV/m] | QP Limit [dBµV/m] | QP Margin [dB] |
|-----|-------------|---------------|-------------------|-------------------|----------------|
| 1   | 196.036     | -17.38        | 31.10             | 43.50             | 12.40          |
| 2   | 343.6236    | -13.46        | 42.70             | 46.00             | 3.30           |
| 3   | 442.6627    | -11.17        | 35.84             | 46.00             | 10.16          |
| 4   | 638.7988    | -6.31         | 42.08             | 46.00             | 3.92           |
| 5   | 737.8378    | -5.40         | 41.47             | 46.00             | 4.53           |
| 6   | 835.9059    | -3.96         | 40.52             | 46.00             | 5.48           |

**9.8 CONDUCTED EMISSION TEST**

**9.8.1 Applicable Standard**

According to FCC Part 15.207  
 According to IC RSS-Gen 8.8

**9.8.2 Conformance Limit**

| Conducted Emission Limit |            |         |
|--------------------------|------------|---------|
| Frequency(MHz)           | Quasi-peak | Average |
| 0.15-0.5                 | 66-56      | 56-46   |
| 0.5-5.0                  | 56         | 46      |
| 5.0-30.0                 | 60         | 50      |

Note: 1. The lower limit shall apply at the transition frequencies  
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

**9.8.3 Test Configuration**

Test according to clause 7.3 conducted emission test setup


**9.8.4 Test Procedure**

The EUT was placed on a table which is 0.8m above ground plane.  
 Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
 Repeat above procedures until all frequency measured were complete.

**9.8.5 Test Results**

Pass

The AC120V &240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #1

Phase: **N**

Temperature: 21.9

Limit: (CE)FCC PART 15 class B\_QP

Power: AC 120V/60Hz


Humidity: 58 %

Mode: BT

Note:

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1500       | 49.70                    | 9.53                    | 59.23                    | 66.00         | -6.77      | QP       |         |
| 2   |     | 0.1500       | 15.11                    | 9.53                    | 24.64                    | 56.00         | -31.36     | AVG      |         |
| 3   |     | 0.1850       | 48.17                    | 9.53                    | 57.70                    | 64.26         | -6.56      | QP       |         |
| 4   |     | 0.1850       | 33.31                    | 9.53                    | 42.84                    | 54.26         | -11.42     | AVG      |         |
| 5   | *   | 0.2450       | 45.91                    | 9.53                    | 55.44                    | 61.92         | -6.48      | QP       |         |
| 6   |     | 0.2450       | 27.74                    | 9.53                    | 37.27                    | 51.92         | -14.65     | AVG      |         |
| 7   |     | 0.4450       | 34.48                    | 9.54                    | 44.02                    | 56.97         | -12.95     | QP       |         |
| 8   |     | 0.4450       | 16.23                    | 9.54                    | 25.77                    | 46.97         | -21.20     | AVG      |         |
| 9   |     | 4.3650       | 37.58                    | 9.57                    | 47.15                    | 56.00         | -8.85      | QP       |         |
| 10  |     | 4.3650       | 19.19                    | 9.57                    | 28.76                    | 46.00         | -17.24     | AVG      |         |
| 11  |     | 21.3050      | 32.69                    | 10.01                   | 42.70                    | 60.00         | -17.30     | QP       |         |
| 12  |     | 21.3050      | 19.49                    | 10.01                   | 29.50                    | 50.00         | -20.50     | AVG      |         |





Site Conduction #1

Phase: **L1**

Temperature: 21.9

Limit: (CE)FCC PART 15 class B\_QP

Power: AC 120V/60Hz

Humidity: 58 %

Mode: BT

Note:

| No. | Mk. | Freq.  | Reading Level | Correct Factor | Measurement | Limit | Over   | Detector | Comment |
|-----|-----|--------|---------------|----------------|-------------|-------|--------|----------|---------|
|     |     | MHz    | dBuV          | dB             | dBuV        | dBuV  | dB     |          |         |
| 1   |     | 0.1500 | 48.87         | 9.53           | 58.40       | 66.00 | -7.60  | QP       |         |
| 2   |     | 0.1500 | 15.54         | 9.53           | 25.07       | 56.00 | -30.93 | AVG      |         |
| 3   | *   | 0.1800 | 48.44         | 9.53           | 57.97       | 64.49 | -6.52  | QP       |         |
| 4   |     | 0.1800 | 29.38         | 9.53           | 38.91       | 54.49 | -15.58 | AVG      |         |
| 5   |     | 0.1950 | 46.97         | 9.53           | 56.50       | 63.82 | -7.32  | QP       |         |
| 6   |     | 0.1950 | 30.67         | 9.53           | 40.20       | 53.82 | -13.62 | AVG      |         |
| 7   |     | 0.2400 | 45.64         | 9.53           | 55.17       | 62.10 | -6.93  | QP       |         |
| 8   |     | 0.2400 | 27.40         | 9.53           | 36.93       | 52.10 | -15.17 | AVG      |         |
| 9   |     | 0.2650 | 43.89         | 9.53           | 53.42       | 61.27 | -7.85  | QP       |         |
| 10  |     | 0.2650 | 26.30         | 9.53           | 35.83       | 51.27 | -15.44 | AVG      |         |
| 11  |     | 4.1050 | 38.79         | 9.57           | 48.36       | 56.00 | -7.64  | QP       |         |
| 12  |     | 4.1050 | 18.80         | 9.57           | 28.37       | 46.00 | -17.63 | AVG      |         |

## 9.9 ANTENNA APPLICATION

### 9.9.1 Antenna Requirement

| Standard                   | Requirement  |
|----------------------------|--|
| FCC CRF Part15.203         | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.  |
| FCC 47 CFR Part 15.247 (b) | If transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.   |
| RSS-Gen Section 6.8        | The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.   |
| RSS-247 Section 5.4        | If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain. |

### 9.9.2 Result

PASS.

- Note:
- Antenna use a permanently attached antenna which is not replaceable.
  - Not using a standard antenna jack or electrical connector for antenna replacement
  - The antenna has to be professionally installed (please provide method of installation)

Please refer to the attached documentInternal Photos to show the antenna connector.

\*\*\* End of Report \*\*\*