

# RF MEASUREMENT REPORT

---

**FCC ID:** 2BADG-SUBWOOFER  
**Applicant:** Soundvision Technologies DBA TruAudio and VSSL  
**Product:** SX Subwoofer  
**Model No.:** SXSUB  
**Brand Name:** VSSL  
**FCC Classification:** Digital Transmission System (DTS)  
**FCC Rule Part(s):** Part 15 Subpart C (Section 15.247)  
**Result:** Complies  
**Received Date:** 2023-02-20  
**Test Date:** 2023-02-21 ~ 2023-03-02

**Reviewed By:**

\_\_\_\_\_  
Kevin Guo

**Approved By:**

\_\_\_\_\_  
Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

### Revision History

Report No.	Version	Description	Issue Date	Note
2302RSU036-U1	V01	Initial Report	2023-03-30	Valid

## CONTENTS

Description	Page
<b>1. General Information .....</b>	<b>5</b>
1.1. Applicant .....	5
1.2. Manufacturer .....	5
1.3. Testing Facility .....	5
1.4. Product Information.....	6
1.5. Radio Specification under Test .....	6
1.6. Working Frequencies .....	7
<b>2. Test Configuration .....</b>	<b>8</b>
2.1. Test Mode.....	8
2.2. Test System Connection Diagram.....	8
2.3. Test Software .....	8
2.4. Applied Standards.....	8
2.5. Test Environment Condition .....	8
<b>3. Antenna Requirements .....</b>	<b>9</b>
<b>4. Measuring Instrument .....</b>	<b>10</b>
<b>5. Decision Rules and Measurement Uncertainty .....</b>	<b>11</b>
5.1. Decision Rules .....	11
5.2. Measurement Uncertainty .....	11
<b>6. Test Result.....</b>	<b>12</b>
6.1. Summary .....	12
6.2. 6dB Bandwidth Measurement.....	13
6.2.1. Test Limit .....	13
6.2.2. Test Procedure .....	13
6.2.3. Test Setting .....	13
6.2.4. Test Setup .....	13
6.2.5. Test Result .....	13
6.3. Output Power Measurement .....	14
6.3.1. Test Limit .....	14
6.3.2. Test Procedure .....	14
6.3.3. Test Setting .....	14
6.3.4. Test Setup .....	14
6.3.5. Test Result .....	14
6.4. Power Spectral Density Measurement .....	15
6.4.1. Test Limit .....	15
6.4.2. Test Procedure .....	15

6.4.3.	Test Setting .....	15
6.4.4.	Test Setup .....	15
6.4.5.	Test Result .....	15
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement .....	16
6.5.1.	Test Limit .....	16
6.5.2.	Test Procedure .....	16
6.5.3.	Test Settintg .....	16
6.5.4.	Test Setup .....	16
6.5.5.	Test Result .....	17
6.6.	Radiated Spurious Emission Measurement.....	18
6.6.1.	Test Limit .....	18
6.6.2.	Test Procedure .....	18
6.6.3.	Test Setting .....	18
6.6.4.	Test Setup .....	20
6.6.5.	Test Result .....	21
6.7.	Radiated Restricted Band Edge Measurement .....	22
6.7.1.	Test Limit .....	22
6.7.2.	Test Procedure .....	23
6.7.3.	Test Setting .....	23
6.7.4.	Test Setup .....	24
6.7.5.	Test Result .....	24
6.8.	AC Conducted Emissions Measurement .....	25
6.8.1.	Test Limit .....	25
6.8.2.	Test Setup .....	25
6.8.3.	Test Result .....	25
<b>Appendix A - Test Result.....</b>		<b>26</b>
A.1	Duty Cycle Test Result.....	26
A.2	6dB Bandwidth Test Result .....	27
A.3	Output Power Test Result .....	28
A.4	Power Spectral Density Test Result.....	29
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result.....	30
A.6	Radiated Spurious Emission Test Result.....	32
A.7	Radiated Restricted Band Edge Test Result.....	35
A.8	AC Conducted Emissions Test Result .....	43
<b>Appendix B - Test Setup Photograph .....</b>		<b>47</b>
<b>Appendix C - EUT Photograph .....</b>		<b>48</b>



#### 1.4. Product Information

Product Name	SX Subwoofer
Model No.	SXSUB
Sample No.	20230220sample#01 for Conducted; 20230220sample#02 for Radiated
Bluetooth Specification	V5.1 Bluetooth-LE only
Operating Temp.	0 ~ 40°C
Product Voltage	100-120VAC/ 220-240VAC, 50/60Hz, 350W
Note: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

#### 1.5. Radio Specification under Test

Bluetooth Frequency	2402 ~ 2480MHz
Channel Number	40
Type of modulation	GFSK
Data Rate	1Mbps
Antenna Type	PCB Antenna
Antenna Gain	1.13Bi

**1.6. Working Frequencies**

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz	--	--	--	--

## 2. Test Configuration


### 2.1. Test Mode

Mode 1: Transmit by BLE-1Mbps
-------------------------------

### 2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram – Radiated Emission testing & AC Conducted Emissions



### 2.3. Test Software

The test utility software used during testing was “LeKit”, and the version was 2.5.1a.

### 2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- ANSI C63.10-2013

### 2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~75%RH



### 3. Antenna Requirements

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The unit complies with the requirement of §15.203.

#### 4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2023-09-29	WZ-AC2
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2023-05-20	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2023-10-13	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2023-11-05	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2023-05-08	WZ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2024-01-12	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2023-06-04	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11038	1 year	2023-11-01	WZ-AC2
Thermohygrometer	Mingle	ETH529	MRTSUE06170	1 year	2023-11-27	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2023-04-21	WZ-AC2
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2023-06-04	WZ-SR4
Signal Analyzer	Keysight	N9010B	MRTSUE07027	1 year	2023-11-25	WZ-SR4
Attenuator	MVE	MVE2213	MRTSUE11087	1 year	2023-06-09	WZ-SR4
Shielding Room	HUAMING	WZ-SR4	MRTSUE06441	N/A	N/A	WZ-SR4
EMI Test Receiver	R&S	ESR3	MRTSUE06612	1 year	2023-06-01	SIP-SR2
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2023-06-01	SIP-SR2
Shielding Room	MIX-BEP	SIP-SR2	MRTSUE06949	5 years	2024-10-23	SIP-SR2

Software	Version	Function
EMI Software	V3.0.0	EMI Test Software
Controller_MF 7802	1.02	RE Antenna & Turntable
BenchVue Power Meter	2018.1	Power

## 5. Decision Rules and Measurement Uncertainty

### 5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

### 5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>AC Conducted Emission Measurement</b>
Measurement Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 9kHz~150kHz: 3.74dB 150kHz~30MHz: 3.44dB
<b>Radiated Disturbance</b>
Measurement Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): Horizontal: 30MHz~300MHz: 5.04dB 300MHz~1GHz: 4.95dB 1GHz~40GHz: 6.40dB Vertical: 30MHz~300MHz: 5.24dB 300MHz~1GHz: 6.03dB 1GHz~40GHz: 6.40dB
<b>Spurious Emissions, Conducted</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.78dB
<b>Output Power</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.13dB
<b>Power Spectrum Density</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.15dB
<b>Occupied Bandwidth</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.28%

## 6. Test Result

### 6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

#### Notes:

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

## 6.2. 6dB Bandwidth Measurement

### 6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


### 6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

### 6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 6$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

### 6.2.4. Test Setup



### 6.2.5. Test Result

Refer to Appendix A.2.

### 6.3. Output Power Measurement

#### 6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 6.3.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.1.3

ANSI C63.10 - 2013 - Section 11.9.2.3.2

#### 6.3.3. Test Setting

##### Peak Power Measurement


The maximum peak conducted output power may be measured using a broadband peak RF power meter.

The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

##### Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

#### 6.3.4. Test Setup



#### 6.3.5. Test Result

Refer to Appendix A.3.

## 6.4. Power Spectral Density Measurement

### 6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


### 6.4.2. Test Procedure

ANSI C63.10-2013 Section 11.10.2

### 6.4.3. Test Setting

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 10kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

### 6.4.4. Test Setup



### 6.4.5. Test Result

Refer to Appendix A.4.

## 6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

### 6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

### 6.5.2. Test Procedure

ANSI C63.10-2013 - Section 11.11

### 6.5.3. Test Setting


#### Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to  $\geq 1.5$  times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW  $\geq 3 \times$  RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

#### Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

### 6.5.4. Test Setup





### **6.5.5. Test Result**

Refer to Appendix A.5.

## 6.6. Radiated Spurious Emission Measurement

### 6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

### 6.6.3. Test Setting

**Table 1 - RBW as a function of frequency**

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

**Quasi-Peak Measurements below 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

**Peak Measurements above 1GHz**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

**Average Measurements above 1GHz (Method VB)**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle  $\geq 98\%$ , set VBW = 10 Hz.  
If the EUT duty cycle is  $< 98\%$ , set VBW  $\geq 1/T$ . T is the minimum transmission duration.
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize

### 6.6.4. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

## 6.7. Radiated Restricted Band Edge Measurement

### 6.7.1. Test Limit

#### For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

### 6.7.3. Test Setting

#### Peak Field Strength Measurements


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW  $\geq 1/T$
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode

5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

#### 6.7.4. Test Setup



#### 6.7.5. Test Result

Refer to Appendix A.7.



## 6.8. AC Conducted Emissions Measurement


### 6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 6.8.2. Test Setup



### 6.8.3. Test Result

Refer to Appendix A.8.

## Appendix A - Test Result

### A.1 Duty Cycle Test Result


Test Site	WZ-SR4	Test Engineer	Jeff Yang
Test Date	2023-02-21		

Test Mode	Duty Cycle
BLE-1Mbps	100%
Duty Cycle (T = Transmission Duration)	
BLE-1Mbps	

**A.2 6dB Bandwidth Test Result**

Test Site	WZ-SR4	Test Engineer	Jeff Yang
Test Date	2023-02-21		

Test Mode	Data Rate	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
BLE	1Mbps	00	2402	0.7729	≥ 0.5
BLE	1Mbps	19	2440	0.7727	≥ 0.5
BLE	1Mbps	39	2480	0.7954	≥ 0.5



### A.3 Output Power Test Result

Test Site	WZ-SR4	Test Engineer	Jeff Yang
Test Date	2023-02-21		

#### Test Result of Peak Output Power

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Result
BLE	1Mbps	00	2402	0.25	≤ 30.00	Pass
BLE	1Mbps	19	2440	0.46	≤ 30.00	Pass
BLE	1Mbps	39	2480	0.48	≤ 30.00	Pass


#### Test Result of Average Output Power (Reporting Only)

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Average Power (dBm)	Limit (dBm)	Result
BLE	1Mbps	00	2402	-0.24	≤ 30.00	Pass
BLE	1Mbps	19	2440	-0.12	≤ 30.00	Pass
BLE	1Mbps	39	2480	0.02	≤ 30.00	Pass

**A.4 Power Spectral Density Test Result**

Test Site	WZ-SR4	Test Engineer	Jeff Yang
Test Date	2023-02-21		


Test Mode	Data Rate	Channel No.	Frequency (MHz)	PSD Result (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
BLE	1Mbps	00	2402	-14.587	≤ 8.00	Pass
BLE	1Mbps	19	2440	-14.346	≤ 8.00	Pass
BLE	1Mbps	39	2480	-13.943	≤ 8.00	Pass



**A.5 Conducted Band Edge and Out-of-Band Emissions Test Result**

Test Site	WZ-SR4	Test Engineer	Jeff Yang
Test Date	2023-02-21		

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Limit (dBc)	Result
BLE	1Mbps	00	2402	20	Pass
BLE	1Mbps	19	2440	20	Pass
BLE	1Mbps	39	2480	20	Pass




## BLE-1Mbps Out-of-Band Emissions

## Channel 19 (2440MHz)

## 100kHz PSD Reference Level




## Spurious Emission




## Channel 39 (2480MHz)


## 100kHz PSD Reference Level



## High Band Edge



## Spurious Emission



**A.6 Radiated Spurious Emission Test Result**

Test Site	WZ-AC2	Test Engineer	Dick Shen
Test Date	2023-02-22 ~ 2023-02-24	Test Mode:	BLE-1Mbps
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
00	4804.0	45.5	3.7	49.2	74.0	-24.8	Peak	Horizontal
	10758.0	32.5	16.6	49.1	74.0	-24.9	Peak	Horizontal
	11786.5	30.9	17.3	48.2	74.0	-25.8	Peak	Horizontal
	4804.0	49.1	3.7	52.8	74.0	-21.2	Peak	Vertical
	4804.0	45.7	3.7	49.4	54.0	-4.6	Average	Vertical
	8157.0	32.4	12.0	44.4	74.0	-29.6	Peak	Vertical
	10979.0	31.5	17.4	48.9	74.0	-25.1	Peak	Vertical
19	4879.0	48.0	3.7	51.7	74.0	-22.3	Peak	Horizontal
	4879.0	42.8	3.7	46.5	54.0	-7.5	Average	Horizontal
	8182.5	32.5	11.7	44.2	74.0	-29.8	Peak	Horizontal
	11055.5	31.9	17.1	49.0	74.0	-25.0	Peak	Horizontal
	4879.0	50.9	3.7	54.6	74.0	-19.4	Peak	Vertical
	4879.0	45.2	3.7	48.9	54.0	-5.1	Average	Vertical
	8437.5	32.2	12.0	44.2	74.0	-29.8	Peak	Vertical
	10979.0	31.5	17.4	48.9	74.0	-25.1	Peak	Vertical
39	4960.0	46.5	3.5	50.0	74.0	-24.0	Peak	Horizontal
	8293.0	33.3	11.1	44.4	74.0	-29.6	Peak	Horizontal
	11030.0	31.9	17.0	48.9	74.0	-25.1	Peak	Horizontal
	4960.0	49.5	3.5	53.0	74.0	-21.0	Peak	Vertical
	4960.0	44.9	3.5	48.4	54.0	-5.6	Average	Vertical
	8157.0	32.3	12.0	44.3	74.0	-29.7	Peak	Vertical
	10987.5	32.0	17.3	49.3	74.0	-24.7	Peak	Vertical


Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)



**The Result of Radiated Emission below 1GHz:**

Site: WZ-AC2	Test Date: 2023-02-23
Limit: FCC_Part15.209_RSE(3m)	Engineer: Dick Shen
Probe: VULB9162_30-7000MHz	Polarity: Horizontal
EUT: SX Subwoofer	Power: AC 120V/60Hz
<b>Test Mode:</b> Transmit by BLE-1M at channel 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		107.600	38.086	19.734	-5.414	43.500	18.352	PK
2		211.875	40.069	21.968	-3.431	43.500	18.101	PK
3		218.180	41.979	23.646	-4.021	46.000	18.333	PK
4	*	261.110	44.324	24.300	-1.676	46.000	20.025	QP
5		291.900	42.973	22.186	-3.027	46.000	20.787	PK
6		310.330	42.739	21.782	-3.261	46.000	20.957	PK

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).


Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Note 4: Quasi-Peak measurement was not performed when peak measure level was lower than the quasi-peak limit.

Note 5: The amplitude of radiated emissions (frequency range from 9kHz to 30MHz and 18GHz to 25GHz) is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value.

Therefore, the data is not presented in the report.

Site: WZ-AC2	Test Date: 2023-02-23
Limit: FCC_Part15.209_RSE(3m)	Engineer: Dick Shen
Probe: VULB9162_30-7000MHz	Polarity: Vertical
EUT: SX Subwoofer	Power: AC 120V/60Hz
<b>Test Mode:</b> Transmit by BLE-1M at channel 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1	*	107.600	36.454	18.102	-7.046	43.500	18.352	PK
2		211.875	32.357	14.256	-11.143	43.500	18.101	PK
3		260.860	36.566	16.546	-9.434	46.000	20.020	PK
4		328.760	35.211	13.591	-10.789	46.000	21.620	PK
5		456.800	33.519	9.476	-12.481	46.000	24.043	PK
6		540.220	33.573	7.843	-12.427	46.000	25.730	PK

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).


Note 4: Quasi-Peak measurement was not performed when peak measure level was lower than the quasi-peak limit.

Note 5: The amplitude of radiated emissions (frequency range from 9kHz to 30MHz and 18GHz to 25GHz) is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value.

Therefore, the data is not presented in the report.

**A.7 Radiated Restricted Band Edge Test Result**

Site: WZ-AC2	Test Date: 2023-02-22
Limit: FCC_2.4G_RE(3m)	Engineer: Dick Shen
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: SX Subwoofer	Power: AC 120V/60Hz
Test Mode: Transmit by BLE-1M at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1	*	2355.647	55.929	24.160	-18.071	74.000	31.769	PK
2		2390.000	52.680	20.992	-21.320	74.000	31.688	PK
3		2401.675	82.965	51.319	N/A	N/A	31.646	PK

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2023-02-22
Limit: FCC_2.4G_RE(3m)	Engineer: Dick Shen
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: SX Subwoofer	Power: AC 120V/60Hz
Test Mode: Transmit by BLE-1M at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1	*	2347.050	36.119	4.344	-17.881	54.000	31.775	AV
2		2390.000	36.088	4.400	-17.912	54.000	31.688	AV
3		2401.865	80.495	48.849	N/A	N/A	31.646	AV

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2023-02-22
Limit: FCC_2.4G_RE(3m)	Engineer: Dick Shen
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: SX Subwoofer	Power: AC 120V/60Hz
Test Mode: Transmit by BLE-1M at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB $\mu$ V/m)	Reading Level (dB $\mu$ V)	Margin (dB)	Limit (dB $\mu$ V/m)	Factor (dB/m)	Type
1	*	2362.060	55.991	24.223	-18.009	74.000	31.768	PK
2		2390.000	54.493	22.805	-19.507	74.000	31.688	PK
3		2401.722	81.367	49.721	N/A	N/A	31.646	PK

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2023-02-22
Limit: FCC_2.4G_RE(3m)	Engineer: Dick Shen
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: SX Subwoofer	Power: AC 120V/60Hz
Test Mode: Transmit by BLE-1M at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		2341.587	36.072	4.273	-17.928	54.000	31.799	AV
2	*	2390.000	36.151	4.463	-17.849	54.000	31.688	AV
3		2401.865	79.785	48.139	N/A	N/A	31.646	AV

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2023-02-22
Limit: FCC_2.4G_RE(3m)	Engineer: Dick Shen
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: SX Subwoofer	Power: AC 120V/60Hz
Test Mode: Transmit by BLE-1M at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		2480.277	88.518	56.954	N/A	N/A	31.564	PK
2		2483.500	53.470	21.901	-20.530	74.000	31.569	PK
3	*	2495.457	56.456	24.861	-17.544	74.000	31.595	PK

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2023-02-22
Limit: FCC_2.4G_RE(3m)	Engineer: Dick Shen
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: SX Subwoofer	Power: AC 120V/60Hz
Test Mode: Transmit by BLE-1M at 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dB $\mu$ V/m)	Reading Level (dB $\mu$ V)	Margin (dB)	Limit (dB $\mu$ V/m)	Factor (dB/m)	Type
1		2479.936	84.326	52.763	N/A	N/A	31.563	AV
2		2483.500	36.406	4.837	-17.594	54.000	31.569	AV
3	*	2495.985	38.390	6.793	-15.610	54.000	31.597	AV


Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).



Site: WZ-AC2	Test Date: 2023-02-22
Limit: FCC_2.4G_RE(3m)	Engineer: Dick Shen
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: SX Subwoofer	Power: AC 120V/60Hz
Test Mode: Transmit by BLE-1M at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		2480.310	87.914	56.350	N/A	N/A	31.564	PK
2		2483.500	53.462	21.893	-20.538	74.000	31.569	PK
3	*	2496.315	57.268	25.670	-16.732	74.000	31.598	PK

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2023-02-22
Limit: FCC_2.4G_RE(3m)	Engineer: Dick Shen
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: SX Subwoofer	Power: AC 120V/60Hz
Test Mode: Transmit by BLE-1M at 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		2480.002	86.654	55.091	N/A	N/A	31.563	AV
2		2483.500	36.483	4.914	-17.517	54.000	31.569	AV
3	*	2495.853	38.494	6.898	-15.506	54.000	31.596	AV


Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

**A.8 AC Conducted Emissions Test Result**

Site: WZ-SR2	Test Date: 2023-03-02
Limit: FCC_Part15.207_CE_AC Power	Engineer: Bob Zhang
Probe: ENV216_101683_Filter Off	Polarity: Line
EUT: SX Subwoofer	Power: AC 120V/60Hz
<b>Test Mode:</b> Transmit by BLE-1M at 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dBμV)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV)	Factor (dB)	Type
1		0.346	51.203	41.532	-7.855	59.058	9.670	QP
2		0.346	26.906	17.235	-22.152	49.058	9.670	AV
3	*	0.566	48.450	38.665	-7.550	56.000	9.784	QP
4		0.566	20.676	10.891	-25.324	46.000	9.784	AV
5		0.794	47.672	37.777	-8.328	56.000	9.895	QP
6		0.794	22.953	13.057	-23.047	46.000	9.895	AV
7		1.022	46.168	36.179	-9.832	56.000	9.990	QP
8		1.022	19.556	9.567	-26.444	46.000	9.990	AV
9		1.294	44.367	34.374	-11.633	56.000	9.994	QP
10		1.294	19.616	9.622	-26.384	46.000	9.994	AV
11		1.546	44.058	34.061	-11.942	56.000	9.997	QP
12		1.546	18.527	8.530	-27.473	46.000	9.997	AV
13		1.774	42.886	32.886	-13.114	56.000	10.000	QP
14		1.774	18.752	8.752	-27.248	46.000	10.000	AV
15		1.990	41.346	31.344	-14.654	56.000	10.002	QP
16		1.990	18.592	8.590	-27.408	46.000	10.002	AV

---


17		2.266	41.373	31.360	-14.627	56.000	10.013	QP
18		2.266	19.999	9.986	-26.001	46.000	10.013	AV

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dB $\mu$ V) = Reading Level (dB $\mu$ V) + Factor (dB).

Note 3: Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

Site: WZ-SR2	Test Date: 2023-03-02
Limit: FCC_Part15.207_CE_AC Power	Engineer: Bob Zhang
Probe: ENV216_101683_Filter Off	Polarity: Neutral
EUT: SX Subwoofer	Power: AC 120V/60Hz
<b>Test Mode:</b> Transmit by BLE-1M at 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dBμV)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV)	Factor (dB)	Type
1		0.350	51.297	41.629	-7.665	58.962	9.668	QP
2		0.350	28.063	18.395	-20.900	48.962	9.668	AV
3	*	0.574	48.841	39.056	-7.159	56.000	9.785	QP
4		0.574	22.654	12.869	-23.346	46.000	9.785	AV
5		0.794	47.732	37.841	-8.268	56.000	9.891	QP
6		0.794	23.341	13.449	-22.659	46.000	9.891	AV
7		1.066	46.166	36.166	-9.834	56.000	10.000	QP
8		1.066	22.292	12.292	-23.708	46.000	10.000	AV
9		1.310	44.268	34.267	-11.732	56.000	10.001	QP
10		1.310	19.137	9.136	-26.863	46.000	10.001	AV
11		1.546	43.883	33.882	-12.117	56.000	10.002	QP
12		1.546	19.945	9.943	-26.055	46.000	10.002	AV
13		1.770	42.715	32.713	-13.285	56.000	10.002	QP
14		1.770	18.944	8.942	-27.056	46.000	10.002	AV
15		2.022	42.139	32.136	-13.861	56.000	10.003	QP
16		2.022	20.176	10.173	-25.824	46.000	10.003	AV

Note 1: " \* ", means this data is the worst emission level.

Note 2: Measure Level (dB $\mu$ V) = Reading Level (dB $\mu$ V) + Factor (dB).

Note 3: Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

## **Appendix B - Test Setup Photograph**

Refer to "2302RSU036-UT" file.

## Appendix C - EUT Photograph

Refer to "2302RSU036-UE" file.

\_\_\_\_\_ The End \_\_\_\_\_