

LABAU Technology Corp.

Declaration of the Modular Approval

Applicant / Grantee	LABAU Technology Corp.
FCC ID:	2BAFJ-BT820
Model:	BT820PC6E003A

The single module transmitter has been evaluated then tested meeting the requirements under Part 15C Section 2.12 as below:

Modular approval requirement	EUT Condition	Comply
(a) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	According to the internal photos, provided by the applicant after the comparison to determine the module in the RF components are covered with sheet metal to meet the requirements.	Yes
(b) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	The EUT has buffered data inputs, it is integrated in chip.	Yes
(c) The modular transmitter must have its own power supply regulation.	The EUT has its own power supplier regulation , please see the schematic.	Yes
(d) The modular transmitter must comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of Section 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	The EUT meets the FCC antenna requirements. The spurious emission, unique antenna connector and photo of antennas are shown in the test report.	Yes
(e) The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted	The EUT was tested in a stand- alone configuration via a test kit. Please see section Photographs of Test Configuration in the test report.	Yes

LABAU Technology Corp.

requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see Section 15.31(i)) must not be inside another device during testing.		
(f) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.	Yes, the module has FCC ID Label permanently affixed, please refer to the module label.	Yes
(g) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization requirements, which are based on the intended use/configurations.	The EUT is compliant with all applicable FCC rules. Detail instructions for maintaining compliance are given in the Users Manual.	Yes
(h) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	The EUT is compliant with all applicable RF exposure requirements. RF Exposure is addressed in the RF exposure exhibition.	Yes

Rex Lin

Name/Title: Rex Lin / Engineer

Company Name: LABAU Technology Corp.

Address: 9F., #531-1, Zhongzheng Rd., Xindian Dist., New Taipei City 23148, Taiwan