



RF EXPOSURE

REPORT

FOR

Product Name: BLUETOOTH MODULE

Model :BT820PC6E003A

Trade Name : LABAU

Issued to

**LABAU Technology Corp.
9F., #531-1, ZhongZheng Rd., Xindian Dist., New Taipei City 23148, Taiwan**

Issued by

**Global Certification Corp.
No.146, Sec. 2, Xiangzhang Rd., Xizhi Dist., New Taipei City 221,
Taiwan (R.O.C.)**

*Note: This test refers exclusively to the test presented test model and sample. This report shall not be reproduced except in full, without the written approval of Global Certification Corporation. This document may be altered or revised by Global Certification Corporation. Personnel only, and shall be noted in the revision section of the document.
The decision rule is according to the standard test method and request, that measurement result doesn't consider uncertainty.*



Revision History

Revision	No.	Report Number	Issue Date	Description	Author/ Revised by
1.	3O0301	FR0-3O0301a	Dec.07.2023	Original Report	Judy



TABLE OF CONTENTS	-----	3
1. GENERAL INFORMATION	-----	4
1.1 DESCRIPTION OF THE TESTED SAMPLES	-----	5
2. GENERAL SAR TEST REDUCTION AND EXCLUSION GUIDANCE	-----	6
3. MPE CALCULATION METHOD	-----	7
3.1 LIMIT	-----	7
3.2. CACULATION METHOD	-----	7
3.3. CALCULATED RESULT	-----	7



1. GENERAL INFORMATION

Applicant : LABAU Technology Corp.

Address : 9F., #531-1, ZhongZheng Rd., Xindian Dist., New Taipei City 23148, Taiwan

Manufacturer : LABAU Technology Corp.

Address : 9F., #531-1, ZhongZheng Rd., Xindian Dist., New Taipei City 23148, Taiwan

EUT : BLUETOOTH MODULE

Model No. : BT820PC6E003A

Trade Name : LABAU

Model Differences : --

Is here with confirmed to comply with the requirements set out in the FCC Rules and Regulations. The said equipment has been tested and found compliance with the requirement of the relative standards .

Test Standard : FCC Title 47 Part 2.1091, KDB 447498 D01 V06

Tested By:

Dec.07.2023
Date

John Wu, Engineer

Approved by:

Adam Chou, Manager

Designation Number: TW1640



1.1 DESCRIPTION OF THE TESTED SAMPLES

EUT Name : BLUETOOTH MODULE
Model : BT820PC6E003A
FCC ID : 2BAFJ-BT820
Power From : Inside Outside
Adaptor Battery Power Supply DC Power Source Support Unit PC
Power Rating(Battery) : 5 Vdc
Power Rating(Adapter) : --
Operate Frequency : Refer to the channel list as described below
Basic Spec : Bluetooth Bluetooth LE 802.11b 802.11g 802.11n HT20/HT40
Operate Frequency : 2402 MHz ~ 2480 MHz
Number of Channels : 40
Step of Channel : N/A _____ MHz
Modulation Type : GFSK FHSS DSSS CCK OFDM
Antenna Quantity : 1Tx/1Rx
Antenna Type : IFA
Antenna gain : -1.51 dBi
EUT Received Date : Oct.03.2023
EUT Channel List :

Channels	Frequencies(MHz)
1	2402
2	2440
3	2480



2. GENERAL SAR TEST REDUCTION AND EXCLUSION GUIDANCE

2.1 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] .

- $[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²¹ where $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²²
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2.2 At 100 MHz to 6 GHz and for test separation distances $>$ 50 mm, the SAR test exclusion threshold is determined according to the following

- [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) \cdot (f(MHz)/150)] mW, at 100 MHz to 1500 MHz
- [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) \cdot 10] mW at $>$ 1500 MHz and \leq 6 GHz

2.3 At frequencies below 100 MHz, the following may be considered for SAR test exclusion

- The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances $>$ 50 mm and $<$ 200 mm
- The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances \leq 50 mm
- SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.



3. MPE CALCULATION METHOD

3.1 LIMIT

Limits for Maximum Permissible Exposure

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

3.2. CACULATION METHOD

Calculation Method of RF Safety Distance:

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3.3. CALCULATED RESULT

Test Mode	Frequency (MHz)	Max Output Power (dbm)	Max Output Power (mW)	Power Density (mW / cm ²)	Limit of Power Density (mW / cm ²)
BLE 1M	2402	2.89	1.94536	0.000273	1

The calculated distance is 20 cm and choose the max output power test mode..

END