

# EMF TEST REPORT

**Test Report No.** : OT-235-RWD-023  
**Reception No.** : 2304001248  
**Applicant** : Fitogther  
**Address** : #302, 95 Hangang-daero, Yongsan-gu, Seoul, 04378, South Korea  
**Manufacturer** : Fitogther  
**Address** : #302, 95 Hangang-daero, Yongsan-gu, Seoul, 04378, South Korea  
**Type of Equipment** : Real Time Tracking System  
**FCC ID.** : 2BAGE-FITOLIVEHUBP2  
**Model Name** : OHCOACH Live Hub  
**Multiple Model Name** : LHP2-1A  
**Serial number** : N/A  
**Total page of Report** : 7 pages (including this page)  
**Date of Incoming** : May 16, 2023  
**Date of issue** : May 26, 2023

## SUMMARY

The equipment complies with the regulation; **FCC CFR 47 PART 2.1091**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.



---

Tested by  
Myeong-Hwa, Jang / Sr. Engineer  
ONETECH Corp.

Reviewed by  
Tae-Ho, Kim / Chief Engineer  
ONETECH Corp.

Approved by  
Jae-Ho, Lee / Chief Engineer  
ONETECH Corp.

## CONTENTS

	PAGE
<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
<b>2.1 PRODUCT DESCRIPTION.....</b>	5
<b>2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....</b>	5
<b>3. EUT MODIFICATIONS.....</b>	<b>5</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>6</b>
<b>4.1 RF EXPOSURE CALCULATION .....</b>	6
<b>4.2 EUT DESCRIPTION.....</b>	6
<b>4.3 CALCULATED MPE SAFE DISTANCE.....</b>	7

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-235-RWD-023	May 26, 2023	Initial Release	All

## 1. VERIFICATION OF COMPLIANCE

Applicant : Fitogther  
Address : #302, 95 Hangang-daero, Yongsan-gu, Seoul, 04378, South Korea  
Contact Person : Bobby, Shin / Senior Engineer  
Telephone No. : +82-10-6263-8930  
FCC ID : 2BAGE-FITOLIVEHUBP2  
Model Name : OHCOACH Live Hub  
Brand Name : -  
Serial Number : N/A  
Date : May 26, 2023

E.U.T. DESCRIPTION	Real Time Tracking System
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	KDB 447498 D01 General RF Exposure Guidance v06
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	Certification
AUTHORIZATION REQUESTED	
Modifications on the Equipment to Achieve Compliance	None

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The Fitogther, Model OHCOACH Live Hub (referred to as the EUT in this report) is a Real Time Tracking System. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Real Time Tracking System
OPERATING FREQUENCY	2 412 MHz ~ 2 462 MHz (802.11g)
MODULATION TYPE	802.11g: OFDM Modulation (BPSK/QPSK/16QAM/64QAM)
RF OUTPUT POWER	Antenna 0: 6.33 dBm Antenna 1: 5.76 dBm Antenna 2: 5.78 dBm Multiple Antenna: 10.66 dBm
ANTENNA TYPE	Antenna 0: PCB Antenna Antenna 1: Patch Antenna Antenna 2: Patch Antenna
ANTENNA GAIN	Antenna 0: 3.72 dBi Antenna 1: 9.13 dBi Antenna 2: 9.13 dBi Multiple Antenna: 12.72 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	25 MHz, 40 MHz
RATED SUPPLY VOLTAGE	DC 7.40 V

### 2.2 Alternative type(s)/model(s); also covered by this test report.

- The following lists consist of the added model and their differences.

Model Name	Differences	Tested
OHCOACH Live Hub	Basic Model	<input checked="" type="checkbox"/>
LHP2-1A	The model is identical to basic model except for the model name only.	<input type="checkbox"/>

Note: 1. Applicant consigns only basic model to test. Therefore this test report just guarantees the units, which have been tested.

2. The Applicant/manufacturer is responsible for the compliance of all variants.

## 3. EUT MODIFICATIONS

- None

## 4. MAXIMUM PERMISSIBLE EXPOSURE

### 4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are  $f/1500 \text{ mW/cm}^2$  for the frequency range between 300 MHz and 1 500 MHz and  $1.0 \text{ mW/cm}^2$  for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a  $1 \text{ mW/cm}^2$  exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

$S$  = Power density in  $\text{mW/cm}^2$ ,  $Z$  = Impedance of free space,  $377 \Omega$

$E$  = Electric field strength in  $\text{V/m}$ ,  $G$  = Numeric antenna gain, and  $d$  = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using  $P (\text{mW}) = P (\text{W}) / 1000$ ,  $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

$d$  = distance in cm,  $P$  = Power in mW,  $G$  = Numeric antenna gain, and  $S$  = Power density in  $\text{mW/cm}^2$

### 4.2 EUT Description

Kind of EUT	Real Time Tracking System
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input checked="" type="checkbox"/> Mobile (> 20 cm separation) <input type="checkbox"/> Others
Exposure	<input checked="" type="checkbox"/> MPE
Evaluation Applied	<input type="checkbox"/> SAR <input type="checkbox"/> N/A

### 4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11g [Antenna 0]	6.33 ± 1.0	7.33	5.41	3.72	2.36	1.01	0.002 5	1
	802.11g [Antenna 1]	5.76 ± 1.0	6.76	4.74	9.13	8.18	1.76	0.007 7	1
	802.11g [Antenna 2]	5.78 ± 1.0	6.78	4.76	9.13	8.18	1.76	0.007 7	1
	802.11g [Multiple Antenna]	10.66 ± 1.0	11.66	14.66	12.72	18.71	4.67	0.054 6	1

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 g [Antenna 0]), safe distance,

$$D = 0.282 * \sqrt{(5.41 * 2.36) / 1.00} = 1.01 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 5.41 * 2.36 / (4 * \pi * 20^2) = 0.002 5$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna