

SPECIFICATION FOR APPROVAL

Customer Name	Fuwei				
Customer Project Name	T156A-YD	SDC Project Name	T156A-YD		
Customer P/N		SDC P/N	WF5760B-0814L-335 MIAN WF5760B-0814R-315 AUX		
Band	WIF12. 4G/5. 8G/BT				
Version	A0				
	Designer Info	ormation			
RF Engineer	Yong-hui Yang R&D Diretor FuXueRong				
ME Engineer	Huang Zongbao				

Approval			Customer	Approval	
	Prepared By	Checked By	Approval By	Checked By	Approval By
Signature	Huang Zongbao	Yong-hui Yang	FuXueRong		
Date	2024. 06. 17	2024. 06. 17	2024. 06. 17		


Change Log				
Version	Change Description	Person in Charge	Approval By	Date



	Catalogue	
No.	ltem	Page No.
1	Drawing or Product Image	3
2	Dimensions Test Report	4
3	RF Performance Test Report	5–8
4	Reliability Test Report1	9
5	Package Document	10
6	RoHS Control list for Sample	11
7	Install Wizard or Other	11



Drawing or Product Image



Company Address: 4th Floor, Building B5, Xinfu Industrial Park, Chongqing Road, Fuyong Town, Baoan District, Shenzhen Telephone :0755-27211658 Fax :0755-29485750




Sample Dimensions Test Report

Test Date	2024. 06. 17	Sample Qty.	3	Inspector	Xu Yanfang
Dimension No.	Standard	Sample 1	Sample 2	Sample 3	Pass/NG
①length	28±0.2mm	28	28. 1	28	Pass
②width	25±0.2mm	25	25. 1	25	Pass
③thickness	0.1±0.03mm	0. 1	0. 1	0. 1	Pass
④Line length	335±2mm	335	336	335	Pass
	•	Conclusion		·	PASS
Inspector & Date	Xu Yanfang 20	24. 06. 17	Approval &D ate		



Drawing or Product Image





Sample Dimensions Test Report


Test Date	2024. 06. 17	Sample Qty.	3	Inspector	Xu Yanfang
Dimension No.	Standard	Sample 1	Sample 2	Sample 3	Pass/NG
①length	28±0.2mm	28	28. 1	28	Pass
②width	25±0.2mm	25	25. 1	25	Pass
3 thickness	0.1±0.03mm	0. 1	0. 1	0. 1	Pass
④Line length	315±2mm	315	315	316	Pass
		Conclusion			PASS
Inspector & Date	Xu Yanfang 20	24. 06. 17	Approval &D ate		



RF Performance Test Report

Antenna Test Equipment Introduction

Test of antenna input characteristics using **Agilent E5071C and Agilent 5062A** vector network analyzer; The radiation pattern of the antenna are tested using the guangping 3D near field Anechoic Chamber, and the instrument is used to agilent8960 E5515 and Agilent E4438C. The test coordinates of the darkroom are as follows:




1. S11 Parameter-VSWR


Measuring Method is a 50 Ω coaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the S11 parameter, Keeping this fixture away from metal at least 20cm.



S11 Parameter-VSWR









	ANT 1	
Frequency (MHz)	Efficiency (%)	Peak GAIN (dBi)
2400	34.8	1.34
2450	34.05	1.35
2500	33.79	1.35
5150	32.51	1.26
5720	33.72	1.26
5850	32.65	1.25



	ANT 2	
Frequency (MHz)	Efficiency (%)	Peak GAIN (dBi)
2400	34.81	1.36
2450	35.01	1.37
2500	32.19	1.37
5150	31.4	1.19
5720	34.82	1.20
5850	33.75	1.20

4. WIFI OTA Data



2. 4G	802.11b, (2.4G)11M			
Channe1	CH1	CH6	CH11	
TRP	12.28	12.1	11. 79	
TIS	-76.64	-77 . 5	-75.23	
5.8G	802.11a, (5.8G)54M			
Channe1	CH36	CH60	CH161	
TRP	10.63	10. 5	10.87	
TIS	-68.16	-68.24	-68.45	



Reliability Test Report

Test Date	2024. 06. 17	Sample Qty.	3	Inspector	Xu Y	anfang
Test Item	Requirement	testing equipment	Sample 1	Sample 2	Sample 3	PASS/NG
High temperatur e storage	The test was carried out after 24H exposure at +85℃ and 2H recovery	Constant temperature and humidity box	ОК	ок	ок	Pass
Low temperatur e storage	The test was carried out after 24H exposure at -40℃ and 2H recovery	Constant temperature and humidity box	ОК	ОК	ОК	Pass
High temperatur e work	At +60 $^{\circ}$ C for 24H	Constant temperature and humidity box	ок	ок	ок	Pass
Work in low temperatur e	At -20℃ under the condition of power work for 24H	Constant temperature and humidity box	ОК	ок	ОК	Pass
Salt spray test	The pH value was 6.5 ~ 7.2, and the temperature of the experimental chamber was (35± 2)℃ □24H ☑48H	Salt spray testing machine	ок	ОК	ОК	Pass
Connector riveting and drawing force	1.13wire diameter ≥ 10N 0.81wire diameter ≥ 8N RG174 ≥60N RG178 ≥50N	Push pull meter	≥10N	≥10N	≥10N	Pass
Conclusion						Pass
Inspector & Date	Xu Yanfang 2024 .06.17		Approval &D ate			



Install Wizard or Other

Installation process:

Take 1PCS of products and tear off the release paper on the back of the FPC by hand. Then align the positioning holes of the FPC with the positioning holes of the shell (positioning bars or positioning wires) and attach them to the shell smoothly. The specific positions are shown in the figure below:

Precautions for installation:


After attaching the antenna, ensure that the FPC is fully attached to the shell;

The positioning hole is aligned with the position of the housing positioning column;

FPC edges are aligned with housing edges;

When connecting the antenna with terminal to the PCBA end of the motherboard, align the terminal first and then close it vertically.

When removing the antenna terminal, use a tool (such as a dedicated crowbar) to lift the terminal vertically. Do not pull the cable to remove the terminal directly





ROHS





Certificate Number: UNIB23083106HC-01

Product:	5G/4G/WIFI/GPS/BT antenna
Applicant:	ShenZhen ShunDaCheng Technology Co., Ltd.
	4th Floor, Building B5, Xinfu Industrial Zone, Fuyong Chongqing Road, Baoan District, Shenzhen
Manufacturer:	N/A
Model No.:	N/A
Trade Name:	N/A
Test Methods:	IEC 62321-2:2021, IEC 62321-3-1:2013, IEC 62321-4:2013 +A1:2017, IEC 62321-5:2013, IEC 62321-6:2015, IEC 62321-7-1:2015 IEC 62321-7-2:2017, IEC 62321-8:2017

The laboratory tested the product provided by the applicant according to the above test methods. According to the test results, the product conforms to RoHS Directive [(2011/65/EU and Amendment (EU) 2015/863)] issued by the European Commission. It is possible to use CE marking to demonstrate the compliance with RoHS Directive.

The certificate applies to the tested sample above mentioned only and shall not imply an assessment of the whole production. It is only valid in connection with the test report number: UNIB23083106HR-01.

Note: According to the requirements of the applicant for testing, details are shown in the test report.

