

Valeo North America Inc.

TEST REPORT

SCOPE OF WORK
FCC TESTING–KNW2

REPORT NUMBER
231025028SZN-001

ISSUE DATE **[REVISED DATE]**
January 23, 2024 [-----]

PAGES
16

DOCUMENT CONTROL NUMBER
FCC ID 209_b
© 2017 INTERTEK



Valeo North America Inc.

Application
For
Certification

FCC ID: 2BAHD-KNW2

KIN

Model: KNW2

Transmitter

Report No.: 231025028SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-22]

Prepared and Checked by:

Approved by:

Robin Zhou
Senior Project Engineer

Ryan Chen
Project Engineer
Date: January 23, 2024

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one) Original Grant Class II Change

Equipment Type: DCD - Part 15 Low Power Transmitter Below 1705 kHz

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-22] Edition] provision.

Report prepared by:

Robin Zhou

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8614 0694 Fax: (86 755) 8601 6751

Table of Contents

1.0	Summary of Test Results	4
2.0	General Description	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
3.0	System Test Configuration	6
3.1	Justification	6
3.2	EUT Exercising Software	6
3.3	Special Accessories	6
3.4	Equipment Modification	6
3.5	Measurement Uncertainty	7
3.6	Support Equipment List and Description	7
4.0	Measurement Results	8
4.1	Field Strength Calculation	8
4.2	Radiated Emission Configuration Photograph	9
4.3	Radiated Spurious Emission	9
5.0	Equipment Photographs	13
6.0	Product Labelling	13
7.0	Technical Specifications	13
8.0	Instruction Manual	13
9.0	Miscellaneous Information	14
9.1	20dB Bandwidth	14
9.2	Emissions Test Procedures	15
10.0	Test Equipment List	16

1.0 Summary of Test Results

Applicant: Valeo North America Inc.

Applicant Address: 150 Stephenson Hwy, Troy, Michigan 48083, United States

Manufacturer: Valeo North America Inc.

Manufacturer Address: 150 Stephenson Hwy, Troy, Michigan 48083, United States

Equipment Under Test (EUT):

Product Description: KIN
Model: KNW2
Part ID No.: KIN20001
Type of device: Tx (125kHz)
Operating frequency: 125kHz
Number of Channels: 1
Modulation Type: ASK
Type of Antenna: Inductor antenna
HW version: bb61343_01_b
SW version: NA
FW version: NA
Standards/guidance: FCC Title 47 CFR Part 15.209:2022
ANSI C63.10:2013
Sample Receipt Date: November 21, 2023
Test Conducted Date: November 21, 2023 to December 11, 2023
Test Condition: 21.9 °C, 43.0% HR, 100.5 kPa

FCC ID: 2BAHD-KNW2

TEST ITEM	REFERENCE	RESULTS
20 dB Bandwidth	15.215(c)	Pass
Transmitter Radiated Emissions	15.209&15.205	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a KIN operating at 125 kHz. The EUT is powered by DC 12V Car Battery. For more detailed features description, please refer to the user's manual.

Antenna Type: Inductor antenna

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of the KIN portion.

2.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst-case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are Intertek **Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

3.0 System Test Configuration

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by DC 12V Car Battery (fully charged) during the test. Only the worst-case data was shown in this report.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the bottom of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emission at and above 30 MHz, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data report in Section 4.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the styrene turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

3.2 EUT Exercising Software

Stallantis WLWS Homogation Tester: TSMASTERR V2022.12.20.810

3.3 Special Accessories

No Special accessories used.

3.4 Equipment Modification

Any modifications installed previous to testing by Valeo North America Inc. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Measurement Uncertainty	Uncertainty
Channel Bandwidth	±3.46%
Radiated emission (Up to 1GHz)	±4.8dB
Temperature	±1°C
Humidity	±5%

3.6 Support Equipment List and Description

Description	Manufacturer	Model/ Cable length
RFHM	Valeo	RFH1A
25 pins RFHM connect cable*2	Valeo	2m
Loadbox	Valeo	TF6045
DC input cable*2	Valeo	1m
4 pins KIN Connect cable*1	Valeo	0.6m
ToSun CANoE	Tosun	TC1012P*
USB-A to 9 pins CAN port cable*1	Valeo	1m*
9 pins CAN port conncet cable *1	Valeo	0.6m*
Laptop	DELL	Latitude 3480*

*: To avoid interference, these parts have been removed during the testing process. They are only used to send test commands before testing.

4.0 Measurement Results

4.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB μ V/m
RA = Receiver Amplitude (including preamplifier) in dB μ V
CF = Cable Attenuation Factor in dB
AF = Antenna Factor in dB/m
AG = Amplifier Gain in dB
PD = Pulse Desensitization in dB
AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0dB μ V is obtained. The antenna factor of 7.4dB and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0dB, and the resultant average factor was -10dB. The net field strength for comparison to the appropriate emission limit is 32dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 62.0dB μ V
AF = 7.4 dB/m
CF = 1.6dB
AG = 29.0dB
PD = 0dB
AV = -10dB
FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32dB μ V/m
Level in μ V/m = Common Antilogarithm [(32dB μ V/m)/20] = 39.8 μ V/m

4.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

4.3 Radiated Spurious Emission

Worst Case Radiated Spurious Emission
at
709.161667MHz

Judgement: Passed by 14.5dB margin

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

Sign on file

Robin Zhou, Senior Project Engineer
Typed/Printed Name

December 04, 2023
Date

Applicant: Valeo North America Inc.


Date of Test: December 04, 2023

Model: KNW2

Worst Case Operating Mode: Transmitting

Radiated Emissions (30MHz – 1000MHz)

ANT Polarity: Horizontal



Frequency (MHz)	Quasi Peak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.240000	23.4	1000.0	120.000	Horizontal	23.3	16.6	40.0
549.435000	29.4	1000.0	120.000	Horizontal	29.0	16.6	46.0
868.468000	31.3	1000.0	120.000	Horizontal	31.7	14.7	46.0


Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBµV/m) = Corr. (dB/m) + Read Level (dBµV)
3. Margin (dB) = Limit Line(dBµV/m) – Level (dBµV/m)

Applicant: Valeo North America Inc.
Date of Test: December 04, 2023
Worst Case Operating Mode: Transmitting

Model: KNW2

ANT Polarity: Vertical



Frequency (MHz)	Quasi Peak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.360000	23.0	1000.0	120.000	Vertical	23.2	17.0	40.0
399.990333	26.4	1000.0	120.000	Vertical	25.4	19.6	46.0
709.161667	31.5	1000.0	120.000	Vertical	30.9	14.5	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBµV/m) = Corr. (dB/m) + Read Level (dBµV)
3. Margin (dB) = Limit Line(dBµV/m) – Level (dBµV/m)


Applicant: Valeo North America Inc.

Date of Test: December 04, 2023

Model: KNW2

Worst Case Operating Mode: Transmitting

Fundamental & Spurious Emission Below 30MHz



Polarization	Frequency (MHz)	Reading (dBµV)	Antenna Factor (dB/m)	Net at 3m (dBµV/m)	Distance Factor (-dB)	Calculated at 300m (dBµV/m)	Limit at 300m (dBµV/m)	Margin (dB)
Horizontal	0.125	59.3	15.2	74.5	80	-5.5	25.7	-31.2
Horizontal	0.0099	47.7	18.8	66.5	80	-13.5	47.7	-61.2
Horizontal	0.0604	40.4	15.3	55.7	80	-24.3	32.0	-56.3
Horizontal	0.110*	16.8	15.2	32.0	80	-48.0	26.8	-74.8
Horizontal	0.313	31.7	15.1	46.8	80	-33.2	17.7	-50.9
Polarization	Frequency (MHz)	Reading (dBµV)	Antenna Factor (dB/m)	Net at 3m (dBµV/m)	Distance Factor (-dB)	Calculated at 30m (dBµV/m)	Limit at 30m (dBµV/m)	Margin (dB)
Horizontal	0.717	27.5	14.1	41.6	40	1.6	30.5	-28.9

- Notes:
1. The specified limits of frequency band 9~90 kHz, 110~490 kHz are in average and measurements are made with peak detectors. Quasi-Peak detector is used for other frequency band.
 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Loop antenna is used for the emission under 30MHz.
 5. "*" Emission within restricted band fulfils the requirement of section 15.205.
 6. Horizontal and Vertical polarization were tested and only the worst-case data were shown.

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.


This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Miscellaneous Information

This miscellaneous information includes 20dB bandwidth and emission measuring procedure.

9.1 20dB bandwidth

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered. The test plots are reported as below.



9.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Average detector is used for 9–90 KHz, 110–490 KHz and Quasi-Peak detector is used for other frequency band. The IF bandwidth used for measurement of radiated signal strength was 10 KHz for emission below 30 MHz and 120 KHz for emission from 30 MHz to 1000 MHz.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz up to the 1GHz. For line-conducted emissions, the range scanned is 150kHz to 30MHz.

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.10 - 2013.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitization is applicable to this unit is included in this report.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	Aug-04-2021	Aug-04-2024
SZ185-03	EMI Receiver	R & S	ESR7	100547	Apr-27-2023	Apr-27-2024
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	May-18-2021	May-18-2024
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	Apr-27-2023	Apr-27-2024
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	Dec-19-2022	Dec-19-2023
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	Dec-12-2021	Dec-12-2024
SZ062-02	RF Cable	RADIALL	RG 213U	--	Nov-01-2023	May-01-2024
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	Nov-01-2023	May-01-2024
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	Nov-01-2023	May-01-2024

*****End of Report*****