

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product	43 inch LCD display
Main Model	RCS-430LYAZ
FCC ID	2BAL6430LYAZ

2. EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S = PG/4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

CALCULATION

A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated.

Mode	Max PK Output Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Power Density Limit (mW/cm ²)
11b	15.25	15±1(16)	39.811	0.029713	1
11g	16.68	17±1(18)	63.096	0.047092	1
11n/HT20	16.32	16±1(17)	50.119	0.037407	1
11n/HT40	15.70	16±1(17)	50.119	0.037407	1

Note: The estimation distance is 20cm.
2.4G WIFI: Antenna Gain=5.74dBi (linear: 3.7497), $\pi=3.14$

Note: PK Output power=conducted power.
Conducted power see the test report UNIA23030812ER-61, antenna gain=5.74dBi.

-----The End-----