

TEST REPORT

FCC ID.	2BAMG-IGO3600
Test Report No.	TCT230320E907
Date of issue	May 10, 2023
Testing laboratory	SHENZHEN TONGCE TESTING LAB
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
Applicant's name	Foxtheon Energy Technology (Fujian) Co., Ltd.
Address	Room 409 Building 16, Hi-tech Zone Haixiyuan, Fuzhou, China
Manufacturer's name ...	Foxtheon Energy Technology (Fujian) Co., Ltd.
Address	Room 409 Building 16, Hi-tech Zone Haixiyuan, Fuzhou, China
Standard(s)	FCC CFR Title 47 Part 1.1307
Product Name	Portable Power Station
Trade Mark	Foxtheon
Model/Type reference	iGo3600
Rating(s)	AC 120V/60Hz Rechargeable Li-ion Battery DC 57.6V
Date of receipt of test item	Mar. 20, 2023
Date (s) of performance of test	Feb. 27, 2023 - Apr. 26, 2023
Tested by (+signature) ...	Aaron MO
Check by (+signature) ...	Beryl ZHAO
Approved by (+signature) :	Tomsin



General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
2. General Information.....	4
2.1. Test environment and mode.....	4
2.2. Description of Support Units.....	4
3. Facilities and Accreditations	5
3.1. Facilities	5
3.2. Location	5
4. Test Results and Measurement Data	6

1. General Product Information

1.1. EUT description

Product Name	Portable Power Station
Model/Type reference	iGo3600
Sample Number	TCT230227E016-0101
Operation Frequency	For BLE: 2402MHz~2480MHz For WIFI: 2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) LTE Band 2: TX: 1850 MHz ~ 1910 MHz, RX: 1930 MHz ~ 1990 MHz LTE Band 5: TX: 824 MHz ~ 849 MHz, RX: 869 MHz ~ 894 MHz
Modulation Type	For BLE: GFSK For WIFI: DSSS(802.11b), OFDM (802.11g/802.11n) For LTE: QPSK, 16-QAM
Antenna Type	For BLE/WIFI: PCB Antenna For LTE: Internal Antenna
Antenna Gain	BLE: 2.41dBi WIFI: 2.41dBi LTE Band 2: 1.5dBi LTE Band 5: 0.5dBi
Rating(s)	AC 120V/60Hz Rechargeable Li-ion Battery DC 57.6V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

2. General Information

2.1. Test environment and mode

Item	Normal condition
Temperature	+25°C
Voltage	DC 57.6V
Humidity	56%
Atmospheric Pressure:	1008 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.
4. This test report was based on FCC ID: 2A986-QX3600; Change applicant, manufacturer, address, product name, product model No., trade mark and external photographs of EUT.

3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1)

For BLE: The tune-up Power for antenna is 8dBm (6.32mW) at 2402MHz, 2.41dBi antenna gain(with 1.74 numeric antenna gain.)

For WIFI: The tune-up Power for antenna is 18dBm (63.10mW) at 2462MHz, 2.41dBi antenna gain(with 1.74 numeric antenna gain.)

For LTE Band 2: The tune-up Power for antenna is 24dBm (251.19mW) at 1880MHz, 1.5dBi antenna gain(with 1.41 numeric antenna gain.)

For LTE Band 5: The tune-up Power for antenna is 23dBm (199.53mW) at 836.5MHz, 0.5dBi antenna gain(with 1.12 numeric antenna gain.)

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Calculation:

$$\text{Given } E = \frac{\sqrt{30*P*G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Substituting the MPE safe distance using $d=20\text{cm}$ into above equation.

Yields: $S=0.000199*P*G$

Mode	Power(mW)	numeric antenna gain	Power density (mW/cm ²)	Limit (mW/cm ²)	Result
BLE	6.32	1.74	0.002188	1.0	PASS
WIFI	63.10	1.74	0.021849		
LTE Band 2	251.19	1.41	0.070481		
LTE Band 5	199.53	1.12	0.044471		

The device contain transmitters (BT & LTE, WIFI & LTE) can transmit multiple transmission modes at the same time.

Maximum Emissions Level			
Mode	Power density	Limit	Result
BT & LTE	0.072669	1.0	
WIFI & LTE	0.092330		Pass

*******END OF REPORT*******