


RF EXPOSURE REPORT

Report No.: DDT-B24011002-2E02

Applicant	:	Sensata Technologies (Changzhou) Co., Ltd.
Applicant Address	:	No. 18, Chuangxin Road, Xinbei District, Changzhou City, Jiangsu, China, 213031
Equipment Under Test	:	TPMS Sensor
Model No.	:	AG5PF4
Trade Mark	:	
FCC ID	:	2BAW4-AG5PF4
Manufacturer	:	Sensata Technologies (Changzhou) Co., Ltd.
Manufacturer Address	:	No. 18, Chuangxin Road, Xinbei District, Changzhou City, Jiangsu, China, 213031

Issued By: Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park, Development Area, Tianjin, China

Tel: +86-22-58038033, **E-mail:** ddt@dddt.com, **http://**www.ddttest.com



REPORT

Table of Contents

1.	General information.....	5
1.1.	Description of Equipment.....	5
1.2.	Assess laboratory.....	5
2.	RF Exposure Evaluation.....	6
2.1.	Requirement.....	6
2.2.	Estimation result.....	6

Test Report Declare

Applicant	:	Sensata Technologies (Changzhou) Co., Ltd.
Address	:	No. 18, Chuangxin Road, Xinbei District, Changzhou City, Jiangsu, China, 213031
Equipment under Test	:	TPMS Sensor
Model No.	:	AG5PF4
Trade Mark	:	
FCC ID	:	2BAW4-AG5PF4
Manufacturer	:	Sensata Technologies (Changzhou) Co., Ltd.
Address	:	No. 18, Chuangxin Road, Xinbei District, Changzhou City, Jiangsu, China, 213031

Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Tianjin Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Tianjin Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-B24011002-2E02		
Date of Receipt:	Jan. 12, 2024	Date of Test:	Jan. 15, 2024 ~ Jan. 20, 2024

Prepared By:

Novak Wei

Novak Wei/Engineer

Approved By:

Aaron Zhang

Aaron Zhang /Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Tianjin Dongdian Testing Service Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jan. 24, 2024	

1. General information

1.1. Description of Equipment

EUT Description	: TPMS Sensor
Model Number	: AG5PF4
Serial Number	: N/A
Hardware Version	: 01
Software Version	: 01
Sample Type	: Vehicle Device
EUT function description	: Please refer to user manual of this device
Power supply	: Internal 3V DC 2032 Lithium battery power supply
Support Frequency	: 433.92 MHz
Max. Power	: 62.11 dB μ V/m@3m (Test result)
Max. EIRP	: -33.15 dBm/0.00484(mW) (Calculate result)
Max. ERP	: -35.3 dBm/0.00295 (mW) (Calculate result)
Conducted Power	: -10.8 dBm/0.0832(mW) (Calculate result)
Type of Modulation	: FSK
TX. Antenna Gain	: Max peak gain -24.5 dBi
Antenna Type	: Internal PCB loop antenna

Note:

$$EIRP(W)=(E1*d)^2/30$$

$$EIRP(dBm)=10\log_{10}(EIRP(W))+30=E2+20\log(d)-104.8$$

$$\text{Conducted Power} = \text{Max. EIRP} - \text{Antenna Gain}$$

E1: Electric field strength in V/m

E2: Electric field strength in dB μ V/m

d: measurement distance in m

1.2. Assess laboratory

Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China., 300385

Tel: +86-22-58038033, <http://www.ddttest.com>, Email: ddt@dgdtd.com

NVLAP (National Voluntary Laboratory Accreditation Program) CODE: 500036-0

CNAS (China National Accreditation Service for Conformity Assessment) CODE: L13402

FCC Designation Number: CN5004; FCC Test Firm Registration Number: 368676

ISED (Innovation, Science and Economic Development Canada) Company Number: 27768

Conformity Assessment Body Identifier: CN0125

VCCI Facility Registration Number: C-20089, T-20093, R-20125, G-20122

2. RF Exposure Evaluation

2.1. Requirement

Per § 1.1307(b)(3)(i)(A), a single RF source is *exempt RF device* (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions.

This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

2.2. Estimation result

Mode	Band	EIRP Tune-up (dBm)	EIRP Tune-up (mW)	Conducted Power (dBm)	Conducted Power (mW)
Transmitter Emissions	433.92MHz	-32	0.000631	-10.8	0.0832

Conclusion: No SAR and evaluation of exposure required since transmitter power is below FCC threshold 1mW.

END OF REPORT