

TEST REPORT

EUT Description	WLAN and BT, 2x2 PCIe M.2 1216 SD adapter card
Brand Name	Intel® Wi-Fi 6E AX211
Model Name	AX211D2W
FCC/IC ID	FCCID: PD9AX211D2 / IC 1000M-AX211D2
Date of Test Start/End	2020-12-01 /2021-01-20
Features	802.11ax, Dual Band, 2x2 Wi-Fi + Bluetooth® 5.2 (see section 5)

Applicant	Intel Mobile Communications
Address	100 Center Point Circle, Suite 200 Columbia, South Carolina 29210 USA
Contact Person	Steven Hackett
Telephone/Fax/ Email	steven.c.hackett@intel.com

Reference Standards	FCC CFR Title 47 Part 15 E RSS-247 issue 2, RSS-Gen A1 issue 5 (see section 1)
---------------------	--

Test Report identification	201120-03.TR02
Revision Control	Rev. 00 This test report revision replaces any previous test report revision (see section 8)

The test results relate only to the samples tested.
This report shall not be reproduced, except in full, without the written approval of the laboratory.
Reference to accreditation shall be used only by full reproduction of test report.


Issued by



Digitally signed by
Z.OUACHICHA
Date: 2021.02.05 18:54:18
+01'00'

Zayd OUACHICHA
(Test Engineer Lead)

Reviewed by



Olivier FARGANT
cn=Olivier FARGANT, o=Intel
Corporation, ou,
email=olivier.fargant@intel.com, c=FR
2021.02.05 18:58:17 +01'00'

Olivier FARGANT
(Technical Officer)

Intel Corporation S.A.S – WRF Lab
425 rue de Goa – Le Cargo B6 - 06600, Antibes, France
Tel. +33493001400 / Fax +33493001401

Table of Contents

1. Standards, reference documents and applicable test methods	3
2. General conditions, competences and guarantees	3
3. Environmental Conditions	3
4. Test samples	4
5. EUT Features	5
6. Remarks and comments	5
7. Test Verdicts summary	6
7.1. 802.11 A/N/AC/AX – U-NII-2C	6
8. Document Revision History	6
Annex A. Test & System Description	7
A.1 MEASUREMENT SYSTEM	7
A.2 TEST EQUIPMENT LIST	9
A.3 MEASUREMENT UNCERTAINTY EVALUATION	10
Annex B. Test Results U-NII-2C	11
B.1 TEST CONDITIONS	11
B.2 TEST RESULTS TABLES	12
B.2.1 26dB & 99% Bandwidth	12
B.2.2 Power Limits. Maximum Output power & Maximum power spectral Density	16
B.2.3 Undesirable emission limits : out of band (Conducted)	26
B.2.4 Radiated spurious emission	27
Annex C. System Plots	44
C.1.1 26dB Bandwidth	44
C.1.2 99% Bandwidth	48
C.1.3 Maximum Output Power & Maximum power spectral Density	53
C.1.4 Maximum output power & Maximum power spectral Density (Overlapped Channel)	60
C.1.5 Undesirable emission limits: out of band (Conducted)	63
Annex D. Photographs	81
D.1 TEST SETUP	81
D.2 TEST SAMPLE	83

1. Standards, reference documents and applicable test methods

FCC	<ol style="list-style-type: none"> 1. FCC Title 47 CFR part 15 – Subpart E – Unlicensed National Information Infrastructure Devices. 2019-10-01 Edition 2. FCC Title 47 CFR part 15 - Subpart C – §15.209 Radiated emission limits; general requirements. 2019-10-01 Edition 3. FCC OET KDB 789033 D02 v02r01 - General U-NII Test Procedures New Rules – Guidelines for compliance testing of Unlicensed National Information Infrastructure (U-NII) Devices (Part 15, Subpart E). 4. ANSI C63.10-2013 American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
ISED	<ol style="list-style-type: none"> 1. RSS-Gen Issue 5 Amendment 1 - General Requirements for Compliance of Radio Apparatus. 2. RSS-247 Issue 2 - Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and License-Exempt Local Area Network (LE-LAN) Devices. 3. FCC OET KDB 789033 D02 v02r01 - General U-NII Test Procedures New Rules – Guidelines for compliance testing of Unlicensed National Information Infrastructure (U-NII) Devices (Part 15, Subpart E) 4. ANSI C63.10-2013 American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

2. General conditions, competences and guarantees

- ✓ Tests performed under FCC standards identified in section 1 are covered by A2LA accreditation.
- ✓ Tests performed under ISED standards identified in section 1 are covered by Cofrac accreditation.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 laboratory accredited by the American Association for Laboratory Accreditation (A2LA) with the certificate number 3478.01.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an Accredited Test Firm recognized by the FCC, with Designation Number FR0011.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 testing laboratory accredited by the French Committee for Accreditation (Cofrac) with the certificate number 1-6736.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is a Registered Test Site listed by ISED, with ISED #1000Y.
- ✓ Intel WRF Lab declines any responsibility with respect to the identified information provided by the customer and that may affect the validity of results.
- ✓ Intel WRF Lab only provides testing services and is committed to providing reliable, unbiased test results and interpretations.
- ✓ Intel WRF Lab is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.
- ✓ Intel WRF Lab has developed calibration and proficiency programs for its measurement equipment to ensure correlated and reliable results to its customers.
- ✓ This report is only referred to the item that has undergone the test.
- ✓ This report does not imply an approval of the product by the Certification Bodies or competent Authorities.
- ✓ Complete or partial reproduction of the report cannot be made without written permission of Intel WRF Lab.

3. Environmental Conditions

- ✓ At the site where the measurements were performed the following limits were not exceeded during the tests:

Temperature	20.2°C ± 4.8°C
Humidity	44.6% ±9.5%

4. Test samples

Sample	Control #	Description	Model	Serial #	Date of receipt	Note
#1	201120-03.S07	WiFi 6E Module	AX211D2W	WFM: D8F8834E56F1	2020-11-23	Used for RF Conducted test
	180000-01.S06	Adapter 1216SD to M.2	Adapter M2	N/A	2017-05-11	
	170000-01.S02	Laptop	Latitude E5450	21HTPF2	2017-03-28	
	200611-01.S10	Extender	PCB00651_01	-	2020-11-30	
#2	201120-03.S09	WiFi 6E Module	AX211D2W	WFM:DF8834E4C92	2020-11-23	See note ¹
	200102-01.S03	Extender	ADEXELEC	-	2020-01-02	
	200611-01.S06	Adaptor	PowerBy SNJ A4	-	2020-11-30	
	200602-03.S06	Absorber	MCS0	-	2020-07-03	
	180000-01.S05	Socket	Adapter 1216SD to M.2	-	2017-08-09	
	170801-01.S10	Laptop	Latitude E7470	7KNOXF2	2017-09-08	
	200611-03.S28	Main Antenna	SkyCross	-	2020-07-01	
	200611-03.S29	Aux Antenna	SkyCross	-	2020-07-01	
#3	201120-03.S08	WiFi 6E Module	AX211D2W	WFM:D8F8834E56AB	2020-11-23	See note ²
	200611-03.S26	Extender	ADEXELEC	-	2020-07-01	
	200611-01.S07	Adaptor	PowerBy SNJ A4	-	2020-11-30	
	200602-03.S06	Absorber	MCS0	-	2020-07-03	
	180000-01.S02	Socket	Adapter 1216SD to M.2	-	2017-08-09	
	170000-01.S01	Laptop	Latitude E5470	DBPLMC2	2017-03-28	
	200928-03.S08	Main Antenna	SkyCross	-	2020-09-01	
	200928-03.S09	Aux Antenna	SkyCross	-	2020-09-01	

¹ Used for Radiated Spurious Emissions tests for the following spurious frequency ranges:

- 1GHz to 6.4GHz and 18GHz-40GHz for SISO and MIMO DUT modes
- 6.4 to 18GHz for MIMO DUT mode

² Used for Radiated Spurious Emissions tests for the following spurious frequency ranges:

- 30MHz-1GHz for SISO and MIMO DUT modes
- 6.4GHz-18GHz for SISO DUT mode

5. EUT Features

The herein information are provided by the customer

Brand Name	Intel® Wi-Fi 6E AX211		
Model Name	AX211D2W		
Software Version	DRTU Version: 11195_99_2100_51G		
Driver Version	99.0.58.3		
Prototype / Production	Production		
Supported Radios	802.11b/g/n/ax	2.4GHz (2400.0 – 2483.5 MHz)	
	802.11a/n/ac/ax	5.2GHz (5150.0 – 5350.0 MHz)	
		5.6GHz (5470.0 – 5725.0 MHz)	
		5.8GHz (5725.0 – 5850.0 MHz)	
	Bluetooth 5.2	2.4GHz (2400.0 – 2483.5 MHz)	
Antenna Information	Transmitter	Main (chain A)	Aux (chain B)
	Manufacturer	SkyCross	Skycross
	Antenna type	PIFA antenna	PIFA antenna
	Part number	N/A	N/A
	Declared antenna gain (dBi)	+5	+5
Document	Filename	Date of receipt	
	Intel_Ref_Antenna data_HMC-M2 Ant_Spec_Universe_SkyCross Antenna	2013-01-28	

6. Remarks and comments

1. No deviations were made from the test methods listed in section 1 of this report

7. Test Verdicts summary

The statement of conformity to applicable standards in the table below are based on the measured values, without taking into account the measurement uncertainties.

7.1. 802.11 a/n/ac/ax – U-NII-2C

FCC part	RSS clause	Test name	Verdict
15.407 (a) (2)	RSS-247 Clause 6.2.3.1	Power Limits. Maximum output power	P
15.407 (a) (2)	RSS-247 Clause 6.2.3.1	Power spectral density	P
15.407 (b) (3) 15.209 (a)	RSS-247 Clause 6.2.3.2 RSS-GEN A1 Clause 8.9	Undesirable emissions limits: out of band (conducted)	P
15.407 (b) (3) 15.209 (a)	RSS-247 Clause 6.2.3.2 RSS-GEN A1 Clause 8.9	Undesirable emissions limits: Spurious emissions (radiated)	P

P: Pass

F: Fail

NM: Not Measured

NA: Not Applicable

8. Document Revision History


Revision #	Modified by	Revision Details
Rev. 00	C.Requin	First Issue

Annex A. Test & System Description

A.1 Measurement System


Measurements were performed using the following setups, made in accordance to the general provisions of FCC OET KDB 789033 D02 General UNII Test Procedures.

The DUT was installed in a test fixture and this test fixture is connected to a laptop computer and AC/DC power adapter. The laptop computer was used to configure the EUT to continuously transmit at a specified output power using all different modes and modulation schemes, using the Intel proprietary tool DRTU.





Radiated test setup

Radiated Setup 30 MHz - 1 GHz



Radiated Setup 1 GHz – 6.4 GHz





Sample Calculation

The spurious received voltage V(dBμV) in the spectrum Analyzer is converted to Electric field strength using the transducer factor F corresponding to the Rx path Loss:

$$F \text{ (dB/m)} = \text{Rx Antenna Factor (dB/m)} + \text{Cable losses (dB)} - \text{Amplifiers Gain (dBi)}$$

$$E \text{ (dB}\mu\text{V/m)} = V \text{ (dB}\mu\text{V)} + F \text{ (dB/m)}$$

For field strength measurements made at other than the distance at which the applicable limit is specified, the field strength of the emission at the distance specified by the limit is deduced as follows:

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \cdot \log(D_{\text{Meas}}/D_{\text{SpecLimit}})$$

where

- E_{SpecLimit}* is the field strength of the emission at the distance specified by the limit, in dBμV/m
- E_{Meas}* is the field strength of the emission at the measurement distance, in dBμV/m
- D_{Meas}* is the measurement distance, in m
- D_{SpecLimit}* is the distance specified by the limit, in m

A.2 Test Equipment List

Conducted setup

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
0316	Spectrum Analyzer	FSV30	103309	Rohde & Schwarz	2019-09-02	2021-09-02
0442	RF cable 50cm	Coax 2.92mm Male To 2.92mm Male	N/A	PASTERNAK	2020-08-26	2021-02-26
1044	10dB Attenuator + MH4	N/A	N/A	N/A	N/A	N/A
0581	Temp & Humidity Logger	RA12E-TH1-RAS	RA12-B89BE3	Avtech	2020-01-23	2022-01-23
1002	Measurement SW v1.5.4.2	Octopi	N/A	Step AT	N/A	N/A

Radiated Setup #1

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
0135	Anechoic Chamber	FACT3	5720	ETS-Lindgren	2020-07-06	2022-01-07
0136	Turn Table	ETS	-	ETS-Lindgren	N/A	N/A
0147	Switch & Positioning systems	EMC Center	00159757	ETS-Lindgren	N/A	N/A
0530	Measurement SW	EMC32, v10.40.10	100623	Rohde & Schwarz	N/A	N/A
1033	Boresight antenna mast	BAM 4.0-P	P/278/2890.01	Maturo	N/A	N/A
1076	Spectrum Analyzer	FSW43	101847	Rohde & Schwarz	2020-11-02	2022-11-02
0993	Biconical antenna 30 MHz – 1 GHz	UBAA9115 BBVU9135 DGA9552N	+ + 0286 + CH 9044	Schwarzbeck	2019-11-22	2021-11-22
0325	Horn antenna	3117	00157734	ETS-Lindgren	2019-08-12	2021-08-12
0141	Horn Antenna + Amplifier + HPF6.4	3117	00157736	ETS-Lindgren	2020-04-02	2022-04-02
0334	Double-Ridged Waveguide Horn with Pre-Amplifier 18 GHz to 40 GHz	3116C+PA	00169308bis + 00196308	ETS-Lindgren	2019-07-24	2021-07-24
0859	Cable 2.5m - 30MHz to 18GHz	0500990992500KE	19.23.395	Radiall	2020-11-27	2021-05-27
0206	Cable 1.2m – 18 to 40 GHz	UFA147A-0-0480- 200200	MFR 64639223720-003	Micro-coax	2020-08-25	2021-02-25
0263	Cable 1m - 1GHz to 18GHz	UFA147A	-	Utilflex	2020-08-25	2021-02-25
0369	Cable 2m - 26.5GHz to 40GHz	794-9191-2000A	E00327	Atem	2020-08-25	2021-02-25
0371	Cable 1m – 30 MHz - 18GHz	UFB311A-0-0590- 50U50U	MFR 64639 223230-001	Micro-coax	2020-08-25	2021-02-25
1099	Cable 7m DC-18 GHz	0501051057000GX	19.35.850	Radiall	2020-11-27	2021-05-27
0809	Cable 7m - 18GHz to 40GHz	R286304009	-	Radiall	2020-08-25	2021-02-25
1098	Cable 1.5m - DC-18GHz	CBL-1.5M-SMSM+	202879	Mini-Circuits	2020-11-27	2021-05-27
0797	Temp & Humidity Logger	RA12E-TH1-RAS	RA12-D0EB1A	Avtech	2019-07-04	2021-07-04

N/A: Not Applicable

Radiated Setup #2

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
0337	Anechoic chamber	RFD-FA-100	5996	ETS Lindgren	2020-07-06	2022-07-06
0238	Switch & Positioner	EMCenter	00151232	ETS Lindgren	N/A	N/A
0382	Antenna Tower	2171B-3.0M	00150123	ETS Lindgren	N/A	N/A
0383	Turntable	-	-	ETS Lindgren	N/A	N/A
0329	Measurement SW	EMC32, v10.50.10	100401	Rohde & Schwarz	N/A	N/A
0133	Spectrum Analyzer	FSV40	101358	Rohde & Schwarz	2020-02-25	2022-02-25
0138	Double Ridge Horn (1- 18GHz)	3117	00152266	ETS Lindgren	2020-03-08	2022-03-08
0141	Horn Antenna 3117 + Amplifier + HPF6.4	3117	00157736	ETS-Lindgren	2020-04-02	2022-04-02
0334	Double Horn Ridged antenna	3116C-PA	00169308bis + 00196308	ETS-Lindgren	2019-07-24	2021-07-24
0871	RF Cable 1-18GHz, 1.5 m	0501050991200GX	19.21.710	Radiall	2020-08-20	2021-02-20
0860	RF Cable 1-18GHz, 1.2 m	2301761761200PJ	12.22.1104	Radiall	2020-08-20	2021-02-20
0275	RF Cable 1-18GHz - 6.5m	140-8500-11-51	001	Spectrum	2020-08-20	2021-02-20
0684	RF Cable 1GHz-18GHz 1.5m	-	-	Spirent	2020-08-20	2021-02-20
0679	RF Cable 18-40 GHz 6m	R286304009	1747364	Radiall	2020-08-20	2021-02-20
0028	RF Cable 1.2m 40MHz-40GHz	794-9191-1200A	DA585	Atem	2020-08-20	2021-02-20
0725	RF Cable 1-9.5GHz 1.2m	0500990991200KE	-	Radiall	2020-08-20	2021-02-20
0796	Temp & Humidity Logger	RA12E-TH1-RAS	RA12-D4F316	Avtech	2019-07-05	2021-07-05

N/A: Not Applicable

Shared Radiated Equipment

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
0616	Power Sensor	NRP-Z81	104385	Rohde & Schwarz	2020-04-08	2022-04-08
0617	Power Sensor	NRP-Z81	104386	Rohde & Schwarz	2020-04-08	2022-04-08
0618	Power Sensor	NRP-Z81	104382	Rohde & Schwarz	2020-04-08	2022-04-08

A.3 Measurement Uncertainty Evaluation

The system uncertainty evaluation is shown in table below with a coverage factor of $k = 2$ to indicate a 95% level of confidence:

Measurement type	Uncertainty	Unit
Timing	± 0.12	%
Power Spectral density	± 1.47	dB
Occupied bandwidth	± 2.07	%
Conducted Power	± 1.03	dB
Conducted Spurious Emission <40 GHz	± 3.45	dB
Radiated tests <1GHz	± 5.26	dB
Radiated tests 1GHz – 40 GHz	± 4.85	dB

Annex B. Test Results U-NII-2C

The herein test results were performed by:

Test case measurement	Test Engineer
Power Limits. Maximum output power	C.Requin
Power spectral density	C.Requin
Undesirable emissions limits: out of band (conducted)	C.Requin
Undesirable emissions limits (radiated)	A.Lounes. N.Nachabe, N.Bui

B.1 Test Conditions

For 802.11a mode the EUT can transmit at both CHAIN A and CHAIN B RF outputs individually, but not simultaneously.

For 802.11n20 & 802.11ax20 (20 MHz channel bandwidth), 802.11n40 & 802.11ax40 (40MHz channel bandwidth), 802.11ac80 & 802.11ax80 (80MHz channel bandwidth) and 802.11ac160 & 802.11ax160 (160MHz channel bandwidth) modes the EUT can transmit at both CHAIN A and CHAIN B RF outputs individually, and also simultaneously.

The following data rates were selected based on preliminary testing that identified those rates as the worst cases for output power and spurious levels at the band edges:

Transmission	Mode	Bandwidth (MHz)	Worst Case Data Rate
SISO	802.11a	20	6Mbps
	802.11n	20	HT0
		40	HT0
	802.11ac	80	VHT0
		160	VHT0
	802.11ax	20	HE0
		40	HE0
		80	HE0
160		HE0	
MIMO	802.11n	20/40	HT8
	802.11ac	80/160	VHT0
	802.11ax	20/40/80/160	HE0

B.2 Test Results Tables

B.2.1 26dB & 99% Bandwidth

Test procedure

The conducted setup shown in section *Test & System Description* was used to measure the 26dB & 99% bandwidth. The antenna terminal of the EUT is connected to the spectrum analyzer through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

For the overlapped channels between U-NII-2C and U-NII-3 bands, and according to FCC OET KDB 789033 D02, the boundary frequency between the bands is used as one edge for defining the portion of the 26dB bandwidth that falls within a particular U-NII band. This rule is only applicable for the 26dB bandwidth and for those channels marked as overlapped.

Results tables**U-NII-2C channels**

Mode	Rate	Antenna	Channel	Freq [MHz]	26dB BW [MHz]	99% BW [MHz]
802.11a	6Mbps	SISO A	100	5500	24.30	16.64
			120	5600	24.40	16.79
			140	5700	24.45	16.58
		SISO B	100	5500	24.05	16.59
			120	5600	24.30	16.63
802.11n20	HT0	SISO A	100	5500	24.70	17.71
			120	5600	24.75	17.79
			140	5700	24.60	17.77
		SISO B	100	5500	24.55	17.77
			120	5600	24.65	17.76
			140	5700	24.65	17.83
	HT8	MIMO A	100	5500	25.15	17.68
			120	5600	25.00	17.93
			140	5700	24.65	17.80
		MIMO B	100	5500	24.50	17.81
			120	5600	24.55	17.90
			140	5700	24.25	17.77
802.11n40	HT0	SISO A	102	5510	44.19	36.16
			118	5590	45.76	36.16
			134	5670	47.08	36.24
		SISO B	102	5510	44.19	36.08
			118	5590	45.65	36.16
			134	5670	46.09	36.24
	HT8	MIMO A	102	5510	44.73	36.16
			118	5590	50.71	36.32
			134	5670	45.32	36.16
		MIMO B	102	5510	43.02	36.00
			118	5590	45.32	36.32
			134	5670	43.45	36.00
802.11ac80	VHT0	SISO A	106	5530	87.40	75.12
			122	5610	93.48	75.36
		SISO B	106	5530	89.49	75.00
			122	5610	89.30	75.24
		MIMO A	106	5530	88.35	75.00
			122	5610	90.25	75.24
		MIMO B	106	5530	85.12	75.00
			122	5610	91.01	75.12
802.11ac160	VHT0	SISO A	114	5570	164.34	153.00
		SISO B			240.90	153.40
		MIMO A			164.34	153.00
		MIMO B			163.35	153.00

Max Value

Mode	Rate	Antenna	Channel	Freq [MHz]	RU config.	26dB BW [MHz]	99% BW [MHz]		
802.11ax20	HE0	SISO A	100	5500	Full	24.85	18.90		
					26/0	20.75	18.37		
					52/37	22.55	18.53		
					106/53	22.90	18.23		
			120	5600	Full	23.85	18.90		
					Full	24.55	18.95		
		140	5700	26/8	20.95	18.09			
				52/40	22.35	18.13			
				106/54	23.35	18.03			
				Full	24.95	18.87			
		SISO B	100	5500	26/0	20.65	18.60		
					52/37	21.40	18.49		
					106/53	23.00	18.18		
					Full	24.30	18.95		
			120	5600	Full	24.90	18.86		
					26/8	21.30	18.55		
		140	5700	52/40	22.10	18.51			
				106/54	23.80	17.81			
				Full	23.65	19.03			
				26/0	20.75	18.65			
		MIMO A	100	5500	52/37	22.45	18.29		
					106/53	23.10	18.38		
					Full	24.00	18.88		
					Full	24.70	18.93		
120	5600		26/8	21.00	17.93				
			52/40	21.60	18.14				
140	5700	106/54	23.50	18.19					
		Full	23.60	19.05					
		26/0	21.00	18.65					
		52/37	22.30	18.33					
MIMO B	100	5500	106/53	23.65	18.24				
			Full	24.45	18.93				
			Full	23.95	18.91				
			26/8	21.05	18.85				
	120	5600	52/40	20.45	17.80				
			106/54	23.75	17.95				
802.11ax40	HE0	SISO A	102	5510	Full	43.38	37.68		
					242/61	24.57	19.12		
			118	5590	Full	44.91	37.68		
					134	5670	Full	46.53	37.52
		134	5670	242/62	25.65	18.80			
				Full	43.02	37.44			
		SISO B	102	5510	242/61	24.21	18.96		
					118	5590	Full	43.92	37.60
			134	5670	Full	44.28	37.68		
					242/62	24.12	18.88		
		MIMO A	102	5510	Full	44.01	37.68		
					242/61	25.47	18.88		
			118	5590	Full	47.25	37.68		
					134	5670	Full	44.10	37.68
		134	5670	242/62	25.74	18.88			
				Full	43.02	37.44			
		MIMO B	102	5510	242/61	24.84	18.80		
					118	5590	Full	47.70	37.84
			134	5670	Full	43.20	37.60		
					242/62	25.02	18.88		
		802.11ax80	HE0	SISO A	106	5530	Full	83.79	76.68
							484/65	43.51	37.56
				122	5610	Full	84.93	76.92	
						Full	83.79	76.68	
SISO B	106			5530	484/65	43.13	37.44		
					Full	86.07	76.80		
122	5610			Full	85.12	76.68			
				484/65	44.65	37.44			
MIMO A	106			5530	Full	87.59	76.80		
					Full	82.65	76.68		
122	5610			484/65	43.51	37.44			
				Full	88.92	76.80			

Max Value

Mode	Rate	Antenna	Channel	Freq [MHz]	RU config.	26dB BW [MHz]	99% BW [MHz]	
802.11ax160	HE0	SISO A	114	5570	Full	163.02	154.80	
					996/67	85.80	76.80	
					996/S67	86.13	77.00	
		SISO B			Full	163.35	155.00	
					996/67	86.46	77.00	
					996/S67	85.47	77.00	
		MIMO A			Full	164.01	154.80	
					996/67	88.77	77.00	
					996/S67	86.13	77.00	
					MIMO B	Full	163.35	154.80
						996/67	84.15	76.80
						996/S67	86.46	77.00

Max Value

Overlapped channels between U-NII-2C and U-NII-3

Mode	Rate	Channel	Frequency (MHz)	Antenna	Chain	26dB BW [MHz] UNII2C
802.11n20	HT0	144	5720	SISO	A	16.67
					B	16.92
	HT8			MIMO	A	16.92
					B	16.47
802.11n40	HT0	142	5710	SISO	A	37.90
					B	38.62
	HT8			MIMO	A	37.00
					B	36.01
802.11ac80	VHT0	138	5690	SISO	A	79.17
					B	78.22
				MIMO	A	77.27
					B	77.27
802.11ax20	HE0	144	5720	SISO	A	17.07
					B	16.92
				MIMO	A	16.52
					B	16.67
802.11ax40	HE0	142	5710	SISO	A	35.83
					B	36.55
				MIMO	A	36.01
					B	36.19
802.11ax80	HE0	138	5690	SISO	A	77.27
					B	75.94
				MIMO	A	76.51
					B	75.94

Max Value

See annex C.1.1 and C.1.2 for screenshot results

B.2.2 Power Limits. Maximum Output power & Maximum power spectral Density

Test limits

Part	Limits
FCC 15.407 (a) (2)	For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the peak power spectral density shall not exceed 11 dBm in any 1 megahertz band.
RSS-247 Clause 6.2.3 (1)	The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band. The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Test procedure

The Maximum Conducted Output Power was measured using the channel integration method according to section E) 2) e) (Method SA-2 Alternative) of FCC OET KDB 789033 D02.

The maximum power spectral density (PSD) was measured using the method according to section F) (Method SA-2 Alternative) of FCC OET KDB 789033 D02.

In the measure-and-sum approach for MIMO mode, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically in linear power units to determine the total emission level from the device.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

The conducted setup shown in section *Test & System Description* was used to measure the maximum conducted output power and power spectral density. The antenna terminal of the EUT is connected to the spectrum analyser through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

For the overlapped channels between U-NII-2C and U-NII-3, and according to FCC OET KDB 789033 D02 the power is computed based on the portion of the emission bandwidth contained within that band. This rule is only applicable for those channels marked as overlapped

Results tables
Duty cycle

Mode	Rate	Antenna	Duty Cycle [%]
802.11a	6Mbps	SISO A	97.60
		SISO B	97.60
802.11n20	HT0	SISO A	98.00
		SISO B	98.00
	HT8	MIMO A	98.00
		MIMO B	98.00
802.11ax20	HE0	SISO A	98.00
		SISO B	98.00
		MIMO A	98.00
		MIMO B	98.00
802.11n40	HT0	SISO A	98.00
		SISO B	98.00
	HT8	MIMO A	98.00
		MIMO B	98.00
802.11ax40	HE0	SISO A	98.00
		SISO B	98.00
		MIMO A	98.00
		MIMO B	98.00
802.11ac80	VHT0	SISO A	98.40
		SISO B	98.40
		MIMO A	97.70
		MIMO B	97.70
802.11ax80	HE0	SISO A	98.00
		SISO B	98.00
		MIMO A	97.10
		MIMO B	97.10
802.11ac160	VTH0	SISO A	97.60
		SISO B	97.60
		MIMO A	96.20
		MIMO B	96.20
802.11ax160	HE0	SISO A	97.10
		SISO B	97.10
		MIMO A	94.00
		MIMO B	94.00

Maximum output power – U-NII-2C Channels

Mode	Rate	#Ch	Freq [MHz]	Antenna	Average Conducted Output Power [dBm]	Avg Max* Conducted Output Power [dBm]	Avg Max*. EIRP [dBm]	Avg Max* Conducted Power [mW]	
802.11a	6Mbps	100	5500	SISO A	20.83	20.94	25.94	124.04	
				SISO B	20.70	20.81	25.81	120.38	
		120	5600	SISO A	20.92	21.03	26.03	126.63	
				SISO B	20.98	21.09	26.09	128.40	
		140	5700	SISO A	20.67	20.78	25.78	119.55	
				SISO B	20.48	20.59	25.59	114.43	
802.11n20	HT0	100	5500	SISO A	20.65	20.65	25.65	116.14	
				SISO B	20.52	20.52	25.52	112.72	
		120	5600	SISO A	20.88	20.88	25.88	122.46	
				SISO B	20.86	20.86	25.86	121.90	
		140	5700	SISO A	20.51	20.51	25.51	112.46	
				SISO B	20.60	20.60	25.60	114.82	
	HT8	100	5500	MIMO A	18.69	18.69	23.69	73.96	
				MIMO B	18.60	18.60	23.60	72.44	
				Combined A+B	21.66	21.66	26.66	146.40	
		120	5600	MIMO A	18.73	18.73	23.73	74.64	
				MIMO B	18.67	18.67	23.67	73.62	
				Combined A+B	21.71	21.71	26.71	148.27	
	140	5700	MIMO A	18.66	18.66	23.66	73.45		
			MIMO B	18.70	18.70	23.70	74.13		
			Combined A+B	21.69	21.69	26.69	147.58		
	802.11n40	HT0	102	5510	SISO A	19.81	19.81	24.81	95.72
					SISO B	19.96	19.96	24.96	99.08
			118	5590	SISO A	21.10	21.10	26.10	128.82
SISO B					21.06	21.06	26.06	127.64	
134			5670	SISO A	21.02	21.02	26.02	126.47	
				SISO B	20.87	20.87	25.87	122.18	
HT8		102	5510	MIMO A	18.33	18.33	23.33	68.08	
				MIMO B	17.92	17.92	22.92	61.94	
				Combined A+B	21.14	21.14	26.14	130.02	
		118	5590	MIMO A	20.77	20.77	25.77	119.40	
				MIMO B	21.13	21.13	26.13	129.72	
				Combined A+B	23.96	23.96	28.96	248.89	
134	5670	MIMO A	20.08	20.08	25.08	101.86			
		MIMO B	19.77	19.77	24.77	94.84			
		Combined A+B	22.94	22.94	27.94	196.70			
802.11ac80	VHT0	106	5530	SISO A	18.06	18.06	23.06	63.97	
				SISO B	17.94	17.94	22.94	62.23	
				MIMO A	21.02	21.02	26.02	126.47	
				MIMO B	21.00	21.00	26.00	125.89	
		122	5610	Combined A+B	15.76	15.86	20.86	38.56	
				SISO A	15.77	15.87	20.87	38.65	
				SISO B	18.78	18.88	23.88	77.20	
				MIMO A	20.36	20.46	25.46	111.20	
				MIMO B	20.42	20.52	25.52	112.75	
				Combined A+B	23.40	23.50	28.50	223.95	
802.11ac160	VHT0	114	5570	SISO A	15.97	16.08	21.08	40.51	
				SISO B	16.89	17.00	22.00	50.07	
				MIMO A	14.67	14.84	19.84	30.47	
				MIMO B	14.58	14.75	19.75	29.84	
				Combined A+B	17.64	17.80	22.80	60.31	

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Max/Min Value

Mode	Rate	#Ch	Freq [MHz]	Antenna	RU config.	Average Conducted Output Power [dBm]	Avg Max* Conducted Output Power [dBm]	Avg Max*. EIRP [dBm]	Avg Max* Conducted Power [mW]		
802.11ax20	HE0	100	5500	SISO A	Full	20.90	20.90	25.90	123.03		
					26/0	13.42	13.42	18.42	21.98		
					52/37	16.31	16.31	21.31	42.76		
					106/53	19.47	19.47	24.47	88.51		
				SISO B	Full	20.67	20.67	25.67	116.68		
					26/0	13.44	13.44	18.44	22.08		
					52/37	16.17	16.17	21.17	41.40		
					106/53	19.50	19.50	24.50	89.13		
				MIMO A	Full	18.80	18.80	23.80	75.86		
					26/0	10.71	10.71	15.71	11.78		
					52/37	13.51	13.51	18.51	22.44		
					106/53	15.85	15.85	20.85	38.46		
		MIMO B	Full	18.93	18.93	23.93	78.16				
			26/0	10.56	10.56	15.56	11.38				
			52/37	13.62	13.62	18.62	23.01				
			106/53	16.22	16.22	21.22	41.88				
		Combined A+B	Full	21.88	21.88	26.88	154.02				
			26/0	13.65	13.65	18.65	23.15				
			52/37	16.58	16.58	21.58	45.45				
			106/53	19.05	19.05	24.05	80.34				
		120	5600	SISO A	Full	20.95	20.95	25.95	124.45		
					26/0	13.42	13.42	18.42	21.98		
					52/37	16.31	16.31	21.31	42.76		
					106/53	19.47	19.47	24.47	88.51		
				SISO B	Full	21.00	21.00	26.00	125.89		
					26/0	10.71	10.71	15.71	11.78		
					52/37	13.51	13.51	18.51	22.44		
					106/53	15.85	15.85	20.85	38.46		
		MIMO A	Full	18.88	18.88	23.88	77.27				
			26/0	10.71	10.71	15.71	11.78				
			52/37	13.51	13.51	18.51	22.44				
			106/53	15.85	15.85	20.85	38.46				
		MIMO B	Full	18.82	18.82	23.82	76.21				
			26/0	10.56	10.56	15.56	11.38				
			52/37	13.62	13.62	18.62	23.01				
			106/53	16.22	16.22	21.22	41.88				
		Combined A+B	Full	21.86	21.86	26.86	153.48				
			26/0	13.65	13.65	18.65	23.15				
			52/37	16.58	16.58	21.58	45.45				
			106/53	19.05	19.05	24.05	80.34				
		140	5700	SISO A	Full	20.58	20.58	25.58	114.29		
					26/8	13.33	13.33	18.33	21.53		
					52/40	16.39	16.39	21.39	43.55		
					106/54	19.34	19.34	24.34	85.90		
					SISO B	Full	20.75	20.75	25.75	118.85	
						26/8	13.42	13.42	18.42	21.98	
						52/40	16.35	16.35	21.35	43.15	
						106/54	19.59	19.59	24.59	90.99	
MIMO A	Full				19.04	19.04	24.04	80.17			
	26/8				10.51	10.51	15.51	11.25			
	52/40				13.26	13.26	18.26	21.18			
	106/54				16.45	16.45	21.45	44.16			
MIMO B	Full			18.84	18.84	23.84	76.56				
	26/8			10.63	10.63	15.63	11.56				
	52/40			13.45	13.45	18.45	22.13				
	106/54			16.46	16.46	21.46	44.26				
Combined A+B	Full			21.95	21.95	26.95	156.73				
	26/8			13.58	13.58	18.58	22.81				
	52/40			16.37	16.37	21.37	43.31				
	106/54			19.47	19.47	24.47	88.42				
802.11ax40	HE0			102	5510	SISO A	Full	19.91	19.91	24.91	97.95
							242/61	21.03	21.03	26.03	126.77
							52/37	16.31	16.31	21.31	42.76
							106/53	19.47	19.47	24.47	88.51
		SISO B	Full			19.80	19.80	24.80	95.50		
			242/61			21.16	21.16	26.16	130.62		
			52/37			16.31	16.31	21.31	42.76		
			106/53			19.47	19.47	24.47	88.51		
		MIMO A	Full			17.78	17.78	22.78	59.98		
			242/61			19.24	19.24	24.24	83.95		
			52/37			16.31	16.31	21.31	42.76		
			106/53			19.47	19.47	24.47	88.51		
		MIMO B	Full	17.65	17.65	22.65	58.21				
			242/61	19.26	19.26	24.26	84.33				
			52/37	16.31	16.31	21.31	42.76				
			106/53	19.47	19.47	24.47	88.51				
		Combined A+B	Full	20.73	20.73	25.73	118.19				
			242/61	22.26	22.26	27.26	168.28				
			52/37	16.31	16.31	21.31	42.76				
			106/53	19.47	19.47	24.47	88.51				
		118	5590	SISO A	Full	21.06	21.06	26.06	127.64		
					242/61	21.04	21.04	26.04	127.06		
					52/37	16.31	16.31	21.31	42.76		
					106/53	19.47	19.47	24.47	88.51		
SISO B	Full			20.88	20.88	25.88	122.46				
	242/61			20.83	20.83	25.83	121.06				
	52/37			16.31	16.31	21.31	42.76				
	106/53			19.47	19.47	24.47	88.51				
MIMO A	Full	23.87	23.87	28.87	243.52						
	242/61	21.19	21.19	26.19	131.52						
	52/37	16.31	16.31	21.31	42.76						
	106/53	19.47	19.47	24.47	88.51						
134	5670	SISO A	Full	21.09	21.09	26.09	128.53				
			242/62	20.95	20.95	25.95	124.45				
			52/37	16.31	16.31	21.31	42.76				
			106/53	19.47	19.47	24.47	88.51				
		SISO B	Full	20.97	20.97	25.97	125.03				
			242/62	20.15	20.15	25.15	103.51				
			52/37	16.31	16.31	21.31	42.76				
			106/53	19.47	19.47	24.47	88.51				
MIMO A	Full	19.08	19.08	24.08	80.91						
	242/62	19.29	19.29	24.29	84.92						
	52/37	16.31	16.31	21.31	42.76						
	106/53	19.47	19.47	24.47	88.51						
MIMO B	Full	18.82	18.82	23.82	76.21						
	242/62	22.75	22.75	27.75	188.43						
	52/37	16.31	16.31	21.31	42.76						
	106/53	19.47	19.47	24.47	88.51						
Combined A+B	Full	21.96	21.96	26.96	157.12						
	242/62	21.96	21.96	26.96	157.12						

* Maximum values are the duty cycle compensated values calculated from the average (measured) values. Max/Min Value

Mode	Rate	#Ch	Freq [MHz]	Antenna	RU config.	Average Conducted Output Power [dBm]	Avg Max* Conducted Output Power [dBm]	Avg Max*. EIRP [dBm]	Avg Max* Conducted Power [mW]
802.11ax80	HE0	106	5530	SISO A	Full	18.43	18.43	23.43	69.66
					484/65	19.99	19.99	24.99	99.77
				SISO B	Full	18.31	18.31	23.31	67.76
					484/65	19.08	19.08	24.08	80.91
				MIMO A	Full	21.04	21.04	26.04	127.06
					484/65	21.03	21.03	26.03	126.77
		MIMO B	Full	15.47	15.60	20.60	36.29		
			484/65	17.46	17.59	22.59	57.38		
		Combined A+B	Full	15.47	15.60	20.60	36.29		
			484/65	15.87	16.00	21.00	39.79		
122	5610	SISO A	Full	18.48	18.61	23.61	72.58		
		SISO B	Full	19.75	19.88	24.88	97.17		
		MIMO A	Full	20.82	20.95	25.95	124.39		
		MIMO B	Full	20.71	20.84	25.84	121.28		
		Combined A+B	Full	23.78	23.90	28.90	245.67		
802.11ax160	HE0	114	5570	SISO A	Full	16.25	16.38	21.38	43.43
					996/67	17.12	17.25	22.25	53.06
					996/S67	20.33	20.46	25.46	111.12
				SISO B	Full	16.30	16.43	21.43	43.93
					996/67	17.23	17.36	22.36	54.42
					996/S67	20.50	20.63	25.63	115.55
				MIMO A	Full	14.75	15.02	20.02	31.76
					996/67	15.65	15.92	20.92	39.07
					996/S67	19.16	19.43	24.43	87.67
				MIMO B	Full	15.06	15.33	20.33	34.11
					996/67	14.65	14.92	19.92	31.04
					996/S67	19.37	19.64	24.64	92.02
Combined A+B	Full	17.92	18.19	23.19	65.87				
	996/67	18.19	18.46	23.46	70.11				
	996/S67	22.28	22.55	27.55	179.69				

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Max/Min Value

Maximum output power – Overlapped channels between U-NII-2C and U-NII-3

Mode	Rate	Antenna	Chain	Channel	Frequency (MHz)	Average Cond. Output Power - UNII-2C [dBm]	Max.* Cond. Output Power - UNII-2C [dBm]	Max.* EIRP UNII2C [dBm]	Max.* Cond. Output Power - UNII-2C [mW]
802.11n20	HT0	SISO	A	144	5720	20.17	20.17	25.17	103.99
			B		5720	20.58	20.58	25.58	114.29
	HT8	MIMO	A		5720	17.53	17.53	22.53	56.62
			B		5720	17.54	17.54	22.54	56.75
			Combined		A+B	5720	20.55	20.55	25.55
802.11n40	HT0	SISO	A	142	5710	20.90	20.90	25.90	123.03
			B		5710	21.06	21.06	26.06	127.64
	HT8	MIMO	A		5710	17.81	17.81	22.81	60.39
			B		5710	17.97	17.97	22.97	62.66
			Combined		A+B	5710	20.90	20.90	25.90
802.11ac80	VHT0	SISO	A	138	5690	21.12	21.19	26.19	131.52
			B		5690	20.99	21.06	26.06	127.65
		MIMO	A		5690	17.91	18.01	23.01	63.26
			B		5690	18.09	18.19	23.19	65.93
		Combined	A+B		5690	21.01	21.11	26.11	129.19
802.11ax20	HE0	SISO	A	144	5720	20.24	20.24	25.24	105.68
			B		5720	20.49	20.49	25.49	111.94
		MIMO	A		5720	17.54	17.54	22.54	56.75
			B		5720	17.44	17.44	22.44	55.46
		Combined	A+B		5720	20.50	20.50	25.50	112.22
802.11ax40	HE0	SISO	A	142	5710	20.55	20.55	25.55	113.50
			B		5710	20.65	20.65	25.65	116.14
		MIMO	A		5710	17.46	17.46	22.46	55.72
			B		5710	17.69	17.69	22.69	58.75
		Combined	A+B		5710	20.59	20.59	25.59	114.47
802.11ax80	HE0	SISO	A	138	5690	20.87	20.87	25.87	122.18
			B		5690	20.73	20.73	25.73	118.30
		MIMO	A		5690	17.97	18.10	23.10	64.53
			B		5690	17.88	18.01	23.01	63.21
		Combined	A+B		5690	20.94	21.06	26.06	127.74

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Max/Min Value

Maximum Power Spectral Density (PSD) – U-NII-2C channels

Mode	Rate	Channel	Freq [MHz]	Antenna	Average conducted PSD [dBm/MHz]	Maximum* conducted PSD [dBm/MHz]	
802.11a	6Mbps	100	5500	SISO A	10.06	10.17	
				SISO B	9.89	10.00	
		120	5600	SISO A	10.10	10.21	
				SISO B	10.16	10.27	
		140	5700	SISO A	9.85	9.96	
				SISO B	9.71	9.82	
802.11n20	HT0	100	5500	SISO A	9.66	9.66	
				SISO B	9.50	9.50	
		120	5600	SISO A	9.87	9.87	
				SISO B	9.85	9.85	
		140	5700	SISO A	9.49	9.49	
				SISO B	9.57	9.57	
	HT8	100	5500	MIMO A	7.73	7.73	
				MIMO B	7.60	7.60	
				Combined A+B	10.68	10.68	
		120	5600	MIMO A	7.75	7.75	
				MIMO B	7.64	7.64	
				Combined A+B	10.71	10.71	
	140	5700	MIMO A	7.65	7.65		
			MIMO B	7.72	7.72		
			Combined A+B	10.70	10.70		
	802.11n40	HT0	102	5510	SISO A	5.36	5.36
					SISO B	5.50	5.50
			118	5590	SISO A	6.66	6.66
SISO B					6.65	6.65	
134			5670	SISO A	6.59	6.59	
				SISO B	6.41	6.41	
HT8		102	5510	MIMO A	3.88	3.88	
				MIMO B	3.48	3.48	
				Combined A+B	6.69	6.69	
		118	5590	MIMO A	6.35	6.35	
				MIMO B	6.74	6.74	
				Combined A+B	9.56	9.56	
134	5670	MIMO A	5.66	5.66			
		MIMO B	5.32	5.32			
		Combined A+B	8.50	8.50			
802.11ac80	VHT0	106	5530	SISO A	0.67	0.67	
				SISO B	0.46	0.46	
				MIMO A	-1.72	-1.62	
				MIMO B	-1.71	-1.61	
		122	5610	Combined A+B	1.30	1.40	
				SISO A	3.54	3.54	
				SISO B	3.51	3.51	
				MIMO A	2.85	2.95	
				MIMO B	2.97	3.07	
				Combined A+B	5.92	6.02	
802.11ac160	VHT0	114	5570	SISO A	-4.39	-4.28	
				SISO B	-3.51	-3.40	
				MIMO A	-5.68	-5.51	
				MIMO B	-5.75	-5.58	
				Combined A+B	-2.70	-2.54	

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Mode	Rate	Channel	Freq [MHz]	Antenna	RU config.	Average conducted PSD [dBm/MHz]	Maximum* conducted PSD [dBm/MHz]
802.11ax20	HE0	100	5500	SISO A	Full	9.71	9.71
					26/0	10.56	10.56
					52/37	10.54	10.54
					106/53	10.63	10.63
				SISO B	Full	9.47	9.47
					26/0	10.59	10.59
					52/37	10.40	10.40
					106/53	10.65	10.65
				MIMO A	Full	7.60	7.60
					26/0	7.86	7.86
					52/37	7.74	7.74
					106/53	7.00	7.00
		MIMO B	Full	7.70	7.70		
			26/0	7.70	7.70		
			52/37	7.87	7.87		
			106/53	7.43	7.43		
		Combined A+B	Full	10.66	10.66		
			26/0	10.79	10.79		
			52/37	10.82	10.82		
			106/53	10.23	10.23		
		120	5600	SISO A	Full	9.75	9.75
				SISO B	Full	9.82	9.82
				MIMO A	Full	7.67	7.67
				MIMO B	Full	7.59	7.59
				Combined A+B	Full	10.64	10.64
		140	5700	SISO A	Full	9.37	9.37
					26/8	10.48	10.48
					52/40	10.69	10.69
					106/54	10.51	10.51
				SISO B	Full	9.54	9.54
					26/8	10.60	10.60
					52/40	10.58	10.58
					106/54	10.75	10.75
				MIMO A	Full	7.83	7.83
					26/8	7.66	7.66
					52/40	7.53	7.53
106/54	7.65				7.65		
MIMO B	Full			7.65	7.65		
	26/8			7.75	7.75		
	52/40			7.80	7.80		
	106/54			7.62	7.62		
Combined A+B	Full			10.75	10.75		
	26/8			10.72	10.72		
	52/40			10.68	10.68		
	106/54	10.65	10.65				
802.11ax40	HE0	102	5510	SISO A	Full	5.31	5.31
					242/61	9.75	9.75
				SISO B	Full	5.17	5.17
					242/61	9.87	9.87
				MIMO A	Full	3.18	3.18
					242/61	7.94	7.94
				MIMO B	Full	3.05	3.05
					242/61	7.96	7.96
		Combined A+B	Full	6.13	6.13		
			242/61	10.96	10.96		
		118	5590	SISO A	Full	6.47	6.47
				SISO B	Full	6.45	6.45
				MIMO A	Full	6.40	6.40
				MIMO B	Full	6.29	6.29
		Combined A+B	Full	9.36	9.36		
			Full	9.36	9.36		
		134	5670	SISO A	Full	6.58	6.58
					242/62	9.81	9.81
				SISO B	Full	6.35	6.35
					242/62	9.65	9.65
				MIMO A	Full	5.56	5.56
					242/62	7.80	7.80
				MIMO B	Full	4.66	4.66
					242/62	7.52	7.52
Combined A+B	Full	8.14	8.14				
	242/62	10.67	10.67				

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Mode	Rate	Channel	Freq [MHz]	Antenna	RU config.	Average conducted PSD [dBm/MHz]	Maximum* conducted PSD [dBm/MHz]
802.11ax80	HE0	106	5530	SISO A	Full	0.84	0.84
					484/65	5.43	5.43
				SISO B	Full	0.72	0.72
					484/65	4.53	4.53
				MIMO A	Full	-2.10	-1.97
					484/65	2.89	3.02
		MIMO B	Full	-2.11	-1.98		
			484/65	1.35	1.48		
		Combined A+B	Full	0.91	1.03		
			484/65	5.20	5.33		
		122	5610	SISO A	Full	3.45	3.45
					Full	3.48	3.48
				MIMO A	Full	3.28	3.41
					Full	3.15	3.28
Combined A+B	Full			6.23	6.35		
802.11ax160	HE0	114	5570	SISO A	Full	-4.20	-4.07
					996/67	-0.46	-0.33
					996/S67	2.65	2.78
				SISO B	Full	-4.19	-4.06
					996/67	-0.29	-0.16
					996/S67	2.88	3.01
				MIMO A	Full	-5.71	-5.44
					996/67	-1.83	-1.56
					996/S67	1.51	1.78
				MIMO B	Full	-5.45	-5.18
					996/67	-2.92	-2.65
					996/S67	1.78	2.05
				Combined A+B	Full	-2.57	-2.30
					996/67	0.67	0.94
					996/S67	4.66	4.93

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Maximum Power Spectral Density (PSD) – Overlapped channels between U-NII-2C and U-NII-3

Mode	Rate	Channel	Frequency (MHz)	Antenna	Chain	Average conducted PSD UNII-2C [dBm/MHz]	Maximum* conducted PSD UNII-2C [dBm/MHz]	
802.11n20	HT0	144	5720	SISO	A	9.80	9.80	
					B	10.22	10.22	
	HT8			MIMO	A	7.18	7.18	
					B	7.18	7.00	
	Combined			A+B	10.19	10.10		
	802.11n40			HT0	142	5710	SISO	A
B		6.78	6.78					
HT8		MIMO	A	6.68			6.68	
			B	3.55			3.55	
Combined		A+B	3.78	3.78				
802.11ac80		VHT0	138	5690			SISO	A
	B				3.55	3.62		
	MIMO				A	0.57	0.67	
					B	0.66	0.76	
	Combined				A+B	3.63	3.73	
	802.11ax20				HE0	144	5720	SISO
B		9.99	9.99					
MIMO		A	7.06	7.06				
		B	6.96	6.96				
Combined		A+B	10.02	10.02				
802.11ax40		HE0	142	5710				SISO
	B				5.67	5.67		
	MIMO				A	6.20	6.20	
					B	3.07	3.07	
	Combined				A+B	3.30	3.30	
	802.11ax80				HE0	138	5690	SISO
B		3.23	3.23					
MIMO		A	0.48	0.61				
		B	0.36	0.49				
Combined		A+B	3.43	3.56				

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

See annex C.1.3 and C.1.4 for screenshot results

B.2.3 Undesirable emission limits : out of band (Conducted)

Test limits

FCC part	RSS clause	Limits																				
15.407 (b) (3)	RSS-247 Clause 6.2.3 (2)	For transmitters operating in the 5.47–5.725 GHz band: all emissions outside of the 5.47–5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.																				
15.209	RSS-GEN A1, Clause 8.9	<p>Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):</p> <table border="1"> <thead> <tr> <th>Freq Range (MHz)</th> <th>Field Strength ($\mu\text{V}/\text{m}$)</th> <th>Field Strength ($\text{dB}\mu\text{V}/\text{m}$)</th> <th>Meas. Distance (m)</th> </tr> </thead> <tbody> <tr> <td>30-88</td> <td>100</td> <td>40</td> <td>3</td> </tr> <tr> <td>88-216</td> <td>150</td> <td>43.5</td> <td>3</td> </tr> <tr> <td>216-960</td> <td>200</td> <td>46</td> <td>3</td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>54</td> <td>3</td> </tr> </tbody> </table> <p>The emission limits shown in the table above are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p> <p>For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.</p>	Freq Range (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
Freq Range (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Meas. Distance (m)																			
30-88	100	40	3																			
88-216	150	43.5	3																			
216-960	200	46	3																			
Above 960	500	54	3																			

Test procedure

The conducted setup shown in section *Test & System Description* was used to measure undesirable emissions on the out of band domain. The antenna terminal of the EUT is connected to the spectrum analyzer through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss and the declared antenna gain.

For the lower and upper side of the out of band, the integration method was used as defined in the out of band measurements section II.G.3.d of KDB 789033. Tests were performed using both RMS and peak detectors.

For out of band emission measurements in MIMO mode the emission level of individual output is adjusted by 10 log (Nant) = 3dB for Nant = 2 which is equivalent to compare the individual output emission level to the limit minus 3dB. The same approach is applied for peak and RMS detectors.

In case of out of band measurements falling in restricted bands, the declared antenna gain is also compensated in the graph.

The following limits in dBm were applied for the average detector after the conversion from the limits detailed above in $\text{dB}\mu\text{V}/\text{m}$, according to FCC 47 CFR part 15 - Subpart C – §15.209(a). The limits in dBm for peak detector are 20dB above the indicated values in the table.

§15.209(a)			Converted values	
Freq Range (MHz)	Distance (m)	Field strength (microvolts/meter)	Field strength (dB microvolts/meter)	Power (dBm)
Above 960	3	500	53.98	-41.2

See annec C.1.5 for screenshot results

B.2.4 Radiated spurious emission

Standard references

FCC part	RSS clause	Limits																				
15.407 (b) (3)	RSS-247 Clause 6.2.3 (2)	For transmitters operating in the 5.47–5.725 GHz band: all emissions outside of the 5.47–5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.																				
15.209	RSS-GEN A1, Clause 8.9	<p>Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):</p> <table border="1"> <thead> <tr> <th>Freq Range (MHz)</th> <th>Field Strength ($\mu\text{V}/\text{m}$)</th> <th>Field Strength ($\text{dB}\mu\text{V}/\text{m}$)</th> <th>Meas. Distance (m)</th> </tr> </thead> <tbody> <tr> <td>30-88</td> <td>100</td> <td>40</td> <td>3</td> </tr> <tr> <td>88-216</td> <td>150</td> <td>43.5</td> <td>3</td> </tr> <tr> <td>216-960</td> <td>200</td> <td>46</td> <td>3</td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>54</td> <td>3</td> </tr> </tbody> </table> <p>The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p> <p>For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.</p>	Freq Range (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
Freq Range (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Meas. Distance (m)																			
30-88	100	40	3																			
88-216	150	43.5	3																			
216-960	200	46	3																			
Above 960	500	54	3																			

Test procedure

The radiated setups shown in section *Test & System Description* were used to measure the radiated spurious emissions. Depending of the frequency range and bands being tested, different antennas and filters were used. The final measurement is done by varying the antenna height from 1 m to 4 m, the EUT azimuth over 360° and for both Vertical and Horizontal polarizations.

The radiated spurious emission was measured on the worst case configuration selected from the chapter 0 and using the low, middle and high channels.

For 802.11ax20, 802.11ax40, 802.11ax80 and 802.11ax160 modes, the worst case spurious emission result among the low, mid and high channels tested separately on Chain A and B is used to perform the test on MIMO mode (Chain A+B).

For 802.11n20, 802.11n40, 802.11ac80 and 802.11ac160 modes the worst channel found among all 802.11ax modes mentioned above is chosen to perform the test in Chain A, B , and MIMO (Chain A+B).

Test Results

Radiated spurious - 30 MHz – 1 GHz**Radiated Spurious – All modes**

Frequency	Quasi-Peak	Limit	Margin	Polarization
MHz	dB μ V/m	dB μ V/m	dB	---
73.2	31.3	40.0	8.7	V

Note 1: The spurious signals detected do not depend on either the operating channel or the modulation mode.

[802.11a](#)**1 GHz – 40 GHz, 802.11a, 6Mbps, Chain A****Radiated Spurious – CH100**

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3373.0	59.2	---	68.2	8.9	H
11005.2	---	43.1	54.0	10.9	V
11006.2	53.1	---	74.0	20.9	V
39576.2	---	46.1	54.0	7.9	V
39613.3	56.7	---	74.0	17.3	H

Radiated Spurious – CH120

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3397.5	59.3	---	68.2	8.9	V
11194.2	52.7	---	74.0	21.3	V
11200.5	---	42.0	54.0	12.0	V
39638.9	---	46.1	54.0	7.9	H
39692.4	56.7	---	74.0	17.3	H

Radiated Spurious – CH140

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3396.5	59.2	---	68.2	9.0	V
11402.5	---	42.5	54.0	11.5	V
11403.5	52.3	---	74.0	21.7	V
17099.1	53.0	---	68.2	15.2	H
39558.4	56.9	---	74.0	17.1	V
39629.7	---	46.1	54.0	7.9	V

1 GHz – 40 GHz, 802.11a, 6Mbps, Chain B

Radiated Spurious – CH100

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3400.0	60.7	---	68.2	7.5	H
17844.4	---	43.1	54.0	10.9	H
17844.4	55.3	---	74.0	18.7	V
39524.6	56.3	---	74.0	17.7	V
39642.2	---	46.1	54.0	7.8	V

Radiated Spurious – CH120

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3399.0	59.4	---	68.2	8.8	H
17925.1	---	43.6	54.0	10.4	V
17925.1	55.7	---	74.0	18.3	V
39592.6	56.8	---	74.0	17.2	V
39631.2	---	46.2	54.0	7.8	H

Radiated Spurious – CH140

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
3391.5	59.1	---	68.2	9.1	H
17104.4	55.0	---	68.2	13.2	V
39602.2	---	45.8	54.0	8.2	V
39653.8	57.7	---	74.0	16.3	H

802.11n

1 GHz – 40 GHz, 802.11n20, HT0, Chain A

Radiated Spurious – CH140

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
3388.5	58.8	---	68.2	9.4	V
11399.1	---	42.5	54.0	11.5	V
11399.1	52.5	---	74.0	21.5	V
39651.4	---	46.3	54.0	7.7	H
39664.4	56.5	---	74.0	17.5	H

1 GHz – 40 GHz, 802.11n20, HT0, Chain B

Radiated Spurious – CH140

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
3397.0	57.6	---	68.2	10.6	V
17097.6	53.4	---	68.2	14.8	H
39622.0	---	46.3	54.0	7.7	H
39642.2	57.5	---	74.0	16.5	H

1 GHz – 40 GHz, 802.11n20, HT8, Chain A+B

Radiated Spurious – CH140

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
2433.0	57.2	---	68.2	11.0	H
11400.1	53.8	---	74.0	20.2	V
11400.1	---	44.6	54.0	9.4	V
39628.3	---	45.5	54.0	8.6	H
39628.3	56.9	---	74.0	17.1	V

1 GHz – 40 GHz, 802.11n40, HT0, Chain A

Radiated Spurious – CH102

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
3393.0	57.8	---	68.2	10.4	V
11019.7	52.8	---	74.0	21.2	V
11022.6	---	42.2	54.0	11.8	V
39649.5	---	45.8	54.0	8.2	V
39653.3	56.5	---	74.0	17.5	V

1 GHz – 40 GHz, 802.11n40, HT0, Chain B

Radiated Spurious – CH102

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
3390.5	57.9	---	68.2	10.3	V
17989.4	---	44.1	54.0	9.9	V
17989.4	55.8	---	74.0	18.2	H
39507.2	---	46.0	54.0	8.0	V
39571.4	56.9	---	74.0	17.1	V

1 GHz – 40 GHz, 802.11n40, HT8, Chain A+B

Radiated Spurious – CH102

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3377.5	57.7	---	68.2	10.5	V
11017.8	51.6	---	74.0	22.4	V
11017.8	---	42.7	54.0	11.3	V
39716.5	56.8	---	74.0	17.2	H
39718.4	---	45.2	54.0	8.8	V

802.11ac

1 GHz – 40 GHz, 802.11ac80, VHT0, Chain A

Radiated Spurious – CH106

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3381.0	57.6	---	68.2	10.6	V
11059.3	50.6	---	74.0	23.4	V
11059.3	---	40.8	54.0	13.2	V
39587.3	---	46.1	54.0	7.9	V
39641.3	56.9	---	74.0	17.1	V

1 GHz – 40 GHz, 802.11ac80, VHT0, Chain B

Radiated Spurious – CH106

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3393.5	58.8	---	68.2	9.4	H
17891.7	---	42.9	54.0	11.1	V
17891.7	55.5	---	74.0	18.6	H
39599.8	57.2	---	74.0	16.8	H
39646.1	---	46.3	54.0	7.7	V

1 GHz – 40 GHz, 802.11ac80, VHT0, Chain A+B

Radiated Spurious – CH106

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3379.0	57.9	---	68.2	10.3	V
11037.6	---	39.5	54.0	14.5	V
11037.6	51.4	---	74.0	22.6	V
39556.4	57.1	---	74.0	16.9	H
39556.4	---	45.0	54.0	8.9	H

1 GHz – 40 GHz, 802.11ac160, VHT0, Chain A

Radiated Spurious – CH114

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3395.0	57.5	---	68.2	10.7	V
17930.9	---	42.9	54.0	11.2	H
17930.9	55.9	---	74.0	18.1	V
39493.3	---	45.8	54.0	8.2	H
39626.3	57.2	---	74.0	16.8	V

1 GHz – 40 GHz, 802.11ac160, VHT0, Chain B

Radiated Spurious – CH114

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3390.5	57.8	---	68.2	10.4	H
17818.8	55.2	---	74.0	18.8	H
17819.2	---	43.2	54.0	10.8	H
39623.9	57.0	---	74.0	17.0	V
39633.1	---	46.4	54.0	7.6	H

1 GHz – 40 GHz, 802.11ac160, VHT0, Chain A+B

Radiated Spurious – CH114

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3379.5	57.7	---	68.2	10.5	V
11049.7	48.5	---	74.0	25.5	V
11049.7	---	38.7	54.0	15.3	V
39658.2	56.7	---	74.0	17.3	H
39658.2	---	46.4	54.0	7.6	H

802.11ax

1 GHz – 40 GHz, 802.11ax20, HE0, Chain A

Radiated Spurious – CH100

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3398.0	57.8	---	68.2	10.4	H
6865.4	47.1	---	68.2	21.1	V
10982.5	55.2	---	74.0	18.8	V
10982.5	---	47.5	54.0	6.5	V
16476.0	53.8	---	68.2	14.4	V
39652.9	---	46.1	54.0	7.8	V
39713.6	57.4	---	74.0	16.6	H

Radiated Spurious – CH120

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3398.5	58.0	---	68.2	10.2	V
11183.5	53.9	---	74.0	20.1	V
11183.5	---	43.9	54.0	10.1	H
16774.3	54.4	---	68.2	13.8	V
39613.8	57.0	---	74.0	16.9	V
39649.0	---	46.3	54.0	7.7	V

Radiated Spurious – CH140

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3383.5	57.5	---	68.2	10.7	V
11382.7	56.0	---	74.0	18.0	V
11382.7	---	48.3	54.0	5.7	V
39655.3	---	46.5	54.0	7.5	V
39667.3	57.9	---	74.0	16.1	H

1 GHz – 40 GHz, 802.11ax20, HE0, Chain B

Radiated Spurious – CH100

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3386.5	57.9	---	68.2	10.3	H
6866.4	47.1	---	68.2	21.1	V
6874.6	46.9	---	68.2	21.3	V
10982.0	48.3	---	74.0	25.7	V
10982.5	---	38.6	54.0	15.4	H
16475.1	51.5	---	68.2	16.7	H
39684.2	57.5	---	74.0	16.5	H
39685.6	---	46.1	54.0	7.9	H

Radiated Spurious – CH120

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3398.0	58.5	---	68.2	9.7	V
11182.1	50.9	---	74.0	23.1	V
11183.1	---	40.9	54.0	13.1	V
16775.7	54.1	---	68.2	14.1	V
39508.7	57.3	---	74.0	16.7	H
39640.3	---	46.2	54.0	7.8	H

Radiated Spurious – CH140

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3390.0	58.4	---	68.2	9.8	H
11382.2	50.9	---	74.0	23.1	V
11383.2	---	40.2	54.0	13.8	V
17075.4	56.2	---	68.2	12.0	V
39620.1	---	46.9	54.0	7.1	V
39664.9	56.8	---	74.0	17.2	H

1 GHz – 40 GHz, 802.11ax20, HE0, Chain A+B

Radiated Spurious – CH140

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3374.5	59.5	---	68.2	8.7	H
7121.1	47.9	---	68.2	20.3	V
11383.2	56.8	---	74.0	17.2	H
11383.2	---	49.9	54.0	4.1	H
17073.5	53.5	---	68.2	14.7	V
22766.6	49.1	---	74.0	24.9	V
22766.6	---	38.3	54.0	15.7	V

1 GHz – 40 GHz, 802.11ax40, HE0, Chain A

Radiated Spurious – CH102

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3389.5	57.4	---	68.2	10.8	H
10983.9	55.4	---	74.0	18.6	H
10983.9	---	47.0	54.0	7.0	V
39609.5	56.7	---	74.0	17.3	H
39662.0	---	46.1	54.0	7.9	V

Radiated Spurious – CH118

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3384.0	58.1	---	68.2	10.1	V
11143.9	---	47.0	54.0	7.0	H
11144.4	55.9	---	74.0	18.1	H
16711.4	52.0	---	68.2	16.2	V

Radiated Spurious – CH134

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3386.5	57.7	---	68.2	10.5	H
11303.9	---	41.5	54.0	12.6	V
11304.9	50.3	---	74.0	23.7	V
16955.0	58.2	---	68.2	10.0	H
39643.7	---	46.4	54.0	7.6	V
39745.4	57.1	---	74.0	16.9	V

1 GHz – 40 GHz, 802.11ax40, HE0, Chain B**Radiated Spurious – CH102**

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3396.0	58.4	---	68.2	9.8	V
6865.0	46.4	---	68.2	21.8	V
16478.5	52.7	---	68.2	15.5	V
39635.0	---	46.2	54.0	7.8	H
39666.8	56.9	---	74.0	17.1	V

Radiated Spurious – CH118

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3387.5	57.7	---	68.2	10.5	H
11143.9	51.1	---	74.0	22.9	H
11144.4	---	41.9	54.0	12.1	H
16087.5	51.2	---	74.0	22.8	H
16087.5	---	41.0	54.0	13.0	H
39635.0	---	46.4	54.0	7.6	V
39670.2	57.2	---	74.0	16.8	H

Radiated Spurious – CH134

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3389.0	58.3	---	68.2	9.9	H
16956.5	58.8	---	68.2	9.4	V
22607.5	---	38.2	54.0	15.8	V
22607.9	49.8	---	74.0	24.2	V

1 GHz – 40 GHz, 802.11ax40, HE0, Chain A+B

Radiated Spurious – CH102

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3372.0	60.0	---	68.2	8.2	V
6865.0	46.1	---	68.2	22.1	H
10983.5	58.9	---	74.0	15.1	V
10983.5	---	51.1	54.0	2.9	V
16476.5	53.2	---	68.2	15.0	V
21970.0	46.6	---	68.2	21.6	V

1 GHz – 40 GHz, 802.11ax80, HE0, Chain A

Radiated Spurious – CH106

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3394.5	57.9	---	68.2	10.3	H
6868.8	48.9	---	68.2	19.3	V
6887.2	46.2	---	68.2	22.0	H
10983.9	53.5	---	74.0	20.5	H
10983.9	---	46.9	54.0	7.1	H
16477.0	54.1	---	68.2	14.1	V
39494.7	57.5	---	74.0	16.5	H
39624.9	---	45.6	54.0	8.3	H

Radiated Spurious – CH122

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3388.0	58.0	---	68.2	10.2	V
11143.9	55.0	---	74.0	19.0	H
11143.9	---	46.6	54.0	7.3	H
16716.3	52.3	---	68.2	15.9	V
22284.9	48.3	---	74.0	25.7	V
22287.8	---	37.4	54.0	16.6	H

Radiated Spurious – CH138

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3388.5	57.8	---	68.2	10.4	V
7074.7	46.8	---	68.2	21.4	H
11303.4	51.8	---	74.0	22.2	V
11304.9	---	42.1	54.0	11.9	V
16957.0	59.1	---	68.2	9.1	H
28388.6	51.4	---	68.2	16.8	H

1 GHz – 40 GHz, 802.11ax80, HE0, Chain B

Radiated Spurious – CH106

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
4114.1	51.6	---	74.0	22.4	V
4114.6	---	41.8	54.0	12.2	V
4132.0	49.8	---	74.0	24.2	V
4132.4	---	40.3	54.0	13.7	V
6868.8	48.0	---	68.2	20.2	V
6887.2	46.4	---	68.2	21.8	V
10983.9	47.6	---	74.0	26.4	V
10983.9	---	38.7	54.0	15.3	H
16478.0	53.0	---	68.2	15.2	V
39501.5	57.0	---	74.0	17.0	H
39655.8	---	46.2	54.0	7.8	V

Radiated Spurious – CH122

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3384.5	58.1	---	68.2	10.1	H
11143.4	51.4	---	74.0	22.6	V
11144.4	---	41.9	54.0	12.1	H
16716.8	52.1	---	68.2	16.1	V
39641.8	---	46.5	54.0	7.5	H
39676.5	57.1	---	74.0	16.9	V

Radiated Spurious – CH138

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
3393.0	57.7	---	68.2	10.5	H
7074.2	47.8	---	68.2	20.4	V
11073.8	---	37.9	54.0	16.1	V
11074.3	48.5	---	74.0	25.5	V
16955.5	58.9	---	68.2	9.3	V
22608.4	48.6	---	74.0	25.4	V
22608.4	---	39.1	54.0	14.9	V

1 GHz – 40 GHz, 802.11ax80, HE0, Chain A+B

Radiated Spurious – CH106

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
4113.7	50.6	---	74.0	23.4	V
4114.6	---	41.0	54.0	13.1	V
6868.8	48.4	---	68.2	19.8	V
6887.2	46.1	---	68.2	22.1	V
10983.9	58.1	---	74.0	15.9	V
10983.9	---	49.0	54.0	5.0	V
11007.1	---	38.7	54.0	15.3	V
11007.1	51.6	---	74.0	22.4	V
39697.7	---	45.0	54.0	9.0	V
39697.7	57.0	---	74.0	17.0	V

1 GHz – 40 GHz, 802.11ax160, HE0, Chain A

Radiated Spurious – CH114

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
3388.0	58.1	---	68.2	10.1	V
6874.1	50.5	---	68.2	17.7	V
6912.3	45.8	---	68.2	22.4	V
10983.9	53.8	---	74.0	20.2	V
10983.9	---	47.4	54.0	6.6	V
16476.0	52.8	---	68.2	15.4	V
39483.1	---	46.1	54.0	7.9	V
39572.8	56.9	---	74.0	17.1	H

1 GHz – 40 GHz, 802.11ax160, HE0, Chain B

Radiated Spurious – CH114

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dBµV/m	dBµV/m	dBµV/m	dB	---
3378.5	57.7	---	68.2	10.5	V
6874.6	48.8	---	68.2	19.4	V
6912.3	46.3	---	68.2	21.9	V
10983.9	48.2	---	74.0	25.8	H
10983.9	---	38.9	54.0	15.1	V
16501.7	52.4	---	68.2	15.8	V
39641.3	57.1	---	74.0	16.9	V
39664.9	---	46.1	54.0	7.9	V


1 GHz – 40 GHz, 802.11ax160, HE0, Chain A+B**Radiated Spurious – CH114**

Frequency	MaxPeak	Average	Limit	Margin	Polar
MHz	dB μ V/m	dB μ V/m	dB μ V/m	dB	---
3385.5	58.0	---	68.2	10.2	V
6874.1	50.2	---	68.2	18.0	V
6912.3	46.5	---	68.2	21.6	H
10983.9	59.2	---	74.0	14.8	V
10983.9	---	50.6	54.0	3.4	V
39651.9	56.9	---	74.0	17.1	V
39658.6	---	46.2	54.0	7.8	H

Annex C. System Plots


C.1.1 26dB Bandwidth

SISO-B, 802.11a, 6Mbps



Channel 140


MIMO-A, 802.11n20, HT8



Date: 3 DEC 2010 19:02:05

Channel 100


MIMO-A, 802.11n40, HT8



Date: 3 DEC 2010 19:47:45

Channel 118


SISO-A, 802.11ac80, VHT0



Date: 3 DEC 2010 08:25:28


Channel 122

SISO-B, 802.11ac160, VHT0




Channel 114

SISO-B, 802.11ax20, HE0




Channel 100

MIMO-B, 802.11ax40, HE0




Channel 118

MIMO-B, 802.11ax80, HE0



Channel 122


MIMO-A, 802.11ax160, HE0



Channel 114

C.1.2 99% Bandwidth


SISO-A, 802.11a, 6Mbps



Date: 3 DEC 2010 02:23:22

Channel 120


MIMO-A, 802.11n20, HT8



Date: 3 DEC 2010 19:03:13

Channel 120


MIMO-A, 802.11n40, HT8



Date: 3 DEC 2010 19:47:46

Channel 118


SISO-A, 802.11ac80, VHT0



Date: 3 DEC 2010 08:25:31


Channel 122

SISO-B, 802.11ac160, VHT0




Channel 114

MIMO-B, 802.11ax20, HE0




Channel 100

MIMO-B, 802.11ax40, HE0



Channel 118


SISO-A, 802.11ax80, HE0



Date: 3 DEC 2020 08:17:05

Channel 122


SISO-B, 802.11ax160, HE0



Channel 114


C.1.3 Maximum Output Power & Maximum power spectral Density

SISO-B, 802.11a, 6Mbps



Channel 120


MIMO-A, 802.11n20, HT8



Date: 3 DEC 2010 19:03:25


Channel 120

MIMO-B, 802.11n20, HT8




Channel 120

MIMO-A, 802.11n40, HT8




Channel 118

MIMO-B, 802.11n40, HT8




Channel 118

MIMO-A, 802.11ac80, VHT0




Channel 122

MIMO-B, 802.11ac80, VHT0




Channel 122

MIMO-A, 802.11ac160, VHT0




Channel 114

MIMO-B, 802.11ac160, VHT0




Channel 114

MIMO-A, 802.11ax20, HE0




Channel 140

MIMO-B, 802.11ax20, HE0




Channel 140

MIMO-A, 802.11ax40, HE0




Channel 118

MIMO-B, 802.11ax40, HE0




Channel 118

MIMO-A, 802.11ax80, HE0




Channel 122

MIMO-B, 802.11ax80, HE0




Channel 122

MIMO-A, 802.11ax160 RU: 996/S67, HE0



Channel 114


MIMO-B, 802.11ax160 RU: 996/S67, HE0



Channel 114


C.1.4 Maximum output power & Maximum power spectral Density (Overlapped Channel)

SISO-B, 802.11n20, HT0




Channel 144 (Overlapped Channel)

SISO-B, 802.11n40, HT0




Channel 142 (Overlapped Channel)

SISO-A, 802.11ac80, VHT0




Channel 138 (Overlapped Channel)

MIMO-A, 802.11ax20, HE0




Channel 144 (Overlapped Channel)

MIMO-B, 802.11ax20, HE0




Channel 144 (Overlapped Channel)

SISO-B, 802.11ax40, HE0




Channel 142 (Overlapped Channel)

MIMO-A, 802.11ax80, HE0



Channel 138 (Overlapped Channel)


MIMO-B, 802.11ax80, HE0



Channel 138 (Overlapped Channel)


C.1.5 Undesirable emission limits: out of band (Conducted)

SISO A




Date: 3 DEC 2020 17:17:43

BE-R-LOW, SISO-A, 802.11a20-6Mbps, Ch100




Date: 3 DEC 2020 17:18:00

BE-NR-LOW, SISO-A, 802.11a20-6Mbps, Ch100




Date: 3 DEC 2020 02:30:07

BE-NR-HIGH, SISO-A, 802.11a20-6Mbps, Ch140




Date: 3 DEC 2020 17:18:51

BE-R-LOW, SISO-A, 802.11n20-HT0, Ch100




Date: 3 DEC 2020 17:19:04

BE-NR-LOW, SISO-A, 802.11n20-HT0, Ch100




Date: 3 DEC 2020 02:36:45

BE-NR-HIGH, SISO-A, 802.11n20-HT0, Ch140




Date: 3 DEC 2020 17:19:53

BE-R-LOW, SISO-A, 802.11n40-HT0, Ch102




Date: 3 DEC 2020 17:34:20

BE-NR-LOW, SISO-A, 802.11n40-HT0, Ch102




Date: 3 DEC 2020 02:43:24

BE-NR-HIGH, SISO-A, 802.11n40-HT0, Ch134




Date: 15 JAN 2021 11:45:19

BE-R-LOW, SISO-A, 802.11ac80-VHT0, Ch106



Date: 15 JAN 2021 11:48:23


BE-NR-LOW, SISO-A, 802.11ac80-VHT0, Ch106



Date: 3 DEC 2020 09:25:57


BE-NR-HIGH, SISO-A, 802.11ac80-VHT0, Ch122

Test Report N° 201120-03.TR02




Date: 3 DEC 2020 17:29:04

BE-R-LOW, SISO-A, 802.11ac160-VHT0, Ch114




Date: 3 DEC 2020 17:29:16

BE-NR-LOW, SISO-A, 802.11ac160-VHT0, Ch114




Date: 3 DEC 2020 17:29:30

BE-NR-HIGH, SISO-A, 802.11ac160-VHT0, Ch114




Date: 3 DEC 2020 02:46:24

BE-R-LOW, SISO-A, 802.11ax20-HE0, Ch100




Date: 3 DEC 2020 02:46:36

BE-NR-LOW, SISO-A, 802.11ax20-HE0, Ch100




Date: 3 DEC 2020 02:52:00

BE-NR-HIGH, SISO-A, 802.11ax20-HE0, Ch140




Date: 3 DEC 2020 17:21:54

BE-R-LOW, SISO-A, 802.11ax40-HE0, Ch102




Date: 3 DEC 2020 17:37:12

BE-NR-LOW, SISO-A, 802.11ax40-HE0, Ch102




Date: 3 DEC 2020 08:10:24

BE-NR-HIGH, SISO-A, 802.11ax40-HE0, Ch134




Date: 3 DEC 2020 08:15:22

BE-R-LOW, SISO-A, 802.11ax80-HE0, Ch106




Date: 3 DEC 2020 08:15:34

BE-NR-LOW, SISO-A, 802.11ax80-HE0, Ch106




Date: 3 DEC 2020 08:17:32

BE-NR-HIGH, SISO-A, 802.11ax80-HE0, Ch122




Date: 3 DEC 2020 17:24:02

BE-R-LOW, SISO-A, 802.11ax160-HE0, Ch114



Date: 3 DEC 2020 17:24:14


BE-NR-LOW, SISO-A, 802.11ax160-HE0, Ch114




Date: 3 DEC 2020 17:24:28

BE-NR-HIGH, SISO-A, 802.11ax160-HE0, Ch114

SISO B



BE-R-LOW, SISO-B, 802.11a20-6Mbps, Ch100



BE-NR-LOW, SISO-B, 802.11a20-6Mbps, Ch100