

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

FCC ID	2BAWU-MPC43
Product Description	Mini PC
Model Name	MPC43
Frequency Band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input checked="" type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> WLAN: 5.925GHz ~ 7.125GHz <input checked="" type="checkbox"/> Bluetooth: 2.402GHz ~ 2.480GHz <input type="checkbox"/> Others
Device Category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others:
Antenna Diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas
Max. Output Power	Bluetooth(BLE): 9.13dBm Bluetooth(BR/EDR): 10.41dBm WLAN 2.4G: 23.66dBm WLAN 5G: 24.28dBm WLAN 6E: 16.19dBm
Antenna Gain	Bluetooth(BLE): 2.63dBi Bluetooth(BR/EDR): 2.63dBi WLAN 2.4G: Antenna 1: 2.63dBi; Antenna 2: 1.39dBi WLAN 5G: U-NII 1 & U-NII 2A :Antenna 1: 2.78dBi; Antenna 2: 2.36dBi U-NII 2C & U-NII 3: Antenna 1: 2.94dBi; Antenna 2: 2.80dBi WLAN 6E: U-NII 5 & U-NII 6: Antenna 1: 2.81dBi ;Antenna 2: 2.93dBi U-NII 7 & U-NII 8: Antenna 1: 2.81dBi ;Antenna 2: 2.93dBi
Minimum Assessment Distance	20cm
Evaluation Applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation
Evaluation Result	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



2. PORTABLE DEVICE EVALUATION METHOD AND LIMIT

Following FCC KDB 447498 D01 "General SAR test exclusion guidance" The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] [f(GHz)] s
3.0 for 1-g SAR and ≈ 7.5 for 10-g extremity SAR, where
 - f(GHz) is the RF channel transmit frequency in GHz.
 - Power and distance are rounded to the nearest mW and mm before calculation.
 - The result is rounded to one decimal place for comparison The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
 - a) [Threshold at 50 mm in step 1) + (test separation distance - 50mm) (f(MHz)/150)] mW, at 100MHz to 1500 MHz;
 - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)-10] mW at > 1500 MHz and ≤ 6 GHz;

- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
 - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by [1 + log(100/f(MHz))] for test separation distances > 50 mm and < 200 mm.
 - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by 1/2 for test separation distances ≈ 50 mm.
 - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



3. MOBILE DEVICE EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S=PG/4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

4. MEASUREMENT RESULT

A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated.

BT: Antenna Gain=2.63dBi (Numeric 1.83), $\pi=3.14$

2.4G WLAN:

Antenna 1: Antenna Gain=2.63dBi (Numeric 1.83), $\pi=3.14$

Antenna 2: Antenna Gain=1.39dBi (Numeric 1.38), $\pi=3.14$

5G WLAN(U-NII 1 & U-NII 2A):

Antenna 1: Antenna Gain=2.78dBi (Numeric 1.90), $\pi=3.14$

Antenna 2: Antenna Gain=2.36dBi (Numeric 1.72), $\pi=3.14$

Antenna 2: 2.36dBi

5G WLAN(U-NII 2C & U-NII 3):

Antenna 1: Antenna Gain=2.94dBi (Numeric 1.97), $\pi=3.14$

Antenna 2: Antenna Gain=2.80dBi (Numeric 1.91), $\pi=3.14$

WLAN 6E(U-NII 5 & U-NII 6):

Antenna 1: Antenna Gain=2.81dBi (Numeric 1.91), $\pi=3.14$

Antenna 2: Antenna Gain=2.93dBi (Numeric 1.96), $\pi=3.14$

WLAN 6E(U-NII 7 & U-NII 8):

Antenna 1: Antenna Gain=1.69dBi (Numeric 1.48), $\pi=3.14$

Antenna 2: Antenna Gain=1.62dBi (Numeric 1.45), $\pi=3.14$

Test Mode	Test Frequency (MHz)	Max.Output Power (dBm)	Max.Output Power (mW)	Power Density (mW/cm ²)	Measurement Limit (mW/cm ²)
BT(BLE)	2480	9.13	8.185	0.0030	1
BT(BR/EDR)	2480	10.41	10.990	0.0040	1
2.4G WLAN -Antenna 1	2442	21.20	131.826	0.0361	1
2.4G WLAN -Antenna 2	2442	21.80	151.356	0.0552	1
2.4G WLAN -MIMO	2442	23.66	232.274	0.0847	1
5G WLAN (U-NII 1 & U-NII 2A) -Antenna 1	5200	22.11	162.555	0.0613	1
5G WLAN (U-NII 1 & U-NII 2A) -Antenna 2	5230	21.26	133.660	0.0458	1
5G WLAN (U-NII 1 & U-NII 2A) -MIMO	5230	23.97	249.459	0.0941	1
5G WLAN (U-NII 2C & U-NII 3) -Antenna 1	5785	21.21	132.130	0.0517	1
5G WLAN (U-NII 2C & U-NII 3) -Antenna 2	5745	21.25	133.352	0.0506	1
5G WLAN (U-NII 2C & U-NII 3) -MIMO	5610	24.28	267.917	0.1049	1
WLAN 6E (U-NII 5 & U-NII 6) -Antenna 1	6505	15.99	39.719	0.0151	1

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

WLAN 6E (U-NII 5 & U-NII 6) -Antenna 2	6505	16.14	41.115	0.0161	1
WLAN 6E (U-NII 5 & U-NII 6) -MIMO	6505	16.19	41.591	0.0162	1
WLAN 6E (U-NII 7 & U-NII 8) -Antenna 1	6985	14.75	29.854	0.0088	1
WLAN 6E (U-NII 7 & U-NII 8) -Antenna 2	6985	14.69	29.444	0.0085	1
WLAN 6E (U-NII 7 & U-NII 8) -MIMO	13.19	14.88	30.761	0.0090	1

Note:

1. Only the worst case recorded.
2. The BT, 2.4GHz WIFI band antenna 1 with antenna 2, 5GHz band antenna 1 with antenna 2 and 6GHz band antenna 1 with antenna 2 can transmit simultaneously:
 $0.0040/1+0.0847/1+0.1049/1+0.0162/1=0.2098<1$

5. CONCLUSION

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.