

# FCC ID: 2BAYB-BEHEALTHY2023

## Portable device

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right]^* \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

### BLE

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power(dBm)	Result calculation	1-g SAR
2.402	GFSK	1.03	2	0.49	3
2.441	GFSK	1.93	2	0.50	3
2.480	GFSK	1.93	2	0.50	3

### BR+EDR

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power(dBm)	Result calculation	1-g SAR
2.402	GFSK	1.01	2	0.49	3
2.441	GFSK	1.88	2	0.50	3
2.480	GFSK	1.93	2	0.50	3
2.402	PI/4 DQPSK	1.54	2	0.49	3
2.441	PI/4 DQPSK	2.67	3	0.62	3
2.480	PI/4 DQPSK	2.15	3	0.63	3

Conclusion:

For the max result :  $0.63 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.