

RF EXPOSURE EVALUATION REPORT

APPLICANT : Savi Controls, LLC

PRODUCT NAME : 0-10V Dimmer

MODEL NAME : QZ10D-01

BRAND NAME : N/A

FCC ID : 2BAZT10022001

STANDARD(S) : 47 CFR Part 2(2.1091)

RECEIPT DATE : 2023-06-21

TEST DATE : 2023-06-27 to 2023-07-13

ISSUE DATE : 2023-11-03



DIRECTORY

1. Technical Information 3

1.1 Applicant and Manufacturer Information 3

1.2 Equipment under Test (EUT) Description 3

1.3 Applied Reference Documents 4

2. Device Category and RF Exposure Limit 5

3. RF Output Power 6

4. RF Exposure Assessment 7

Annex A Testing Laboratory Information 错误！未定义书签。

Change History		
Version	Date	Reason for change
1.0	2023-10-27	First edition



1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	Savi Controls, LLC
Applicant Address:	2520 Marsh Lane, Carrollton, TX 75006, United States
Manufacturer:	Savi Controls, LLC
Manufacturer Address:	2520 Marsh Lane, Carrollton, TX 75006, United States

1.2 Equipment under Test (EUT) Description

Product Name:	0-10V Dimmer	
Sample No.:	3#	
Hardware Version:	N/A	
Software Version:	N/A	
Modulation Technology:	Bluetooth	GFSK
	WLAN 2.4GHz	DSSS, OFDM
Operating Frequency Range:	Bluetooth	2402MHz-2480MHz
	WLAN 2.4GHz	2412MHz-2472MHz
Antenna Type:	PCB Antenna	
Antenna Gain:	0.91dBi	



1.3 Applied Reference Documents

Leading reference documents for testing:

Identity	Document Title	Method determination /Remark
47 CFR Part 2(2.1091)	Radio Frequency Radiation Exposure Assessment: mobile devices	No deviation
KDB 447498 D01v06	General RF Exposure Guidance	No deviation
Note 1: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.		
Note 2: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.		



2. Device Category and RF Exposure Limit

Per user manual, based on 47 CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47 CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz* = Plane-wave equivalent power density



3. RF Output Power

Mode	Channel	Frequency (MHz)	Average Power (dBm)
			GFSK
BLE 1M	CH 00	2402	1.63
	CH 19	2440	2.32
	CH 39	2480	2.82
Tune-up Limit			3.00

2.4GHz WLAN					
Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
802.11b	CH 1	2412	18.82	19.00	100
	CH 7	2442	19.21	20.00	100
	CH 13	2472	19.71	20.00	100
802.11g	CH 1	2412	18.19	19.00	99.53
	CH 7	2442	18.77	19.00	99.53
	CH 13	2472	19.29	19.50	99.56
802.11n (HT20)	CH 1	2412	17.3	17.50	99.49
	CH 7	2442	17.98	18.00	99.53
	CH 13	2472	18.62	19.00	99.49

Note 1: According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

Note 2: The output power refers to report (Report No.: SZ23060138W01/W02).



4. RF Exposure Assessment

➤ Standalone Transmission Assessment:

Bands	Frequency (MHz)	Tune-up Power(dBm)	Antenna Gain(dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit for MPE (mW/cm ²)
Bluetooth	2480	3.00	0.91	2.46	0.0005	1.0
WLAN 2.4GHz	2472	20.00	0.91	123.31	0.0245	1.0

Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. MPE calculate method

$$S = PG/4\pi R^2$$

Where: S= Power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune-up power (in appropriate units, e.g. dBm)

G = numeric gain of the antenna (in appropriate units, e.g. dBi)

R = Separation distance to the centre of radiation of the antenna (20cm)

➤ Simultaneous Transmission Assessment:

According to the user manual, both the WLAN and Bluetooth transmitters in the device cannot operate simultaneously, therefore simultaneous transmission analysis is not required.

➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.

END OF REPORT

