

DH5-Ant1-2480-0~Reference



DH5-Ant1-2480-30~1000



DH5-Ant1-2480-1000~26500

2DH5-Ant1-2402-0~Reference



2DH5-Ant1-2402-30~1000



2DH5-Ant1-2402-1000~26500

2DH5-Ant1-2441-0~Reference



2DH5-Ant1-2441-30~1000



2DH5-Ant1-2441-1000~26500



2DH5-Ant1-2480-0~Reference



2DH5-Ant1-2480-30~1000



2DH5-Ant1-2480-1000~26500

3DH5-Ant1-2402-0~Reference



3DH5-Ant1-2402-30~1000



3DH5-Ant1-2402-1000~26500

3DH5-Ant1-2441-0~Reference



3DH5-Ant1-2441-30~1000



3DH5-Ant1-2441-1000~26500

3DH5-Ant1-2480-0~Reference



3DH5-Ant1-2480-30~1000



3DH5-Ant1-2480-1000~26500

14 Antenna Requirement

14.1 Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

14.2 Antenna Connected Construction

The antenna is PIFA Antenna which permanently attached, and the best case gain of the antenna is -0.41dBi. It complies with the standard requirement.

15 APPENDIX I -- TEST SETUP PHOTOGRAPH

Conducted Emissions

Radiated Emissions
From 30M-1GHz



Above 1GHz



16 APPENDIX II -- EUT PHOTOGRAPH




Zwide®


Zwide®


Zwide
1cm 2 3 4 5 6 7


Zwide
1cm 2 3 4 5 6 7 8 9 10


ENC


M3










M3


45
46
47
48
1cm 2 3 4 5 6 7 8 9



********THE END REPORT********