

FCC ID: 2BB4V-E13

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Left

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-0.49	0.89	0±1	1.00	1.26	<5	0.39023	3.00	YES
$\pi/4$ DQPSK	2.402	1.64	1.46	1±1	2.00	1.58	<5	0.49127	3.00	YES
8DPSK	2.402	2.34	1.71	2±1	3.00	2.00	<5	0.61847	3.00	YES

Right

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	0.01	1.00	0±1	1.00	1.26	<5	0.39023	3.00	YES
$\pi/4$ DQPSK	2.402	1.91	1.55	1±1	2.00	1.58	<5	0.49127	3.00	YES
8DPSK	2.402	2.57	1.81	2±1	3.00	2.00	<5	0.61847	3.00	YES

For the Max simultaneous transmission

Evaluation mode	Result calculation	Total Result calculation	SAR Exclusion threshold	Result
Left	0.61847	1.23694	3.0	Pass
Right	0.61847			

Conclusion:

For the max result : $1.23694 < 3$, the SAR testing is not required.