

TEST REPORT

Applicant: Cavli Inc.
Address: 99 South Almaden Blvd., Suite 600, San Jose, CA
95113 United States
Equipment Type: LTE Modem/Module
Model Name: C10GS (refer to section 2.4)
Brand Name: Cavli Wireless
FCC ID: 2BB64C10GS
ISED Number: 31113-C10GS
Test Standard: 47 CFR Part 2
(Others refer to chapter 3.1)
Sample Arrival Date: Jul. 07, 2023
Test Date: Jul. 07, 2023 - Aug. 18, 2023
Date of Issue: Aug. 25, 2023

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Huang Jinsheng

Checked by: Wu Huihui

Approved by: Tolan Tu
(Testing Director)

Huang Jinsheng

Wu Huihui

Tolan Tu

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Aug. 25, 2023</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location.....	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information.....	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards.....	8
3.2	Test Verdict.....	9
4	GENERAL TEST CONFIGURATIONS	11
4.1	Test Environments	11
4.2	Test Equipment List.....	11
4.3	Test Configurations	13
4.4	Test Setup.....	20
5	TEST ITEMS	23
5.1	Transmitter Radiated Power (EIRP/ERP)	23
5.2	Peak to Average Ratio.....	27
5.3	Occupied Bandwidth	29
5.4	Frequency Stability.....	31
5.5	Spurious Emission at Antenna Terminals	34
5.6	Band Edge	39
5.7	Field Strength of Spurious Radiation	44
5.8	Receiver Spurious Emissions	50

5.9 AC Power-line Conducted Emissions	52
ANNEX A TEST RESULTS	54
A.1 Transmitter Radiated Power (EIRP/ERP)	54
A.2 Peak to Average Ratio.....	108
A.3 Occupied Bandwidth	111
A.4 Frequency Stability.....	122
A.5 Spurious Emission at Antenna Terminals	142
A.6 Band Edge	152
A.7 Field Strength of Spurious Radiation	166
A.8 Receiver Spurious Emissions	167
A.9 AC Power-line Conducted Emissions	171
ANNEX B TEST SETUP PHOTOS	173
ANNEX C EUT EXTERNAL PHOTOS.....	173
ANNEX D EUT INTERNAL PHOTOS.....	173

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Cavli Inc.
Address	99 South Almaden Blvd., Suite 600, San Jose, CA 95113 United States

2.2 Manufacturer Information

Manufacturer	Cavli Inc.
Address	99 South Almaden Blvd., Suite 600, San Jose, CA 95113 United States

2.3 General Description for Equipment under Test (EUT)

EUT Name	LTE Modem/Module
Model Name Under Test	C10GS
Series Model Name	C10GS-S001H, C10GS-S001N, C10GS-GNA1H, C10GS-GNA1N, C10GS-S004H, C10GS-S004N, C10GS-GNA4H, C10GS-GNA4N
Description of Model name differentiation	All these have the same PCB are same product with optional features omitted (this information provided by the customer)
Hardware Version	2.8
Software Version	1.3.0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

All Network and Wireless connectivity for EUT	4G Network LTE FDD Band 2/4/5/18/19/25/26/66 LTE TDD Band 40
About the Product	The equipment is LTE Modem/Module, intended for used with information technology equipment.

The following is the technical information of the EUT tested frequency bands in this report.

Operating Bands	FDD Band 2/4/5/18/19/25/26/66 TDD Band 40		
Modulation Type	LTE	QPSK/16QAM	
Antenna Type	PIFA Antenna		
Antenna Gain	FDD LTE Band 2: 2.0 dBi FDD LTE Band 4: 2.0 dBi FDD LTE Band 5: 2.0 dBi FDD LTE Band 18: 2.0 dBi FDD LTE Band 19: 2.0 dBi FDD LTE Band 25: 2.0 dBi FDD LTE Band 26: 2.0 dBi FDD LTE Band 66: 2.0 dBi TDD LTE Band 40: 2.0 dBi		
The Max RF Output Power (EIRP/ERP)	FDD LTE Band 2: 22.76 dBm FDD LTE Band 4: 21.69 dBm FDD LTE Band 5: 20.46 dBm FDD LTE Band 18(824-830 MHz): 20.32 dBm FDD LTE Band 18(815-824 MHz): 20.45 dBm FDD LTE Band 19: 20.55 dBm FDD LTE Band 25: 22.80 dBm FDD LTE Band 26(824-849 MHz): 20.45 dBm FDD LTE Band 26(814-824 MHz): 20.46 dBm FDD LTE Band 66: 22.53 dBm TDD LTE Band 40(2305-2315 MHz): 19.45 dBm TDD LTE Band 40(2350-2360 MHz): 19.14 dBm		
Band	Power Class	Tx Frequency Range	Rx Frequency Range
LTE B2	3	1850 MHz ~ 1910 MHz	1930 MHz ~ 1990 MHz
LTE B4	3	1710 MHz ~ 1755 MHz	2110 MHz ~ 2155 MHz
LTE B5	3	824 MHz ~ 849 MHz	869 MHz ~ 894 MHz
LTE B18	3	815 MHz ~ 824 MHz ^{Note2}	860 MHz ~ 869 MHz ^{Note2}
		824 MHz ~ 830 MHz	869 MHz ~ 875 MHz
LTE B19	3	830 MHz ~ 845 MHz	875 MHz ~ 890 MHz
LTE B25	3	1850 MHz ~ 1915 MHz	1930 MHz ~ 1995 MHz

LTE B26	3	814 MHz ~ 824 MHz ^{Note2}	859 MHz ~ 869 MHz ^{Note2}
		824 MHz ~ 849 MHz	869 MHz ~ 894 MHz
LTE B66	3	1710 MHz ~ 1780 MHz	2110 MHz ~ 2180 MHz
LTE B40	3	2305 MHz ~ 2315 MHz	2305 MHz ~ 2315 MHz
		2350 MHz ~ 2360 MHz	2350 MHz ~ 2360 MHz

Note1: The EUT information provided by the applicant, except for The Max RF Conducted Power. For more detailed band specifications and features description, please refer to the manufacturer's specifications or user's manual.

Note2: These frequency ranges are only applicable in the United States.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 Subpart H	Cellular Radiotelephone Service
3	47 CFR Part 24 Subpart E	Broadband PCS
4	47 CFR Part 27	Miscellaneous Wireless Communications Services
5	47 CFR Part 90 Subpart S	Regulations Governing Licensing and Use of Frequencies in the 806-824, 851-869, 896-901, and 935-940 MHz Bands
6	RSS-Gen Issue5	General Requirements and Information for the Certification of Radio Apparatus
7	RSS-132 Issue3	Cellular Telephone Systems Operating in the Bands 824-849 MHz and 869-894 MHz
8	RSS-133 Issue6	2 GHz Personal Communications Services
9	RSS-139 Issue4	Advanced Wireless Services (AWS) Equipment Operating in the Bands 1710-1780 MHz and 2110-2200 MHz
10	RSS-195 Issue2	Wireless Communication Service (WCS) Equipment Operating in the Bands 2305-2320MHz and 2345-2360MHz
11	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
12	KDB 971168 D01 v03	Measurement Guidance for Certification of Licensed Digital Transmitters

3.2 Test Verdict

No.	Test Description	FCC Part No.	ISED Part No.	Test Result	Test Verdict
1	Conducted RF Output Power	2.1046	RSS-Gen 6.12 RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-195 5.5	Reporting only (ANNEX A.1)	Pass
2	Effective (Isotropic) Radiated Power	2.1046 22.913 24.232 27.50 90.635(b)	RSS-Gen 6.12 RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-195 5.5	ANNEX A.1	Pass
3	Peak to Average Ratio	2.1046 24.232(d) 27.50(d)	RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-195 5.5	ANNEX A.2	Pass
4	Occupied Bandwidth	2.1049 22.917 24.238 27.53 90.209	RSS-Gen 6.7	ANNEX A.3	Pass
5	Frequency Stability	2.1055 22.355 24.235 27.54 90.213	RSS-Gen 6.11 RSS-132 5.3 RSS-133 6.3 RSS-139 6.4 RSS-195 5.4	ANNEX A.4	Pass
6	Spurious Emission at Antenna Terminals	2.1051 22.917 24.238 27.53 90.691	RSS-Gen 6.13 RSS-132 5.5 RSS-133 6.5 RSS-139 6.6 RSS-195 5.6	ANNEX A.5	Pass
7	Band Edge	2.1051 22.917 24.238 27.53 90.691	RSS-132 5.5 RSS-133 6.5 RSS-139 6.6 RSS-195 5.6	ANNEX A.6	Pass
8	Field Strength of Spurious Radiation	2.1053 22.917 24.238 27.53 90.691	RSS-Gen 6.13 RSS-132 5.5 RSS-133 6.5 RSS-139 6.6 RSS-195 5.6	ANNEX A.7	Pass
9	Receiver Spurious Emissions	N/A	RSS-Gen 7	ANNEX A.8	Pass

No.	Test Description	FCC Part No.	ISED Part No.	Test Result	Test Verdict
			RSS-132 5.6 RSS-133 6.6		
10	AC Power-line Conducted Emissions	N/A	RSS-Gen 8.8	ANNEX A.9	Pass

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the environmental conditions were within the listed ranges:

Relative Humidity		20% to 75%
Atmospheric Pressure		98 kPa to 102 kPa
Test Voltage of the EUT	NV (Normal Voltage)	3.8 V
	LV (Low Voltage)	3.6 V
	HV (High Voltage)	4.5 V
Test Temperature of the EUT	NT (Normal Temperature)	15 °C to 35 °C
	LT (Low Temperature)	-30 °C
	HT (High Temperature)	+70 °C

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Version	Cal. Date	Cal. Due
2/3/4/5G RF Test System						
BL410 Test Software	BALUN	BL410R	N/A	2.1.1.496	N/A	N/A
Temperature Chamber	AHK	SP20	1412	N/A	2022.09.20	2023.09.19
Wideband Radio Communication Tester	R&S	CMW 500	167190	V4.0.60	2023.05.11	2024.05.10
Wideband Radio Communication Tester	R&S	CMW 500	102318	V3.2.71	2023.05.16	2024.05.15
Spectrum Analyzer	keysight	N9020A	MY50531628	A.16.09	2023.05.12	2024.05.11
Spectrum Analyzer	R&S	FSV40	101544	2.30.SP4	2022.12.28	2023.12.27
DC Power Supply	ITECH	IT6863A	800014020757120005	N/A	2022.09.09	2023.09.08
Radiated Test System						
Radiated Test System Test Software	BALUN	BL410-E	N/A	V19.918	N/A	N/A
Wideband Radio Communication Tester	R&S	CMW 500	167190	V4.0.60	2023.05.11	2024.05.10

Wideband Radio Communication Tester	R&S	CMW 500	102318	V3.2.71	2023.05.16	2024.05.15
Spectrum Analyzer	R&S	FSV40	101544	2.30.SP4	2022.12.28	2023.12.27
Test Antenna-Bi-Log(30 MHz-3 GHz)	Schwarzbeck	VULB 9163	9163-624	N/A	2021.08.20	2024.08.19
Test Antenna-Horn(1-18 GHz)	Schwarzbeck	BBHA 9120D	01917	N/A	2022.06.09	2025.06.08
Test Antenna-Horn(18-40 GHz)	A-INFO	LB-180400KF	J211060273	N/A	2021.07.02	2024.07.01
Anechoic Chamber	YIHENG	9m*6m*6m	144	N/A	2022.02.09	2024.09.03
EMI Receiver	Keysight	N9038A	MY53220118	A.14.16	2022.09.08	2023.09.07

4.3 Test Configurations

LTE Band	Bandwidth (MHz)						Modulation Type		RB#			Test Channel		
	1.4	3	5	10	15	20	QPSK	16-QAM	1	Half	Full	LCH	MCH	HCH
Effective (Isotropic) Radiated Power														
2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
4	v	v	v	v	v	v	v	v	v	v	v	v	v	v
5	v	v	v	v	n	n	v	v	v	v	v	v	v	v
18 (824~830 MHz)	n	n	v	--	--	n	v	v	v	v	v	v	v	v
18 (815-824 MHz)	n	n	v	--	--	n	v	v	v	v	v	v	v	v
19	n	n	v	v	v	n	v	v	v	v	v	v	v	v
25	v	v	v	v	v	v	v	v	v	v	v	v	v	v
26 (824~849 MHz)	v	v	v	v	v	n	v	v	v	v	v	v	v	v
26 (814-824 MHz)	v	v	v	v	--	n	v	v	v	v	v	v	v	v
66	v	v	v	v	v	v	v	v	v	v	v	v	v	v
40 (2305~2315 MHz)	n	n	v	v	--	--	v	v	v	v	v	v	v	v
40 (2350~2360 MHz)	n	n	v	v	--	--	v	v	v	v	v	v	v	v
Peak to Average Ratio														
2	--	--	--	--	--	v	v	v	v	--	v	v	v	v
4	--	--	--	--	--	v	v	v	v	--	v	v	v	v
5	--	--	--	v	n	n	v	v	v	--	v	v	v	v
18 (824~830 MHz)	n	n	v	--	--	n	v	v	v	--	v	v	v	v
18 (815-824 MHz)	n	n	v	--	--	n	v	v	v	--	v	v	v	v
19	n	n	--	--	v	n	v	v	v	--	v	--	v	--
25	--	--	--	--	--	v	v	v	v	--	v	v	v	v
26 (824~849 MHz)	--	--	--	--	v	n	v	v	v	--	v	v	v	v
26 (814-824 MHz)	--	--	--	v	--	n	v	v	v	--	v	--	v	--
66	--	--	--	--	--	v	v	v	v	--	v	v	v	v
40 (2305~2315 MHz)	n	n	--	v	--	--	v	v	v	--	v	--	v	--
40 (2350~2360 MHz)	n	n	--	v	--	--	v	v	v	--	v	--	v	--
Occupied Bandwidth														
2	v	v	v	v	v	v	v	v	v	--	--	v	v	v

LTE Band	Bandwidth (MHz)						Modulation Type		RB#			Test Channel		
	1.4	3	5	10	15	20	QPSK	16-QAM	1	Half	Full	LCH	MCH	HCH
4	v	v	v	v	v	v	v	v	--	--	v	v	v	v
5	v	v	v	v	n	n	v	v	--	--	v	v	v	v
18 (824~830 MHz)	n	n	v	--	--	n	v	v	--	--	v	v	v	v
18 (815-824 MHz)	n	n	v	--	--	n	v	v	--	--	v	v	v	v
19	n	n	v	v	v	n	n	v	--	--	v	v	v	v
25	v	v	v	v	v	v	v	v	--	--	v	v	v	v
26 (824~849 MHz)	v	v	v	v	v	n	v	v	--	--	v	v	v	v
26 (814-824 MHz)	v	v	v	v	--	n	v	v	--	--	v	v	v	v
66	v	v	v	v	v	v	v	v	--	--	v	v	v	v
40 (2305~2315 MHz)	n	n	v	v	--	--	v	v	--	--	v	v	v	v
40 (2350~2360 MHz)	n	n	v	v	--	--	v	v	--	--	v	v	v	v
Frequency Stability														
2	--	--	--	v	--	--	v	v	--	--	v	--	v	--
4	--	--	--	v	--	--	v	v	--	--	v	--	v	--
5	--	--	--	v	n	n	v	v	--	--	v	--	v	--
18 (824~830 MHz)	n	n	v	--	--	n	v	v	--	--	v	--	v	--
18 (815-824 MHz)	n	n	v	--	--	n	v	v	--	--	v	--	v	--
19	n	n	--	v	--	n	v	v	--	--	v	--	v	--
25	--	--	--	v	--	--	v	v	--	--	v	--	v	--
26 (824~849 MHz)	--	--	--	v	--	n	v	v	--	--	v	--	v	--
26 (814-824 MHz)	--	--	--	v	--	n	v	v	--	--	v	--	v	--
66	--	--	--	v	--	--	v	v	--	--	v	--	v	--
40 (2305~2315 MHz)	n	n	--	v	--	--	v	v	--	--	v	--	v	--
40 (2350~2360 MHz)	n	n	--	v	--	--	v	v	--	--	v	--	v	--
Spurious Emission at Antenna Terminals														
2	v	v	v	v	v	v	v	v	v	--	--	v	v	v
4	v	v	v	v	v	v	v	v	v	--	--	v	v	v
5	v	v	v	v	n	n	v	v	v	--	--	v	v	v
18	n	n	v	--	--	n	v	v	v	--	--	v	v	v

LTE Band	Bandwidth (MHz)						Modulation Type		RB#			Test Channel		
	1.4	3	5	10	15	20	QPSK	16-QAM	1	Half	Full	LCH	MCH	HCH
(824~830 MHz)														
18 (815-824 MHz)	n	n	v	--	--	n	v	v	v	--	--	v	v	v
19	n	n	v	v	v	n	v	v	v	--	--	v	v	v
25	v	v	v	v	v	v	v	v	v	--	--	v	v	v
26 (824~849 MHz)	v	v	v	v	v	n	v	v	v	--	--	v	v	v
26 (814-824 MHz)	v	v	v	v	--	n	v	v	v	--	--	v	v	v
66	v	v	v	v	v	v	v	v	v	--	--	v	v	v
40 (2305~2315 MHz)	n	n	v	v	--	--	v	v	v	--	--	v	v	v
40 (2350~2360 MHz)	n	n	v	v	--	--	v	v	v	--	--	v	v	v
Band Edge														
2	v	v	v	v	v	v	v	v	v	--	v	v	--	v
4	v	v	v	v	v	v	v	v	v	--	v	v	--	v
5	v	v	v	v	n	n	v	v	v	--	v	v	--	v
18 (824~830 MHz)	n	n	v	--	--	n	v	v	v	--	v	v	--	v
18 (815-824 MHz)	n	n	v	--	--	n	v	v	v	--	v	v	--	v
19	n	n	v	v	v	n	v	v	v	--	v	v	--	v
25	v	v	v	v	v	v	v	v	v	--	v	v	--	v
26 (824~849 MHz)	v	v	v	v	v	n	v	v	v	--	v	v	--	v
26 (814-824 MHz)	v	v	v	v	--	n	v	v	v	--	v	v	--	v
66	v	v	v	v	v	v	v	v	v	--	v	v	--	v
40 (2305~2315 MHz)	n	n	v	v	--	--	v	v	v	--	v	v	--	v
40 (2350~2360 MHz)	n	n	v	v	--	--	v	v	v	--	v	v	--	v
Field Strength of Spurious Radiation														
2	worst case													
4	worst case													
5	worst case													
18 (824~830 MHz)	worst case													
18 (815-824 MHz)	worst case													

LTE Band	Bandwidth (MHz)						Modulation Type		RB#			Test Channel		
	1.4	3	5	10	15	20	QPSK	16-QAM	1	Half	Full	LCH	MCH	HCH
19	worst case													
25	worst case													
26 (824~849 MHz)	worst case													
26 (814-824 MHz)	worst case													
66	worst case													
40 (2305~2315 MHz)	worst case													
40 (2350~2360 MHz)	worst case													
Note 1: The mark "v" means that this configuration is chosen for testing.														
Note 2: The mark "n" means that this bandwidth is not supported.														


Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
LTE Band 2	Low Range	1.4	18607	1850.7
		3	18615	1851.5
		5	18625	1852.5
		10	18650	1855
		15	18675	1857.5
		20	18700	1860
	Middle Range	1.4/3/5/10/15/20	18900	1880
	High Range	1.4	19193	1909.3
		3	19185	1908.5
		5	19175	1907.5
		10	19150	1905
		15	19125	1902.5
		20	19100	1900
LTE Band 4	Low Range	1.4	19957	1710.7
		3	19965	1711.5
		5	19975	1712.5
		10	20000	1715
		15	20025	1717.5
		20	20050	1720
	Middle Range	1.4/3/5/10/15/20	20175	1732.5
	High Range	1.4	20393	1754.3
		3	20385	1753.5
		5	20375	1752.5
		10	20350	1750
		15	20325	1747.5
		20	20300	1745
LTE Band 5	Low Range	1.4	20407	824.7
		3	20415	825.5
		5	20425	826.5
		10	20450	829
	Middle Range	1.4/3/5/10	20525	836.5
	High Range	1.4	20643	848.3
		3	20635	847.5
		5	20625	846.5
		10	20600	844
LTE Band 18 (824-830 MHz)	Low Range	5	23965	826.5
	Middle Range	5	23970	827
	High Range	5	23975	827.5
LTE Band 18 (815-824 MHz)	Low Range	5	23875	817.5
	Middle Range	5	23895	819.5

Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
	High Range	5	23915	821.5
LTE Band 19	Low Range	5	24025	832.5
		10	24050	835
		15	--	--
	Middle Range	5/10/15	24075	837.5
	High Range	5	24125	842.5
		10	24100	840
15		--	--	
LTE Band 25	Low Range	1.4	26047	1850.7
		3	26055	1851.5
		5	26065	1852.5
		10	26090	1855
		15	26115	1857.5
		20	26140	1860
	Middle Range	1.4/3/5/10/15/20	26365	1882.5
	High Range	1.4	26683	1914.3
		3	26675	1913.5
		5	26665	1912.5
		10	26640	1910
		15	26615	1907.5
20		26590	1905	
LTE Band 26 (824-849 MHz)	Low Range	1.4	26797	824.7
		3	26805	825.5
		5	26815	826.5
		10	26840	829
		15	26865	831.5
	Middle Range	1.4/3/5/10/15	26915	836.5
	High Range	1.4	27033	848.3
		3	27025	847.5
		5	27015	846.5
		10	26990	844
15		26965	841.5	
LTE Band 26 (814-824 MHz)	Low Range	1.4	26697	814.7
		3	26705	815.5
		5	26715	816.5
		10	---	---
	Middle Range	1.4/3/5/10	26740	819
	High Range	1.4	26783	823.3
		3	26775	822.5
		5	26765	821.5
		10	---	---

Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
LTE-Band 66	Low Range	1.4	131979	1710.7
		3	131987	1711.5
		5	131997	1712.5
		10	132022	1715
		15	132047	1717.5
		20	132072	1720
	Middle Range	1.4/3/5/10/15/20	132322	1745
	High Range	1.4	132665	1779.3
		3	132657	1778.5
		5	132647	1777.5
		10	132622	1775
		15	132597	1772.5
20		132572	1770	
LTE Band 40 (2305-2315MHz)	Low Range	5	38725	2307.5
		10	--	--
	Middle Range	5/10	38750	2310
	High Range	5	38775	2312.5
10		--	--	
LTE Band 40 (2350-2360MHz)	Low Range	5	39175	2352.5
		10	--	--
	Middle Range	5/10	39200	2355
	High Range	5	39225	2357.5
10		--	--	


4.4 Test Setup

4.4.1 For Antenna Port Test




(Diagram 1)

4.4.2 For Frequency Stability Test




(Diagram 2)

4.4.3 For Radiated Test (30 MHz ~ 1 GHz)




(Diagram 3)

4.4.4 For Radiated Test (Above 1 GHz)



(Diagram 4)

4.4.5 For AC Power-line Conducted Emissions



(Diagram 5)

5 TEST ITEMS

5.1 Transmitter Radiated Power (EIRP/ERP)

5.1.1 Limit

FCC § 2.1046 & 22.913(a) & 24.232(c) & 27.50(a) & 27.50(b) & 27.50(c) & 27.50(d) & 27.50(h) & 27.50(j) & 27.50(k) & 90.635(b)

According to FCC section 22.913(a) (5), the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC section 24.232(c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to FCC section 27.50(a) (3), for mobile and portable stations transmitting in the 2305-2315MHz band or the 2350-2360MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, except that for mobile and portable stations compliant with 3GPP LTE standards. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands.

FCC section 27.50(b) (10), portable stations (hand-held devices) transmitting in the 746-757MHz, 776-788MHz, and 805-806MHz bands are limited to 3 watts ERP.

FCC section 27.50(c) (10), portable stations (hand-held devices) in the 600MHz uplink band and the 698-746MHz band, and fixed and mobile stations in the 600MHz uplink band are limited to 3 watts ERP.

FCC section 27.50(d) (4), fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(7) Fixed, mobile, and portable (hand-held) stations operating in the 2000-2020 MHz band are limited to 2 watts EIRP.

And FCC section 27.50(h) (2), for mobile and other user stations, mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

FCC section 27.50(j) (3), for mobile, and portable (hand-held) stations operating in the 3700-3980 MHz band are limited to 1 watt EIRP.

FCC section 27.50(k) (3), Mobile devices are limited to 1Watt (30 dBm) EIRP in the 3450-3550 MHz band.

According to FCC section 90.635(b), the maximum output power of the transmitter for mobile stations is 100 watts (20dBW).

RSS-Gen § 6.12 & RSS-132 § 5.4 & RSS-133 § 6.4 & RSS-139 & RSS-195 § 5.5

According to RSS-132 § 5.4, the Effective Radiated Power (ERP) for mobile equipment shall not exceed

11.5 watts.

According to RSS-133 § 6.4 (SRSP 510), mobile stations and hand-held portables are limited to 2 watts maximum EIRP.

According to RSS-139 § 6.5, the EIRP for mobile and portable transmitters shall not exceed 1 watt.

According to RSS-195 § 5.5, the EIRP of mobile or portable equipment transmitting in the band 2305-2315MHz or the band 2350-2360MHz, employing 3GPP LTE standards, shall not exceed 250mW within 5MHz bandwidth. For other technologies, the EIRP shall not exceed 50mW within any 1MHz bandwidth.

5.1.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for conducted test, and the section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description is used for radiated test. The photo of test setup please refer to ANNEX B.

5.1.3 Test Procedure

Description of the Conducted Output Power Measurement

The EUT is coupled to the SS with attenuator through power splitter; the RF load attached to EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. A system simulator is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The relevant equation for determining the conducted measured value is:

Conducted Output Power Value (dBm) = Measured Value (dBm) + Path Loss (dB)

where:

Conducted Output Power Value = final conducted measured value in the conducted power test, in dBm;
Measured Value = measured conducted power received by spectrum analyzer or power meter, in dBm;
Path Loss = signal attenuation in the connecting cable between the transmitter and spectrum analyzer or power meter, including external cable loss, in dB;

During the test, the data of Path Loss (dB) is added in the spectrum analyzer or power meter, so Measured Value (dBm) is the final values which contains the data of Path Loss (dB).

For example:

In the conducted output power test, when measured value for GSM850 is 24.7 dBm, and path loss is 8.5 dB, then final conducted output power value is:

Conducted Output Power Value (dBm) = 24.7 dBm + 8.5 dB = 33.2 dBm

Description of the Transmitter Radiated Power Measurement

In many cases, the RF output power limits for licensed digital transmission devices is specified in terms of effective radiated power (ERP) or equivalent isotropic radiated power (EIRP). Typically, ERP is specified when the operating frequency is less than or equal to 1 GHz and EIRP is specified when the operating frequency is greater than 1 GHz. Both are determined by adding the transmit antenna gain to the conducted RF output power with the primary difference between the two being that when determining the ERP, the transmit antenna gain is referenced to a dipole antenna (i.e., dBd) whereas when determining the EIRP, the transmit antenna gain is referenced to an isotropic antenna (dBi).

Final measurement calculation as below:

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP/EIRP} = P_{\text{Meas}} + \text{GT} - \text{LC}$$

where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

dBd (ERP)=dBi (EIRP) -2.15 dB

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

For devices utilizing multiple antennas, KDB 662911 provides guidance for determining the effective array transmit antenna gain term to be used in the above equation.

For example:

In the EIRP test, when P_{Meas} value for GSM1900 is 30.2 dBm, LC is 0.6 dB, and GT is -3.4 dB, then final EIRP value is:

$$\text{EIRP for GSM1900} = 30.2 \text{ dBm} - 3.4 \text{ dBi} - 0.6 \text{ dB} = 26.2 \text{ dBm}$$

The relevant equation for determining the ERP/EIRP from the radiated RF output power is:

$$\text{ERP/EIRP (dBm)} = \text{SA Read Value (dBm)} + \text{Correction Factor (dB)}$$

where:

ERP/EIRP = effective or equivalent radiated power, in dBm;

SA Read Value = measured transmitter power received by EMI receiver or spectrum analyzer, in dBm;

Correction Factor = total correction factor including cable loss, in dB;

During the test, the data of Correction Factor (dB) is added in the EMI receiver or spectrum analyzer, so SA Read Value (dBm) is the final values which contains the data of Correction Factor (dB).

For example:

In the ERP test, when SA read value for GSM850 is 21dBm, and correction factor is 8dB, then final ERP value for GSM850 is:

$$\text{ERP (dBm)} = 21\text{dBm} + 8\text{dB} = 29\text{dBm}$$

5.1.4 Test Result

Please refer to ANNEX A.1.

5.2 Peak to Average Ratio

5.2.1 Limit

FCC § 2.1046 & 24.232(d) & 27.50(d) & 27.50(j) & 27.50(k)

In addition, when the transmitter power is measured in terms of average value, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

According to FCC section 24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with 24.232 (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

FCC section 24.232(e), peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

According to FCC section 27.50(d) (5) & 27.50(j) & 27.50(k), in measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.

RSS-132 § 5.4 & RSS-133 § 6.4 & RSS-139 & RSS-195 § 5.5

According to RSS-132 § 5.4, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

According to RSS-133 § 6.4, the transmitter's peak-to-average power ratio (PAPR) shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

According to RSS-139 § 5.5, the peak to average power ratio (PAPR) of the equipment shall not exceed 13 dB for more than 0.1% of the time, using a signal that corresponds to the highest PAPR during periods of continuous transmission.

According to RSS-195 § 5.5.1, the PAPR of the transmitter output power of base and fixed station equipment shall not exceed 13 dB for more than 0.1% of the time, using a signal that corresponds to the highest PAPR during periods of continuous transmission.

5.2.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Here the lowest, middle and highest channels are selected to perform testing to verify the peak-to-average ratio.

According to KDB 971168 D01, there is CCDF procedure for PAPR:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval as follows:
 - 1) for continuous transmissions, set to 1 ms,
 - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- e) Record the maximum PAPR level associated with a probability of 0.1%.

Alternate procedure for PAPR:

Use one of the procedures presented in 4.1 to measure the total peak power and record as P_{PK} . Use one of the applicable procedures presented 4.2 to measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{PK} (dBm) - P_{Avg} (dBm).$$

5.2.4 Test Result

Please refer to ANNEX A.2.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC § 2.1049

RSS-Gen § 6.7

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Many of the individual rule parts specify a relative OBW in lieu of the 99% OBW. In such cases, the OBW is defined as the width of the signal between two points, one below the carrier center frequency and on above the carrier center frequency, outside of which all emissions are attenuated by at least X dB below the transmitter power, where the value of X is typically specified as 26.

5.3.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The following procedure shall be used for measuring power bandwidth.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the anticipated OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least $10\log(\text{OBW} / \text{RBW})$ below the reference level.
- d) NOTE—Steps a) through c) may require iteration to adjust within the specified tolerances.
- e) For -26 dB OBW, the dynamic range of the spectrum analyzer at the selected RBW shall be at least 10dB below the target “-X dB down” requirement, e.g. -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be 36dB below the reference value.
- f) Set the detection mode to peak, and the trace mode to max hold.
- g) For 99% OBW, use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the measured bandwidth.

If the instrument does not have a 99 % power bandwidth function, the trace data points are to be recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at

the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99 % power bandwidth is the difference between these two frequencies.

h) For -26 dB OBW, determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).

Determine the “-X dB down amplitude” as equal to (reference value -X). Alternatively, this calculation can be performed by the analyzer by using the marker-delta function.

Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below “-X dB down amplitude” determined in step g). If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.

i) The OBW shall be reported by providing plot(s) of the measuring instrument display. The frequency and amplitude axes and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

j) Change variable modulations, coding, or channel bandwidth settings, then repeat above test procedures.

5.3.4 Test Result

Please refer to ANNEX A.3.

5.4 Frequency Stability

5.4.1 Limit

FCC § 2.1055 & 22.355 & 24.235 & 27.54 & 90.213

FCC § 2.1055

The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) The temperature is varied from -30°C to +50°C.
- (2) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10°C through the range.

The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating and point which shall be specified by the manufacture.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

FCC § 22.355

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

Table C-1—Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10.0	n/a	n/a

FCC § 24.235

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

FCC § 27.54

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

FCC § 90.213

The frequency stability shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

RSS-Gen § 6.11 & RSS-132 § 5.3 & RSS-133 § 6.3 & RSS-139 § 6.4 & RSS-195 § 5.4

RSS-Gen § 6.11

The frequency stability shall be measured with variation of ambient temperature as follows:

(1) The temperature is varied from -30°C to $+50^{\circ}\text{C}$.

(2) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10°C through the range.

The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating and point which shall be specified by the manufacture.

(3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

RSS-132 § 5.3

The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations and ± 1.5 ppm for base stations.

RSS-133 § 6.3

The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations and ± 1.0 ppm for base stations.

RSS-139 § 6.4

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block when tested to the temperature and supply voltage variations specified in RSS-Gen.

RSS-195 § 5.4

The applicant shall ensure frequency stability by showing that the occupied bandwidth is maintained within the range of the operating frequency blocks when testing under the temperature and supply voltage variations specified for the frequency stability measurement in RSS-Gen.

5.4.2 Test Setup

The section 4.4.2 (Diagram 2) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

1. The EUT is placed in a temperature chamber.
2. The temperature is set to 25°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured.
3. The temperature is increased by not more than 10 degrees, allowed to stabilize and soak, and then repeat the frequency error measurement.
4. Repeat procedure 3 until +50°C and -30°C is reached.
5. Change supply voltage, and repeat measurement until extreme voltage is reached.

5.4.4 Test Result

Please refer to ANNEX A.4.

5.5 Spurious Emission at Antenna Terminals

5.5.1 Limit

FCC § 2.1051 & 22.917(a) & 24.238(a) & 27.53(a) & 27.53(c) & 27.53(f) & 27.53(g) & 27.53(h) & 27.53(l) & 27.53(m) & 27.53(n) & 90.691

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

FCC § 22.917(a) & 24.238(a)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10\log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(a) (4)

For mobile and portable stations operating in the 2305-2315MHz and 2350-2360MHz bands:

(1) By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320MHz and on all frequencies between 2345 and 2360MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324MHz and on all frequencies between 2341 and 2345MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328MHz and on all frequencies between 2337 and 2341MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337MHz.

(2) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292MHz, and $70 + 10 \log (P)$ dB below 2288MHz.

(3) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365MHz, and not less than $70 + 10 \log (P)$ dB above 2365MHz.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the

band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the

band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth

of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(f)

For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43+10*\log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1)

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.

FCC § 27.53(l) (2)

For mobile operations in the 3700-3980 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

FCC § 27.53(m) (4)

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40+10\log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43+10\log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,
- $55+10\log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

FCC § 27.53(n) (2)

For mobile operations in the $3450-3550$ MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

FCC § 90.691

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

RSS-Gen § 6.13 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-195 § 5.6

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This is calculated to be -13 dBm.

RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.

RSS-195 § 5.6

The power of any emission outside the frequency range(s) in which the equipment operates shall be attenuated below the transmitter power, P (dBW), by the amount indicated in table below and graphically represented in figure below, where p is the transmitter output power measured in watts.

Frequency (MHz)	Attenuation (dB)	Frequency (MHz)	Attenuation (dB)
<2200	$43+10 \log_{10} (p)$	2324-2328	$61+10 \log_{10} (p)$
2200-2288	$70+10 \log_{10} (p)$	2328-2337	$67+10 \log_{10} (p)$
2288-2292	$67+10 \log_{10} (p)$	2337-2341	$61+10 \log_{10} (p)$
2292-2296	$61+10 \log_{10} (p)$	2341-2345	$55+10 \log_{10} (p)$
2296-2300	$55+10 \log_{10} (p)$	2345-2360	$43+10 \log_{10} (p)$ ^{Note}
2300-2305	$43+10 \log_{10} (p)$	2360-2365	$43+10 \log_{10} (p)$
2305-2320	$43+10 \log_{10} (p)$ ^{Note}	2365-2395	$70+10 \log_{10} (p)$
2320-2324	$55+10 \log_{10} (p)$	>2395	$43+10 \log_{10} (p)$

Note: Measured at the edges of the highest and lowest frequency range(s) in which the equipment is designed to operate. See section 5.2 for the permitted frequency ranges for various equipment types.

5.5.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation

employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency blocks a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

1. The EUT is coupled to the system simulator and spectrum analyzer; the RF load attached to EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.
2. Base Station is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power.
3. The RF output of the transmitter is connected to the input of the spectrum analyzer through sufficient attenuation.
4. Spurious emissions are tested with 0.001MHz RBW for frequency less than 150kHz, 0.01MHz RBW for frequency less than 30MHz, 0.1MHz RBW for frequency less than 1GHz, and 1MHz RBW for frequency above 1GHz. And sweep point number are at least 401, referring to following formula.

Sweep point number = Span/RBW

VBW=3*RBW

Detector Mode=mean or average power

5. Record the frequencies and levels of spurious emissions.

5.5.4 Test Result

Please refer to ANNEX A.5.

5.6 Band Edge

5.6.1 Limit

FCC § 2.1051 & 22.917(a) & 24.238(a) & 27.53(a) & 27.53(c) & 27.53(g) & 27.53(h) & 27.53(l) & 27.53(m) & 27.53(n) & 90.691

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

FCC § 22.917(a) & 24.238(a)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(a) (4)

For mobile and portable stations operating in the 2305-2315MHz and 2350-2360MHz bands:

(1)By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320MHz and on all frequencies between 2345 and 2360MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324MHz and on all frequencies between 2341 and 2345MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328MHz and on all frequencies between 2337 and 2341MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337MHz.

(2)By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292MHz, and $70 + 10 \log (P)$ dB below 2288MHz.

(3)By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365MHz, and not less than $70 + 10 \log (P)$ dB above 2365MHz.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee’s frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the

band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the

band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth

of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43+10*\log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1)

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.

FCC § 27.53(l) (2)

For mobile operations in the 3700-3980 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

FCC § 27.53(m) (4)

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40+10\log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43+10\log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,

• $55+10\log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

FCC § 27.53(n) (2)

For mobile operations in the 3450 - 3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

FCC § 90.691

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

RSS-Gen § 6.13 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-195 § 5.6

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This is calculated to be -13 dBm.

RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695 - 1710 MHz, 1710 - 1755 MHz, 1755 - 1780

MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

RSS-195 § 5.6

The power of any emission outside the frequency range(s) in which the equipment operates shall be attenuated below the transmitter power, P (dBW), by the amount indicated in table below and graphically represented in figure below, where p is the transmitter output power measured in watts.

Frequency (MHz)	Attenuation (dB)	Frequency (MHz)	Attenuation (dB)
<2200	$43+10 \log_{10}(p)$	2324-2328	$61+10 \log_{10}(p)$
2200-2288	$70+10 \log_{10}(p)$	2328-2337	$67+10 \log_{10}(p)$
2288-2292	$67+10 \log_{10}(p)$	2337-2341	$61+10 \log_{10}(p)$
2292-2296	$61+10 \log_{10}(p)$	2341-2345	$55+10 \log_{10}(p)$
2296-2300	$55+10 \log_{10}(p)$	2345-2360	$43+10 \log_{10}(p)$ ^{Note}
2300-2305	$43+10 \log_{10}(p)$	2360-2365	$43+10 \log_{10}(p)$
2305-2320	$43+10 \log_{10}(p)$ ^{Note}	2365-2395	$70+10 \log_{10}(p)$
2320-2324	$55+10 \log_{10}(p)$	> 2395	$43+10 \log_{10}(p)$

Note: Measured at the edges of the highest and lowest frequency range(s) in which the equipment is designed to operate. See section 5.2 for the permitted frequency ranges for various equipment types.

5.6.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

1. The EUT is coupled to the system simulator and spectrum analyzer; the RF load attached to EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

2. Base Station is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power.

3. The RF output of the transmitter is connected to the input of the spectrum analyzer through sufficient attenuation.

4. The center of the spectrum analyzer was set to block edge frequency.

5. Band edge are tested with 1%*cBW (RBW), and sweep point number referred to following formula.

$$\text{Sweep point number} = 2 * \text{Span} / \text{RBW}$$

$$\text{VBW} = 3 \text{RBW}$$

6. Record the frequencies and levels of spurious emissions.

For mobile and portable stations, on all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment. Since it was not possible to set the resolution bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance. By using a 10 kHz bandwidth on the spectrum analyzer.

$$10 * \log(10 \text{ kHz} / 6.25 \text{ kHz}) = 2.04 \text{ dB}$$

$$\text{Limit Line} = -35 \text{ dBm} + 2.04 \text{ dB} = -32.96 \text{ dBm}$$

5.6.4 Test Result

Please refer to ANNEX A.6.

5.7 Field Strength of Spurious Radiation

5.7.1 Limit

FCC § 2.1053 & 22.917(a) & 24.238(a) & 27.53(a) & 27.53(c) & 27.53(f) & 27.53(g) & 27.53(h) & 27.53(l) & 27.53(m) & 27.53(n) & 90.691

FCC § 22.917(a) & 24.238(a)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10\log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(a) (4)

For mobile and portable stations operating in the 2305-2315MHz and 2350-2360MHz bands:

(1) By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320MHz and on all frequencies between 2345 and 2360MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324MHz and on all frequencies between 2341 and 2345MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328MHz and on all frequencies between 2337 and 2341MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337MHz.

(2) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292MHz, and $70 + 10 \log (P)$ dB below 2288MHz.

(3) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365MHz, and not less than $70 + 10 \log (P)$ dB above 2365MHz.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the

band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the

band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of

measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth

of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(f)

For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to - 70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43+10*\log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1)

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

FCC § 27.53(l) (2)

For mobile operations in the 3700-3980 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

FCC § 27.53(m) (4)

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40+10\log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43+10\log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,
- $55+10\log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service

licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

FCC § 27.53(n) (2)

For mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

FCC § 90.691

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{Log}_{10}(f/6.1)$ decibels or $50 + 10 \text{Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\text{Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

RSS-Gen § 6.13 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-195 § 5.6

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This is calculated to be -13 dBm.

RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

RSS-195 § 5.6

The power of any emission outside the frequency range(s) in which the equipment operates shall be attenuated below the transmitter power, P (dBW), by the amount indicated in table below and graphically represented in figure below, where p is the transmitter output power measured in watts.

Frequency (MHz)	Attenuation (dB)	Frequency (MHz)	Attenuation (dB)
<2200	$43+10 \log_{10} (p)$	2324-2328	$61+10 \log_{10} (p)$
2200-2288	$70+10 \log_{10} (p)$	2328-2337	$67+10 \log_{10} (p)$
2288-2292	$67+10 \log_{10} (p)$	2337-2341	$61+10 \log_{10} (p)$
2292-2296	$61+10 \log_{10} (p)$	2341-2345	$55+10 \log_{10} (p)$
2296-2300	$55+10 \log_{10} (p)$	2345-2360	$43+10 \log_{10} (p)$ ^{Note}
2300-2305	$43+10 \log_{10} (p)$	2360-2365	$43+10 \log_{10} (p)$
2305-2320	$43+10 \log_{10} (p)$ ^{Note}	2365-2395	$70+10 \log_{10} (p)$
2320-2324	$55+10 \log_{10} (p)$	> 2395	$43+10 \log_{10} (p)$

Note: Measured at the edges of the highest and lowest frequency range(s) in which the equipment is designed to operate. See section 5.2 for the permitted frequency ranges for various equipment types.

5.7.2 Test Setup

The section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

1. On a test site, the EUT shall be placed at 80cm height on a turn table, and in the position close to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3 m from EUT to correspond to the fundamental frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the peak detector is used for the measurement.
4. During the measurement of the EUT, the resolution bandwidth was to 1 MHz and the average bandwidth was set to 1 MHz.
5. The transmitter shall be switched on; the measuring receiver shall be tuned to the frequency of the transmitter under test.

6. The test antenna shall be raised and lowered through the specified range of height until the maximum signal level is detected by the measuring receiver.
7. The transmitter shall be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
8. The test antenna shall be raised and lowered again through the specified range of height until the maximum signal level is detected by the measuring receiver.
9. The maximum signal level detected by the measuring receiver shall be noted.
10. The EUT was replaced by half-wave dipole (824 ~ 849 MHz) or horn antenna (1 850 ~ 1 910 MHz) connected to a signal generator.
11. In necessary, the input attenuator setting on the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
12. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
13. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring received, which is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
14. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
15. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.

Final measurement calculation as below:

The relevant equation for determining the ERP/EIRP from the radiated RF output power is:

$$\text{ERP/EIRP (dBm)} = \text{SA Read Value (dBm)} + \text{Correction Factor (dB)}$$

where:

ERP/EIRP = effective or equivalent radiated power, in dBm;

SA Read Value = measured transmitter power received by EMI receiver or spectrum analyzer, in dBm;

Correction Factor = total correction factor including cable loss, in dB;

During the test, the data of Correction Factor (dB) is added in the EMI receiver or spectrum analyzer, so SA Read Value (dBm) is the final values which contains the data of Correction Factor (dB).

For example:

In the ERP test, when SA read value for GSM850 is 21dBm, and correction factor is 8dB, then final ERP value for GSM850 is:

$$\text{ERP (dBm)} = 21\text{dBm} + 8\text{dB} = 29\text{dBm}$$

5.7.4 Test Result

Please refer to ANNEX A.7.

5.8 Receiver Spurious Emissions

5.8.1 Limit

RSS-Gen § 7.3/4 & RSS-132 § 5.6 & RSS-133 § 6.6

For emissions at frequencies below 1 GHz, measurements shall be performed using a CISPR quasi-peak detector and the related measurement bandwidth. At frequencies above 1 GHz, measurements shall be performed using a linear average detector with a minimum resolution bandwidth of 1 MHz.

As an alternative to CISPR quasi-peak or average measurements, compliance with the emission limit can be demonstrated using measuring equipment employing a peak detector function properly adjusted for factors such as pulse desensitization, as required, with a measurement bandwidth equal to, or greater than, the applicable CISPR quasi-peak bandwidth or 1 MHz bandwidth, respectively.

Receiver Radiated Limits

Radiated emission measurements shall be performed with the receiver antenna connected to the receiver antenna ports. The search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is higher, to at least five times the highest tunable or local oscillator frequency, whichever is higher, without exceeding 40 GHz.

Spurious emissions from receivers shall not exceed the radiated emissions limits shown in Table 2 below.

Table 2 –Receiver radiated emissions limits

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at 3 metres)
30 - 88	100
88 - 216	150
216 - 960	200
Above 960	500

Receiver Conducted Limits

If the receiver has a detachable antenna of known impedance, an antenna-conducted spurious emissions measurement is permitted as an alternative to radiated measurement. However, the radiated method is preferred.

The antenna-conducted test shall be performed with the antenna disconnected and with the receiver antenna port connected to a measuring instrument having equal input impedance to that specified for the antenna. The RF cable connecting the receiver under test to the measuring instrument shall also have the same impedance to that specified for the receiver's antenna.

The spurious emissions from the receiver at any discrete frequency, measured at the antenna port by the antenna-conducted method, shall not exceed 2 nW in the frequency range 30-1000 MHz and 5 nW above 1 GHz.

5.8.2 Test Setup

The section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

5.8.4 Test Result

Please refer to ANNEX A.8.

5.9 AC Power-line Conducted Emissions

5.9.1 Limit

RSS-Gen § 8.8

For AC power-line conducted emissions, both quasi-peak and average detectors having the characteristics specified in CAN/CSA-CISPR 16-1-1:15 for the 150 kHz to 30 MHz frequency range shall be employed.

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 3, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 3 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 3 –AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ^{Note1}	56 to 46 ^{Note1}
0.5 - 5	56	46
5 - 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

5.9.2 Test Setup

The section 4.4.5 (Diagram 5) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULTS

A.1 Transmitter Radiated Power (EIRP/ERP)

LTE Mode Test Data

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
1.4 MHz	LCH	QPSK	RB1#0	20.68	2	22.68	0.185	2.00	Pass
			RB1#3	20.39	2	22.39	0.173	2.00	Pass
			RB1#5	20.46	2	22.46	0.176	2.00	Pass
			RB3#0	20.76	2	22.76	0.189	2.00	Pass
			RB3#2	20.37	2	22.37	0.173	2.00	Pass
			RB3#3	20.37	2	22.37	0.173	2.00	Pass
		16-QAM	RB6#0	19.45	2	21.45	0.140	2.00	Pass
			RB1#0	19.87	2	21.87	0.154	2.00	Pass
			RB1#3	19.6	2	21.60	0.145	2.00	Pass
			RB1#5	19.65	2	21.65	0.146	2.00	Pass
			RB3#0	19.76	2	21.76	0.150	2.00	Pass
			RB3#2	19.45	2	21.45	0.140	2.00	Pass
	MCH	QPSK	RB3#3	19.51	2	21.51	0.142	2.00	Pass
			RB6#0	18.67	2	20.67	0.117	2.00	Pass
			RB1#0	19.23	2	21.23	0.133	2.00	Pass
			RB1#3	18.99	2	20.99	0.126	2.00	Pass
			RB1#5	19.34	2	21.34	0.136	2.00	Pass
			RB3#0	19	2	21.00	0.126	2.00	Pass
		16-QAM	RB3#2	18.91	2	20.91	0.123	2.00	Pass
			RB3#3	19.13	2	21.13	0.130	2.00	Pass
			RB6#0	18.13	2	20.13	0.103	2.00	Pass
			RB1#0	18.6	2	20.60	0.115	2.00	Pass
			RB1#3	18.4	2	20.40	0.110	2.00	Pass
			RB1#5	18.72	2	20.72	0.118	2.00	Pass
	HCH	QPSK	RB3#0	18.23	2	20.23	0.105	2.00	Pass
			RB3#2	18.17	2	20.17	0.104	2.00	Pass
			RB3#3	18.39	2	20.39	0.109	2.00	Pass
			RB6#0	17.13	2	19.13	0.082	2.00	Pass
			RB1#0	19.48	2	21.48	0.141	2.00	Pass
				RB1#3	19.33	2	21.33	0.136	2.00
			RB1#5	19.56	2	21.56	0.143	2.00	Pass
			RB3#0	19.35	2	21.35	0.136	2.00	Pass
			RB3#2	19.46	2	21.46	0.140	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict		
LTE BAND2											
		16-QAM	RB3#3	19.68	2	21.68	0.147	2.00	Pass		
			RB6#0	18.34	2	20.34	0.108	2.00	Pass		
			RB1#0	18.44	2	20.44	0.111	2.00	Pass		
			RB1#3	18.31	2	20.31	0.107	2.00	Pass		
			RB1#5	18.57	2	20.57	0.114	2.00	Pass		
			RB3#0	18.46	2	20.46	0.111	2.00	Pass		
			RB3#2	18.47	2	20.47	0.111	2.00	Pass		
			RB3#3	18.68	2	20.68	0.117	2.00	Pass		
		RB6#0	17.53	2	19.53	0.090	2.00	Pass			
		3 MHz	LCH	QPSK	RB1#0	20.65	2	22.65	0.184	2.00	Pass
					RB1#7	20.05	2	22.05	0.160	2.00	Pass
					RB1#14	19.78	2	21.78	0.151	2.00	Pass
					RB8#0	19.14	2	21.14	0.130	2.00	Pass
					RB8#4	19.14	2	21.14	0.130	2.00	Pass
					RB8#7	18.96	2	20.96	0.125	2.00	Pass
					RB15#0	19.1	2	21.10	0.129	2.00	Pass
16-QAM	RB1#0			19.67	2	21.67	0.147	2.00	Pass		
	RB1#7			18.95	2	20.95	0.124	2.00	Pass		
	RB1#14			18.69	2	20.69	0.117	2.00	Pass		
	RB8#0			18.21	2	20.21	0.105	2.00	Pass		
	RB8#4			18.23	2	20.23	0.105	2.00	Pass		
	RB8#7			18.04	2	20.04	0.101	2.00	Pass		
	RB15#0			18.13	2	20.13	0.103	2.00	Pass		
MCH	QPSK			RB1#0	19.35	2	21.35	0.136	2.00	Pass	
				RB1#7	19.02	2	21.02	0.126	2.00	Pass	
		RB1#14	19.3	2	21.30	0.135	2.00	Pass			
		RB8#0	17.76	2	19.76	0.095	2.00	Pass			
		RB8#4	18.14	2	20.14	0.103	2.00	Pass			
		RB8#7	18.15	2	20.15	0.104	2.00	Pass			
		RB15#0	18.09	2	20.09	0.102	2.00	Pass			
	16-QAM	RB1#0	18.66	2	20.66	0.116	2.00	Pass			
		RB1#7	18.3	2	20.30	0.107	2.00	Pass			
		RB1#14	18.59	2	20.59	0.115	2.00	Pass			
		RB8#0	16.84	2	18.84	0.077	2.00	Pass			
		RB8#4	17.2	2	19.20	0.083	2.00	Pass			
		RB8#7	17.2	2	19.20	0.083	2.00	Pass			
		RB15#0	17.07	2	19.07	0.081	2.00	Pass			
HCH	QPSK	RB1#0	19.08	2	21.08	0.128	2.00	Pass			

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
			RB1#7	19.06	2	21.06	0.128	2.00	Pass
			RB1#14	19.49	2	21.49	0.141	2.00	Pass
			RB8#0	17.7	2	19.70	0.093	2.00	Pass
			RB8#4	18.1	2	20.10	0.102	2.00	Pass
			RB8#7	18.27	2	20.27	0.106	2.00	Pass
			RB15#0	18.15	2	20.15	0.104	2.00	Pass
		16-QAM	RB1#0	18.18	2	20.18	0.104	2.00	Pass
			RB1#7	18.18	2	20.18	0.104	2.00	Pass
			RB1#14	18.58	2	20.58	0.114	2.00	Pass
			RB8#0	16.83	2	18.83	0.076	2.00	Pass
			RB8#4	17.24	2	19.24	0.084	2.00	Pass
			RB8#7	17.27	2	19.27	0.085	2.00	Pass
			RB15#0	17.11	2	19.11	0.081	2.00	Pass
			5 MHz	LCH	QPSK	RB1#0	20.44	2	22.44
RB1#13	19.7	2				21.70	0.148	2.00	Pass
RB1#24	18.81	2				20.81	0.121	2.00	Pass
RB12#0	18.96	2				20.96	0.125	2.00	Pass
RB12#6	18.65	2				20.65	0.116	2.00	Pass
RB12#13	18.22	2				20.22	0.105	2.00	Pass
RB25#0	18.74	2				20.74	0.119	2.00	Pass
16-QAM	RB1#0	19.71			2	21.71	0.148	2.00	Pass
	RB1#13	18.84			2	20.84	0.121	2.00	Pass
	RB1#24	18			2	20.00	0.100	2.00	Pass
	RB12#0	18.08			2	20.08	0.102	2.00	Pass
	RB12#6	17.75			2	19.75	0.094	2.00	Pass
	RB12#13	17.32			2	19.32	0.086	2.00	Pass
	RB25#0	17.79			2	19.79	0.095	2.00	Pass
MCH	QPSK	RB1#0	18.98	2	20.98	0.125	2.00	Pass	
		RB1#13	18.97	2	20.97	0.125	2.00	Pass	
		RB1#24	18.96	2	20.96	0.125	2.00	Pass	
		RB12#0	17.85	2	19.85	0.097	2.00	Pass	
		RB12#6	18.08	2	20.08	0.102	2.00	Pass	
		RB12#13	17.98	2	19.98	0.100	2.00	Pass	
		RB25#0	18.08	2	20.08	0.102	2.00	Pass	
	16-QAM	RB1#0	18.5	2	20.50	0.112	2.00	Pass	
		RB1#13	18.52	2	20.52	0.113	2.00	Pass	
		RB1#24	18.52	2	20.52	0.113	2.00	Pass	
		RB12#0	16.93	2	18.93	0.078	2.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
10 MHz	HCH	QPSK	RB12#6	17.19	2	19.19	0.083	2.00	Pass
			RB12#13	17.1	2	19.10	0.081	2.00	Pass
			RB25#0	17.1	2	19.10	0.081	2.00	Pass
		QPSK	RB1#0	18.66	2	20.66	0.116	2.00	Pass
			RB1#13	18.99	2	20.99	0.126	2.00	Pass
			RB1#24	19.49	2	21.49	0.141	2.00	Pass
			RB12#0	17.61	2	19.61	0.091	2.00	Pass
			RB12#6	17.87	2	19.87	0.097	2.00	Pass
			RB12#13	18.08	2	20.08	0.102	2.00	Pass
		16-QAM	RB25#0	18.05	2	20.05	0.101	2.00	Pass
			RB1#0	17.88	2	19.88	0.097	2.00	Pass
			RB1#13	18.16	2	20.16	0.104	2.00	Pass
			RB1#24	18.55	2	20.55	0.114	2.00	Pass
			RB12#0	16.67	2	18.67	0.074	2.00	Pass
			RB12#6	17.06	2	19.06	0.081	2.00	Pass
	LCH	QPSK	RB12#13	17.27	2	19.27	0.085	2.00	Pass
			RB25#0	17.11	2	19.11	0.081	2.00	Pass
			RB1#0	20.21	2	22.21	0.166	2.00	Pass
			RB1#25	18.12	2	20.12	0.103	2.00	Pass
			RB1#49	17.94	2	19.94	0.099	2.00	Pass
			RB25#0	18.34	2	20.34	0.108	2.00	Pass
RB25#13			17.47	2	19.47	0.089	2.00	Pass	
16-QAM		RB25#25	17.1	2	19.10	0.081	2.00	Pass	
		RB50#0	17.75	2	19.75	0.094	2.00	Pass	
		RB1#0	19.18	2	21.18	0.131	2.00	Pass	
		RB1#25	17.23	2	19.23	0.084	2.00	Pass	
		RB1#49	16.86	2	18.86	0.077	2.00	Pass	
		RB25#0	17.32	2	19.32	0.086	2.00	Pass	
		RB25#13	16.62	2	18.62	0.073	2.00	Pass	
		RB25#25	16.11	2	18.11	0.065	2.00	Pass	
MCH	QPSK	RB50#0	16.76	2	18.76	0.075	2.00	Pass	
		RB1#0	18.62	2	20.62	0.115	2.00	Pass	
		RB1#25	18.55	2	20.55	0.114	2.00	Pass	
		RB1#49	19.08	2	21.08	0.128	2.00	Pass	
		RB25#0	17.71	2	19.71	0.094	2.00	Pass	
		RB25#13	17.6	2	19.60	0.091	2.00	Pass	
		RB25#25	17.83	2	19.83	0.096	2.00	Pass	
RB50#0	17.81	2	19.81	0.096	2.00	Pass			

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
15 MHz	HCH	16-QAM	RB1#0	18.07	2	20.07	0.102	2.00	Pass
			RB1#25	17.98	2	19.98	0.100	2.00	Pass
			RB1#49	18.41	2	20.41	0.110	2.00	Pass
			RB25#0	16.82	2	18.82	0.076	2.00	Pass
			RB25#13	16.61	2	18.61	0.073	2.00	Pass
			RB25#25	16.84	2	18.84	0.077	2.00	Pass
			RB50#0	16.82	2	18.82	0.076	2.00	Pass
		QPSK	RB1#0	17.97	2	19.97	0.099	2.00	Pass
			RB1#25	18.25	2	20.25	0.106	2.00	Pass
			RB1#49	19.34	2	21.34	0.136	2.00	Pass
			RB25#0	17.06	2	19.06	0.081	2.00	Pass
			RB25#13	17.14	2	19.14	0.082	2.00	Pass
			RB25#25	17.69	2	19.69	0.093	2.00	Pass
			RB50#0	17.37	2	19.37	0.086	2.00	Pass
	16-QAM	RB1#0	17.07	2	19.07	0.081	2.00	Pass	
		RB1#25	17.34	2	19.34	0.086	2.00	Pass	
		RB1#49	18.28	2	20.28	0.107	2.00	Pass	
		RB25#0	16.26	2	18.26	0.067	2.00	Pass	
		RB25#13	16.33	2	18.33	0.068	2.00	Pass	
		RB25#25	16.77	2	18.77	0.075	2.00	Pass	
		RB50#0	16.51	2	18.51	0.071	2.00	Pass	
	LCH	QPSK	RB1#0	20.22	2	22.22	0.167	2.00	Pass
			RB1#38	18.23	2	20.23	0.105	2.00	Pass
			RB1#74	17.98	2	19.98	0.100	2.00	Pass
			RB36#0	18.04	2	20.04	0.101	2.00	Pass
			RB36#19	17.28	2	19.28	0.085	2.00	Pass
			RB36#39	16.82	2	18.82	0.076	2.00	Pass
			RB75#0	17.46	2	19.46	0.088	2.00	Pass
16-QAM		RB1#0	19.14	2	21.14	0.130	2.00	Pass	
		RB1#38	17.18	2	19.18	0.083	2.00	Pass	
		RB1#74	16.99	2	18.99	0.079	2.00	Pass	
		RB36#0	17.09	2	19.09	0.081	2.00	Pass	
		RB36#19	16.27	2	18.27	0.067	2.00	Pass	
		RB36#39	15.91	2	17.91	0.062	2.00	Pass	
		RB75#0	16.57	2	18.57	0.072	2.00	Pass	
MCH	QPSK	RB1#0	18.55	2	20.55	0.114	2.00	Pass	
		RB1#38	19	2	21.00	0.126	2.00	Pass	
		RB1#74	19.18	2	21.18	0.131	2.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict	
LTE BAND2										
			RB36#0	17.76	2	19.76	0.095	2.00	Pass	
			RB36#19	18.03	2	20.03	0.101	2.00	Pass	
			RB36#39	18.17	2	20.17	0.104	2.00	Pass	
			RB75#0	18.02	2	20.02	0.100	2.00	Pass	
		16-QAM	RB1#0	18.11	2	20.11	0.103	2.00	Pass	
			RB1#38	18.39	2	20.39	0.109	2.00	Pass	
			RB1#74	18.62	2	20.62	0.115	2.00	Pass	
			RB36#0	16.75	2	18.75	0.075	2.00	Pass	
			RB36#19	17.05	2	19.05	0.080	2.00	Pass	
			RB36#39	17.18	2	19.18	0.083	2.00	Pass	
		RB75#0	17	2	19.00	0.079	2.00	Pass		
		HCH	QPSK	RB1#0	18.1	2	20.10	0.102	2.00	Pass
				RB1#38	18.4	2	20.40	0.110	2.00	Pass
				RB1#74	19.26	2	21.26	0.134	2.00	Pass
	RB36#0			16.82	2	18.82	0.076	2.00	Pass	
	RB36#19			17.37	2	19.37	0.086	2.00	Pass	
	RB36#39			17.73	2	19.73	0.094	2.00	Pass	
	RB75#0		17.42	2	19.42	0.087	2.00	Pass		
	16-QAM		RB1#0	17.66	2	19.66	0.092	2.00	Pass	
			RB1#38	17.94	2	19.94	0.099	2.00	Pass	
			RB1#74	18.81	2	20.81	0.121	2.00	Pass	
			RB36#0	15.92	2	17.92	0.062	2.00	Pass	
			RB36#19	16.33	2	18.33	0.068	2.00	Pass	
			RB36#39	16.69	2	18.69	0.074	2.00	Pass	
			RB75#0	16.39	2	18.39	0.069	2.00	Pass	
		20 MHz	LCH	QPSK	RB1#0	20.19	2	22.19	0.166	2.00
	RB1#50				17.99	2	19.99	0.100	2.00	Pass
	RB1#99				18.39	2	20.39	0.109	2.00	Pass
RB50#0	17.97				2	19.97	0.099	2.00	Pass	
RB50#25	17.09				2	19.09	0.081	2.00	Pass	
RB50#50	17.06				2	19.06	0.081	2.00	Pass	
RB100#0	17.47				2	19.47	0.089	2.00	Pass	
16-QAM	RB1#0			19.69	2	21.69	0.148	2.00	Pass	
	RB1#50			17.52	2	19.52	0.090	2.00	Pass	
	RB1#99			17.94	2	19.94	0.099	2.00	Pass	
	RB50#0			16.93	2	18.93	0.078	2.00	Pass	
	RB50#25			16.18	2	18.18	0.066	2.00	Pass	
	RB50#50			16.14	2	18.14	0.065	2.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
	MCH	QPSK	RB100#0	16.6	2	18.60	0.072	2.00	Pass
			RB1#0	18.55	2	20.55	0.114	2.00	Pass
			RB1#50	19.13	2	21.13	0.130	2.00	Pass
			RB1#99	19.4	2	21.40	0.138	2.00	Pass
			RB50#0	17.95	2	19.95	0.099	2.00	Pass
			RB50#25	18.15	2	20.15	0.104	2.00	Pass
			RB50#50	18.36	2	20.36	0.109	2.00	Pass
		RB100#0	18.18	2	20.18	0.104	2.00	Pass	
		16-QAM	RB1#0	18.23	2	20.23	0.105	2.00	Pass
			RB1#50	18.68	2	20.68	0.117	2.00	Pass
			RB1#99	18.89	2	20.89	0.123	2.00	Pass
			RB50#0	17	2	19.00	0.079	2.00	Pass
			RB50#25	17.24	2	19.24	0.084	2.00	Pass
			RB50#50	17.35	2	19.35	0.086	2.00	Pass
	RB100#0		17.27	2	19.27	0.085	2.00	Pass	
	HCH	QPSK	RB1#0	19.12	2	21.12	0.129	2.00	Pass
			RB1#50	17.98	2	19.98	0.100	2.00	Pass
			RB1#99	19.39	2	21.39	0.138	2.00	Pass
			RB50#0	17.42	2	19.42	0.087	2.00	Pass
			RB50#25	17.21	2	19.21	0.083	2.00	Pass
			RB50#50	17.74	2	19.74	0.094	2.00	Pass
			RB100#0	17.56	2	19.56	0.090	2.00	Pass
		16-QAM	RB1#0	18.52	2	20.52	0.113	2.00	Pass
			RB1#50	17.51	2	19.51	0.089	2.00	Pass
			RB1#99	18.86	2	20.86	0.122	2.00	Pass
			RB50#0	16.44	2	18.44	0.070	2.00	Pass
			RB50#25	16.21	2	18.21	0.066	2.00	Pass
			RB50#50	16.83	2	18.83	0.076	2.00	Pass
RB100#0			16.59	2	18.59	0.072	2.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
1.4 MHz	LCH	QPSK	RB1#0	19.69	2	21.69	0.148	1.00	Pass
			RB1#3	19.54	2	21.54	0.143	1.00	Pass
			RB1#5	19.61	2	21.61	0.145	1.00	Pass
			RB3#0	19.66	2	21.66	0.147	1.00	Pass
			RB3#2	19.51	2	21.51	0.142	1.00	Pass
			RB3#3	19.57	2	21.57	0.144	1.00	Pass
			RB6#0	18.58	2	20.58	0.114	1.00	Pass
		16-QAM	RB1#0	18.85	2	20.85	0.122	1.00	Pass
			RB1#3	18.75	2	20.75	0.119	1.00	Pass
			RB1#5	18.77	2	20.77	0.119	1.00	Pass
			RB3#0	18.78	2	20.78	0.120	1.00	Pass
			RB3#2	18.6	2	20.60	0.115	1.00	Pass
			RB3#3	18.6	2	20.60	0.115	1.00	Pass
			RB6#0	17.71	2	19.71	0.094	1.00	Pass
	MCH	QPSK	RB1#0	18.21	2	20.21	0.105	1.00	Pass
			RB1#3	18.13	2	20.13	0.103	1.00	Pass
			RB1#5	18.35	2	20.35	0.108	1.00	Pass
			RB3#0	18.2	2	20.20	0.105	1.00	Pass
			RB3#2	18.02	2	20.02	0.100	1.00	Pass
			RB3#3	18.14	2	20.14	0.103	1.00	Pass
			RB6#0	17.08	2	19.08	0.081	1.00	Pass
		16-QAM	RB1#0	17.74	2	19.74	0.094	1.00	Pass
			RB1#3	17.36	2	19.36	0.086	1.00	Pass
			RB1#5	17.79	2	19.79	0.095	1.00	Pass
			RB3#0	17.32	2	19.32	0.086	1.00	Pass
			RB3#2	17.16	2	19.16	0.082	1.00	Pass
			RB3#3	17.29	2	19.29	0.085	1.00	Pass
			RB6#0	16.01	2	18.01	0.063	1.00	Pass
	HCH	QPSK	RB1#0	18.66	2	20.66	0.116	1.00	Pass
			RB1#3	18.48	2	20.48	0.112	1.00	Pass
RB1#5			18.66	2	20.66	0.116	1.00	Pass	
RB3#0			18.74	2	20.74	0.119	1.00	Pass	
RB3#2			18.58	2	20.58	0.114	1.00	Pass	
RB3#3			18.61	2	20.61	0.115	1.00	Pass	
RB6#0			17.48	2	19.48	0.089	1.00	Pass	
16-QAM		RB1#0	17.73	2	19.73	0.094	1.00	Pass	
		RB1#3	17.45	2	19.45	0.088	1.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
3 MHz			RB1#5	17.55	2	19.55	0.090	1.00	Pass
			RB3#0	17.85	2	19.85	0.097	1.00	Pass
			RB3#2	17.61	2	19.61	0.091	1.00	Pass
			RB3#3	17.62	2	19.62	0.092	1.00	Pass
			RB6#0	16.77	2	18.77	0.075	1.00	Pass
	LCH	QPSK	RB1#0	19.68	2	21.68	0.147	1.00	Pass
			RB1#7	19.13	2	21.13	0.130	1.00	Pass
			RB1#14	19.01	2	21.01	0.126	1.00	Pass
			RB8#0	18.31	2	20.31	0.107	1.00	Pass
			RB8#4	18.19	2	20.19	0.104	1.00	Pass
			RB8#7	18	2	20.00	0.100	1.00	Pass
			RB15#0	18.14	2	20.14	0.103	1.00	Pass
		16-QAM	RB1#0	18.8	2	20.80	0.120	1.00	Pass
			RB1#7	18.04	2	20.04	0.101	1.00	Pass
			RB1#14	17.91	2	19.91	0.098	1.00	Pass
			RB8#0	17.35	2	19.35	0.086	1.00	Pass
			RB8#4	17.38	2	19.38	0.087	1.00	Pass
			RB8#7	17.25	2	19.25	0.084	1.00	Pass
	MCH	QPSK	RB1#0	18.3	2	20.30	0.107	1.00	Pass
			RB1#7	17.91	2	19.91	0.098	1.00	Pass
			RB1#14	18.3	2	20.30	0.107	1.00	Pass
			RB8#0	16.73	2	18.73	0.075	1.00	Pass
			RB8#4	17.1	2	19.10	0.081	1.00	Pass
			RB8#7	17.16	2	19.16	0.082	1.00	Pass
			RB15#0	17.08	2	19.08	0.081	1.00	Pass
		16-QAM	RB1#0	17.58	2	19.58	0.091	1.00	Pass
			RB1#7	17.36	2	19.36	0.086	1.00	Pass
			RB1#14	17.62	2	19.62	0.092	1.00	Pass
RB8#0			15.85	2	17.85	0.061	1.00	Pass	
RB8#4			16.22	2	18.22	0.066	1.00	Pass	
RB8#7	16.27		2	18.27	0.067	1.00	Pass		
HCH	QPSK	RB1#0	18.64	2	20.64	0.116	1.00	Pass	
		RB1#7	18.47	2	20.47	0.111	1.00	Pass	
		RB1#14	18.63	2	20.63	0.116	1.00	Pass	
		RB8#0	17.35	2	19.35	0.086	1.00	Pass	
		RB8#4	17.51	2	19.51	0.089	1.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict		
LTE BAND4											
		16-QAM	RB8#7	17.41	2	19.41	0.087	1.00	Pass		
			RB15#0	17.46	2	19.46	0.088	1.00	Pass		
			RB1#0	17.6	2	19.60	0.091	1.00	Pass		
			RB1#7	17.55	2	19.55	0.090	1.00	Pass		
			RB1#14	17.62	2	19.62	0.092	1.00	Pass		
			RB8#0	16.4	2	18.40	0.069	1.00	Pass		
			RB8#4	16.61	2	18.61	0.073	1.00	Pass		
			RB8#7	16.47	2	18.47	0.070	1.00	Pass		
					RB15#0	16.5	2	18.50	0.071	1.00	Pass
		5 MHz	LCH	QPSK	RB1#0	19.63	2	21.63	0.146	1.00	Pass
					RB1#13	18.84	2	20.84	0.121	1.00	Pass
					RB1#24	18.68	2	20.68	0.117	1.00	Pass
					RB12#0	18.12	2	20.12	0.103	1.00	Pass
					RB12#6	17.97	2	19.97	0.099	1.00	Pass
					RB12#13	17.58	2	19.58	0.091	1.00	Pass
					RB25#0	18.07	2	20.07	0.102	1.00	Pass
				16-QAM	RB1#0	18.96	2	20.96	0.125	1.00	Pass
					RB1#13	18.05	2	20.05	0.101	1.00	Pass
					RB1#24	17.87	2	19.87	0.097	1.00	Pass
					RB12#0	17.22	2	19.22	0.084	1.00	Pass
					RB12#6	17.05	2	19.05	0.080	1.00	Pass
			RB12#13		16.67	2	18.67	0.074	1.00	Pass	
				RB25#0	17.11	2	19.11	0.081	1.00	Pass	
	MCH		QPSK	RB1#0	17.93	2	19.93	0.098	1.00	Pass	
					RB1#13	18.11	2	20.11	0.103	1.00	Pass
					RB1#24	18.44	2	20.44	0.111	1.00	Pass
					RB12#0	16.8	2	18.80	0.076	1.00	Pass
					RB12#6	16.97	2	18.97	0.079	1.00	Pass
					RB12#13	16.98	2	18.98	0.079	1.00	Pass
					RB25#0	17.11	2	19.11	0.081	1.00	Pass
				16-QAM	RB1#0	17.46	2	19.46	0.088	1.00	Pass
					RB1#13	17.51	2	19.51	0.089	1.00	Pass
					RB1#24	17.72	2	19.72	0.094	1.00	Pass
			RB12#0		15.95	2	17.95	0.062	1.00	Pass	
			RB12#6		16.15	2	18.15	0.065	1.00	Pass	
		RB12#13	16.14		2	18.14	0.065	1.00	Pass		
			RB25#0	16.19	2	18.19	0.066	1.00	Pass		
	HCH	QPSK	RB1#0	18.93	2	20.93	0.124	1.00	Pass		

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
			RB1#13	18.4	2	20.40	0.110	1.00	Pass
			RB1#24	18.37	2	20.37	0.109	1.00	Pass
			RB12#0	17.35	2	19.35	0.086	1.00	Pass
			RB12#6	17.43	2	19.43	0.088	1.00	Pass
			RB12#13	17.47	2	19.47	0.089	1.00	Pass
			RB25#0	17.57	2	19.57	0.091	1.00	Pass
		16-QAM	RB1#0	18.02	2	20.02	0.100	1.00	Pass
			RB1#13	17.59	2	19.59	0.091	1.00	Pass
			RB1#24	17.65	2	19.65	0.092	1.00	Pass
			RB12#0	16.56	2	18.56	0.072	1.00	Pass
			RB12#6	16.54	2	18.54	0.071	1.00	Pass
			RB12#13	16.56	2	18.56	0.072	1.00	Pass
			RB25#0	16.56	2	18.56	0.072	1.00	Pass
			10 MHz	LCH	QPSK	RB1#0	19.33	2	21.33
RB1#25	18.14	2				20.14	0.103	1.00	Pass
RB1#49	17.9	2				19.90	0.098	1.00	Pass
RB25#0	17.63	2				19.63	0.092	1.00	Pass
RB25#13	17.19	2				19.19	0.083	1.00	Pass
RB25#25	16.98	2				18.98	0.079	1.00	Pass
16-QAM	RB50#0	17.38			2	19.38	0.087	1.00	Pass
	RB1#0	18.37			2	20.37	0.109	1.00	Pass
	RB1#25	17.14			2	19.14	0.082	1.00	Pass
	RB1#49	16.89			2	18.89	0.077	1.00	Pass
	RB25#0	16.66			2	18.66	0.073	1.00	Pass
	RB25#13	16.35			2	18.35	0.068	1.00	Pass
	RB25#25	16.13			2	18.13	0.065	1.00	Pass
	RB50#0	16.43			2	18.43	0.070	1.00	Pass
10 MHz	MCH	QPSK	RB1#0	17.53	2	19.53	0.090	1.00	Pass
			RB1#25	17.68	2	19.68	0.093	1.00	Pass
			RB1#49	18.21	2	20.21	0.105	1.00	Pass
			RB25#0	16.67	2	18.67	0.074	1.00	Pass
			RB25#13	16.74	2	18.74	0.075	1.00	Pass
			RB25#25	16.97	2	18.97	0.079	1.00	Pass
		16-QAM	RB50#0	16.76	2	18.76	0.075	1.00	Pass
			RB1#0	16.99	2	18.99	0.079	1.00	Pass
			RB1#25	17.17	2	19.17	0.083	1.00	Pass
			RB1#49	17.51	2	19.51	0.089	1.00	Pass
			RB25#0	15.76	2	17.76	0.060	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict	
LTE BAND4										
15 MHz	HCH	QPSK	RB25#13	15.76	2	17.76	0.060	1.00	Pass	
			RB25#25	16.02	2	18.02	0.063	1.00	Pass	
			RB50#0	15.79	2	17.79	0.060	1.00	Pass	
		16-QAM	QPSK	RB1#0	18.97	2	20.97	0.125	1.00	Pass
				RB1#25	18.46	2	20.46	0.111	1.00	Pass
				RB1#49	18.29	2	20.29	0.107	1.00	Pass
			16-QAM	RB25#0	17.6	2	19.60	0.091	1.00	Pass
				RB25#13	17.39	2	19.39	0.087	1.00	Pass
				RB25#25	17.25	2	19.25	0.084	1.00	Pass
	RB50#0			17.61	2	19.61	0.091	1.00	Pass	
	RB1#0			18.16	2	20.16	0.104	1.00	Pass	
	RB1#25			17.57	2	19.57	0.091	1.00	Pass	
	LCH	QPSK	RB1#49	17.39	2	19.39	0.087	1.00	Pass	
			RB25#0	16.77	2	18.77	0.075	1.00	Pass	
			RB25#13	16.6	2	18.60	0.072	1.00	Pass	
			RB25#25	16.36	2	18.36	0.069	1.00	Pass	
			RB50#0	16.67	2	18.67	0.074	1.00	Pass	
			RB1#0	19.37	2	21.37	0.137	1.00	Pass	
		16-QAM	RB1#38	17.98	2	19.98	0.100	1.00	Pass	
			RB1#74	17.68	2	19.68	0.093	1.00	Pass	
			RB36#0	17.36	2	19.36	0.086	1.00	Pass	
RB36#19			17	2	19.00	0.079	1.00	Pass		
RB36#39			16.77	2	18.77	0.075	1.00	Pass		
RB75#0			17.06	2	19.06	0.081	1.00	Pass		
MCH	QPSK	RB1#0	18.52	2	20.52	0.113	1.00	Pass		
		RB1#38	17.09	2	19.09	0.081	1.00	Pass		
		RB1#74	16.69	2	18.69	0.074	1.00	Pass		
		RB36#0	16.47	2	18.47	0.070	1.00	Pass		
		RB36#19	16.11	2	18.11	0.065	1.00	Pass		
		RB36#39	15.8	2	17.80	0.060	1.00	Pass		
		RB75#0	16.19	2	18.19	0.066	1.00	Pass		
QPSK	RB1#0	17.77	2	19.77	0.095	1.00	Pass			
	RB1#38	18.2	2	20.20	0.105	1.00	Pass			
	RB1#74	18.44	2	20.44	0.111	1.00	Pass			
	RB36#0	16.66	2	18.66	0.073	1.00	Pass			
	RB36#19	17	2	19.00	0.079	1.00	Pass			
	RB36#39	17.04	2	19.04	0.080	1.00	Pass			
	RB75#0	17.03	2	19.03	0.080	1.00	Pass			

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
20 MHz	HCH	16-QAM	RB1#0	17.2	2	19.20	0.083	1.00	Pass
			RB1#38	17.46	2	19.46	0.088	1.00	Pass
			RB1#74	17.68	2	19.68	0.093	1.00	Pass
			RB36#0	15.83	2	17.83	0.061	1.00	Pass
			RB36#19	16.17	2	18.17	0.066	1.00	Pass
			RB36#39	16.22	2	18.22	0.066	1.00	Pass
			RB75#0	16.06	2	18.06	0.064	1.00	Pass
		QPSK	RB1#0	18.72	2	20.72	0.118	1.00	Pass
			RB1#38	18.94	2	20.94	0.124	1.00	Pass
			RB1#74	18.56	2	20.56	0.114	1.00	Pass
			RB36#0	17.96	2	19.96	0.099	1.00	Pass
			RB36#19	18.09	2	20.09	0.102	1.00	Pass
			RB36#39	17.77	2	19.77	0.095	1.00	Pass
			RB75#0	17.78	2	19.78	0.095	1.00	Pass
	16-QAM	RB1#0	18.39	2	20.39	0.109	1.00	Pass	
		RB1#38	18.57	2	20.57	0.114	1.00	Pass	
		RB1#74	17.95	2	19.95	0.099	1.00	Pass	
		RB36#0	16.73	2	18.73	0.075	1.00	Pass	
		RB36#19	16.86	2	18.86	0.077	1.00	Pass	
		RB36#39	16.77	2	18.77	0.075	1.00	Pass	
		RB75#0	16.72	2	18.72	0.074	1.00	Pass	
	LCH	QPSK	RB1#0	19.37	2	21.37	0.137	1.00	Pass
			RB1#50	18.08	2	20.08	0.102	1.00	Pass
			RB1#99	17.87	2	19.87	0.097	1.00	Pass
			RB50#0	17.61	2	19.61	0.091	1.00	Pass
			RB50#25	17.05	2	19.05	0.080	1.00	Pass
			RB50#50	16.92	2	18.92	0.078	1.00	Pass
			RB100#0	17.23	2	19.23	0.084	1.00	Pass
16-QAM		RB1#0	18.81	2	20.81	0.121	1.00	Pass	
		RB1#50	17.67	2	19.67	0.093	1.00	Pass	
		RB1#99	17.33	2	19.33	0.086	1.00	Pass	
		RB50#0	16.74	2	18.74	0.075	1.00	Pass	
		RB50#25	16.18	2	18.18	0.066	1.00	Pass	
		RB50#50	15.91	2	17.91	0.062	1.00	Pass	
		RB100#0	16.24	2	18.24	0.067	1.00	Pass	
MCH		QPSK	RB1#0	17.84	2	19.84	0.096	1.00	Pass
			RB1#50	18.16	2	20.16	0.104	1.00	Pass
			RB1#99	18.85	2	20.85	0.122	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict		
LTE BAND4											
			RB50#0	17.03	2	19.03	0.080	1.00	Pass		
			RB50#25	17.08	2	19.08	0.081	1.00	Pass		
			RB50#50	17.41	2	19.41	0.087	1.00	Pass		
			RB100#0	17.1	2	19.10	0.081	1.00	Pass		
		16-QAM	RB1#0	17.44	2	19.44	0.088	1.00	Pass		
			RB1#50	17.72	2	19.72	0.094	1.00	Pass		
			RB1#99	18.43	2	20.43	0.110	1.00	Pass		
			RB50#0	16.03	2	18.03	0.064	1.00	Pass		
			RB50#25	16.08	2	18.08	0.064	1.00	Pass		
			RB50#50	16.42	2	18.42	0.070	1.00	Pass		
			RB100#0	16.11	2	18.11	0.065	1.00	Pass		
			HCH	QPSK	RB1#0	18.28	2	20.28	0.107	1.00	Pass
					RB1#50	19.2	2	21.20	0.132	1.00	Pass
					RB1#99	18.77	2	20.77	0.119	1.00	Pass
	RB50#0	17.86			2	19.86	0.097	1.00	Pass		
	RB50#25	18.06			2	20.06	0.101	1.00	Pass		
	RB50#50	17.89			2	19.89	0.097	1.00	Pass		
	RB100#0	17.72			2	19.72	0.094	1.00	Pass		
	16-QAM	RB1#0	17.77	2	19.77	0.095	1.00	Pass			
		RB1#50	18.58	2	20.58	0.114	1.00	Pass			
		RB1#99	17.99	2	19.99	0.100	1.00	Pass			
		RB50#0	16.62	2	18.62	0.073	1.00	Pass			
		RB50#25	16.96	2	18.96	0.079	1.00	Pass			
		RB50#50	16.88	2	18.88	0.077	1.00	Pass			
		RB100#0	16.8	2	18.80	0.076	1.00	Pass			

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND5										
1.4 MHz	LCH	QPSK	RB1#0	20.07	2	-0.15	19.92	0.098	7.00	Pass
			RB1#3	19.81	2	-0.15	19.66	0.092	7.00	Pass
			RB1#5	20.12	2	-0.15	19.97	0.099	7.00	Pass
			RB3#0	20.02	2	-0.15	19.87	0.097	7.00	Pass
			RB3#2	19.9	2	-0.15	19.75	0.094	7.00	Pass
			RB3#3	20.13	2	-0.15	19.98	0.100	7.00	Pass
			RB6#0	19.1	2	-0.15	18.95	0.079	7.00	Pass
		16-QAM	RB1#0	19.28	2	-0.15	19.13	0.082	7.00	Pass
			RB1#3	19.07	2	-0.15	18.92	0.078	7.00	Pass
			RB1#5	19.35	2	-0.15	19.20	0.083	7.00	Pass
			RB3#0	19.08	2	-0.15	18.93	0.078	7.00	Pass
			RB3#2	18.92	2	-0.15	18.77	0.075	7.00	Pass
			RB3#3	19.1	2	-0.15	18.95	0.079	7.00	Pass
			RB6#0	18.22	2	-0.15	18.07	0.064	7.00	Pass
	MCH	QPSK	RB1#0	20.58	2	-0.15	20.43	0.110	7.00	Pass
			RB1#3	20.36	2	-0.15	20.21	0.105	7.00	Pass
			RB1#5	20.61	2	-0.15	20.46	0.111	7.00	Pass
			RB3#0	20.46	2	-0.15	20.31	0.107	7.00	Pass
			RB3#2	20.33	2	-0.15	20.18	0.104	7.00	Pass
			RB3#3	20.48	2	-0.15	20.33	0.108	7.00	Pass
			RB6#0	19.4	2	-0.15	19.25	0.084	7.00	Pass
		16-QAM	RB1#0	19.82	2	-0.15	19.67	0.093	7.00	Pass
			RB1#3	19.78	2	-0.15	19.63	0.092	7.00	Pass
			RB1#5	19.86	2	-0.15	19.71	0.094	7.00	Pass
			RB3#0	19.59	2	-0.15	19.44	0.088	7.00	Pass
			RB3#2	19.57	2	-0.15	19.42	0.087	7.00	Pass
			RB3#3	19.64	2	-0.15	19.49	0.089	7.00	Pass
			RB6#0	18.36	2	-0.15	18.21	0.066	7.00	Pass
	HCH	QPSK	RB1#0	20.23	2	-0.15	20.08	0.102	7.00	Pass
			RB1#3	20.02	2	-0.15	19.87	0.097	7.00	Pass
			RB1#5	20.02	2	-0.15	19.87	0.097	7.00	Pass
			RB3#0	20.23	2	-0.15	20.08	0.102	7.00	Pass
			RB3#2	20.09	2	-0.15	19.94	0.099	7.00	Pass
			RB3#3	20.12	2	-0.15	19.97	0.099	7.00	Pass
			RB6#0	19.05	2	-0.15	18.90	0.078	7.00	Pass
		16-QAM	RB1#0	19.32	2	-0.15	19.17	0.083	7.00	Pass
RB1#3			19.12	2	-0.15	18.97	0.079	7.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND5										
3 MHz			RB1#5	19.14	2	-0.15	18.99	0.079	7.00	Pass
			RB3#0	19.39	2	-0.15	19.24	0.084	7.00	Pass
			RB3#2	19.29	2	-0.15	19.14	0.082	7.00	Pass
			RB3#3	19.3	2	-0.15	19.15	0.082	7.00	Pass
			RB6#0	18.28	2	-0.15	18.13	0.065	7.00	Pass
	LCH	QPSK	RB1#0	20.1	2	-0.15	19.95	0.099	7.00	Pass
			RB1#7	20.2	2	-0.15	20.05	0.101	7.00	Pass
			RB1#14	20.35	2	-0.15	20.20	0.105	7.00	Pass
			RB8#0	18.83	2	-0.15	18.68	0.074	7.00	Pass
			RB8#4	19.24	2	-0.15	19.09	0.081	7.00	Pass
			RB8#7	19.21	2	-0.15	19.06	0.081	7.00	Pass
		RB15#0	19.23	2	-0.15	19.08	0.081	7.00	Pass	
		16-QAM	RB1#0	19.1	2	-0.15	18.95	0.079	7.00	Pass
			RB1#7	19.24	2	-0.15	19.09	0.081	7.00	Pass
			RB1#14	19.3	2	-0.15	19.15	0.082	7.00	Pass
			RB8#0	17.85	2	-0.15	17.70	0.059	7.00	Pass
			RB8#4	18.35	2	-0.15	18.20	0.066	7.00	Pass
			RB8#7	18.52	2	-0.15	18.37	0.069	7.00	Pass
	MCH	QPSK	RB1#0	20.37	2	-0.15	20.22	0.105	7.00	Pass
			RB1#7	20.32	2	-0.15	20.17	0.104	7.00	Pass
			RB1#14	20.23	2	-0.15	20.08	0.102	7.00	Pass
			RB8#0	19.14	2	-0.15	18.99	0.079	7.00	Pass
			RB8#4	19.56	2	-0.15	19.41	0.087	7.00	Pass
			RB8#7	19.51	2	-0.15	19.36	0.086	7.00	Pass
		RB15#0	19.45	2	-0.15	19.30	0.085	7.00	Pass	
		16-QAM	RB1#0	19.75	2	-0.15	19.60	0.091	7.00	Pass
			RB1#7	19.85	2	-0.15	19.70	0.093	7.00	Pass
			RB1#14	19.77	2	-0.15	19.62	0.092	7.00	Pass
RB8#0			18.25	2	-0.15	18.10	0.065	7.00	Pass	
RB8#4			18.57	2	-0.15	18.42	0.070	7.00	Pass	
RB8#7	18.5		2	-0.15	18.35	0.068	7.00	Pass		
HCH	QPSK	RB15#0	18.4	2	-0.15	18.25	0.067	7.00	Pass	
		RB1#0	20.61	2	-0.15	20.46	0.111	7.00	Pass	
		RB1#7	20.15	2	-0.15	20.00	0.100	7.00	Pass	
		RB1#14	20.05	2	-0.15	19.90	0.098	7.00	Pass	
		RB8#0	19	2	-0.15	18.85	0.077	7.00	Pass	
RB8#4	19.16	2	-0.15	19.01	0.080	7.00	Pass			

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict		
LTE BAND5												
		16-QAM	RB8#7	18.99	2	-0.15	18.84	0.077	7.00	Pass		
			RB15#0	19.24	2	-0.15	19.09	0.081	7.00	Pass		
			RB1#0	19.61	2	-0.15	19.46	0.088	7.00	Pass		
			RB1#7	19.17	2	-0.15	19.02	0.080	7.00	Pass		
			RB1#14	19.08	2	-0.15	18.93	0.078	7.00	Pass		
			RB8#0	18.18	2	-0.15	18.03	0.064	7.00	Pass		
			RB8#4	18.22	2	-0.15	18.07	0.064	7.00	Pass		
			RB8#7	18.03	2	-0.15	17.88	0.061	7.00	Pass		
					RB15#0	18.12	2	-0.15	17.97	0.063	7.00	Pass
		5 MHz	LCH	QPSK	RB1#0	20.06	2	-0.15	19.91	0.098	7.00	Pass
					RB1#13	20.26	2	-0.15	20.11	0.103	7.00	Pass
					RB1#24	20.39	2	-0.15	20.24	0.106	7.00	Pass
					RB12#0	18.93	2	-0.15	18.78	0.076	7.00	Pass
					RB12#6	19.28	2	-0.15	19.13	0.082	7.00	Pass
					RB12#13	19.21	2	-0.15	19.06	0.081	7.00	Pass
					RB25#0	19.33	2	-0.15	19.18	0.083	7.00	Pass
				16-QAM	RB1#0	19.21	2	-0.15	19.06	0.081	7.00	Pass
					RB1#13	19.5	2	-0.15	19.35	0.086	7.00	Pass
					RB1#24	19.67	2	-0.15	19.52	0.090	7.00	Pass
					RB12#0	17.96	2	-0.15	17.81	0.060	7.00	Pass
					RB12#6	18.49	2	-0.15	18.34	0.068	7.00	Pass
					RB12#13	18.3	2	-0.15	18.15	0.065	7.00	Pass
					RB25#0	18.49	2	-0.15	18.34	0.068	7.00	Pass
	MCH		QPSK	RB1#0	20.54	2	-0.15	20.39	0.109	7.00	Pass	
					RB1#13	20.37	2	-0.15	20.22	0.105	7.00	Pass
					RB1#24	20.13	2	-0.15	19.98	0.100	7.00	Pass
					RB12#0	19.16	2	-0.15	19.01	0.080	7.00	Pass
					RB12#6	19.44	2	-0.15	19.29	0.085	7.00	Pass
					RB12#13	19.28	2	-0.15	19.13	0.082	7.00	Pass
					RB25#0	19.43	2	-0.15	19.28	0.085	7.00	Pass
				16-QAM	RB1#0	19.85	2	-0.15	19.70	0.093	7.00	Pass
					RB1#13	20.05	2	-0.15	19.90	0.098	7.00	Pass
					RB1#24	19.79	2	-0.15	19.64	0.092	7.00	Pass
	HCH	QPSK	RB12#0	18.2	2	-0.15	18.05	0.064	7.00	Pass		
				RB12#6	18.51	2	-0.15	18.36	0.069	7.00	Pass	
				RB12#13	18.33	2	-0.15	18.18	0.066	7.00	Pass	
			RB25#0	18.52	2	-0.15	18.37	0.069	7.00	Pass		
			RB1#0	20.22	2	-0.15	20.07	0.102	7.00	Pass		

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND5										
			RB1#13	20.49	2	-0.15	20.34	0.108	7.00	Pass
			RB1#24	20.16	2	-0.15	20.01	0.100	7.00	Pass
			RB12#0	19.19	2	-0.15	19.04	0.080	7.00	Pass
			RB12#6	19.27	2	-0.15	19.12	0.082	7.00	Pass
			RB12#13	19.06	2	-0.15	18.91	0.078	7.00	Pass
			RB25#0	19.41	2	-0.15	19.26	0.084	7.00	Pass
		16-QAM	RB1#0	19.33	2	-0.15	19.18	0.083	7.00	Pass
			RB1#13	19.57	2	-0.15	19.42	0.087	7.00	Pass
			RB1#24	19.26	2	-0.15	19.11	0.081	7.00	Pass
			RB12#0	18.25	2	-0.15	18.10	0.065	7.00	Pass
			RB12#6	18.43	2	-0.15	18.28	0.067	7.00	Pass
			RB12#13	18.14	2	-0.15	17.99	0.063	7.00	Pass
			RB25#0	18.29	2	-0.15	18.14	0.065	7.00	Pass
			10 MHz	LCH	QPSK	RB1#0	19.83	2	-0.15	19.68
RB1#25	19.91	2				-0.15	19.76	0.095	7.00	Pass
RB1#49	20.17	2				-0.15	20.02	0.100	7.00	Pass
RB25#0	19.11	2				-0.15	18.96	0.079	7.00	Pass
RB25#13	18.94	2				-0.15	18.79	0.076	7.00	Pass
RB25#25	19.14	2				-0.15	18.99	0.079	7.00	Pass
RB50#0	19.04	2				-0.15	18.89	0.077	7.00	Pass
16-QAM	RB1#0	18.78			2	-0.15	18.63	0.073	7.00	Pass
	RB1#25	18.8			2	-0.15	18.65	0.073	7.00	Pass
	RB1#49	19.08			2	-0.15	18.93	0.078	7.00	Pass
	RB25#0	18.25			2	-0.15	18.10	0.065	7.00	Pass
	RB25#13	17.79			2	-0.15	17.64	0.058	7.00	Pass
	RB25#25	18.02			2	-0.15	17.87	0.061	7.00	Pass
	RB50#0	17.93			2	-0.15	17.78	0.060	7.00	Pass
MCH	QPSK	RB1#0	20.19	2	-0.15	20.04	0.101	7.00	Pass	
		RB1#25	20.1	2	-0.15	19.95	0.099	7.00	Pass	
		RB1#49	19.84	2	-0.15	19.69	0.093	7.00	Pass	
		RB25#0	18.91	2	-0.15	18.76	0.075	7.00	Pass	
		RB25#13	19.08	2	-0.15	18.93	0.078	7.00	Pass	
		RB25#25	18.85	2	-0.15	18.70	0.074	7.00	Pass	
		RB50#0	19.03	2	-0.15	18.88	0.077	7.00	Pass	
	16-QAM	RB1#0	19.52	2	-0.15	19.37	0.086	7.00	Pass	
		RB1#25	19.52	2	-0.15	19.37	0.086	7.00	Pass	
		RB1#49	19.08	2	-0.15	18.93	0.078	7.00	Pass	
		RB25#0	18.1	2	-0.15	17.95	0.062	7.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict		
LTE BAND5												
			RB25#13	17.99	2	-0.15	17.84	0.061	7.00	Pass		
			RB25#25	17.77	2	-0.15	17.62	0.058	7.00	Pass		
			RB50#0	18.04	2	-0.15	17.89	0.062	7.00	Pass		
		HCH	QPSK	RB1#0	19.8	2	-0.15	19.65	0.092	7.00	Pass	
				RB1#25	19.75	2	-0.15	19.60	0.091	7.00	Pass	
				RB1#49	20.01	2	-0.15	19.86	0.097	7.00	Pass	
				RB25#0	18.62	2	-0.15	18.47	0.070	7.00	Pass	
				RB25#13	18.74	2	-0.15	18.59	0.072	7.00	Pass	
				RB25#25	18.94	2	-0.15	18.79	0.076	7.00	Pass	
				RB50#0	18.85	2	-0.15	18.70	0.074	7.00	Pass	
				16-QAM	RB1#0	18.78	2	-0.15	18.63	0.073	7.00	Pass
					RB1#25	18.76	2	-0.15	18.61	0.073	7.00	Pass
					RB1#49	19.02	2	-0.15	18.87	0.077	7.00	Pass
					RB25#0	17.71	2	-0.15	17.56	0.057	7.00	Pass
					RB25#13	17.86	2	-0.15	17.71	0.059	7.00	Pass
					RB25#25	18.16	2	-0.15	18.01	0.063	7.00	Pass
					RB50#0	17.92	2	-0.15	17.77	0.060	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND18(824~830 MHz)										
5 MHz	LCH	QPSK	RB1#0	20.07	2	-0.15	19.92	0.098	7.000	Pass
			RB1#13	20.21	2	-0.15	20.06	0.101	7.000	Pass
			RB1#24	20.47	2	-0.15	20.32	0.108	7.000	Pass
			RB12#0	18.99	2	-0.15	18.84	0.077	7.000	Pass
			RB12#6	19.26	2	-0.15	19.11	0.081	7.000	Pass
			RB12#13	19.2	2	-0.15	19.05	0.080	7.000	Pass
			RB25#0	19.32	2	-0.15	19.17	0.083	7.000	Pass
		16-QAM	RB1#0	19.23	2	-0.15	19.08	0.081	7.000	Pass
			RB1#13	19.46	2	-0.15	19.31	0.085	7.000	Pass
			RB1#24	19.77	2	-0.15	19.62	0.092	7.000	Pass
			RB12#0	18.11	2	-0.15	17.96	0.063	7.000	Pass
			RB12#6	18.58	2	-0.15	18.43	0.070	7.000	Pass
			RB12#13	18.4	2	-0.15	18.25	0.067	7.000	Pass
			RB25#0	18.59	2	-0.15	18.44	0.070	7.000	Pass
	MCH	QPSK	RB1#0	20.09	2	-0.15	19.94	0.099	7.000	Pass
			RB1#13	20.35	2	-0.15	20.20	0.105	7.000	Pass
			RB1#24	20.37	2	-0.15	20.22	0.105	7.000	Pass
			RB12#0	18.98	2	-0.15	18.83	0.076	7.000	Pass
			RB12#6	19.35	2	-0.15	19.20	0.083	7.000	Pass
			RB12#13	19.29	2	-0.15	19.14	0.082	7.000	Pass
			RB25#0	19.46	2	-0.15	19.31	0.085	7.000	Pass
		16-QAM	RB1#0	19.74	2	-0.15	19.59	0.091	7.000	Pass
			RB1#13	19.89	2	-0.15	19.74	0.094	7.000	Pass
			RB1#24	20.13	2	-0.15	19.98	0.100	7.000	Pass
			RB12#0	18.35	2	-0.15	18.20	0.066	7.000	Pass
			RB12#6	18.68	2	-0.15	18.53	0.071	7.000	Pass
			RB12#13	18.55	2	-0.15	18.40	0.069	7.000	Pass
			RB25#0	18.66	2	-0.15	18.51	0.071	7.000	Pass
	HCH	QPSK	RB1#0	20.2	2	-0.15	20.05	0.101	7.000	Pass
			RB1#13	20.32	2	-0.15	20.17	0.104	7.000	Pass
			RB1#24	20.34	2	-0.15	20.19	0.104	7.000	Pass
			RB12#0	18.95	2	-0.15	18.80	0.076	7.000	Pass
			RB12#6	19.35	2	-0.15	19.20	0.083	7.000	Pass
			RB12#13	19.4	2	-0.15	19.25	0.084	7.000	Pass
			RB25#0	19.53	2	-0.15	19.38	0.087	7.000	Pass
		16-QAM	RB1#0	19.37	2	-0.15	19.22	0.084	7.000	Pass
RB1#13			19.54	2	-0.15	19.39	0.087	7.000	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND18(824~830 MHz)										
			RB1#24	19.6	2	-0.15	19.45	0.088	7.000	Pass
			RB12#0	18.27	2	-0.15	18.12	0.065	7.000	Pass
			RB12#6	18.68	2	-0.15	18.53	0.071	7.000	Pass
			RB12#13	18.46	2	-0.15	18.31	0.068	7.000	Pass
			RB25#0	18.62	2	-0.15	18.47	0.070	7.000	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND18(815-824 MHz)										
5 MHz	LCH	QPSK	RB1#0	20.4	2	-0.15	20.25	0.106	100.000	Pass
			RB1#13	20.42	2	-0.15	20.27	0.106	100.000	Pass
			RB1#24	20.18	2	-0.15	20.03	0.101	100.000	Pass
			RB12#0	19.14	2	-0.15	18.99	0.079	100.000	Pass
			RB12#6	19.39	2	-0.15	19.24	0.084	100.000	Pass
			RB12#13	19.05	2	-0.15	18.90	0.078	100.000	Pass
			RB25#0	19.46	2	-0.15	19.31	0.085	100.000	Pass
		16-QAM	RB1#0	19.45	2	-0.15	19.30	0.085	100.000	Pass
			RB1#13	19.5	2	-0.15	19.35	0.086	100.000	Pass
			RB1#24	19.23	2	-0.15	19.08	0.081	100.000	Pass
			RB12#0	18.13	2	-0.15	17.98	0.063	100.000	Pass
			RB12#6	18.38	2	-0.15	18.23	0.067	100.000	Pass
			RB12#13	18.04	2	-0.15	17.89	0.062	100.000	Pass
			RB25#0	18.4	2	-0.15	18.25	0.067	100.000	Pass
	MCH	QPSK	RB1#0	20.6	2	-0.15	20.45	0.111	100.000	Pass
			RB1#13	20.15	2	-0.15	20.00	0.100	100.000	Pass
			RB1#24	19.78	2	-0.15	19.63	0.092	100.000	Pass
			RB12#0	18.98	2	-0.15	18.83	0.076	100.000	Pass
			RB12#6	18.99	2	-0.15	18.84	0.077	100.000	Pass
			RB12#13	18.69	2	-0.15	18.54	0.071	100.000	Pass
			RB25#0	19.19	2	-0.15	19.04	0.080	100.000	Pass
		16-QAM	RB1#0	19.92	2	-0.15	19.77	0.095	100.000	Pass
			RB1#13	19.53	2	-0.15	19.38	0.087	100.000	Pass
			RB1#24	19.37	2	-0.15	19.22	0.084	100.000	Pass
			RB12#0	18.12	2	-0.15	17.97	0.063	100.000	Pass
			RB12#6	18.03	2	-0.15	17.88	0.061	100.000	Pass
			RB12#13	17.73	2	-0.15	17.58	0.057	100.000	Pass
			RB25#0	18.17	2	-0.15	18.02	0.063	100.000	Pass
	HCH	QPSK	RB1#0	20.25	2	-0.15	20.10	0.102	100.000	Pass
			RB1#13	19.77	2	-0.15	19.62	0.092	100.000	Pass
RB1#24			19.89	2	-0.15	19.74	0.094	100.000	Pass	
RB12#0			18.73	2	-0.15	18.58	0.072	100.000	Pass	
RB12#6			18.71	2	-0.15	18.56	0.072	100.000	Pass	
RB12#13			18.61	2	-0.15	18.46	0.070	100.000	Pass	
RB25#0			18.97	2	-0.15	18.82	0.076	100.000	Pass	
16-QAM		RB1#0	19.35	2	-0.15	19.20	0.083	100.000	Pass	
		RB1#13	18.77	2	-0.15	18.62	0.073	100.000	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND18(815-824 MHz)										
			RB1#24	19.07	2	-0.15	18.92	0.078	100.000	Pass
			RB12#0	17.67	2	-0.15	17.52	0.056	100.000	Pass
			RB12#6	17.75	2	-0.15	17.60	0.058	100.000	Pass
			RB12#13	17.64	2	-0.15	17.49	0.056	100.000	Pass
			RB25#0	17.92	2	-0.15	17.77	0.060	100.000	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND19										
5 MHz	LCH	QPSK	RB1#0	20.27	2	-0.15	20.12	0.103	7.0	Pass
			RB1#13	20.17	2	-0.15	20.02	0.100	7.0	Pass
			RB1#24	20.7	2	-0.15	20.55	0.114	7.0	Pass
			RB12#0	19.35	2	-0.15	19.20	0.083	7.0	Pass
			RB12#6	19.41	2	-0.15	19.26	0.084	7.0	Pass
			RB12#13	19.34	2	-0.15	19.19	0.083	7.0	Pass
			RB25#0	19.42	2	-0.15	19.27	0.085	7.0	Pass
		16-QAM	RB1#0	19.5	2	-0.15	19.35	0.086	7.0	Pass
			RB1#13	19.38	2	-0.15	19.23	0.084	7.0	Pass
			RB1#24	19.76	2	-0.15	19.61	0.091	7.0	Pass
			RB12#0	18.45	2	-0.15	18.30	0.068	7.0	Pass
			RB12#6	18.38	2	-0.15	18.23	0.067	7.0	Pass
			RB12#13	18.36	2	-0.15	18.21	0.066	7.0	Pass
			RB25#0	18.37	2	-0.15	18.22	0.066	7.0	Pass
	MCH	QPSK	RB1#0	20.56	2	-0.15	20.41	0.110	7.0	Pass
			RB1#13	20.21	2	-0.15	20.06	0.101	7.0	Pass
			RB1#24	20.18	2	-0.15	20.03	0.101	7.0	Pass
			RB12#0	19.14	2	-0.15	18.99	0.079	7.0	Pass
			RB12#6	19.22	2	-0.15	19.07	0.081	7.0	Pass
			RB12#13	18.94	2	-0.15	18.79	0.076	7.0	Pass
			RB25#0	19.36	2	-0.15	19.21	0.083	7.0	Pass
		16-QAM	RB1#0	20.03	2	-0.15	19.88	0.097	7.0	Pass
			RB1#13	19.78	2	-0.15	19.63	0.092	7.0	Pass
			RB1#24	19.74	2	-0.15	19.59	0.091	7.0	Pass
			RB12#0	18.33	2	-0.15	18.18	0.066	7.0	Pass
			RB12#6	18.42	2	-0.15	18.27	0.067	7.0	Pass
			RB12#13	18.12	2	-0.15	17.97	0.063	7.0	Pass
			RB25#0	18.48	2	-0.15	18.33	0.068	7.0	Pass
	HCH	QPSK	RB1#0	20.03	2	-0.15	19.88	0.097	7.0	Pass
			RB1#13	19.75	2	-0.15	19.60	0.091	7.0	Pass
			RB1#24	20.56	2	-0.15	20.41	0.110	7.0	Pass
			RB12#0	18.55	2	-0.15	18.40	0.069	7.0	Pass
RB12#6			18.72	2	-0.15	18.57	0.072	7.0	Pass	
RB12#13			18.95	2	-0.15	18.80	0.076	7.0	Pass	
RB25#0			19.03	2	-0.15	18.88	0.077	7.0	Pass	
16-QAM		RB1#0	19.18	2	-0.15	19.03	0.080	7.0	Pass	
		RB1#13	18.91	2	-0.15	18.76	0.075	7.0	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND19										
10 MHz			RB1#24	19.52	2	-0.15	19.37	0.086	7.0	Pass
			RB12#0	17.53	2	-0.15	17.38	0.055	7.0	Pass
			RB12#6	17.79	2	-0.15	17.64	0.058	7.0	Pass
			RB12#13	17.91	2	-0.15	17.76	0.060	7.0	Pass
			RB25#0	17.97	2	-0.15	17.82	0.061	7.0	Pass
	LCH	QPSK	RB1#0	20.1	2	-0.15	19.95	0.099	7.0	Pass
			RB1#25	20.08	2	-0.15	19.93	0.098	7.0	Pass
			RB1#49	19.92	2	-0.15	19.77	0.095	7.0	Pass
			RB25#0	19.08	2	-0.15	18.93	0.078	7.0	Pass
			RB25#13	19.02	2	-0.15	18.87	0.077	7.0	Pass
			RB25#25	19.15	2	-0.15	19.00	0.079	7.0	Pass
			RB50#0	18.98	2	-0.15	18.83	0.076	7.0	Pass
		16-QAM	RB1#0	19.05	2	-0.15	18.90	0.078	7.0	Pass
			RB1#25	19.05	2	-0.15	18.90	0.078	7.0	Pass
			RB1#49	18.86	2	-0.15	18.71	0.074	7.0	Pass
			RB25#0	18	2	-0.15	17.85	0.061	7.0	Pass
			RB25#13	17.94	2	-0.15	17.79	0.060	7.0	Pass
			RB25#25	18.05	2	-0.15	17.90	0.062	7.0	Pass
			RB50#0	17.94	2	-0.15	17.79	0.060	7.0	Pass
	MCH	QPSK	RB1#0	20.13	2	-0.15	19.98	0.100	7.0	Pass
			RB1#25	20	2	-0.15	19.85	0.097	7.0	Pass
			RB1#49	19.65	2	-0.15	19.50	0.089	7.0	Pass
			RB25#0	19	2	-0.15	18.85	0.077	7.0	Pass
			RB25#13	18.96	2	-0.15	18.81	0.076	7.0	Pass
			RB25#25	18.78	2	-0.15	18.63	0.073	7.0	Pass
			RB50#0	19.02	2	-0.15	18.87	0.077	7.0	Pass
		16-QAM	RB1#0	19.32	2	-0.15	19.17	0.083	7.0	Pass
			RB1#25	19.41	2	-0.15	19.26	0.084	7.0	Pass
RB1#49			19.03	2	-0.15	18.88	0.077	7.0	Pass	
RB25#0			18.19	2	-0.15	18.04	0.064	7.0	Pass	
RB25#13			17.92	2	-0.15	17.77	0.060	7.0	Pass	
RB25#25			17.8	2	-0.15	17.65	0.058	7.0	Pass	
RB50#0			18.03	2	-0.15	17.88	0.061	7.0	Pass	
HCH	QPSK	RB1#0	20.1	2	-0.15	19.95	0.099	7.0	Pass	
		RB1#25	19.49	2	-0.15	19.34	0.086	7.0	Pass	
		RB1#49	20.1	2	-0.15	19.95	0.099	7.0	Pass	
		RB25#0	18.81	2	-0.15	18.66	0.073	7.0	Pass	
		RB25#13	18.36	2	-0.15	18.21	0.066	7.0	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND19										
		16-QAM	RB25#25	18.5	2	-0.15	18.35	0.068	7.0	Pass
			RB50#0	18.74	2	-0.15	18.59	0.072	7.0	Pass
			RB1#0	19.25	2	-0.15	19.10	0.081	7.0	Pass
			RB1#25	18.65	2	-0.15	18.50	0.071	7.0	Pass
			RB1#49	18.99	2	-0.15	18.84	0.077	7.0	Pass
			RB25#0	17.79	2	-0.15	17.64	0.058	7.0	Pass
			RB25#13	17.55	2	-0.15	17.40	0.055	7.0	Pass
			RB25#25	17.67	2	-0.15	17.52	0.056	7.0	Pass
		16-QAM	RB50#0	17.79	2	-0.15	17.64	0.058	7.0	Pass
			RB1#0	20.05	2	-0.15	19.90	0.098	7.0	Pass
			RB1#38	20.08	2	-0.15	19.93	0.098	7.0	Pass
			RB1#74	20.12	2	-0.15	19.97	0.099	7.0	Pass
			RB36#0	19.1	2	-0.15	18.95	0.079	7.0	Pass
			RB36#19	19.21	2	-0.15	19.06	0.081	7.0	Pass
			RB36#39	18.81	2	-0.15	18.66	0.073	7.0	Pass
RB75#0	18.96		2	-0.15	18.81	0.076	7.0	Pass		
16-QAM	RB1#0	18.92	2	-0.15	18.77	0.075	7.0	Pass		
	RB1#38	19.14	2	-0.15	18.99	0.079	7.0	Pass		
	RB1#74	18.88	2	-0.15	18.73	0.075	7.0	Pass		
	RB36#0	18.14	2	-0.15	17.99	0.063	7.0	Pass		
	RB36#19	18.16	2	-0.15	18.01	0.063	7.0	Pass		
	RB36#39	17.85	2	-0.15	17.70	0.059	7.0	Pass		
	RB75#0	18.03	2	-0.15	17.88	0.061	7.0	Pass		

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND25									
1.4 MHz	LCH	QPSK	RB1#0	20.78	2	22.78	0.190	2.00	Pass
			RB1#3	20.3	2	22.30	0.170	2.00	Pass
			RB1#5	20.43	2	22.43	0.175	2.00	Pass
			RB3#0	20.72	2	22.72	0.187	2.00	Pass
			RB3#2	20.3	2	22.30	0.170	2.00	Pass
			RB3#3	20.33	2	22.33	0.171	2.00	Pass
			RB6#0	19.46	2	21.46	0.140	2.00	Pass
		16-QAM	RB1#0	19.85	2	21.85	0.153	2.00	Pass
			RB1#3	19.56	2	21.56	0.143	2.00	Pass
			RB1#5	19.64	2	21.64	0.146	2.00	Pass
			RB3#0	19.72	2	21.72	0.149	2.00	Pass
			RB3#2	19.41	2	21.41	0.138	2.00	Pass
			RB3#3	19.48	2	21.48	0.141	2.00	Pass
			RB6#0	18.61	2	20.61	0.115	2.00	Pass
	MCH	QPSK	RB1#0	19.27	2	21.27	0.134	2.00	Pass
			RB1#3	19.03	2	21.03	0.127	2.00	Pass
			RB1#5	19.36	2	21.36	0.137	2.00	Pass
			RB3#0	19.06	2	21.06	0.128	2.00	Pass
			RB3#2	18.98	2	20.98	0.125	2.00	Pass
			RB3#3	19.19	2	21.19	0.132	2.00	Pass
			RB6#0	18.06	2	20.06	0.101	2.00	Pass
		16-QAM	RB1#0	18.54	2	20.54	0.113	2.00	Pass
			RB1#3	18.37	2	20.37	0.109	2.00	Pass
			RB1#5	18.64	2	20.64	0.116	2.00	Pass
			RB3#0	18.18	2	20.18	0.104	2.00	Pass
			RB3#2	18.12	2	20.12	0.103	2.00	Pass
			RB3#3	18.34	2	20.34	0.108	2.00	Pass
			RB6#0	16.95	2	18.95	0.079	2.00	Pass
	HCH	QPSK	RB1#0	18.18	2	20.18	0.104	2.00	Pass
			RB1#3	17.69	2	19.69	0.093	2.00	Pass
RB1#5			17.61	2	19.61	0.091	2.00	Pass	
RB3#0			18.03	2	20.03	0.101	2.00	Pass	
RB3#2			17.67	2	19.67	0.093	2.00	Pass	
RB3#3			17.82	2	19.82	0.096	2.00	Pass	
RB6#0			16.83	2	18.83	0.076	2.00	Pass	
16-QAM		RB1#0	17.18	2	19.18	0.083	2.00	Pass	
		RB1#3	16.68	2	18.68	0.074	2.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND25									
3 MHz			RB1#5	16.78	2	18.78	0.076	2.00	Pass
			RB3#0	17.32	2	19.32	0.086	2.00	Pass
			RB3#2	16.98	2	18.98	0.079	2.00	Pass
			RB3#3	16.99	2	18.99	0.079	2.00	Pass
			RB6#0	16.16	2	18.16	0.065	2.00	Pass
	LCH	QPSK	RB1#0	20.73	2	22.73	0.187	2.00	Pass
			RB1#7	20.09	2	22.09	0.162	2.00	Pass
			RB1#14	19.74	2	21.74	0.149	2.00	Pass
			RB8#0	19.22	2	21.22	0.132	2.00	Pass
			RB8#4	19.23	2	21.23	0.133	2.00	Pass
			RB8#7	18.92	2	20.92	0.124	2.00	Pass
			RB15#0	19.19	2	21.19	0.132	2.00	Pass
		16-QAM	RB1#0	19.64	2	21.64	0.146	2.00	Pass
			RB1#7	19.05	2	21.05	0.127	2.00	Pass
			RB1#14	18.65	2	20.65	0.116	2.00	Pass
			RB8#0	18.32	2	20.32	0.108	2.00	Pass
			RB8#4	18.33	2	20.33	0.108	2.00	Pass
			RB8#7	18.01	2	20.01	0.100	2.00	Pass
	MCH	QPSK	RB1#0	19.36	2	21.36	0.137	2.00	Pass
			RB1#7	19.06	2	21.06	0.128	2.00	Pass
			RB1#14	19.32	2	21.32	0.136	2.00	Pass
			RB8#0	17.74	2	19.74	0.094	2.00	Pass
			RB8#4	18.09	2	20.09	0.102	2.00	Pass
			RB8#7	18.09	2	20.09	0.102	2.00	Pass
			RB15#0	18.05	2	20.05	0.101	2.00	Pass
		16-QAM	RB1#0	18.64	2	20.64	0.116	2.00	Pass
			RB1#7	18.4	2	20.40	0.110	2.00	Pass
			RB1#14	18.67	2	20.67	0.117	2.00	Pass
RB8#0			16.82	2	18.82	0.076	2.00	Pass	
RB8#4			17.16	2	19.16	0.082	2.00	Pass	
HCH	QPSK	RB1#0	19.12	2	21.12	0.129	2.00	Pass	
		RB1#7	18	2	20.00	0.100	2.00	Pass	
		RB1#14	17.62	2	19.62	0.092	2.00	Pass	
		RB8#0	17.3	2	19.30	0.085	2.00	Pass	
		RB8#4	17.23	2	19.23	0.084	2.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict		
LTE BAND25											
		16-QAM	RB8#7	16.9	2	18.90	0.078	2.00	Pass		
			RB15#0	17.27	2	19.27	0.085	2.00	Pass		
			RB1#0	18.26	2	20.26	0.106	2.00	Pass		
			RB1#7	16.99	2	18.99	0.079	2.00	Pass		
			RB1#14	16.78	2	18.78	0.076	2.00	Pass		
			RB8#0	16.45	2	18.45	0.070	2.00	Pass		
			RB8#4	16.31	2	18.31	0.068	2.00	Pass		
			RB8#7	15.95	2	17.95	0.062	2.00	Pass		
		RB15#0	16.3	2	18.30	0.068	2.00	Pass			
		5 MHz	LCH	QPSK	RB1#0	20.8	2	22.80	0.191	2.00	Pass
					RB1#13	19.9	2	21.90	0.155	2.00	Pass
					RB1#24	19.04	2	21.04	0.127	2.00	Pass
					RB12#0	19.09	2	21.09	0.129	2.00	Pass
					RB12#6	18.81	2	20.81	0.121	2.00	Pass
					RB12#13	18.44	2	20.44	0.111	2.00	Pass
RB25#0	18.89				2	20.89	0.123	2.00	Pass		
16-QAM	RB1#0			19.92	2	21.92	0.156	2.00	Pass		
	RB1#13			19.01	2	21.01	0.126	2.00	Pass		
	RB1#24			18.17	2	20.17	0.104	2.00	Pass		
	RB12#0			18.29	2	20.29	0.107	2.00	Pass		
	RB12#6			17.9	2	19.90	0.098	2.00	Pass		
	RB12#13			17.57	2	19.57	0.091	2.00	Pass		
RB25#0	18			2	20.00	0.100	2.00	Pass			
MCH	QPSK			RB1#0	19.34	2	21.34	0.136	2.00	Pass	
		RB1#13	19.03	2	21.03	0.127	2.00	Pass			
		RB1#24	19.43	2	21.43	0.139	2.00	Pass			
		RB12#0	18.06	2	20.06	0.101	2.00	Pass			
		RB12#6	18.07	2	20.07	0.102	2.00	Pass			
		RB12#13	18.21	2	20.21	0.105	2.00	Pass			
		RB25#0	18.17	2	20.17	0.104	2.00	Pass			
	16-QAM	RB1#0	18.81	2	20.81	0.121	2.00	Pass			
		RB1#13	18.61	2	20.61	0.115	2.00	Pass			
		RB1#24	18.88	2	20.88	0.122	2.00	Pass			
		RB12#0	17.16	2	19.16	0.082	2.00	Pass			
		RB12#6	17.15	2	19.15	0.082	2.00	Pass			
		RB12#13	17.32	2	19.32	0.086	2.00	Pass			
RB25#0	17.18	2	19.18	0.083	2.00	Pass					
HCH	QPSK	RB1#0	19.84	2	21.84	0.153	2.00	Pass			

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND25									
			RB1#13	18.96	2	20.96	0.125	2.00	Pass
			RB1#24	17.77	2	19.77	0.095	2.00	Pass
			RB12#0	18.27	2	20.27	0.106	2.00	Pass
			RB12#6	18.01	2	20.01	0.100	2.00	Pass
			RB12#13	17.26	2	19.26	0.084	2.00	Pass
			RB25#0	17.94	2	19.94	0.099	2.00	Pass
		16-QAM	RB1#0	18.97	2	20.97	0.125	2.00	Pass
			RB1#13	18	2	20.00	0.100	2.00	Pass
			RB1#24	16.82	2	18.82	0.076	2.00	Pass
			RB12#0	17.3	2	19.30	0.085	2.00	Pass
			RB12#6	17.06	2	19.06	0.081	2.00	Pass
			RB12#13	16.3	2	18.30	0.068	2.00	Pass
			RB25#0	16.89	2	18.89	0.077	2.00	Pass
			10 MHz	LCH	QPSK	RB1#0	20.28	2	22.28
RB1#25	18.39	2				20.39	0.109	2.00	Pass
RB1#49	18.27	2				20.27	0.106	2.00	Pass
RB25#0	18.49	2				20.49	0.112	2.00	Pass
RB25#13	17.61	2				19.61	0.091	2.00	Pass
RB25#25	17.25	2				19.25	0.084	2.00	Pass
16-QAM	RB50#0	17.92			2	19.92	0.098	2.00	Pass
	RB1#0	19.36			2	21.36	0.137	2.00	Pass
	RB1#25	17.49			2	19.49	0.089	2.00	Pass
	RB1#49	17.16			2	19.16	0.082	2.00	Pass
	RB25#0	17.42			2	19.42	0.087	2.00	Pass
	RB25#13	16.75			2	18.75	0.075	2.00	Pass
	RB25#25	16.51			2	18.51	0.071	2.00	Pass
	RB50#0	16.97			2	18.97	0.079	2.00	Pass
10 MHz	MCH	QPSK	RB1#0	19.06	2	21.06	0.128	2.00	Pass
			RB1#25	18.66	2	20.66	0.116	2.00	Pass
			RB1#49	19.38	2	21.38	0.137	2.00	Pass
			RB25#0	17.89	2	19.89	0.097	2.00	Pass
			RB25#13	17.75	2	19.75	0.094	2.00	Pass
			RB25#25	18.06	2	20.06	0.101	2.00	Pass
		16-QAM	RB50#0	18.01	2	20.01	0.100	2.00	Pass
			RB1#0	18.46	2	20.46	0.111	2.00	Pass
			RB1#25	18.09	2	20.09	0.102	2.00	Pass
			RB1#49	18.69	2	20.69	0.117	2.00	Pass
			RB25#0	17.02	2	19.02	0.080	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict	
LTE BAND25										
15 MHz			RB25#13	16.76	2	18.76	0.075	2.00	Pass	
			RB25#25	17.09	2	19.09	0.081	2.00	Pass	
			RB50#0	17	2	19.00	0.079	2.00	Pass	
	HCH	QPSK	RB1#0	18.51	2	20.51	0.112	2.00	Pass	
			RB1#25	19.22	2	21.22	0.132	2.00	Pass	
			RB1#49	17.67	2	19.67	0.093	2.00	Pass	
			RB25#0	17.89	2	19.89	0.097	2.00	Pass	
			RB25#13	17.97	2	19.97	0.099	2.00	Pass	
			RB25#25	17.71	2	19.71	0.094	2.00	Pass	
			RB50#0	17.76	2	19.76	0.095	2.00	Pass	
			16-QAM	RB1#0	17.61	2	19.61	0.091	2.00	Pass
				RB1#25	18.23	2	20.23	0.105	2.00	Pass
		RB1#49		16.65	2	18.65	0.073	2.00	Pass	
		RB25#0		16.97	2	18.97	0.079	2.00	Pass	
		RB25#13		17.04	2	19.04	0.080	2.00	Pass	
		RB25#25		16.79	2	18.79	0.076	2.00	Pass	
		LCH	QPSK	RB1#0	20.32	2	22.32	0.171	2.00	Pass
				RB1#38	18.46	2	20.46	0.111	2.00	Pass
	RB1#74			18.09	2	20.09	0.102	2.00	Pass	
	RB36#0			18.21	2	20.21	0.105	2.00	Pass	
	RB36#19			17.49	2	19.49	0.089	2.00	Pass	
RB36#39	17.06			2	19.06	0.081	2.00	Pass		
RB75#0	17.77			2	19.77	0.095	2.00	Pass		
16-QAM	RB1#0		19.34	2	21.34	0.136	2.00	Pass		
	RB1#38		17.49	2	19.49	0.089	2.00	Pass		
	RB1#74		17.08	2	19.08	0.081	2.00	Pass		
	RB36#0		17.28	2	19.28	0.085	2.00	Pass		
	RB36#19		16.57	2	18.57	0.072	2.00	Pass		
	RB36#39		16.1	2	18.10	0.065	2.00	Pass		
	RB75#0		16.72	2	18.72	0.074	2.00	Pass		
	MCH		QPSK	RB1#0	18.89	2	20.89	0.123	2.00	Pass
RB1#38		19.09		2	21.09	0.129	2.00	Pass		
RB1#74		19.39		2	21.39	0.138	2.00	Pass		
RB36#0		17.9		2	19.90	0.098	2.00	Pass		
RB36#19		18.15		2	20.15	0.104	2.00	Pass		
RB36#39		18.26		2	20.26	0.106	2.00	Pass		
RB75#0		18.15		2	20.15	0.104	2.00	Pass		

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND25									
20 MHz	HCH	16-QAM	RB1#0	18.29	2	20.29	0.107	2.00	Pass
			RB1#38	18.49	2	20.49	0.112	2.00	Pass
			RB1#74	18.71	2	20.71	0.118	2.00	Pass
			RB36#0	17.01	2	19.01	0.080	2.00	Pass
			RB36#19	17.28	2	19.28	0.085	2.00	Pass
			RB36#39	17.42	2	19.42	0.087	2.00	Pass
			RB75#0	17.17	2	19.17	0.083	2.00	Pass
		QPSK	RB1#0	18.21	2	20.21	0.105	2.00	Pass
			RB1#38	19.01	2	21.01	0.126	2.00	Pass
			RB1#74	17.91	2	19.91	0.098	2.00	Pass
			RB36#0	17.41	2	19.41	0.087	2.00	Pass
			RB36#19	18.16	2	20.16	0.104	2.00	Pass
			RB36#39	18.09	2	20.09	0.102	2.00	Pass
			RB75#0	17.79	2	19.79	0.095	2.00	Pass
	16-QAM	RB1#0	17.73	2	19.73	0.094	2.00	Pass	
		RB1#38	18.54	2	20.54	0.113	2.00	Pass	
		RB1#74	17.46	2	19.46	0.088	2.00	Pass	
		RB36#0	16.33	2	18.33	0.068	2.00	Pass	
		RB36#19	17.09	2	19.09	0.081	2.00	Pass	
		RB36#39	16.99	2	18.99	0.079	2.00	Pass	
		RB75#0	16.76	2	18.76	0.075	2.00	Pass	
	LCH	QPSK	RB1#0	20.35	2	22.35	0.172	2.00	Pass
			RB1#50	18.3	2	20.30	0.107	2.00	Pass
			RB1#99	18.46	2	20.46	0.111	2.00	Pass
			RB50#0	18.24	2	20.24	0.106	2.00	Pass
			RB50#25	17.39	2	19.39	0.087	2.00	Pass
			RB50#50	17.26	2	19.26	0.084	2.00	Pass
			RB100#0	17.72	2	19.72	0.094	2.00	Pass
16-QAM		RB1#0	19.81	2	21.81	0.152	2.00	Pass	
		RB1#50	17.8	2	19.80	0.095	2.00	Pass	
		RB1#99	17.94	2	19.94	0.099	2.00	Pass	
		RB50#0	17.14	2	19.14	0.082	2.00	Pass	
		RB50#25	16.33	2	18.33	0.068	2.00	Pass	
		RB50#50	16.3	2	18.30	0.068	2.00	Pass	
		RB100#0	16.7	2	18.70	0.074	2.00	Pass	
MCH		QPSK	RB1#0	18.71	2	20.71	0.118	2.00	Pass
			RB1#50	19.25	2	21.25	0.133	2.00	Pass
			RB1#99	19.28	2	21.28	0.134	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict	
LTE BAND25										
			RB50#0	18.21	2	20.21	0.105	2.00	Pass	
			RB50#25	18.32	2	20.32	0.108	2.00	Pass	
			RB50#50	18.35	2	20.35	0.108	2.00	Pass	
			RB100#0	18.26	2	20.26	0.106	2.00	Pass	
		16-QAM	RB1#0	18.26	2	20.26	0.106	2.00	Pass	
			RB1#50	18.68	2	20.68	0.117	2.00	Pass	
			RB1#99	18.66	2	20.66	0.116	2.00	Pass	
			RB50#0	17.28	2	19.28	0.085	2.00	Pass	
			RB50#25	17.3	2	19.30	0.085	2.00	Pass	
			RB50#50	17.41	2	19.41	0.087	2.00	Pass	
		RB100#0	17.21	2	19.21	0.083	2.00	Pass		
		HCH	QPSK	RB1#0	18.2	2	20.20	0.105	2.00	Pass
				RB1#50	18.77	2	20.77	0.119	2.00	Pass
				RB1#99	18.12	2	20.12	0.103	2.00	Pass
	RB50#0			17.26	2	19.26	0.084	2.00	Pass	
	RB50#25			17.78	2	19.78	0.095	2.00	Pass	
	RB50#50			18.17	2	20.17	0.104	2.00	Pass	
	RB100#0		17.82	2	19.82	0.096	2.00	Pass		
	16-QAM		RB1#0	17.67	2	19.67	0.093	2.00	Pass	
			RB1#50	18.26	2	20.26	0.106	2.00	Pass	
			RB1#99	17.62	2	19.62	0.092	2.00	Pass	
			RB50#0	16.33	2	18.33	0.068	2.00	Pass	
			RB50#25	16.83	2	18.83	0.076	2.00	Pass	
			RB50#50	17.23	2	19.23	0.084	2.00	Pass	
	RB100#0		16.77	2	18.77	0.075	2.00	Pass		

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND26(824~849 MHz)										
1.4 MHz	LCH	QPSK	RB1#0	20.14	2	-0.15	19.99	0.100	7.00	Pass
			RB1#3	19.88	2	-0.15	19.73	0.094	7.00	Pass
			RB1#5	20.27	2	-0.15	20.12	0.103	7.00	Pass
			RB3#0	19.97	2	-0.15	19.82	0.096	7.00	Pass
			RB3#2	19.84	2	-0.15	19.69	0.093	7.00	Pass
			RB3#3	20.06	2	-0.15	19.91	0.098	7.00	Pass
			RB6#0	19.07	2	-0.15	18.92	0.078	7.00	Pass
		16-QAM	RB1#0	19.34	2	-0.15	19.19	0.083	7.00	Pass
			RB1#3	19.11	2	-0.15	18.96	0.079	7.00	Pass
			RB1#5	19.48	2	-0.15	19.33	0.086	7.00	Pass
			RB3#0	19.12	2	-0.15	18.97	0.079	7.00	Pass
			RB3#2	18.93	2	-0.15	18.78	0.076	7.00	Pass
			RB3#3	19.22	2	-0.15	19.07	0.081	7.00	Pass
			RB6#0	18.21	2	-0.15	18.06	0.064	7.00	Pass
	MCH	QPSK	RB1#0	20.43	2	-0.15	20.28	0.107	7.00	Pass
			RB1#3	20.26	2	-0.15	20.11	0.103	7.00	Pass
			RB1#5	20.55	2	-0.15	20.40	0.110	7.00	Pass
			RB3#0	20.49	2	-0.15	20.34	0.108	7.00	Pass
			RB3#2	20.36	2	-0.15	20.21	0.105	7.00	Pass
			RB3#3	20.52	2	-0.15	20.37	0.109	7.00	Pass
			RB6#0	19.51	2	-0.15	19.36	0.086	7.00	Pass
		16-QAM	RB1#0	19.93	2	-0.15	19.78	0.095	7.00	Pass
			RB1#3	19.78	2	-0.15	19.63	0.092	7.00	Pass
			RB1#5	19.98	2	-0.15	19.83	0.096	7.00	Pass
			RB3#0	19.69	2	-0.15	19.54	0.090	7.00	Pass
			RB3#2	19.57	2	-0.15	19.42	0.087	7.00	Pass
			RB3#3	19.75	2	-0.15	19.60	0.091	7.00	Pass
			RB6#0	18.35	2	-0.15	18.20	0.066	7.00	Pass
	HCH	QPSK	RB1#0	20.26	2	-0.15	20.11	0.103	7.00	Pass
			RB1#3	19.98	2	-0.15	19.83	0.096	7.00	Pass
RB1#5			20.09	2	-0.15	19.94	0.099	7.00	Pass	
RB3#0			20.33	2	-0.15	20.18	0.104	7.00	Pass	
RB3#2			20.11	2	-0.15	19.96	0.099	7.00	Pass	
RB3#3			20.27	2	-0.15	20.12	0.103	7.00	Pass	
RB6#0			19.05	2	-0.15	18.90	0.078	7.00	Pass	
16-QAM		RB1#0	19.27	2	-0.15	19.12	0.082	7.00	Pass	
		RB1#3	18.95	2	-0.15	18.80	0.076	7.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND26(824~849 MHz)										
3 MHz			RB1#5	19.11	2	-0.15	18.96	0.079	7.00	Pass
			RB3#0	19.37	2	-0.15	19.22	0.084	7.00	Pass
			RB3#2	19.29	2	-0.15	19.14	0.082	7.00	Pass
			RB3#3	19.32	2	-0.15	19.17	0.083	7.00	Pass
			RB6#0	18.25	2	-0.15	18.10	0.065	7.00	Pass
	LCH	QPSK	RB1#0	20.15	2	-0.15	20.00	0.100	7.00	Pass
			RB1#7	20.24	2	-0.15	20.09	0.102	7.00	Pass
			RB1#14	20.39	2	-0.15	20.24	0.106	7.00	Pass
			RB8#0	18.87	2	-0.15	18.72	0.074	7.00	Pass
			RB8#4	19.29	2	-0.15	19.14	0.082	7.00	Pass
			RB8#7	19.39	2	-0.15	19.24	0.084	7.00	Pass
		RB15#0	19.41	2	-0.15	19.26	0.084	7.00	Pass	
		16-QAM	RB1#0	19.15	2	-0.15	19.00	0.079	7.00	Pass
			RB1#7	19.28	2	-0.15	19.13	0.082	7.00	Pass
			RB1#14	19.34	2	-0.15	19.19	0.083	7.00	Pass
			RB8#0	17.91	2	-0.15	17.76	0.060	7.00	Pass
			RB8#4	18.4	2	-0.15	18.25	0.067	7.00	Pass
			RB8#7	18.58	2	-0.15	18.43	0.070	7.00	Pass
	MCH	QPSK	RB1#0	20.36	2	-0.15	20.21	0.105	7.00	Pass
			RB1#7	20.31	2	-0.15	20.16	0.104	7.00	Pass
			RB1#14	20.38	2	-0.15	20.23	0.105	7.00	Pass
			RB8#0	19.11	2	-0.15	18.96	0.079	7.00	Pass
			RB8#4	19.42	2	-0.15	19.27	0.085	7.00	Pass
			RB8#7	19.51	2	-0.15	19.36	0.086	7.00	Pass
		RB15#0	19.31	2	-0.15	19.16	0.082	7.00	Pass	
		16-QAM	RB1#0	19.73	2	-0.15	19.58	0.091	7.00	Pass
			RB1#7	19.71	2	-0.15	19.56	0.090	7.00	Pass
			RB1#14	19.79	2	-0.15	19.64	0.092	7.00	Pass
RB8#0			18.24	2	-0.15	18.09	0.064	7.00	Pass	
RB8#4			18.52	2	-0.15	18.37	0.069	7.00	Pass	
RB8#7	18.5		2	-0.15	18.35	0.068	7.00	Pass		
RB15#0	18.35	2	-0.15	18.20	0.066	7.00	Pass			
HCH	QPSK	RB1#0	20.6	2	-0.15	20.45	0.111	7.00	Pass	
		RB1#7	20.06	2	-0.15	19.91	0.098	7.00	Pass	
		RB1#14	20.02	2	-0.15	19.87	0.097	7.00	Pass	
		RB8#0	19.03	2	-0.15	18.88	0.077	7.00	Pass	
		RB8#4	19.19	2	-0.15	19.04	0.080	7.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict	
LTE BAND26(824~849 MHz)											
5 MHz	LCH	16-QAM	RB8#7	19.01	2	-0.15	18.86	0.077	7.00	Pass	
			RB15#0	19.27	2	-0.15	19.12	0.082	7.00	Pass	
			RB1#0	19.61	2	-0.15	19.46	0.088	7.00	Pass	
			RB1#7	19.08	2	-0.15	18.93	0.078	7.00	Pass	
			RB1#14	19.06	2	-0.15	18.91	0.078	7.00	Pass	
			RB8#0	18.2	2	-0.15	18.05	0.064	7.00	Pass	
			RB8#4	18.26	2	-0.15	18.11	0.065	7.00	Pass	
			RB8#7	18.1	2	-0.15	17.95	0.062	7.00	Pass	
	5 MHz	LCH	QPSK	RB1#0	20.16	2	-0.15	20.01	0.100	7.00	Pass
				RB1#13	20.27	2	-0.15	20.12	0.103	7.00	Pass
				RB1#24	20.38	2	-0.15	20.23	0.105	7.00	Pass
				RB12#0	18.94	2	-0.15	18.79	0.076	7.00	Pass
				RB12#6	19.28	2	-0.15	19.13	0.082	7.00	Pass
				RB12#13	19.19	2	-0.15	19.04	0.080	7.00	Pass
				RB25#0	19.42	2	-0.15	19.27	0.085	7.00	Pass
				MCH	16-QAM	RB1#0	19.32	2	-0.15	19.17	0.083
RB1#13		19.5	2			-0.15	19.35	0.086	7.00	Pass	
RB1#24		19.65	2			-0.15	19.50	0.089	7.00	Pass	
RB12#0		17.98	2			-0.15	17.83	0.061	7.00	Pass	
RB12#6		18.49	2			-0.15	18.34	0.068	7.00	Pass	
RB12#13		18.23	2			-0.15	18.08	0.064	7.00	Pass	
RB25#0		18.61	2			-0.15	18.46	0.070	7.00	Pass	
MCH		QPSK	RB1#0			20.41	2	-0.15	20.26	0.106	7.00
			RB1#13	20.37	2	-0.15	20.22	0.105	7.00	Pass	
	RB1#24		20.24	2	-0.15	20.09	0.102	7.00	Pass		
	RB12#0		19.2	2	-0.15	19.05	0.080	7.00	Pass		
	RB12#6		19.37	2	-0.15	19.22	0.084	7.00	Pass		
	RB12#13		19.22	2	-0.15	19.07	0.081	7.00	Pass		
	RB25#0		19.46	2	-0.15	19.31	0.085	7.00	Pass		
	HCH		16-QAM	RB1#0	19.9	2	-0.15	19.75	0.094	7.00	Pass
RB1#13		19.97		2	-0.15	19.82	0.096	7.00	Pass		
RB1#24		19.76		2	-0.15	19.61	0.091	7.00	Pass		
RB12#0		18.35		2	-0.15	18.20	0.066	7.00	Pass		
RB12#6		18.53		2	-0.15	18.38	0.069	7.00	Pass		
RB12#13		18.37		2	-0.15	18.22	0.066	7.00	Pass		
RB25#0		18.43		2	-0.15	18.28	0.067	7.00	Pass		
HCH	QPSK	RB1#0	20.26	2	-0.15	20.11	0.103	7.00	Pass		

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND26(824~849 MHz)										
			RB1#13	20.4	2	-0.15	20.25	0.106	7.00	Pass
			RB1#24	20.24	2	-0.15	20.09	0.102	7.00	Pass
			RB12#0	19.11	2	-0.15	18.96	0.079	7.00	Pass
			RB12#6	19.3	2	-0.15	19.15	0.082	7.00	Pass
			RB12#13	19.05	2	-0.15	18.90	0.078	7.00	Pass
			RB25#0	19.36	2	-0.15	19.21	0.083	7.00	Pass
		16-QAM	RB1#0	19.27	2	-0.15	19.12	0.082	7.00	Pass
			RB1#13	19.53	2	-0.15	19.38	0.087	7.00	Pass
			RB1#24	19.32	2	-0.15	19.17	0.083	7.00	Pass
			RB12#0	18.3	2	-0.15	18.15	0.065	7.00	Pass
			RB12#6	18.37	2	-0.15	18.22	0.066	7.00	Pass
			RB12#13	18.26	2	-0.15	18.11	0.065	7.00	Pass
			RB25#0	18.33	2	-0.15	18.18	0.066	7.00	Pass
			10 MHz	MCH	QPSK	RB1#0	19.86	2	-0.15	19.71
RB1#25	20.01	2				-0.15	19.86	0.097	7.00	Pass
RB1#49	20.21	2				-0.15	20.06	0.101	7.00	Pass
RB25#0	19.1	2				-0.15	18.95	0.079	7.00	Pass
RB25#13	18.91	2				-0.15	18.76	0.075	7.00	Pass
RB25#25	19.07	2				-0.15	18.92	0.078	7.00	Pass
RB50#0	18.95	2				-0.15	18.80	0.076	7.00	Pass
16-QAM	RB1#0	18.89		2	-0.15	18.74	0.075	7.00	Pass	
	RB1#25	18.91		2	-0.15	18.76	0.075	7.00	Pass	
	RB1#49	18.98		2	-0.15	18.83	0.076	7.00	Pass	
	RB25#0	18.18		2	-0.15	18.03	0.064	7.00	Pass	
	RB25#13	17.9		2	-0.15	17.75	0.060	7.00	Pass	
	RB25#25	18.05		2	-0.15	17.90	0.062	7.00	Pass	
	RB50#0	17.94		2	-0.15	17.79	0.060	7.00	Pass	
MCH	QPSK	RB1#0	20.12	2	-0.15	19.97	0.099	7.00	Pass	
		RB1#25	20.1	2	-0.15	19.95	0.099	7.00	Pass	
		RB1#49	19.85	2	-0.15	19.70	0.093	7.00	Pass	
		RB25#0	18.95	2	-0.15	18.80	0.076	7.00	Pass	
		RB25#13	18.99	2	-0.15	18.84	0.077	7.00	Pass	
		RB25#25	18.81	2	-0.15	18.66	0.073	7.00	Pass	
		RB50#0	18.97	2	-0.15	18.82	0.076	7.00	Pass	
	16-QAM	RB1#0	19.45	2	-0.15	19.30	0.085	7.00	Pass	
		RB1#25	19.42	2	-0.15	19.27	0.085	7.00	Pass	
		RB1#49	19.22	2	-0.15	19.07	0.081	7.00	Pass	
			RB25#0	18.01	2	-0.15	17.86	0.061	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict	
LTE BAND26(824~849 MHz)											
15 MHz	HCH	QPSK	RB25#13	18.01	2	-0.15	17.86	0.061	7.00	Pass	
			RB25#25	17.83	2	-0.15	17.68	0.059	7.00	Pass	
			RB50#0	17.99	2	-0.15	17.84	0.061	7.00	Pass	
		16-QAM	QPSK	RB1#0	19.74	2	-0.15	19.59	0.091	7.00	Pass
				RB1#25	19.66	2	-0.15	19.51	0.089	7.00	Pass
				RB1#49	19.88	2	-0.15	19.73	0.094	7.00	Pass
			16-QAM	RB25#0	18.6	2	-0.15	18.45	0.070	7.00	Pass
				RB25#13	18.68	2	-0.15	18.53	0.071	7.00	Pass
				RB25#25	19.02	2	-0.15	18.87	0.077	7.00	Pass
	RB50#0			18.9	2	-0.15	18.75	0.075	7.00	Pass	
	RB1#0			18.78	2	-0.15	18.63	0.073	7.00	Pass	
	RB1#25			18.71	2	-0.15	18.56	0.072	7.00	Pass	
	LCH	QPSK	RB1#49	18.94	2	-0.15	18.79	0.076	7.00	Pass	
			RB25#0	17.69	2	-0.15	17.54	0.057	7.00	Pass	
			RB25#13	17.89	2	-0.15	17.74	0.059	7.00	Pass	
			RB25#25	18.1	2	-0.15	17.95	0.062	7.00	Pass	
			RB50#0	17.98	2	-0.15	17.83	0.061	7.00	Pass	
			RB1#0	19.99	2	-0.15	19.84	0.096	7.00	Pass	
16-QAM		RB1#38	20.12	2	-0.15	19.97	0.099	7.00	Pass		
		RB1#74	20.17	2	-0.15	20.02	0.100	7.00	Pass		
		RB36#0	19.04	2	-0.15	18.89	0.077	7.00	Pass		
	RB36#19	19.17	2	-0.15	19.02	0.080	7.00	Pass			
	RB36#39	19.23	2	-0.15	19.08	0.081	7.00	Pass			
	RB75#0	19.14	2	-0.15	18.99	0.079	7.00	Pass			
	RB1#0	19.03	2	-0.15	18.88	0.077	7.00	Pass			
MCH	QPSK	RB1#38	19.04	2	-0.15	18.89	0.077	7.00	Pass		
		RB1#74	19.17	2	-0.15	19.02	0.080	7.00	Pass		
		RB36#0	17.94	2	-0.15	17.79	0.060	7.00	Pass		
		RB36#19	18.08	2	-0.15	17.93	0.062	7.00	Pass		
		RB36#39	18.15	2	-0.15	18.00	0.063	7.00	Pass		
		RB75#0	18.09	2	-0.15	17.94	0.062	7.00	Pass		
		RB1#0	20.06	2	-0.15	19.91	0.098	7.00	Pass		
RB1#38	20.25	2	-0.15	20.10	0.102	7.00	Pass				
RB1#74	20.08	2	-0.15	19.93	0.098	7.00	Pass				
RB36#0	19.04	2	-0.15	18.89	0.077	7.00	Pass				
RB36#19	19.26	2	-0.15	19.11	0.081	7.00	Pass				
RB36#39	19.01	2	-0.15	18.86	0.077	7.00	Pass				
RB75#0	19.06	2	-0.15	18.91	0.078	7.00	Pass				

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND26(824~849 MHz)										
		16-QAM	RB1#0	19.53	2	-0.15	19.38	0.087	7.00	Pass
			RB1#38	19.69	2	-0.15	19.54	0.090	7.00	Pass
			RB1#74	19.4	2	-0.15	19.25	0.084	7.00	Pass
			RB36#0	18.13	2	-0.15	17.98	0.063	7.00	Pass
			RB36#19	18.23	2	-0.15	18.08	0.064	7.00	Pass
			RB36#39	17.97	2	-0.15	17.82	0.061	7.00	Pass
			RB75#0	18.18	2	-0.15	18.03	0.064	7.00	Pass
		QPSK	RB1#0	20.15	2	-0.15	20.00	0.100	7.00	Pass
			RB1#38	19.69	2	-0.15	19.54	0.090	7.00	Pass
			RB1#74	20.12	2	-0.15	19.97	0.099	7.00	Pass
			RB36#0	18.77	2	-0.15	18.62	0.073	7.00	Pass
			RB36#19	18.76	2	-0.15	18.61	0.073	7.00	Pass
			RB36#39	19.04	2	-0.15	18.89	0.077	7.00	Pass
			RB75#0	19.03	2	-0.15	18.88	0.077	7.00	Pass
	16-QAM	RB1#0	19.61	2	-0.15	19.46	0.088	7.00	Pass	
		RB1#38	19.12	2	-0.15	18.97	0.079	7.00	Pass	
		RB1#74	19.6	2	-0.15	19.45	0.088	7.00	Pass	
		RB36#0	17.75	2	-0.15	17.60	0.058	7.00	Pass	
		RB36#19	17.7	2	-0.15	17.55	0.057	7.00	Pass	
		RB36#39	18.13	2	-0.15	17.98	0.063	7.00	Pass	
		RB75#0	17.99	2	-0.15	17.84	0.061	7.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND26(814~824 MHz)										
1.4 MHz	LCH	QPSK	RB1#0	20.14	2	-0.15	19.99	0.100	100	Pass
			RB1#3	19.91	2	-0.15	19.76	0.095	100	Pass
			RB1#5	20.3	2	-0.15	20.15	0.104	100	Pass
			RB3#0	20.03	2	-0.15	19.88	0.097	100	Pass
			RB3#2	19.9	2	-0.15	19.75	0.094	100	Pass
			RB3#3	20.13	2	-0.15	19.98	0.100	100	Pass
			RB6#0	19.05	2	-0.15	18.90	0.078	100	Pass
		16-QAM	RB1#0	19.23	2	-0.15	19.08	0.081	100	Pass
			RB1#3	19.05	2	-0.15	18.90	0.078	100	Pass
			RB1#5	19.4	2	-0.15	19.25	0.084	100	Pass
			RB3#0	19.09	2	-0.15	18.94	0.078	100	Pass
			RB3#2	18.97	2	-0.15	18.82	0.076	100	Pass
			RB3#3	19.13	2	-0.15	18.98	0.079	100	Pass
			RB6#0	18.02	2	-0.15	17.87	0.061	100	Pass
	MCH	QPSK	RB1#0	20.4	2	-0.15	20.25	0.106	100	Pass
			RB1#3	20	2	-0.15	19.85	0.097	100	Pass
			RB1#5	20.31	2	-0.15	20.16	0.104	100	Pass
			RB3#0	20.35	2	-0.15	20.20	0.105	100	Pass
			RB3#2	20.07	2	-0.15	19.92	0.098	100	Pass
			RB3#3	20.14	2	-0.15	19.99	0.100	100	Pass
			RB6#0	19.12	2	-0.15	18.97	0.079	100	Pass
		16-QAM	RB1#0	19.73	2	-0.15	19.58	0.091	100	Pass
			RB1#3	19.35	2	-0.15	19.20	0.083	100	Pass
			RB1#5	19.51	2	-0.15	19.36	0.086	100	Pass
			RB3#0	19.39	2	-0.15	19.24	0.084	100	Pass
			RB3#2	19.12	2	-0.15	18.97	0.079	100	Pass
			RB3#3	19.34	2	-0.15	19.19	0.083	100	Pass
			RB6#0	18.17	2	-0.15	18.02	0.063	100	Pass
	HCH	QPSK	RB1#0	19.7	2	-0.15	19.55	0.090	100	Pass
			RB1#3	19.67	2	-0.15	19.52	0.090	100	Pass
RB1#5			19.95	2	-0.15	19.80	0.095	100	Pass	
RB3#0			19.76	2	-0.15	19.61	0.091	100	Pass	
RB3#2			19.73	2	-0.15	19.58	0.091	100	Pass	
RB3#3			19.94	2	-0.15	19.79	0.095	100	Pass	
RB6#0			18.88	2	-0.15	18.73	0.075	100	Pass	
16-QAM		RB1#0	18.89	2	-0.15	18.74	0.075	100	Pass	
		RB1#3	18.86	2	-0.15	18.71	0.074	100	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND26(814~824 MHz)										
3 MHz			RB1#5	19.1	2	-0.15	18.95	0.079	100	Pass
			RB3#0	19.08	2	-0.15	18.93	0.078	100	Pass
			RB3#2	19.03	2	-0.15	18.88	0.077	100	Pass
			RB3#3	19.22	2	-0.15	19.07	0.081	100	Pass
			RB6#0	17.91	2	-0.15	17.76	0.060	100	Pass
	LCH	QPSK	RB1#0	20.09	2	-0.15	19.94	0.099	100	Pass
			RB1#7	20.15	2	-0.15	20.00	0.100	100	Pass
			RB1#14	20.61	2	-0.15	20.46	0.111	100	Pass
			RB8#0	18.83	2	-0.15	18.68	0.074	100	Pass
			RB8#4	19.26	2	-0.15	19.11	0.081	100	Pass
			RB8#7	19.25	2	-0.15	19.10	0.081	100	Pass
		RB15#0	19.16	2	-0.15	19.01	0.080	100	Pass	
		16-QAM	RB1#0	18.88	2	-0.15	18.73	0.075	100	Pass
			RB1#7	18.98	2	-0.15	18.83	0.076	100	Pass
			RB1#14	19.42	2	-0.15	19.27	0.085	100	Pass
			RB8#0	17.82	2	-0.15	17.67	0.058	100	Pass
			RB8#4	18.26	2	-0.15	18.11	0.065	100	Pass
			RB8#7	18.34	2	-0.15	18.19	0.066	100	Pass
	RB15#0	18.11	2	-0.15	17.96	0.063	100	Pass		
	MCH	QPSK	RB1#0	20.52	2	-0.15	20.37	0.109	100	Pass
			RB1#7	20.04	2	-0.15	19.89	0.097	100	Pass
			RB1#14	20.01	2	-0.15	19.86	0.097	100	Pass
			RB8#0	19.1	2	-0.15	18.95	0.079	100	Pass
			RB8#4	19.09	2	-0.15	18.94	0.078	100	Pass
			RB8#7	18.95	2	-0.15	18.80	0.076	100	Pass
		RB15#0	19.04	2	-0.15	18.89	0.077	100	Pass	
		16-QAM	RB1#0	19.86	2	-0.15	19.71	0.094	100	Pass
			RB1#7	19.32	2	-0.15	19.17	0.083	100	Pass
RB1#14			19.37	2	-0.15	19.22	0.084	100	Pass	
RB8#0			18.2	2	-0.15	18.05	0.064	100	Pass	
RB8#4			18.18	2	-0.15	18.03	0.064	100	Pass	
RB8#7	18.02		2	-0.15	17.87	0.061	100	Pass		
RB15#0	18.19	2	-0.15	18.04	0.064	100	Pass			
HCH	QPSK	RB1#0	19.93	2	-0.15	19.78	0.095	100	Pass	
		RB1#7	19.68	2	-0.15	19.53	0.090	100	Pass	
		RB1#14	20.13	2	-0.15	19.98	0.100	100	Pass	
		RB8#0	18.33	2	-0.15	18.18	0.066	100	Pass	
		RB8#4	18.71	2	-0.15	18.56	0.072	100	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict		
LTE BAND26(814~824 MHz)												
		16-QAM	RB8#7	18.75	2	-0.15	18.60	0.072	100	Pass		
			RB15#0	18.72	2	-0.15	18.57	0.072	100	Pass		
			RB1#0	18.99	2	-0.15	18.84	0.077	100	Pass		
			RB1#7	18.75	2	-0.15	18.60	0.072	100	Pass		
			RB1#14	19.15	2	-0.15	19.00	0.079	100	Pass		
			RB8#0	17.32	2	-0.15	17.17	0.052	100	Pass		
			RB8#4	17.74	2	-0.15	17.59	0.057	100	Pass		
			RB8#7	17.74	2	-0.15	17.59	0.057	100	Pass		
		5 MHz	LCH	QPSK	RB1#0	20.11	2	-0.15	19.96	0.099	100	Pass
					RB1#13	20.44	2	-0.15	20.29	0.107	100	Pass
					RB1#24	20.33	2	-0.15	20.18	0.104	100	Pass
					RB12#0	18.95	2	-0.15	18.80	0.076	100	Pass
					RB12#6	19.19	2	-0.15	19.04	0.080	100	Pass
					RB12#13	19.24	2	-0.15	19.09	0.081	100	Pass
					RB25#0	19.3	2	-0.15	19.15	0.082	100	Pass
				16-QAM	RB1#0	19.14	2	-0.15	18.99	0.079	100	Pass
RB1#13	19.46				2	-0.15	19.31	0.085	100	Pass		
RB1#24	19.36				2	-0.15	19.21	0.083	100	Pass		
RB12#0	18.06				2	-0.15	17.91	0.062	100	Pass		
RB12#6	18.26				2	-0.15	18.11	0.065	100	Pass		
RB12#13	18.46				2	-0.15	18.31	0.068	100	Pass		
RB25#0	18.33				2	-0.15	18.18	0.066	100	Pass		
MCH	QPSK			RB1#0	20.58	2	-0.15	20.43	0.110	100	Pass	
				RB1#13	20.12	2	-0.15	19.97	0.099	100	Pass	
		RB1#24	19.86	2	-0.15	19.71	0.094	100	Pass			
		RB12#0	19.16	2	-0.15	19.01	0.080	100	Pass			
		RB12#6	18.95	2	-0.15	18.80	0.076	100	Pass			
		RB12#13	18.65	2	-0.15	18.50	0.071	100	Pass			
		RB25#0	19.09	2	-0.15	18.94	0.078	100	Pass			
	16-QAM	RB1#0	20	2	-0.15	19.85	0.097	100	Pass			
		RB1#13	19.57	2	-0.15	19.42	0.087	100	Pass			
		RB1#24	19.41	2	-0.15	19.26	0.084	100	Pass			
		RB12#0	18.29	2	-0.15	18.14	0.065	100	Pass			
		RB12#6	18.23	2	-0.15	18.08	0.064	100	Pass			
		RB12#13	17.92	2	-0.15	17.77	0.060	100	Pass			
		RB25#0	18.29	2	-0.15	18.14	0.065	100	Pass			
HCH	QPSK	RB1#0	20.15	2	-0.15	20.00	0.100	100	Pass			

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND26(814~824 MHz)										
			RB1#13	19.65	2	-0.15	19.50	0.089	100	Pass
			RB1#24	19.87	2	-0.15	19.72	0.094	100	Pass
			RB12#0	18.58	2	-0.15	18.43	0.070	100	Pass
			RB12#6	18.65	2	-0.15	18.50	0.071	100	Pass
			RB12#13	18.52	2	-0.15	18.37	0.069	100	Pass
			RB25#0	18.88	2	-0.15	18.73	0.075	100	Pass
		16-QAM	RB1#0	19.39	2	-0.15	19.24	0.084	100	Pass
			RB1#13	18.69	2	-0.15	18.54	0.071	100	Pass
			RB1#24	19.1	2	-0.15	18.95	0.079	100	Pass
			RB12#0	17.72	2	-0.15	17.57	0.057	100	Pass
			RB12#6	17.68	2	-0.15	17.53	0.057	100	Pass
			RB12#13	17.62	2	-0.15	17.47	0.056	100	Pass
			RB25#0	17.82	2	-0.15	17.67	0.058	100	Pass
			10 MHz	MCH	QPSK	RB1#0	19.8	2	-0.15	19.65
RB1#25	19.71	2				-0.15	19.56	0.090	100	Pass
RB1#49	19.76	2				-0.15	19.61	0.091	100	Pass
RB25#0	19.07	2				-0.15	18.92	0.078	100	Pass
RB25#13	18.62	2				-0.15	18.47	0.070	100	Pass
RB25#25	18.65	2				-0.15	18.50	0.071	100	Pass
RB50#0	18.71	2				-0.15	18.56	0.072	100	Pass
16-QAM	RB1#0	18.76			2	-0.15	18.61	0.073	100	Pass
	RB1#25	18.66			2	-0.15	18.51	0.071	100	Pass
	RB1#49	18.7			2	-0.15	18.55	0.072	100	Pass
	RB25#0	18.08			2	-0.15	17.93	0.062	100	Pass
	RB25#13	17.75			2	-0.15	17.60	0.058	100	Pass
	RB25#25	17.46			2	-0.15	17.31	0.054	100	Pass
	RB50#0	17.84			2	-0.15	17.69	0.059	100	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND66									
1.4 MHz	LCH	QPSK	RB1#0	19.41	2	21.41	0.138	1.00	Pass
			RB1#3	19.11	2	21.11	0.129	1.00	Pass
			RB1#5	19.26	2	21.26	0.134	1.00	Pass
			RB3#0	19.41	2	21.41	0.138	1.00	Pass
			RB3#2	19.17	2	21.17	0.131	1.00	Pass
			RB3#3	19.22	2	21.22	0.132	1.00	Pass
			RB6#0	18.3	2	20.30	0.107	1.00	Pass
		16-QAM	RB1#0	18.49	2	20.49	0.112	1.00	Pass
			RB1#3	18.49	2	20.49	0.112	1.00	Pass
			RB1#5	18.61	2	20.61	0.115	1.00	Pass
			RB3#0	18.51	2	20.51	0.112	1.00	Pass
			RB3#2	18.31	2	20.31	0.107	1.00	Pass
			RB3#3	18.41	2	20.41	0.110	1.00	Pass
			RB6#0	17.32	2	19.32	0.086	1.00	Pass
	MCH	QPSK	RB1#0	18.83	2	20.83	0.121	1.00	Pass
			RB1#3	18.76	2	20.76	0.119	1.00	Pass
			RB1#5	18.98	2	20.98	0.125	1.00	Pass
			RB3#0	18.81	2	20.81	0.121	1.00	Pass
			RB3#2	18.68	2	20.68	0.117	1.00	Pass
			RB3#3	18.96	2	20.96	0.125	1.00	Pass
			RB6#0	17.98	2	19.98	0.100	1.00	Pass
		16-QAM	RB1#0	18.32	2	20.32	0.108	1.00	Pass
			RB1#3	18.26	2	20.26	0.106	1.00	Pass
			RB1#5	18.38	2	20.38	0.109	1.00	Pass
			RB3#0	18.14	2	20.14	0.103	1.00	Pass
			RB3#2	18.02	2	20.02	0.100	1.00	Pass
			RB3#3	18.19	2	20.19	0.104	1.00	Pass
			RB6#0	16.69	2	18.69	0.074	1.00	Pass
	HCH	QPSK	RB1#0	20.16	2	22.16	0.164	1.00	Pass
			RB1#3	20.14	2	22.14	0.164	1.00	Pass
RB1#5			20.49	2	22.49	0.177	1.00	Pass	
RB3#0			20.13	2	22.13	0.163	1.00	Pass	
RB3#2			20.19	2	22.19	0.166	1.00	Pass	
RB3#3			20.43	2	22.43	0.175	1.00	Pass	
RB6#0			19.35	2	21.35	0.136	1.00	Pass	
16-QAM		RB1#0	19.28	2	21.28	0.134	1.00	Pass	
		RB1#3	19.38	2	21.38	0.137	1.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND66									
3 MHz			RB1#5	19.72	2	21.72	0.149	1.00	Pass
			RB3#0	19.46	2	21.46	0.140	1.00	Pass
			RB3#2	19.55	2	21.55	0.143	1.00	Pass
			RB3#3	19.76	2	21.76	0.150	1.00	Pass
			RB6#0	18.73	2	20.73	0.118	1.00	Pass
	LCH	QPSK	RB1#0	19.41	2	21.41	0.138	1.00	Pass
			RB1#7	18.87	2	20.87	0.122	1.00	Pass
			RB1#14	18.77	2	20.77	0.119	1.00	Pass
			RB8#0	17.91	2	19.91	0.098	1.00	Pass
			RB8#4	17.92	2	19.92	0.098	1.00	Pass
			RB8#7	17.74	2	19.74	0.094	1.00	Pass
			RB15#0	17.97	2	19.97	0.099	1.00	Pass
		16-QAM	RB1#0	18.49	2	20.49	0.112	1.00	Pass
			RB1#7	17.74	2	19.74	0.094	1.00	Pass
			RB1#14	17.63	2	19.63	0.092	1.00	Pass
			RB8#0	17.06	2	19.06	0.081	1.00	Pass
			RB8#4	17.08	2	19.08	0.081	1.00	Pass
			RB8#7	16.95	2	18.95	0.079	1.00	Pass
			RB15#0	16.96	2	18.96	0.079	1.00	Pass
	MCH	QPSK	RB1#0	18.62	2	20.62	0.115	1.00	Pass
			RB1#7	18.74	2	20.74	0.119	1.00	Pass
			RB1#14	18.87	2	20.87	0.122	1.00	Pass
			RB8#0	17.34	2	19.34	0.086	1.00	Pass
			RB8#4	17.84	2	19.84	0.096	1.00	Pass
			RB8#7	17.75	2	19.75	0.094	1.00	Pass
			RB15#0	17.81	2	19.81	0.096	1.00	Pass
		16-QAM	RB1#0	18.08	2	20.08	0.102	1.00	Pass
			RB1#7	18.09	2	20.09	0.102	1.00	Pass
RB1#14			18.39	2	20.39	0.109	1.00	Pass	
RB8#0			16.51	2	18.51	0.071	1.00	Pass	
RB8#4			16.85	2	18.85	0.077	1.00	Pass	
RB8#7			16.73	2	18.73	0.075	1.00	Pass	
RB15#0			16.73	2	18.73	0.075	1.00	Pass	
HCH	QPSK	RB1#0	19.53	2	21.53	0.142	1.00	Pass	
		RB1#7	19.99	2	21.99	0.158	1.00	Pass	
		RB1#14	20.53	2	22.53	0.179	1.00	Pass	
		RB8#0	18.48	2	20.48	0.112	1.00	Pass	
		RB8#4	18.98	2	20.98	0.125	1.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict		
LTE BAND66											
		16-QAM	RB8#7	19.23	2	21.23	0.133	1.00	Pass		
			RB15#0	19.05	2	21.05	0.127	1.00	Pass		
			RB1#0	18.67	2	20.67	0.117	1.00	Pass		
			RB1#7	19.26	2	21.26	0.134	1.00	Pass		
			RB1#14	19.71	2	21.71	0.148	1.00	Pass		
			RB8#0	17.4	2	19.40	0.087	1.00	Pass		
			RB8#4	18.04	2	20.04	0.101	1.00	Pass		
			RB8#7	18.35	2	20.35	0.108	1.00	Pass		
					RB15#0	17.9	2	19.90	0.098	1.00	Pass
		5 MHz	LCH	QPSK	RB1#0	19.41	2	21.41	0.138	1.00	Pass
					RB1#13	18.74	2	20.74	0.119	1.00	Pass
					RB1#24	18.47	2	20.47	0.111	1.00	Pass
					RB12#0	17.98	2	19.98	0.100	1.00	Pass
					RB12#6	17.72	2	19.72	0.094	1.00	Pass
					RB12#13	17.33	2	19.33	0.086	1.00	Pass
							RB25#0	17.82	2	19.82	0.096
				16-QAM	RB1#0	18.7	2	20.70	0.117	1.00	Pass
					RB1#13	17.8	2	19.80	0.095	1.00	Pass
					RB1#24	17.59	2	19.59	0.091	1.00	Pass
					RB12#0	16.9	2	18.90	0.078	1.00	Pass
					RB12#6	16.82	2	18.82	0.076	1.00	Pass
			RB12#13		16.45	2	18.45	0.070	1.00	Pass	
				RB25#0	16.81	2	18.81	0.076	1.00	Pass	
	MCH		QPSK	RB1#0	18.63	2	20.63	0.116	1.00	Pass	
					RB1#13	18.81	2	20.81	0.121	1.00	Pass
					RB1#24	18.78	2	20.78	0.120	1.00	Pass
					RB12#0	17.38	2	19.38	0.087	1.00	Pass
					RB12#6	17.9	2	19.90	0.098	1.00	Pass
					RB12#13	17.67	2	19.67	0.093	1.00	Pass
					RB25#0	17.88	2	19.88	0.097	1.00	Pass
				16-QAM	RB1#0	18.18	2	20.18	0.104	1.00	Pass
					RB1#13	18.46	2	20.46	0.111	1.00	Pass
					RB1#24	18.43	2	20.43	0.110	1.00	Pass
			RB12#0		16.43	2	18.43	0.070	1.00	Pass	
			RB12#6		16.85	2	18.85	0.077	1.00	Pass	
		RB12#13	16.75		2	18.75	0.075	1.00	Pass		
			RB25#0	16.75	2	18.75	0.075	1.00	Pass		
	HCH	QPSK	RB1#0	18.1	2	20.10	0.102	1.00	Pass		

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND66									
			RB1#13	19.63	2	21.63	0.146	1.00	Pass
			RB1#24	20.5	2	22.50	0.178	1.00	Pass
			RB12#0	17.12	2	19.12	0.082	1.00	Pass
			RB12#6	18.5	2	20.50	0.112	1.00	Pass
			RB12#13	18.89	2	20.89	0.123	1.00	Pass
			RB25#0	18.57	2	20.57	0.114	1.00	Pass
		16-QAM	RB1#0	17.32	2	19.32	0.086	1.00	Pass
			RB1#13	18.9	2	20.90	0.123	1.00	Pass
			RB1#24	19.81	2	21.81	0.152	1.00	Pass
			RB12#0	16.24	2	18.24	0.067	1.00	Pass
			RB12#6	17.35	2	19.35	0.086	1.00	Pass
			RB12#13	17.86	2	19.86	0.097	1.00	Pass
			RB25#0	17.33	2	19.33	0.086	1.00	Pass
			10 MHz	LCH	QPSK	RB1#0	19.08	2	21.08
RB1#25	17.95	2				19.95	0.099	1.00	Pass
RB1#49	17.79	2				19.79	0.095	1.00	Pass
RB25#0	17.4	2				19.40	0.087	1.00	Pass
RB25#13	16.99	2				18.99	0.079	1.00	Pass
RB25#25	16.81	2				18.81	0.076	1.00	Pass
16-QAM	RB50#0	17.18			2	19.18	0.083	1.00	Pass
	RB1#0	18.09			2	20.09	0.102	1.00	Pass
	RB1#25	16.97			2	18.97	0.079	1.00	Pass
	RB1#49	16.79			2	18.79	0.076	1.00	Pass
	RB25#0	16.5			2	18.50	0.071	1.00	Pass
	RB25#13	16.13			2	18.13	0.065	1.00	Pass
	RB25#25	15.94			2	17.94	0.062	1.00	Pass
	RB50#0	16.21			2	18.21	0.066	1.00	Pass
10 MHz	MCH	QPSK	RB1#0	18.26	2	20.26	0.106	1.00	Pass
			RB1#25	18.57	2	20.57	0.114	1.00	Pass
			RB1#49	18.64	2	20.64	0.116	1.00	Pass
			RB25#0	17.13	2	19.13	0.082	1.00	Pass
			RB25#13	17.18	2	19.18	0.083	1.00	Pass
			RB25#25	17.36	2	19.36	0.086	1.00	Pass
		16-QAM	RB50#0	17.56	2	19.56	0.090	1.00	Pass
			RB1#0	17.74	2	19.74	0.094	1.00	Pass
			RB1#25	17.8	2	19.80	0.095	1.00	Pass
			RB1#49	17.9	2	19.90	0.098	1.00	Pass
			RB25#0	16.22	2	18.22	0.066	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND66									
15 MHz	HCH	QPSK	RB25#13	16.25	2	18.25	0.067	1.00	Pass
			RB25#25	16.45	2	18.45	0.070	1.00	Pass
			RB50#0	16.38	2	18.38	0.069	1.00	Pass
		16-QAM	RB1#0	17.74	2	19.74	0.094	1.00	Pass
			RB1#25	17.66	2	19.66	0.092	1.00	Pass
			RB1#49	20.23	2	22.23	0.167	1.00	Pass
			RB25#0	16.55	2	18.55	0.072	1.00	Pass
			RB25#13	16.81	2	18.81	0.076	1.00	Pass
			RB25#25	17.94	2	19.94	0.099	1.00	Pass
			RB50#0	17.07	2	19.07	0.081	1.00	Pass
			RB1#0	16.77	2	18.77	0.075	1.00	Pass
			RB1#25	16.63	2	18.63	0.073	1.00	Pass
	RB1#49	19.42	2	21.42	0.139	1.00	Pass		
	LCH	QPSK	RB1#0	19.14	2	21.14	0.130	1.00	Pass
			RB1#38	17.89	2	19.89	0.097	1.00	Pass
			RB1#74	17.61	2	19.61	0.091	1.00	Pass
			RB36#0	17.18	2	19.18	0.083	1.00	Pass
			RB36#19	16.88	2	18.88	0.077	1.00	Pass
			RB36#39	16.67	2	18.67	0.074	1.00	Pass
			RB75#0	16.92	2	18.92	0.078	1.00	Pass
		16-QAM	RB1#0	17.98	2	19.98	0.100	1.00	Pass
RB1#38			16.93	2	18.93	0.078	1.00	Pass	
RB1#74			16.57	2	18.57	0.072	1.00	Pass	
RB36#0			16.25	2	18.25	0.067	1.00	Pass	
RB36#19			15.94	2	17.94	0.062	1.00	Pass	
RB36#39			15.67	2	17.67	0.058	1.00	Pass	
RB75#0			16.01	2	18.01	0.063	1.00	Pass	
MCH			QPSK	RB1#0	18.01	2	20.01	0.100	1.00
	RB1#38	18.76		2	20.76	0.119	1.00	Pass	
	RB1#74	18.48		2	20.48	0.112	1.00	Pass	
	RB36#0	17.18		2	19.18	0.083	1.00	Pass	
	RB36#19	17.73		2	19.73	0.094	1.00	Pass	
	RB36#39	17.59		2	19.59	0.091	1.00	Pass	
	RB75#0	17.42		2	19.42	0.087	1.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND66									
20 MHz	HCH	16-QAM	RB1#0	17.3	2	19.30	0.085	1.00	Pass
			RB1#38	18.25	2	20.25	0.106	1.00	Pass
			RB1#74	17.69	2	19.69	0.093	1.00	Pass
			RB36#0	16.25	2	18.25	0.067	1.00	Pass
			RB36#19	16.65	2	18.65	0.073	1.00	Pass
			RB36#39	16.66	2	18.66	0.073	1.00	Pass
			RB75#0	16.47	2	18.47	0.070	1.00	Pass
		QPSK	RB1#0	17.58	2	19.58	0.091	1.00	Pass
			RB1#38	17.65	2	19.65	0.092	1.00	Pass
			RB1#74	20.25	2	22.25	0.168	1.00	Pass
			RB36#0	16.56	2	18.56	0.072	1.00	Pass
			RB36#19	16.79	2	18.79	0.076	1.00	Pass
			RB36#39	17.35	2	19.35	0.086	1.00	Pass
			RB75#0	16.97	2	18.97	0.079	1.00	Pass
	16-QAM	RB1#0	17.17	2	19.17	0.083	1.00	Pass	
		RB1#38	17.27	2	19.27	0.085	1.00	Pass	
		RB1#74	19.89	2	21.89	0.155	1.00	Pass	
		RB36#0	15.69	2	17.69	0.059	1.00	Pass	
		RB36#19	15.8	2	17.80	0.060	1.00	Pass	
		RB36#39	16.47	2	18.47	0.070	1.00	Pass	
		RB75#0	15.98	2	17.98	0.063	1.00	Pass	
	LCH	QPSK	RB1#0	19.05	2	21.05	0.127	1.00	Pass
			RB1#50	17.97	2	19.97	0.099	1.00	Pass
			RB1#99	17.63	2	19.63	0.092	1.00	Pass
			RB50#0	17.49	2	19.49	0.089	1.00	Pass
			RB50#25	16.97	2	18.97	0.079	1.00	Pass
			RB50#50	16.7	2	18.70	0.074	1.00	Pass
			RB100#0	16.99	2	18.99	0.079	1.00	Pass
16-QAM		RB1#0	18.47	2	20.47	0.111	1.00	Pass	
		RB1#50	17.46	2	19.46	0.088	1.00	Pass	
		RB1#99	17.19	2	19.19	0.083	1.00	Pass	
		RB50#0	16.51	2	18.51	0.071	1.00	Pass	
		RB50#25	16.08	2	18.08	0.064	1.00	Pass	
		RB50#50	15.8	2	17.80	0.060	1.00	Pass	
		RB100#0	16.11	2	18.11	0.065	1.00	Pass	
MCH	QPSK	RB1#0	18.06	2	20.06	0.101	1.00	Pass	
		RB1#50	18.99	2	20.99	0.126	1.00	Pass	
		RB1#99	18.62	2	20.62	0.115	1.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict		
LTE BAND66											
			RB50#0	17.45	2	19.45	0.088	1.00	Pass		
			RB50#25	17.81	2	19.81	0.096	1.00	Pass		
			RB50#50	17.69	2	19.69	0.093	1.00	Pass		
			RB100#0	17.47	2	19.47	0.089	1.00	Pass		
		16-QAM	RB1#0	17.47	2	19.47	0.089	1.00	Pass		
			RB1#50	18.28	2	20.28	0.107	1.00	Pass		
			RB1#99	17.92	2	19.92	0.098	1.00	Pass		
			RB50#0	16.34	2	18.34	0.068	1.00	Pass		
			RB50#25	16.7	2	18.70	0.074	1.00	Pass		
			RB50#50	16.68	2	18.68	0.074	1.00	Pass		
			RB100#0	16.51	2	18.51	0.071	1.00	Pass		
			HCH	QPSK	RB1#0	17.61	2	19.61	0.091	1.00	Pass
					RB1#50	17.76	2	19.76	0.095	1.00	Pass
					RB1#99	20.06	2	22.06	0.161	1.00	Pass
	RB50#0	16.65			2	18.65	0.073	1.00	Pass		
	RB50#25	16.81			2	18.81	0.076	1.00	Pass		
	RB50#50	17.18			2	19.18	0.083	1.00	Pass		
	RB100#0	16.98			2	18.98	0.079	1.00	Pass		
	16-QAM	RB1#0	17.13	2	19.13	0.082	1.00	Pass			
		RB1#50	17.32	2	19.32	0.086	1.00	Pass			
		RB1#99	19.63	2	21.63	0.146	1.00	Pass			
		RB50#0	15.77	2	17.77	0.060	1.00	Pass			
		RB50#25	15.72	2	17.72	0.059	1.00	Pass			
		RB50#50	16.16	2	18.16	0.065	1.00	Pass			
		RB100#0	16	2	18.00	0.063	1.00	Pass			

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND40(2305-2315MHz)									
5 MHz	LCH	QPSK	RB1#0	17.27	2	19.27	0.085	0.250	Pass
			RB1#13	17.25	2	19.25	0.084	0.250	Pass
			RB1#24	17.36	2	19.36	0.086	0.250	Pass
			RB12#0	15.99	2	17.99	0.063	0.250	Pass
			RB12#6	16.09	2	18.09	0.064	0.250	Pass
			RB12#13	16.03	2	18.03	0.064	0.250	Pass
			RB25#0	16.17	2	18.17	0.066	0.250	Pass
		16-QAM	RB1#0	16.39	2	18.39	0.069	0.250	Pass
			RB1#13	16.38	2	18.38	0.069	0.250	Pass
			RB1#24	16.56	2	18.56	0.072	0.250	Pass
			RB12#0	14.99	2	16.99	0.050	0.250	Pass
			RB12#6	15.06	2	17.06	0.051	0.250	Pass
			RB12#13	15.16	2	17.16	0.052	0.250	Pass
			RB25#0	15.1	2	17.10	0.051	0.250	Pass
	MCH	QPSK	RB1#0	17.28	2	19.28	0.085	0.250	Pass
			RB1#13	17.39	2	19.39	0.087	0.250	Pass
			RB1#24	17.37	2	19.37	0.086	0.250	Pass
			RB12#0	15.98	2	17.98	0.063	0.250	Pass
			RB12#6	16.3	2	18.30	0.068	0.250	Pass
			RB12#13	16.14	2	18.14	0.065	0.250	Pass
			RB25#0	16.42	2	18.42	0.070	0.250	Pass
		16-QAM	RB1#0	16.57	2	18.57	0.072	0.250	Pass
			RB1#13	16.66	2	18.66	0.073	0.250	Pass
			RB1#24	16.62	2	18.62	0.073	0.250	Pass
			RB12#0	14.93	2	16.93	0.049	0.250	Pass
			RB12#6	15.26	2	17.26	0.053	0.250	Pass
			RB12#13	15.08	2	17.08	0.051	0.250	Pass
			RB25#0	15.41	2	17.41	0.055	0.250	Pass
	HCH	QPSK	RB1#0	17.45	2	19.45	0.088	0.250	Pass
			RB1#13	17.22	2	19.22	0.084	0.250	Pass
			RB1#24	17.37	2	19.37	0.086	0.250	Pass
			RB12#0	16.05	2	18.05	0.064	0.250	Pass
RB12#6			16.19	2	18.19	0.066	0.250	Pass	
RB12#13			16.13	2	18.13	0.065	0.250	Pass	
RB25#0			16.33	2	18.33	0.068	0.250	Pass	
16-QAM		RB1#0	16.75	2	18.75	0.075	0.250	Pass	
		RB1#13	16.62	2	18.62	0.073	0.250	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict	
LTE BAND40(2305-2315MHz)										
10 MHz	MCH		RB1#24	16.82	2	18.82	0.076	0.250	Pass	
			RB12#0	15.12	2	17.12	0.052	0.250	Pass	
			RB12#6	15.27	2	17.27	0.053	0.250	Pass	
			RB12#13	15.2	2	17.20	0.052	0.250	Pass	
			RB25#0	15.3	2	17.30	0.054	0.250	Pass	
		QPSK	RB1#0	16.99	2	18.99	0.079	0.250	Pass	
			RB1#25	16.98	2	18.98	0.079	0.250	Pass	
			RB1#49	17.12	2	19.12	0.082	0.250	Pass	
			RB25#0	15.82	2	17.82	0.061	0.250	Pass	
			RB25#13	15.83	2	17.83	0.061	0.250	Pass	
			RB25#25	15.97	2	17.97	0.063	0.250	Pass	
			RB50#0	15.95	2	17.95	0.062	0.250	Pass	
			16-QAM	RB1#0	16.3	2	18.30	0.068	0.250	Pass
				RB1#25	16.21	2	18.21	0.066	0.250	Pass
				RB1#49	16.36	2	18.36	0.069	0.250	Pass
				RB25#0	14.93	2	16.93	0.049	0.250	Pass
				RB25#13	14.8	2	16.80	0.048	0.250	Pass
RB25#25	14.95	2		16.95	0.050	0.250	Pass			
RB50#0	14.92	2	16.92	0.049	0.250	Pass				

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND40(2350-2360MHz)									
5 MHz	LCH	QPSK	RB1#0	16.13	2	18.13	0.065	0.250	Pass
			RB1#13	16.36	2	18.36	0.069	0.250	Pass
			RB1#24	16.63	2	18.63	0.073	0.250	Pass
			RB12#0	14.78	2	16.78	0.048	0.250	Pass
			RB12#6	15.23	2	17.23	0.053	0.250	Pass
			RB12#13	15.34	2	17.34	0.054	0.250	Pass
			RB25#0	15.3	2	17.30	0.054	0.250	Pass
		16-QAM	RB1#0	15.38	2	17.38	0.055	0.250	Pass
			RB1#13	15.47	2	17.47	0.056	0.250	Pass
			RB1#24	15.79	2	17.79	0.060	0.250	Pass
			RB12#0	13.75	2	15.75	0.038	0.250	Pass
			RB12#6	14.18	2	16.18	0.041	0.250	Pass
			RB12#13	14.32	2	16.32	0.043	0.250	Pass
			RB25#0	14.21	2	16.21	0.042	0.250	Pass
	MCH	QPSK	RB1#0	16.41	2	18.41	0.069	0.250	Pass
			RB1#13	16.52	2	18.52	0.071	0.250	Pass
			RB1#24	16.84	2	18.84	0.077	0.250	Pass
			RB12#0	15.16	2	17.16	0.052	0.250	Pass
			RB12#6	15.41	2	17.41	0.055	0.250	Pass
			RB12#13	15.58	2	17.58	0.057	0.250	Pass
			RB25#0	15.54	2	17.54	0.057	0.250	Pass
		16-QAM	RB1#0	15.59	2	17.59	0.057	0.250	Pass
			RB1#13	15.78	2	17.78	0.060	0.250	Pass
			RB1#24	16.13	2	18.13	0.065	0.250	Pass
			RB12#0	14.08	2	16.08	0.041	0.250	Pass
			RB12#6	14.34	2	16.34	0.043	0.250	Pass
			RB12#13	14.49	2	16.49	0.045	0.250	Pass
			RB25#0	14.48	2	16.48	0.044	0.250	Pass
	HCH	QPSK	RB1#0	16.6	2	18.60	0.072	0.250	Pass
			RB1#13	16.86	2	18.86	0.077	0.250	Pass
RB1#24			17.14	2	19.14	0.082	0.250	Pass	
RB12#0			15.56	2	17.56	0.057	0.250	Pass	
RB12#6			15.71	2	17.71	0.059	0.250	Pass	
RB12#13			15.85	2	17.85	0.061	0.250	Pass	
RB25#0			15.84	2	17.84	0.061	0.250	Pass	
16-QAM		RB1#0	16.07	2	18.07	0.064	0.250	Pass	
		RB1#13	16.2	2	18.20	0.066	0.250	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND40(2350-2360MHz)									
10 MHz	MCH		RB1#24	16.46	2	18.46	0.070	0.250	Pass
			RB12#0	14.57	2	16.57	0.045	0.250	Pass
			RB12#6	14.79	2	16.79	0.048	0.250	Pass
			RB12#13	14.92	2	16.92	0.049	0.250	Pass
			RB25#0	14.82	2	16.82	0.048	0.250	Pass
		QPSK	RB1#0	15.83	2	17.83	0.061	0.250	Pass
			RB1#25	16.23	2	18.23	0.067	0.250	Pass
			RB1#49	16.88	2	18.88	0.077	0.250	Pass
			RB25#0	14.99	2	16.99	0.050	0.250	Pass
			RB25#13	15.12	2	17.12	0.052	0.250	Pass
			RB25#25	15.45	2	17.45	0.056	0.250	Pass
			RB50#0	15.24	2	17.24	0.053	0.250	Pass
		16-QAM	RB1#0	15.09	2	17.09	0.051	0.250	Pass
			RB1#25	15.43	2	17.43	0.055	0.250	Pass
			RB1#49	16.09	2	18.09	0.064	0.250	Pass
			RB25#0	13.92	2	15.92	0.039	0.250	Pass
			RB25#13	14.05	2	16.05	0.040	0.250	Pass
RB25#25	14.42		2	16.42	0.044	0.250	Pass		
RB50#0	14.14	2	16.14	0.041	0.250	Pass			

A.2 Peak to Average Ratio

Note 1: Test plots please refer to the document “Annex No.:BL-SZ2370302-501 Data Part 1.pdf”.

LTE Mode Test Data

Test Band	Test Band width	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note1}	Verdict
LTE Band 2	20 MHz	LCH	QPSK	RB1#0	5.48	13	1.1	Pass
				RB100#0	5.72	13	1.2	Pass
			16-QAM	RB1#0	5.91	13	1.3	Pass
				RB100#0	6.47	13	1.4	Pass
		MCH	QPSK	RB1#0	5.95	13	1.5	Pass
				RB100#0	5.91	13	1.6	Pass
			16-QAM	RB1#0	6.56	13	1.7	Pass
				RB100#0	6.61	13	1.8	Pass
		HCH	QPSK	RB1#0	5.86	13	1.9	Pass
				RB100#0	5.95	13	1.10	Pass
			16-QAM	RB1#0	6.89	13	1.11	Pass
				RB100#0	6.52	13	1.12	Pass
LTE Band 4	20 MHz	LCH	QPSK	RB1#0	5.91	13	2.1	Pass
				RB100#0	5.72	13	2.2	Pass
			16-QAM	RB1#0	7.03	13	2.3	Pass
				RB100#0	6.42	13	2.4	Pass
		MCH	QPSK	RB1#0	5.67	13	2.5	Pass
				RB100#0	5.91	13	2.6	Pass
			16-QAM	RB1#0	6.05	13	2.7	Pass
				RB100#0	6.52	13	2.8	Pass
		HCH	QPSK	RB1#0	5.91	13	2.9	Pass
				RB100#0	5.91	13	2.10	Pass
			16-QAM	RB1#0	6.47	13	2.11	Pass
				RB100#0	6.52	13	2.12	Pass
LTE Band 5	10 MHz	LCH	QPSK	RB1#0	5.2	13	3.1	Pass
				RB50#0	5.86	13	3.2	Pass
			16-QAM	RB1#0	5.77	13	3.3	Pass
				RB50#0	6.52	13	3.4	Pass
		MCH	QPSK	RB1#0	5.62	13	3.5	Pass
				RB50#0	5.53	13	3.6	Pass
			16-QAM	RB1#0	6.47	13	3.7	Pass
				RB50#0	6.23	13	3.8	Pass
		HCH	QPSK	RB1#0	5.67	13	3.9	Pass
				RB50#0	5.72	13	3.10	Pass
		16-QAM	RB1#0	6.42	13	3.11	Pass	

Test Band	Test Band width	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note1}	Verdict
				RB50#0	6.47	13	3.12	Pass
LTE Band 18 (824~830 MHz)	5 MHz	LCH	QPSK	RB1#0	5.81	13	4.1	Pass
				RB25#0	5.67	13	4.2	Pass
			16-QAM	RB1#0	6	13	4.3	Pass
				RB25#0	6.28	13	4.4	Pass
		MCH	QPSK	RB1#0	5.2	13	4.5	Pass
				RB25#0	5.67	13	4.6	Pass
			16-QAM	RB1#0	5.72	13	4.7	Pass
				RB25#0	6.28	13	4.8	Pass
		HCH	QPSK	RB1#0	5.34	13	4.9	Pass
				RB25#0	5.53	13	4.10	Pass
			16-QAM	RB1#0	5.95	13	4.11	Pass
				RB25#0	6.33	13	4.12	Pass
LTE Band 18 (815-824 MHz)	5 MHz	LCH	QPSK	RB1#0	5.48	13	5.1	Pass
				RB25#0	5.62	13	5.2	Pass
			16-QAM	RB1#0	6.14	13	5.3	Pass
				RB25#0	6.37	13	5.4	Pass
		MCH	QPSK	RB1#0	5.86	13	5.5	Pass
				RB25#0	5.72	13	5.6	Pass
			16-QAM	RB1#0	6.14	13	5.7	Pass
				RB25#0	6.33	13	5.8	Pass
		HCH	QPSK	RB1#0	5.34	13	5.9	Pass
				RB25#0	5.72	13	5.10	Pass
			16-QAM	RB1#0	5.81	13	5.11	Pass
				RB25#0	6.37	13	5.12	Pass
LTE Band 19	15 MHz	MCH	QPSK	RB1#0	5.62	13	6.1	Pass
				RB75#0	5.62	13	6.2	Pass
			16-QAM	RB1#0	6.19	13	6.3	Pass
				RB75#0	6.23	13	6.4	Pass
LTE Band 25	20 MHz	LCH	QPSK	RB1#0	5.44	13	7.1	Pass
				RB100#0	5.77	13	7.2	Pass
			16-QAM	RB1#0	5.86	13	7.3	Pass
				RB100#0	6.47	13	7.4	Pass
		MCH	QPSK	RB1#0	5.95	13	7.5	Pass
				RB100#0	5.81	13	7.6	Pass
			16-QAM	RB1#0	6.52	13	7.7	Pass
				RB100#0	6.56	13	7.8	Pass
		HCH	QPSK	RB1#0	5.95	13	7.9	Pass
				RB100#0	6	13	7.10	Pass

Test Band	Test Band width	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note1}	Verdict
			16-QAM	RB1#0	6.94	13	7.11	Pass
				RB100#0	6.61	13	7.12	Pass
LTE Band 26 (824~849 MHz)	15 MHz	LCH	QPSK	RB1#0	5.34	13	8.1	Pass
				RB75#0	5.95	13	8.2	Pass
			16-QAM	RB1#0	6.23	13	8.3	Pass
				RB75#0	6.37	13	8.4	Pass
		MCH	QPSK	RB1#0	5.34	13	8.5	Pass
				RB75#0	5.53	13	8.6	Pass
			16-QAM	RB1#0	6.28	13	8.7	Pass
				RB75#0	6.19	13	8.8	Pass
		HCH	QPSK	RB1#0	5.67	13	8.9	Pass
				RB75#0	6	13	8.10	Pass
			16-QAM	RB1#0	6.09	13	8.11	Pass
				RB75#0	6.47	13	8.12	Pass
LTE Band 26 (814~824 MHz)	10 MHz	MCH	QPSK	RB1#0	5.34	13	9.1	Pass
				RB50#0	5.39	13	9.2	Pass
			16-QAM	RB1#0	5.86	13	9.3	Pass
				RB50#0	6.28	13	9.4	Pass
LTE Band 66	20 MHz	LCH	QPSK	RB1#0	5.95	13	10.1	Pass
				RB100#0	5.77	13	10.2	Pass
			16-QAM	RB1#0	6.98	13	10.3	Pass
				RB100#0	6.42	13	10.4	Pass
		MCH	QPSK	RB1#0	5.67	13	10.5	Pass
				RB100#0	5.86	13	10.6	Pass
			16-QAM	RB1#0	6.09	13	10.7	Pass
				RB100#0	6.52	13	10.8	Pass
		HCH	QPSK	RB1#0	5.86	13	10.9	Pass
				RB100#0	5.86	13	10.10	Pass
			16-QAM	RB1#0	6.52	13	10.11	Pass
				RB100#0	6.56	13	10.12	Pass
LTE Band40 (2305-2315MHz)	10 MHz	MCH	QPSK	RB1#0	9.56	13	11.1	Pass
				RB50#0	9.42	13	11.2	Pass
			16-QAM	RB1#0	10.27	13	11.3	Pass
				RB50#0	10.08	13	11.4	Pass
LTE Band40 (2350-2360MHz)	10 MHz	MCH	QPSK	RB1#0	9.42	13	12.1	Pass
				RB50#0	9.33	13	12.2	Pass
			16-QAM	RB1#0	10.22	13	12.3	Pass
				RB50#0	10.03	13	12.4	Pass

A.3 Occupied Bandwidth

Note 1: All modes were tested, but only the typical data were reported in this report.

Note 2: Test plots please refer to the document “Annex No.:BL-SZ2370302-501 Data Part 2.pdf”.

LTE Mode Test Data

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 2	1.4 MHz	LCH	QPSK	RB6#0	1.092	1.252	1.1
			16-QAM	RB6#0	1.1	1.277	1.2
		MCH	QPSK	RB6#0	1.093	1.263	1.3
			16-QAM	RB6#0	1.089	1.253	1.4
		HCH	QPSK	RB6#0	1.095	1.266	1.5
			16-QAM	RB6#0	1.098	1.261	1.6
	3 MHz	LCH	QPSK	RB15#0	2.704	2.996	1.7
			16-QAM	RB15#0	2.704	3.014	1.8
		MCH	QPSK	RB15#0	2.699	3.002	1.9
			16-QAM	RB15#0	2.701	3.015	1.10
		HCH	QPSK	RB15#0	2.709	3.025	1.11
			16-QAM	RB15#0	2.704	3.009	1.12
	5 MHz	LCH	QPSK	RB25#0	4.518	5.065	1.13
			16-QAM	RB25#0	4.507	5.064	1.14
		MCH	QPSK	RB25#0	4.512	5.121	1.15
			16-QAM	RB25#0	4.524	5.058	1.16
		HCH	QPSK	RB25#0	4.503	5.042	1.17
			16-QAM	RB25#0	4.517	5.115	1.18
	10 MHz	LCH	QPSK	RB50#0	8.983	10.006	1.19
			16-QAM	RB50#0	8.986	10.053	1.20
		MCH	QPSK	RB50#0	8.987	10.003	1.21
			16-QAM	RB50#0	9.002	10.124	1.22
		HCH	QPSK	RB50#0	9.016	10.183	1.23
			16-QAM	RB50#0	9.013	10.13	1.24
	15 MHz	LCH	QPSK	RB75#0	13.461	14.864	1.25
			16-QAM	RB75#0	13.466	14.831	1.26
		MCH	QPSK	RB75#0	13.459	14.86	1.27
			16-QAM	RB75#0	13.514	14.89	1.28
		HCH	QPSK	RB75#0	13.532	15.023	1.29
			16-QAM	RB75#0	13.538	15.016	1.30
20 MHz	LCH	QPSK	RB100#0	17.969	19.865	1.31	
		16-QAM	RB100#0	18.008	19.874	1.32	
	MCH	QPSK	RB100#0	18.007	19.84	1.33	

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
			16-QAM	RB100#0	18.02	20.1	1.34
		HCH	QPSK	RB100#0	18.074	20.214	1.35
			16-QAM	RB100#0	18.052	20.12	1.36

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 4	1.4 MHz	LCH	QPSK	RB6#0	1.091	1.264	2.1
			16-QAM	RB6#0	1.1	1.275	2.2
		MCH	QPSK	RB6#0	1.092	1.261	2.3
			16-QAM	RB6#0	1.089	1.26	2.4
		HCH	QPSK	RB6#0	1.095	1.271	2.5
			16-QAM	RB6#0	1.096	1.271	2.6
	3 MHz	LCH	QPSK	RB15#0	2.707	3.025	2.7
			16-QAM	RB15#0	2.702	3.01	2.8
		MCH	QPSK	RB15#0	2.706	3.007	2.9
			16-QAM	RB15#0	2.699	3.017	2.10
		HCH	QPSK	RB15#0	2.707	3.009	2.11
			16-QAM	RB15#0	2.704	3.002	2.12
	5 MHz	LCH	QPSK	RB25#0	4.523	5.055	2.13
			16-QAM	RB25#0	4.511	5.057	2.14
		MCH	QPSK	RB25#0	4.507	5.099	2.15
			16-QAM	RB25#0	4.518	5.098	2.16
		HCH	QPSK	RB25#0	4.504	5.055	2.17
			16-QAM	RB25#0	4.517	5.121	2.18
	10 MHz	LCH	QPSK	RB50#0	8.992	10.067	2.19
			16-QAM	RB50#0	8.984	10.155	2.20
		MCH	QPSK	RB50#0	8.978	10.021	2.21
			16-QAM	RB50#0	8.997	10.154	2.22
		HCH	QPSK	RB50#0	9.008	10.044	2.23
			16-QAM	RB50#0	8.988	10.106	2.24
	15 MHz	LCH	QPSK	RB75#0	13.453	14.846	2.25
			16-QAM	RB75#0	13.456	14.93	2.26
		MCH	QPSK	RB75#0	13.473	14.801	2.27
			16-QAM	RB75#0	13.515	15.025	2.28
		HCH	QPSK	RB75#0	13.49	14.922	2.29
			16-QAM	RB75#0	13.489	14.819	2.30
20 MHz	LCH	QPSK	RB100#0	17.937	19.934	2.31	
		16-QAM	RB100#0	17.971	20.146	2.32	
	MCH	QPSK	RB100#0	18.016	20.032	2.33	
		16-QAM	RB100#0	18.027	20.366	2.34	
	HCH	QPSK	RB100#0	18.037	20.18	2.35	
		16-QAM	RB100#0	18.007	20.124	2.36	

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 5	1.4 MHz	LCH	QPSK	RB6#0	1.09	1.263	3.1
			16-QAM	RB6#0	1.102	1.274	3.2
		MCH	QPSK	RB6#0	1.093	1.263	3.3
			16-QAM	RB6#0	1.09	1.264	3.4
		HCH	QPSK	RB6#0	1.096	1.253	3.5
			16-QAM	RB6#0	1.095	1.264	3.6
	3 MHz	LCH	QPSK	RB15#0	2.706	3.01	3.7
			16-QAM	RB15#0	2.705	3.026	3.8
		MCH	QPSK	RB15#0	2.696	3.006	3.9
			16-QAM	RB15#0	2.696	2.996	3.10
		HCH	QPSK	RB15#0	2.702	3.001	3.11
			16-QAM	RB15#0	2.697	3.039	3.12
	5 MHz	LCH	QPSK	RB25#0	4.523	5.093	3.13
			16-QAM	RB25#0	4.516	5.099	3.14
		MCH	QPSK	RB25#0	4.501	5.096	3.15
			16-QAM	RB25#0	4.509	5.085	3.16
		HCH	QPSK	RB25#0	4.489	5.029	3.17
			16-QAM	RB25#0	4.494	5.077	3.18
	10 MHz	LCH	QPSK	RB50#0	9.014	10.077	3.19
			16-QAM	RB50#0	9.01	10.134	3.20
		MCH	QPSK	RB50#0	8.929	9.933	3.21
			16-QAM	RB50#0	8.943	9.977	3.22
		HCH	QPSK	RB50#0	8.984	10.097	3.23
			16-QAM	RB50#0	8.984	10.1	3.24

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured - 26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 18 (824-830 MHz)	5 MHz	LCH	QPSK	RB25#0	4.528	5.08	4.1
			16-QAM	RB25#0	4.513	5.106	4.2
		MCH	QPSK	RB25#0	4.513	5.12	4.3
			16-QAM	RB25#0	4.528	5.099	4.4
		HCH	QPSK	RB25#0	4.508	5.07	4.5
			16-QAM	RB25#0	4.527	5.081	4.6

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured - 26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 18 (815-824 MHz)	5 MHz	LCH	QPSK	RB25#0	4.487	5.043	5.1
			16-QAM	RB25#0	4.506	5.103	5.2
		MCH	QPSK	RB25#0	4.507	5.036	5.3
			16-QAM	RB25#0	4.5	5.039	5.4
		HCH	QPSK	RB25#0	4.508	5.051	5.5
			16-QAM	RB25#0	4.521	5.086	5.6

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured - 26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 19	5 MHz	LCH	QPSK	RB25#0	4.501	5.036	6.1
			16-QAM	RB25#0	4.524	5.059	6.2
		MCH	QPSK	RB25#0	4.51	5.06	6.3
			16-QAM	RB25#0	4.501	5.05	6.4
		HCH	QPSK	RB25#0	4.517	5.12	6.5
			16-QAM	RB25#0	4.527	5.08	6.6
	10 MHz	LCH	QPSK	RB50#0	8.953	9.901	6.7
			16-QAM	RB50#0	8.953	9.955	6.8
		MCH	QPSK	RB50#0	8.95	9.945	6.9
			16-QAM	RB50#0	8.954	9.992	6.10
		HCH	QPSK	RB50#0	8.978	10.051	6.11
			16-QAM	RB50#0	9.006	10.035	6.12
	15 MHz	MCH	QPSK	RB75#0	13.414	14.805	6.13
			16-QAM	RB75#0	13.401	14.714	6.14

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 25	1.4 MHz	LCH	QPSK	RB6#0	1.091	1.263	7.1
			16-QAM	RB6#0	1.103	1.275	7.2
		MCH	QPSK	RB6#0	1.093	1.264	7.3
			16-QAM	RB6#0	1.089	1.254	7.4
		HCH	QPSK	RB6#0	1.096	1.255	7.5
			16-QAM	RB6#0	1.099	1.265	7.6
	3 MHz	LCH	QPSK	RB15#0	2.701	3.004	7.7
			16-QAM	RB15#0	2.703	3.018	7.8
		MCH	QPSK	RB15#0	2.706	2.997	7.9
			16-QAM	RB15#0	2.702	3.025	7.10
		HCH	QPSK	RB15#0	2.704	3.015	7.11
			16-QAM	RB15#0	2.701	3.036	7.12
	5 MHz	LCH	QPSK	RB25#0	4.52	5.083	7.13
			16-QAM	RB25#0	4.509	5.061	7.14
		MCH	QPSK	RB25#0	4.512	5.09	7.15
			16-QAM	RB25#0	4.524	5.061	7.16
		HCH	QPSK	RB25#0	4.496	5.018	7.17
			16-QAM	RB25#0	4.502	5.087	7.18
	10 MHz	LCH	QPSK	RB50#0	8.984	10.019	7.19
			16-QAM	RB50#0	8.993	10.063	7.20
		MCH	QPSK	RB50#0	8.981	10.03	7.21
			16-QAM	RB50#0	8.995	10.108	7.22
		HCH	QPSK	RB50#0	8.97	9.968	7.23
			16-QAM	RB50#0	8.965	10.026	7.24
	15 MHz	LCH	QPSK	RB75#0	13.459	14.886	7.25
			16-QAM	RB75#0	13.447	14.775	7.26
		MCH	QPSK	RB75#0	13.453	14.855	7.27
			16-QAM	RB75#0	13.495	15.012	7.28
		HCH	QPSK	RB75#0	13.45	14.921	7.29
			16-QAM	RB75#0	13.47	14.81	7.30
	20 MHz	LCH	QPSK	RB100#0	17.959	19.864	7.31
			16-QAM	RB100#0	17.981	19.96	7.32
		MCH	QPSK	RB100#0	17.951	19.823	7.33
			16-QAM	RB100#0	17.982	20.074	7.34
		HCH	QPSK	RB100#0	18.039	20.142	7.35
			16-QAM	RB100#0	18.016	20.062	7.36

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 26 (824-849 MHz)	1.4 MHz	LCH	QPSK	RB6#0	1.09	1.263	8.1
			16-QAM	RB6#0	1.101	1.274	8.2
		MCH	QPSK	RB6#0	1.092	1.261	8.3
			16-QAM	RB6#0	1.089	1.25	8.4
		HCH	QPSK	RB6#0	1.095	1.254	8.5
			16-QAM	RB6#0	1.098	1.267	8.6
	3 MHz	LCH	QPSK	RB15#0	2.708	3.004	8.7
			16-QAM	RB15#0	2.705	3.015	8.8
		MCH	QPSK	RB15#0	2.697	2.989	8.9
			16-QAM	RB15#0	2.697	3.008	8.10
		HCH	QPSK	RB15#0	2.705	3.008	8.11
			16-QAM	RB15#0	2.698	3.034	8.12
	5 MHz	LCH	QPSK	RB25#0	4.525	5.065	8.13
			16-QAM	RB25#0	4.513	5.095	8.14
		MCH	QPSK	RB25#0	4.495	5.091	8.15
			16-QAM	RB25#0	4.51	5.095	8.16
		HCH	QPSK	RB25#0	4.488	5.029	8.17
			16-QAM	RB25#0	4.501	5.058	8.18
	10 MHz	LCH	QPSK	RB50#0	9.015	10.08	8.19
			16-QAM	RB50#0	9.009	10.091	8.20
		MCH	QPSK	RB50#0	8.938	9.928	8.21
			16-QAM	RB50#0	8.952	10.036	8.22
		HCH	QPSK	RB50#0	8.98	10.028	8.23
			16-QAM	RB50#0	8.986	10.117	8.24
	15 MHz	LCH	QPSK	RB75#0	13.459	14.795	8.25
			16-QAM	RB75#0	13.451	14.74	8.26
		MCH	QPSK	RB75#0	13.371	14.729	8.27
			16-QAM	RB75#0	13.408	14.86	8.28
		HCH	QPSK	RB75#0	13.462	14.826	8.29
			16-QAM	RB75#0	13.471	14.808	8.30

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 26 (814-824 MHz)	1.4 MHz	LCH	QPSK	RB6#0	1.095	1.27	9.1
			16-QAM	RB6#0	1.099	1.272	9.2
		MCH	QPSK	RB6#0	1.091	1.26	9.3
			16-QAM	RB6#0	1.096	1.275	9.4
		HCH	QPSK	RB6#0	1.093	1.263	9.5
			16-QAM	RB6#0	1.089	1.256	9.6
	3 MHz	LCH	QPSK	RB15#0	2.7	3.012	9.7
			16-QAM	RB15#0	2.699	3.029	9.8
		MCH	QPSK	RB15#0	2.702	2.995	9.9
			16-QAM	RB15#0	2.7	3.004	9.10
		HCH	QPSK	RB15#0	2.702	2.998	9.11
			16-QAM	RB15#0	2.698	3.006	9.12
	5 MHz	LCH	QPSK	RB25#0	4.498	5.032	9.13
			16-QAM	RB25#0	4.512	5.114	9.14
		MCH	QPSK	RB25#0	4.508	5.047	9.15
			16-QAM	RB25#0	4.5	5.025	9.16
		HCH	QPSK	RB25#0	4.51	5.086	9.17
			16-QAM	RB25#0	4.518	5.084	9.18
	10 MHz	MCH	QPSK	RB50#0	8.94	9.929	9.19
			16-QAM	RB50#0	8.939	10.022	9.20

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 66	1.4 MHz	LCH	QPSK	RB6#0	1.092	1.268	10.1
			16-QAM	RB6#0	1.101	1.272	10.2
		MCH	QPSK	RB6#0	1.094	1.269	10.3
			16-QAM	RB6#0	1.09	1.253	10.4
		HCH	QPSK	RB6#0	1.095	1.271	10.5
			16-QAM	RB6#0	1.096	1.275	10.6
	3 MHz	LCH	QPSK	RB15#0	2.706	2.994	10.7
			16-QAM	RB15#0	2.702	3.008	10.8
		MCH	QPSK	RB15#0	2.706	3	10.9
			16-QAM	RB15#0	2.698	3.007	10.10
		HCH	QPSK	RB15#0	2.708	3.003	10.11
			16-QAM	RB15#0	2.703	3.044	10.12
	5 MHz	LCH	QPSK	RB25#0	4.526	5.061	10.13
			16-QAM	RB25#0	4.505	5.091	10.14
		MCH	QPSK	RB25#0	4.508	5.063	10.15
			16-QAM	RB25#0	4.524	5.114	10.16
		HCH	QPSK	RB25#0	4.506	5.051	10.17
			16-QAM	RB25#0	4.523	5.081	10.18
	10 MHz	LCH	QPSK	RB50#0	8.986	10.064	10.19
			16-QAM	RB50#0	8.982	10.124	10.20
		MCH	QPSK	RB50#0	8.972	10.099	10.21
			16-QAM	RB50#0	8.999	10.205	10.22
		HCH	QPSK	RB50#0	8.998	10.134	10.23
			16-QAM	RB50#0	8.991	10.207	10.24
	15 MHz	LCH	QPSK	RB75#0	13.462	14.878	10.25
			16-QAM	RB75#0	13.45	14.813	10.26
		MCH	QPSK	RB75#0	13.46	14.95	10.27
			16-QAM	RB75#0	13.491	14.926	10.28
		HCH	QPSK	RB75#0	13.48	14.944	10.29
			16-QAM	RB75#0	13.491	14.813	10.30
	20 MHz	LCH	QPSK	RB100#0	17.936	19.991	10.31
			16-QAM	RB100#0	17.936	19.973	10.32
		MCH	QPSK	RB100#0	18.006	19.96	10.33
			16-QAM	RB100#0	18.026	20.171	10.34
		HCH	QPSK	RB100#0	17.998	20.177	10.35
			16-QAM	RB100#0	18.008	20.076	10.36

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 40 (2305-2315MHz)	5 MHz	LCH	QPSK	RB25#0	4.519	5.88	11.1
			16-QAM	RB25#0	4.533	6.295	11.2
		MCH	QPSK	RB25#0	4.518	5.799	11.3
			16-QAM	RB25#0	4.516	6.265	11.4
		HCH	QPSK	RB25#0	4.521	6.207	11.5
			16-QAM	RB25#0	4.522	6.262	11.6
	10 MHz	MCH	QPSK	RB50#0	8.995	10.314	11.7
			16-QAM	RB50#0	9.009	10.58	11.8

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 40 (2350-2360MHz)	5 MHz	LCH	QPSK	RB25#0	4.519	6.162	12.1
			16-QAM	RB25#0	4.528	6.321	12.2
		MCH	QPSK	RB25#0	4.519	6.183	12.3
			16-QAM	RB25#0	4.516	6.394	12.4
		HCH	QPSK	RB25#0	4.517	6.212	12.5
			16-QAM	RB25#0	4.519	6.258	12.6
	10 MHz	MCH	QPSK	RB50#0	8.993	10.35	12.7
			16-QAM	RB50#0	9.008	10.737	12.8

A.4 Frequency Stability

A.4.1 Frequency Stability

LTE Band 2 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value(Hz)	Limits (Hz)	
3.8	-30	1.72	±4700	Pass
	-20	0.67		
	-10	-0.11		
	0	0.99		
	+10	-0.44		
	+20	0.97		
	+25	1.5		
	+30	1.57		
	+40	0.06		
	+50	1.9		
	+60	1.1		
4.5	+25	0.97		
3.6	+25	0.9		

LTE Band 2 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value(Hz)	Limits (Hz)	
3.8	-30	0.59	±4700	Pass
	-20	0.63		
	-10	0.56		
	0	0.49		
	+10	0.77		
	+20	-0.64		
	+25	0		
	+30	1.23		
	+40	-0.09		
	+50	1.27		
	+60	0.57		
+70	0.5			
4.5	+25	-0.14		

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value(Hz)	Limits (Hz)	
3.6	+25	1.16		

LTE Band 4 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz		
		Value(Hz)	Limits (Hz)	
3.8	-30	1.77	±4331.25	Pass
	-20	1.42		
	-10	2		
	0	1.17		
	+10	2.66		
	+20	1.54		
	+25	1.6		
	+30	2.05		
	+40	1.79		
	+50	0.79		
	+60	1.47		
4.5	+25	1.29		
3.6	+25	1.57		

LTE Band 4 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz		
		Value(Hz)	Limits (Hz)	
3.8	-30	1.89	±4331.25	Pass
	-20	1.76		
	-10	2.19		
	0	1.13		
	+10	1.39		
	+20	1.09		
	+25	1.49		
	+30	0.76		
	+40	1.62		
	+50	1.76		
	+60	1.42		
4.5	+25	1.24		
3.6	+25	1.52		

LTE Band 5 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value(Hz)	Limits (Hz)	
3.8	-30	-0.33	±2091.25	Pass
	-20	-0.2		
	-10	0.1		
	0	-0.34		
	+10	-0.39		
	+20	-0.06		
	+25	-0.33		
	+30	0.37		
	+40	0.19		
	+50	0.2		
	+60	-0.4		
4.5	+25	-0.39		
3.6	+25	-0.66		

LTE Band 5 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value(Hz)	Limits (Hz)	
3.8	-30	-0.4	±2091.25	Pass
	-20	0.23		
	-10	0.17		
	0	0.2		
	+10	0.01		
	+20	0.09		
	+25	0.26		
	+30	0.01		
	+40	0.21		
	+50	0.13		
	+60	0.23		
+70	0.19			
4.5	+25	0.07		
3.6	+25	-0.47		

LTE Band 18 (824-830 MHz) QPSK 5 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 827 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.47	±2067.5	Pass
	-20	0.39		
	-10	0.17		
	0	-0.43		
	+10	-0.01		
	+20	-0.01		
	+25	-0.96		
	+30	-0.23		
	+40	-0.5		
	+50	-0.14		
	+60	-0.23		
4.5	+25	0.53		
3.6	+25	-0.46		

LTE Band 18 (824-830 MHz) 16QAM 5 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 827 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.19	±2067.5	Pass
	-20	-0.49		
	-10	-0.37		
	0	-0.07		
	+10	-0.97		
	+20	-0.54		
	+25	0.04		
	+30	-0.3		
	+40	-0.83		
	+50	-0.31		
	+60	-0.63		
+70	0.11			
4.5	+25	-0.69		
3.6	+25	0.14		

LTE Band 18 (815-824 MHz) QPSK 5 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 819.5 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	0.2	±2048.75	Pass
	-20	-0.26		
	-10	0.63		
	0	-0.1		
	+10	-0.23		
	+20	-0.11		
	+25	-0.27		
	+30	-0.43		
	+40	-0.24		
	+50	0.04		
4.5	+25	0.09		
3.6	+25	-0.03		

LTE Band 18 (815-824 MHz) 16QAM 5 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 819.5 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.39	±2048.75	Pass
	-20	-0.49		
	-10	-0.77		
	0	-0.67		
	+10	-0.13		
	+20	-1.19		
	+25	-0.7		
	+30	-0.82		
	+40	-0.59		
	+50	-0.63		
4.5	+25	-0.33		
3.6	+25	-0.56		

LTE Band 19 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 837.5 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.62	±2093.75	Pass
	-20	-0.63		
	-10	-0.1		
	0	-0.2		
	+10	0.19		
	+20	-0.62		
	+25	-0.24		
	+30	-0.11		
	+40	-0.06		
	+50	-0.46		
	+60	0.19		
+70	0.56			
4.5	+25	-0.29		
3.6	+25	-0.31		

LTE Band 19 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 837.5 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.21	±2093.75	Pass
	-20	-0.2		
	-10	-0.31		
	0	-0.09		
	+10	0.13		
	+20	-0.24		
	+25	-0.1		
	+30	0.01		
	+40	-0.53		
	+50	-0.09		
	+60	0.1		
+70	0.46			
4.5	+25	-0.26		
3.6	+25	-0.04		

LTE Band 25 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1882.5 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	1.52	±4706.25	Pass
	-20	0.59		
	-10	0.62		
	0	0.84		
	+10	0.76		
	+20	0.07		
	+25	1.04		
	+30	1.1		
	+40	0.34		
	+50	0.43		
	+60	1.47		
4.5	+25	0.31		
3.6	+25	0.57		

LTE Band 25 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1882.5 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	0.97	±4706.25	Pass
	-20	1.52		
	-10	-0.63		
	0	0.89		
	+10	0.41		
	+20	0.92		
	+25	0.51		
	+30	-0.44		
	+40	-0.63		
	+50	0.77		
	+60	0.47		
+70	0.14			
4.5	+25	0.53		
3.6	+25	0.4		

LTE Band 26 (824-849 MHz) QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.1	±2091.25	Pass
	-20	0.39		
	-10	-0.39		
	0	-0.19		
	+10	0.31		
	+20	0.26		
	+25	0.29		
	+30	-0.2		
	+40	-0.06		
	+50	-0.24		
	+60	0		
+70	0			
4.5	+25	-0.21		
3.6	+25	-0.16		

LTE Band 26 (824-849 MHz) 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.17	±2091.25	Pass
	-20	0.41		
	-10	-0.51		
	0	0.51		
	+10	0.11		
	+20	-0.09		
	+25	-0.34		
	+30	0.23		
	+40	-0.14		
	+50	-0.41		
	+60	-0.46		
+70	-0.11			
4.5	+25	0		
3.6	+25	-0.67		

LTE Band 26 (814-824 MHz) QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 819 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.01	±2091.25	Pass
	-20	0.07		
	-10	0.41		
	0	0.19		
	+10	0.06		
	+20	-0.4		
	+25	-0.13		
	+30	-0.47		
	+40	-0.11		
	+50	-0.66		
	+60	-0.21		
+70	-0.26			
4.5	+25	-0.13		
3.6	+25	-0.39		

LTE Band 26 (814-824 MHz) 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 819 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.24	±2091.25	Pass
	-20	0.13		
	-10	-0.51		
	0	-0.27		
	+10	0.43		
	+20	0.24		
	+25	-0.51		
	+30	0.14		
	+40	-0.01		
	+50	-0.09		
	+60	0.23		
+70	-0.43			
4.5	+25	-0.13		
3.6	+25	-0.16		

LTE Band 66 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.79	±4362.5	Pass
	-20	-1.93		
	-10	-1.69		
	0	-0.83		
	+10	0.46		
	+20	-0.82		
	+25	-0.79		
	+30	-0.36		
	+40	-0.21		
	+50	-0.06		
	+60	-1.06		
+70	-0.03			
4.5	+25	-1		
3.6	+25	-0.67		

LTE Band 66 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-0.93	±4362.5	Pass
	-20	-0.07		
	-10	-0.33		
	0	-0.74		
	+10	-0.7		
	+20	0.99		
	+25	0		
	+30	0.14		
	+40	-1.03		
	+50	-0.21		
	+60	-1.33		
+70	-0.94			
4.5	+25	-0.14		
3.6	+25	-0.5		

LTE Band 40(2305-2315MHz) QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 2310MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-4.79	±5775	Pass
	-20	-4.98		
	-10	-4.55		
	0	-5.68		
	+10	-4.51		
	+20	-5.18		
	+25	-3.69		
	+30	-4.35		
	+40	-3.29		
	+50	-3.45		
	+60	-4.99		
+70	-4.88			
4.5	+25	-4.18		
3.6	+25	-4.23		

LTE Band 40(2305-2315MHz) 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 2310MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-5.87	±5775	Pass
	-20	-4.58		
	-10	-5.15		
	0	-4.51		
	+10	-3.76		
	+20	-4.43		
	+25	-4.23		
	+30	-4.05		
	+40	-4.81		
	+50	-4.53		
	+60	-4.56		
+70	-5.09			
4.5	+25	-4.53		
3.6	+25	-3.63		

LTE Band 40(2350-2360MHz) QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 2355MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-3.88	±5887.5	Pass
	-20	-3.91		
	-10	-4.58		
	0	-3.85		
	+10	-5.24		
	+20	-5.72		
	+25	-3.36		
	+30	-4.95		
	+40	-3.81		
	+50	-4.48		
	+60	-3.43		
+70	-5.19			
4.5	+25	-4.46		
3.6	+25	-4.94		

LTE Band 40(2350-2360MHz) 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 2355MHz		
		Value (Hz)	Limits (Hz)	
3.8	-30	-5.42	±5887.5	Pass
	-20	-5.48		
	-10	-5.04		
	0	-3.62		
	+10	-5.29		
	+20	-3.96		
	+25	-4.45		
	+30	-4.86		
	+40	-4.36		
	+50	-4.46		
	+60	-4.53		
+70	-4.19			
4.5	+25	-5.28		
3.6	+25	-3.1		

A.4.2 Frequency Range

Note1: Only for relevant requirements of RSS standard.

Note2: Test plots please refer to the document "Annex No.: BL-SZ2370302-501 Data Part 3.1.pdf".

Note3: Test plots please refer to the document "Annex No.: BL-SZ2370302-501 Data Part 3.2.pdf".

LTE Mode Test Verdict

LTE B2								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	1850.5200	1850	1.1	1909.4700	1910	1.1	Pass
	-20	1850.5200		1.2	1909.4700		1.2	Pass
	-10	1850.5300		1.3	1909.4700		1.3	Pass
	0	1850.5300		1.4	1909.4700		1.4	Pass
	+10	1850.5300		1.5	1909.4700		1.5	Pass
	+20	1850.5300		1.6	1909.4700		1.6	Pass
	+25	1850.5300		1.7	1909.4700		1.7	Pass
	+30	1850.5200		1.8	1909.4700		1.8	Pass
	+40	1850.5300		1.9	1909.4700		1.9	Pass
	+50	1850.5300		1.10	1909.4700		1.10	Pass
	+60	1850.5300		1.11	1909.4700		1.11	Pass
	+70	1850.5200	1.12	1909.4700	1.12	Pass		
4.5	+25	1850.5300		1.13	1909.4700		1.13	Pass
3.6	+25	1850.5300		1.14	1909.4700		1.14	Pass

LTE B4								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	1710.5400	1710	2.1	1754.4700	1755	2.1	Pass
	-20	1710.5300		2.2	1754.4700		2.2	Pass
	-10	1710.5400		2.3	1754.4700		2.3	Pass
	0	1710.5300		2.4	1754.4700		2.4	Pass
	+10	1710.5400		2.5	1754.4700		2.5	Pass
	+20	1710.5400		2.6	1754.4700		2.6	Pass
	+25	1710.5400		2.7	1754.4700		2.7	Pass
	+30	1710.5400		2.8	1754.4700		2.8	Pass
	+40	1710.5400		2.9	1754.4700		2.9	Pass
	+50	1710.5400		2.10	1754.4700		2.10	Pass
	+60	1710.5400		2.11	1754.4700		2.11	Pass
	+70	1710.5400		2.12	1754.4700		2.12	Pass
4.5	+25	1710.5400		2.13	1754.4700		2.13	Pass
3.6	+25	1710.5400		2.14	1754.4700		2.14	Pass

LTE B5								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	824.5400	824	3.1	848.4500	849	3.1	Pass
	-20	824.5400		3.2	848.4500		3.2	Pass
	-10	824.5400		3.3	848.4500		3.3	Pass
	0	824.5400		3.4	848.4600		3.4	Pass
	+10	824.5400		3.5	848.4500		3.5	Pass
	+20	824.5400		3.6	848.4600		3.6	Pass
	+25	824.5400		3.7	848.4600		3.7	Pass
	+30	824.5400		3.8	848.4600		3.8	Pass
	+40	824.5400		3.9	848.4600		3.9	Pass
	+50	824.5400		3.10	848.4600		3.10	Pass
	+60	824.5400		3.11	848.4600		3.11	Pass
	+70	824.5400		3.12	848.4600		3.12	Pass
4.5	+25	824.5400		3.13	848.4500		3.13	Pass
3.6	+25	824.5400		3.14	848.4600		3.14	Pass

LTE B18 (824~830 MHz)								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	824.2653	824	4.1	829.7347	830	4.1	Pass
	-20	824.2653		4.2	829.7347		4.2	Pass
	-10	824.2653		4.3	829.7347		4.3	Pass
	0	824.2653		4.4	829.7347		4.4	Pass
	+10	824.2653		4.5	829.7347		4.5	Pass
	+20	824.2653		4.6	829.7347		4.6	Pass
	+25	824.2653		4.7	829.7347		4.7	Pass
	+30	824.2653		4.8	829.7347		4.8	Pass
	+40	824.2653		4.9	829.7347		4.9	Pass
	+50	824.2653		4.10	829.7347		4.10	Pass
	+60	824.2653		4.11	829.7347		4.11	Pass
	+70	824.2653		4.12	829.7347		4.12	Pass
4.5	+25	824.2653		4.13	829.7347		4.13	Pass
3.6	+25	824.2653		4.14	829.7347		4.14	Pass

LTE B19								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	830.5700	830	5.1	844.4600	845	5.1	Pass
	-20	830.5700		5.2	844.4600		5.2	Pass
	-10	830.5700		5.3	844.4600		5.3	Pass
	0	830.5700		5.4	844.4600		5.4	Pass
	+10	830.5700		5.5	844.4600		5.5	Pass
	+20	830.5700		5.6	844.4600		5.6	Pass
	+25	830.5700		5.7	844.4600		5.7	Pass
	+30	830.5700		5.8	844.4600		5.8	Pass
	+40	830.5700		5.9	844.4600		5.9	Pass
	+50	830.5700		5.10	844.4600		5.10	Pass
	+60	830.5700		5.11	844.4600		5.11	Pass
	+70	830.5700		5.12	844.4600		5.12	Pass
4.5	+25	830.5700		5.13	844.4600		5.13	Pass
3.6	+25	830.5700		5.14	844.4600		5.14	Pass

LTE B25								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	1850.5300	1850	6.1	1914.4500	1915	6.1	Pass
	-20	1850.5200		6.2	1914.4500		6.2	Pass
	-10	1850.5200		6.3	1914.4500		6.3	Pass
	0	1850.5300		6.4	1914.4500		6.4	Pass
	+10	1850.5300		6.5	1914.4500		6.5	Pass
	+20	1850.5300		6.6	1914.4500		6.6	Pass
	+25	1850.5300		6.7	1914.4500		6.7	Pass
	+30	1850.5200		6.8	1914.4500		6.8	Pass
	+40	1850.5300		6.9	1914.4500		6.9	Pass
	+50	1850.5200		6.10	1914.4500		6.10	Pass
	+60	1850.5300		6.11	1914.4500		6.11	Pass
	+70	1850.5300		6.12	1914.4500		6.12	Pass
4.5	+25	1850.5300		6.13	1914.4500		6.13	Pass
3.6	+25	1850.5300		6.14	1914.4500		6.14	Pass

LTE B26								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	824.5400	824	7.1	848.4600	849	7.1	Pass
	-20	824.5400		7.2	848.4600		7.2	Pass
	-10	824.5400		7.3	848.4600		7.3	Pass
	0	824.5400		7.4	848.4600		7.4	Pass
	+10	824.5400		7.5	848.4600		7.5	Pass
	+20	824.5400		7.6	848.4600		7.6	Pass
	+25	824.5400		7.7	848.4600		7.7	Pass
	+30	824.5400		7.8	848.4600		7.8	Pass
	+40	824.5400		7.9	848.4600		7.9	Pass
	+50	824.5400		7.10	848.4600		7.10	Pass
	+60	824.5400		7.11	848.4600		7.11	Pass
	+70	824.5400		7.12	848.4600		7.12	Pass
4.5	+25	824.5400		7.13	848.4600		7.13	Pass
3.6	+25	824.5400		7.14	848.4600		7.14	Pass

LTE B66								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	1710.5400	1710	8.1	1779.4600	1780	8.1	Pass
	-20	1710.5400		8.2	1779.4600		8.2	Pass
	-10	1710.5400		8.3	1779.4600		8.3	Pass
	0	1710.5400		8.4	1779.4600		8.4	Pass
	+10	1710.5400		8.5	1779.4600		8.5	Pass
	+20	1710.5400		8.6	1779.4600		8.6	Pass
	+25	1710.5400		8.7	1779.4600		8.7	Pass
	+30	1710.5400		8.8	1779.4600		8.8	Pass
	+40	1710.5400		8.9	1779.4600		8.9	Pass
	+50	1710.5400		8.10	1779.4600		8.10	Pass
	+60	1710.5400		8.11	1779.4600		8.11	Pass
	+70	1710.5400		8.12	1779.4600		8.12	Pass
4.5	+25	1710.5400		8.13	1779.4600		8.13	Pass
3.6	+25	1710.5400		8.14	1779.4600		8.14	Pass

LTE B40(2305-2315MHz)								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	2305.5300	2305	9.1	2314.4600	2315	9.1	Pass
	-20	2305.5300		9.2	2314.4600		9.2	Pass
	-10	2305.5400		9.3	2314.4600		9.3	Pass
	0	2305.5300		9.4	2314.4600		9.4	Pass
	+10	2305.5300		9.5	2314.4600		9.5	Pass
	+20	2305.5300		9.6	2314.4600		9.6	Pass
	+25	2305.5300		9.7	2314.4600		9.7	Pass
	+30	2305.5300		9.8	2314.4600		9.8	Pass
	+40	2305.5300		9.9	2314.4600		9.9	Pass
	+50	2305.5300		9.10	2314.4600		9.10	Pass
	+60	2305.5400		9.11	2314.4600		9.11	Pass
	+70	2305.5300		9.12	2314.4600		9.12	Pass
4.5	+25	2305.5300		9.13	2314.4600		9.13	Pass
3.6	+25	2305.5300		9.14	2314.4600		9.14	Pass

LTE B40(2350-2360MHz)								
Test Condition		LeftEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note2}	RightEdge (MHz)	Limit (MHz)	Refer to Plot ^{Note3}	Verdict
Power (VDC)	Temperature (°C)							
3.8	-30	2350.5300	2350	10.1	2359.4600	2360	10.1	Pass
	-20	2350.5300		10.2	2359.4600		10.2	Pass
	-10	2350.5400		10.3	2359.4600		10.3	Pass
	0	2350.5300		10.4	2359.4600		10.4	Pass
	+10	2350.5400		10.5	2359.4600		10.5	Pass
	+20	2350.5300		10.6	2359.4600		10.6	Pass
	+25	2350.5300		10.7	2359.4600		10.7	Pass
	+30	2350.5400		10.8	2359.4600		10.8	Pass
	+40	2350.5400		10.9	2359.4600		10.9	Pass
	+50	2350.5300		10.10	2359.4600		10.10	Pass
	+60	2350.5300		10.11	2359.4600		10.11	Pass
	+70	2350.5300		10.12	2359.4600		10.12	Pass
4.5	+25	2350.5300		10.13	2359.4600		10.13	Pass
3.6	+25	2350.5300		10.14	2359.4600		10.14	Pass

A.5 Spurious Emission at Antenna Terminals

Note 1: The frequencies of verdict which are marked by "N/A" should be ignored because they are UE carrier frequency.

Note 2: Test plots please refer to the document "Annex No.:BL-SZ2370302-501 Data Part 4.pdf".

Note 4: The disturbance above 26.5GHz was very low, and the above harmonics were the highest point could be found when testing, so only the worst case data displayed in this report.

LTE Mode Test Verdict

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 2	1.4 MHz	LCH	QPSK	RB1#0	1.1	Pass
			16-QAM	RB1#0	1.2	Pass
		MCH	QPSK	RB1#0	1.3	Pass
			16-QAM	RB1#0	1.4	Pass
		HCH	QPSK	RB1#0	1.5	Pass
			16-QAM	RB1#0	1.6	Pass
	3 MHz	LCH	QPSK	RB1#0	1.7	Pass
			16-QAM	RB1#0	1.8	Pass
		MCH	QPSK	RB1#0	1.9	Pass
			16-QAM	RB1#0	1.10	Pass
		HCH	QPSK	RB1#0	1.11	Pass
			16-QAM	RB1#0	1.12	Pass
	5 MHz	LCH	QPSK	RB1#0	1.13	Pass
			16-QAM	RB1#0	1.14	Pass
		MCH	QPSK	RB1#0	1.15	Pass
			16-QAM	RB1#0	1.16	Pass
		HCH	QPSK	RB1#0	1.17	Pass
			16-QAM	RB1#0	1.18	Pass
	10 MHz	LCH	QPSK	RB1#0	1.19	Pass
			16-QAM	RB1#0	1.20	Pass
		MCH	QPSK	RB1#0	1.21	Pass
			16-QAM	RB1#0	1.22	Pass
		HCH	QPSK	RB1#0	1.23	Pass
			16-QAM	RB1#0	1.24	Pass
	15 MHz	LCH	QPSK	RB1#0	1.25	Pass
			16-QAM	RB1#0	1.26	Pass
		MCH	QPSK	RB1#0	1.27	Pass
			16-QAM	RB1#0	1.28	Pass
		HCH	QPSK	RB1#0	1.29	Pass
			16-QAM	RB1#0	1.30	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
	20 MHz	LCH	QPSK	RB1#0	1.31	Pass
			16-QAM	RB1#0	1.32	Pass
		MCH	QPSK	RB1#0	1.33	Pass
			16-QAM	RB1#0	1.34	Pass
		HCH	QPSK	RB1#0	1.35	Pass
			16-QAM	RB1#0	1.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 4	1.4 MHz	LCH	QPSK	RB1#0	2.1	Pass
			16-QAM	RB1#0	2.2	Pass
		MCH	QPSK	RB1#0	2.3	Pass
			16-QAM	RB1#0	2.4	Pass
		HCH	QPSK	RB1#0	2.5	Pass
			16-QAM	RB1#0	2.6	Pass
	3 MHz	LCH	QPSK	RB1#0	2.7	Pass
			16-QAM	RB1#0	2.8	Pass
		MCH	QPSK	RB1#0	2.9	Pass
			16-QAM	RB1#0	2.10	Pass
		HCH	QPSK	RB1#0	2.11	Pass
			16-QAM	RB1#0	2.12	Pass
	5 MHz	LCH	QPSK	RB1#0	2.13	Pass
			16-QAM	RB1#0	2.14	Pass
		MCH	QPSK	RB1#0	2.15	Pass
			16-QAM	RB1#0	2.16	Pass
		HCH	QPSK	RB1#0	2.17	Pass
			16-QAM	RB1#0	2.18	Pass
	10 MHz	LCH	QPSK	RB1#0	2.19	Pass
			16-QAM	RB1#0	2.20	Pass
		MCH	QPSK	RB1#0	2.21	Pass
			16-QAM	RB1#0	2.22	Pass
		HCH	QPSK	RB1#0	2.23	Pass
			16-QAM	RB1#0	2.24	Pass
	15 MHz	LCH	QPSK	RB1#0	2.25	Pass
			16-QAM	RB1#0	2.26	Pass
		MCH	QPSK	RB1#0	2.27	Pass
			16-QAM	RB1#0	2.28	Pass
		HCH	QPSK	RB1#0	2.29	Pass
			16-QAM	RB1#0	2.30	Pass
	20 MHz	LCH	QPSK	RB1#0	2.31	Pass
			16-QAM	RB1#0	2.32	Pass
		MCH	QPSK	RB1#0	2.33	Pass
			16-QAM	RB1#0	2.34	Pass
		HCH	QPSK	RB1#0	2.35	Pass
			16-QAM	RB1#0	2.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 5	1.4 MHz	LCH	QPSK	RB1#0	3.1	Pass
			16-QAM	RB1#0	3.2	Pass
		MCH	QPSK	RB1#0	3.3	Pass
			16-QAM	RB1#0	3.4	Pass
		HCH	QPSK	RB1#0	3.5	Pass
			16-QAM	RB1#0	3.6	Pass
	3 MHz	LCH	QPSK	RB1#0	3.7	Pass
			16-QAM	RB1#0	3.8	Pass
		MCH	QPSK	RB1#0	3.9	Pass
			16-QAM	RB1#0	3.10	Pass
		HCH	QPSK	RB1#0	3.11	Pass
			16-QAM	RB1#0	3.12	Pass
	5 MHz	LCH	QPSK	RB1#0	3.13	Pass
			16-QAM	RB1#0	3.14	Pass
		MCH	QPSK	RB1#0	3.15	Pass
			16-QAM	RB1#0	3.16	Pass
		HCH	QPSK	RB1#0	3.17	Pass
			16-QAM	RB1#0	3.18	Pass
	10 MHz	LCH	QPSK	RB1#0	3.19	Pass
			16-QAM	RB1#0	3.20	Pass
		MCH	QPSK	RB1#0	3.21	Pass
			16-QAM	RB1#0	3.22	Pass
		HCH	QPSK	RB1#0	3.23	Pass
			16-QAM	RB1#0	3.24	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 18 (824-830 MHz)	5 MHz	LCH	QPSK	RB1#0	4.1	Pass
			16-QAM	RB1#0	4.2	Pass
		MCH	QPSK	RB1#0	4.3	Pass
			16-QAM	RB1#0	4.4	Pass
		HCH	QPSK	RB1#0	4.5	Pass
			16-QAM	RB1#0	4.6	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 18 (815-824 MHz)	5 MHz	LCH	QPSK	RB1#0	5.1	Pass
			16-QAM	RB1#0	5.2	Pass
		MCH	QPSK	RB1#0	5.3	Pass
			16-QAM	RB1#0	5.4	Pass
		HCH	QPSK	RB1#0	5.5	Pass
			16-QAM	RB1#0	5.6	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 19	5 MHz	LCH	QPSK	RB1#0	6.1	Pass
			16-QAM	RB1#0	6.2	Pass
		MCH	QPSK	RB1#0	6.3	Pass
			16-QAM	RB1#0	6.4	Pass
		HCH	QPSK	RB1#0	6.5	Pass
			16-QAM	RB1#0	6.6	Pass
	10 MHz	LCH	QPSK	RB1#0	6.7	Pass
			16-QAM	RB1#0	6.8	Pass
		MCH	QPSK	RB1#0	6.9	Pass
			16-QAM	RB1#0	6.10	Pass
		HCH	QPSK	RB1#0	6.11	Pass
			16-QAM	RB1#0	6.12	Pass
	15 MHz	MCH	QPSK	RB1#0	6.13	Pass
			16-QAM	RB1#0	6.14	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 25	1.4 MHz	LCH	QPSK	RB1#0	7.1	Pass
			16-QAM	RB1#0	7.2	Pass
		MCH	QPSK	RB1#0	7.3	Pass
			16-QAM	RB1#0	7.4	Pass
		HCH	QPSK	RB1#0	7.5	Pass
			16-QAM	RB1#0	7.6	Pass
	3 MHz	LCH	QPSK	RB1#0	7.7	Pass
			16-QAM	RB1#0	7.8	Pass
		MCH	QPSK	RB1#0	7.9	Pass
			16-QAM	RB1#0	7.10	Pass
		HCH	QPSK	RB1#0	7.11	Pass
			16-QAM	RB1#0	7.12	Pass
	5 MHz	LCH	QPSK	RB1#0	7.13	Pass
			16-QAM	RB1#0	7.14	Pass
		MCH	QPSK	RB1#0	7.15	Pass
			16-QAM	RB1#0	7.16	Pass
		HCH	QPSK	RB1#0	7.17	Pass
			16-QAM	RB1#0	7.18	Pass
	10 MHz	LCH	QPSK	RB1#0	7.19	Pass
			16-QAM	RB1#0	7.20	Pass
		MCH	QPSK	RB1#0	7.21	Pass
			16-QAM	RB1#0	7.22	Pass
		HCH	QPSK	RB1#0	7.23	Pass
			16-QAM	RB1#0	7.24	Pass
	15 MHz	LCH	QPSK	RB1#0	7.25	Pass
			16-QAM	RB1#0	7.26	Pass
		MCH	QPSK	RB1#0	7.27	Pass
			16-QAM	RB1#0	7.28	Pass
		HCH	QPSK	RB1#0	7.29	Pass
			16-QAM	RB1#0	7.30	Pass
	20 MHz	LCH	QPSK	RB1#0	7.31	Pass
			16-QAM	RB1#0	7.32	Pass
		MCH	QPSK	RB1#0	7.33	Pass
			16-QAM	RB1#0	7.34	Pass
		HCH	QPSK	RB1#0	7.35	Pass
			16-QAM	RB1#0	7.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 26 (824-849 MHz)	1.4 MHz	LCH	QPSK	RB1#0	8.1	Pass
			16-QAM	RB1#0	8.2	Pass
		MCH	QPSK	RB1#0	8.3	Pass
			16-QAM	RB1#0	8.4	Pass
		HCH	QPSK	RB1#0	8.5	Pass
			16-QAM	RB1#0	8.6	Pass
	3 MHz	LCH	QPSK	RB1#0	8.7	Pass
			16-QAM	RB1#0	8.8	Pass
		MCH	QPSK	RB1#0	8.9	Pass
			16-QAM	RB1#0	8.10	Pass
		HCH	QPSK	RB1#0	8.11	Pass
			16-QAM	RB1#0	8.12	Pass
	5 MHz	LCH	QPSK	RB1#0	8.13	Pass
			16-QAM	RB1#0	8.14	Pass
		MCH	QPSK	RB1#0	8.15	Pass
			16-QAM	RB1#0	8.16	Pass
		HCH	QPSK	RB1#0	8.17	Pass
			16-QAM	RB1#0	8.18	Pass
	10 MHz	LCH	QPSK	RB1#0	8.19	Pass
			16-QAM	RB1#0	8.20	Pass
		MCH	QPSK	RB1#0	8.21	Pass
			16-QAM	RB1#0	8.22	Pass
		HCH	QPSK	RB1#0	8.23	Pass
			16-QAM	RB1#0	8.24	Pass
	15 MHz	LCH	QPSK	RB1#0	8.25	Pass
			16-QAM	RB1#0	8.26	Pass
		MCH	QPSK	RB1#0	8.27	Pass
			16-QAM	RB1#0	8.28	Pass
		HCH	QPSK	RB1#0	8.29	Pass
			16-QAM	RB1#0	8.30	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 26 (814-824 MHz)	1.4 MHz	LCH	QPSK	RB1#0	9.1	Pass
			16-QAM	RB1#0	9.2	Pass
		MCH	QPSK	RB1#0	9.3	Pass
			16-QAM	RB1#0	9.4	Pass
		HCH	QPSK	RB1#0	9.5	Pass
			16-QAM	RB1#0	9.6	Pass
	3 MHz	LCH	QPSK	RB1#0	9.7	Pass
			16-QAM	RB1#0	9.8	Pass
		MCH	QPSK	RB1#0	9.9	Pass
			16-QAM	RB1#0	9.10	Pass
		HCH	QPSK	RB1#0	9.11	Pass
			16-QAM	RB1#0	9.12	Pass
	5 MHz	LCH	QPSK	RB1#0	9.13	Pass
			16-QAM	RB1#0	9.14	Pass
		MCH	QPSK	RB1#0	9.15	Pass
			16-QAM	RB1#0	9.16	Pass
		HCH	QPSK	RB1#0	9.17	Pass
			16-QAM	RB1#0	9.18	Pass
	10 MHz	MCH	QPSK	RB1#0	9.19	Pass
			16-QAM	RB1#0	9.20	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 66	1.4 MHz	LCH	QPSK	RB1#0	10.1	Pass
			16-QAM	RB1#0	10.2	Pass
		MCH	QPSK	RB1#0	10.3	Pass
			16-QAM	RB1#0	10.4	Pass
		HCH	QPSK	RB1#0	10.5	Pass
			16-QAM	RB1#0	10.6	Pass
	3 MHz	LCH	QPSK	RB1#0	10.7	Pass
			16-QAM	RB1#0	10.8	Pass
		MCH	QPSK	RB1#0	10.9	Pass
			16-QAM	RB1#0	10.10	Pass
		HCH	QPSK	RB1#0	10.11	Pass
			16-QAM	RB1#0	10.12	Pass
	5 MHz	LCH	QPSK	RB1#0	10.13	Pass
			16-QAM	RB1#0	10.14	Pass
		MCH	QPSK	RB1#0	10.15	Pass
			16-QAM	RB1#0	10.16	Pass
		HCH	QPSK	RB1#0	10.17	Pass
			16-QAM	RB1#0	10.18	Pass
	10 MHz	LCH	QPSK	RB1#0	10.19	Pass
			16-QAM	RB1#0	10.20	Pass
		MCH	QPSK	RB1#0	10.21	Pass
			16-QAM	RB1#0	10.22	Pass
		HCH	QPSK	RB1#0	10.23	Pass
			16-QAM	RB1#0	10.24	Pass
	15 MHz	LCH	QPSK	RB1#0	10.25	Pass
			16-QAM	RB1#0	10.26	Pass
		MCH	QPSK	RB1#0	10.27	Pass
			16-QAM	RB1#0	10.28	Pass
		HCH	QPSK	RB1#0	10.29	Pass
			16-QAM	RB1#0	10.30	Pass
	20 MHz	LCH	QPSK	RB1#0	10.31	Pass
			16-QAM	RB1#0	10.32	Pass
		MCH	QPSK	RB1#0	10.33	Pass
			16-QAM	RB1#0	10.34	Pass
		HCH	QPSK	RB1#0	10.35	Pass
			16-QAM	RB1#0	10.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 40 (2305-2315MHz)	5 MHz	LCH	QPSK	RB1#0	11.1	Pass
			16-QAM	RB1#0	11.2	Pass
		MCH	QPSK	RB1#0	11.3	Pass
			16-QAM	RB1#0	11.4	Pass
		HCH	QPSK	RB1#0	11.5	Pass
			16-QAM	RB1#0	11.6	Pass
	10 MHz	MCH	QPSK	RB1#0	11.7	Pass
			16-QAM	RB1#0	11.8	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note2}	Verdict
Band 40 (2350-2360MHz)	5 MHz	LCH	QPSK	RB1#0	12.1	Pass
			16-QAM	RB1#0	12.2	Pass
		MCH	QPSK	RB1#0	12.3	Pass
			16-QAM	RB1#0	12.4	Pass
		HCH	QPSK	RB1#0	12.5	Pass
			16-QAM	RB1#0	12.6	Pass
	10 MHz	MCH	QPSK	RB1#0	12.7	Pass
			16-QAM	RB1#0	12.8	Pass

A.6 Band Edge

Note 1: Test plots please refer to the document “Annex No.:BL-SZ2370302-501 Data Part 5.pdf”.

LTE Mode Test Verdict

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 2	1.4 MHz	LCH	QPSK	RB1#0	1.1	Pass
				RB6#0	1.2	Pass
			16-QAM	RB1#0	1.3	Pass
				RB6#0	1.4	Pass
		HCH	QPSK	RB1#5	1.5	Pass
				RB6#0	1.6	Pass
			16-QAM	RB1#5	1.7	Pass
				RB6#0	1.8	Pass
	3 MHz	LCH	QPSK	RB1#0	1.9	Pass
				RB15#0	1.10	Pass
			16-QAM	RB1#0	1.11	Pass
				RB15#0	1.12	Pass
		HCH	QPSK	RB1#14	1.13	Pass
				RB15#0	1.14	Pass
			16-QAM	RB1#14	1.15	Pass
				RB15#0	1.16	Pass
	5 MHz	LCH	QPSK	RB1#0	1.17	Pass
				RB25#0	1.18	Pass
			16-QAM	RB1#0	1.19	Pass
				RB25#0	1.20	Pass
		HCH	QPSK	RB1#24	1.21	Pass
				RB25#0	1.22	Pass
			16-QAM	RB1#24	1.23	Pass
				RB25#0	1.24	Pass
	10 MHz	LCH	QPSK	RB1#0	1.25	Pass
				RB50#0	1.26	Pass
			16-QAM	RB1#0	1.27	Pass
				RB50#0	1.28	Pass
		HCH	QPSK	RB1#49	1.29	Pass
				RB50#0	1.30	Pass
			16-QAM	RB1#49	1.31	Pass
				RB50#0	1.32	Pass
	15 MHz	LCH	QPSK	RB1#0	1.33	Pass
				RB75#0	1.34	Pass
			16-QAM	RB1#0	1.35	Pass
				RB75#0	1.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
		HCH	QPSK	RB1#74	1.37	Pass
				RB75#0	1.38	Pass
			16-QAM	RB1#74	1.39	Pass
				RB75#0	1.40	Pass
	20 MHz	LCH	QPSK	RB1#0	1.41	Pass
				RB100#0	1.42	Pass
			16-QAM	RB1#0	1.43	Pass
				RB100#0	1.44	Pass
		HCH	QPSK	RB1#99	1.45	Pass
				RB100#0	1.46	Pass
			16-QAM	RB1#99	1.47	Pass
				RB100#0	1.48	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 4	1.4 MHz	LCH	QPSK	RB1#0	2.1	Pass
				RB6#0	2.2	Pass
			16-QAM	RB1#0	2.3	Pass
				RB6#0	2.4	Pass
		HCH	QPSK	RB1#5	2.5	Pass
				RB6#0	2.6	Pass
			16-QAM	RB1#5	2.7	Pass
				RB6#0	2.8	Pass
	3 MHz	LCH	QPSK	RB1#0	2.9	Pass
				RB15#0	2.10	Pass
			16-QAM	RB1#0	2.11	Pass
				RB15#0	2.12	Pass
		HCH	QPSK	RB1#14	2.13	Pass
				RB15#0	2.14	Pass
			16-QAM	RB1#14	2.15	Pass
				RB15#0	2.16	Pass
	5 MHz	LCH	QPSK	RB1#0	2.17	Pass
				RB25#0	2.18	Pass
			16-QAM	RB1#0	2.19	Pass
				RB25#0	2.20	Pass
		HCH	QPSK	RB1#24	2.21	Pass
				RB25#0	2.22	Pass
			16-QAM	RB1#24	2.23	Pass
				RB25#0	2.24	Pass
	10 MHz	LCH	QPSK	RB1#0	2.25	Pass
				RB50#0	2.26	Pass
			16-QAM	RB1#0	2.27	Pass
				RB50#0	2.28	Pass
		HCH	QPSK	RB1#49	2.29	Pass
				RB50#0	2.30	Pass
			16-QAM	RB1#49	2.31	Pass
				RB50#0	2.32	Pass
	15 MHz	LCH	QPSK	RB1#0	2.33	Pass
				RB75#0	2.34	Pass
			16-QAM	RB1#0	2.35	Pass
				RB75#0	2.36	Pass
		HCH	QPSK	RB1#74	2.37	Pass
				RB75#0	2.38	Pass
			16-QAM	RB1#74	2.39	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
				RB75#0	2.40	Pass
	20 MHz	LCH	QPSK	RB1#0	2.41	Pass
				RB100#0	2.42	Pass
			16-QAM	RB1#0	2.43	Pass
				RB100#0	2.44	Pass
		HCH	QPSK	RB1#99	2.45	Pass
				RB100#0	2.46	Pass
			16-QAM	RB1#99	2.47	Pass
				RB100#0	2.48	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 5	1.4 MHz	LCH	QPSK	RB1#0	3.1	Pass
				RB6#0	3.2	Pass
			16-QAM	RB1#0	3.3	Pass
				RB6#0	3.4	Pass
		HCH	QPSK	RB1#5	3.5	Pass
				RB6#0	3.6	Pass
			16-QAM	RB1#5	3.7	Pass
				RB6#0	3.8	Pass
	3 MHz	LCH	QPSK	RB1#0	3.9	Pass
				RB15#0	3.10	Pass
			16-QAM	RB1#0	3.11	Pass
				RB15#0	3.12	Pass
		HCH	QPSK	RB1#14	3.13	Pass
				RB15#0	3.14	Pass
			16-QAM	RB1#14	3.15	Pass
				RB15#0	3.16	Pass
	5 MHz	LCH	QPSK	RB1#0	3.17	Pass
				RB25#0	3.18	Pass
			16-QAM	RB1#0	3.19	Pass
				RB25#0	3.20	Pass
		HCH	QPSK	RB1#24	3.21	Pass
				RB25#0	3.22	Pass
			16-QAM	RB1#24	3.23	Pass
				RB25#0	3.24	Pass
	10 MHz	LCH	QPSK	RB1#0	3.25	Pass
				RB50#0	3.26	Pass
			16-QAM	RB1#0	3.27	Pass
				RB50#0	3.28	Pass
		HCH	QPSK	RB1#49	3.29	Pass
				RB50#0	3.30	Pass
			16-QAM	RB1#49	3.31	Pass
				RB50#0	3.32	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 18 (824-830 MHz)	5 MHz	LCH	QPSK	RB1#0	4.1	Pass
				RB25#0	4.2	Pass
			16-QAM	RB1#0	4.3	Pass
				RB25#0	4.4	Pass
		HCH	QPSK	RB1#24	4.5	Pass
				RB25#0	4.6	Pass
			16-QAM	RB1#24	4.7	Pass
				RB25#0	4.8	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 18 (815-824 MHz)	5 MHz	LCH	QPSK	RB1#0	5.1	Pass
				RB25#0	5.2	Pass
			16-QAM	RB1#0	5.3	Pass
				RB25#0	5.4	Pass
		HCH	QPSK	RB1#24	5.5	Pass
				RB25#0	5.6	Pass
			16-QAM	RB1#24	5.7	Pass
				RB25#0	5.8	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 19	5 MHz	LCH	QPSK	RB1#0	6.1	Pass
				RB25#0	6.2	Pass
			16-QAM	RB1#0	6.3	Pass
				RB25#0	6.4	Pass
		HCH	QPSK	RB1#24	6.5	Pass
				RB25#0	6.6	Pass
			16-QAM	RB1#24	6.7	Pass
				RB25#0	6.8	Pass
	10 MHz	LCH	QPSK	RB1#0	6.9	Pass
				RB50#0	6.10	Pass
			16-QAM	RB1#0	6.11	Pass
				RB50#0	6.12	Pass
		HCH	QPSK	RB1#49	6.13	Pass
				RB50#0	6.14	Pass
			16-QAM	RB1#49	6.15	Pass
				RB50#0	6.16	Pass
	15 MHz	LCH	QPSK	RB1#0	6.17	Pass
				RB75#0	6.18	Pass
			16-QAM	RB1#0	6.19	Pass
				RB75#0	6.20	Pass
		HCH	QPSK	RB1#74	6.21	Pass
				RB75#0	6.22	Pass
			16-QAM	RB1#74	6.23	Pass
				RB75#0	6.24	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 25	1.4 MHz	LCH	QPSK	RB1#0	7.1	Pass
				RB6#0	7.2	Pass
			16-QAM	RB1#0	7.3	Pass
				RB6#0	7.4	Pass
		HCH	QPSK	RB1#5	7.5	Pass
				RB6#0	7.6	Pass
			16-QAM	RB1#5	7.7	Pass
				RB6#0	7.8	Pass
	3 MHz	LCH	QPSK	RB1#0	7.9	Pass
				RB15#0	7.10	Pass
			16-QAM	RB1#0	7.11	Pass
				RB15#0	7.12	Pass
		HCH	QPSK	RB1#14	7.13	Pass
				RB15#0	7.14	Pass
			16-QAM	RB1#14	7.15	Pass
				RB15#0	7.16	Pass
	5 MHz	LCH	QPSK	RB1#0	7.17	Pass
				RB25#0	7.18	Pass
			16-QAM	RB1#0	7.19	Pass
				RB25#0	7.20	Pass
		HCH	QPSK	RB1#24	7.21	Pass
				RB25#0	7.22	Pass
			16-QAM	RB1#24	7.23	Pass
				RB25#0	7.24	Pass
	10 MHz	LCH	QPSK	RB1#0	7.25	Pass
				RB50#0	7.26	Pass
			16-QAM	RB1#0	7.27	Pass
				RB50#0	7.28	Pass
		HCH	QPSK	RB1#49	7.29	Pass
				RB50#0	7.30	Pass
			16-QAM	RB1#49	7.31	Pass
				RB50#0	7.32	Pass
	15 MHz	LCH	QPSK	RB1#0	7.33	Pass
				RB75#0	7.34	Pass
			16-QAM	RB1#0	7.35	Pass
				RB75#0	7.36	Pass
		HCH	QPSK	RB1#74	7.37	Pass
				RB75#0	7.38	Pass
			16-QAM	RB1#74	7.39	Pass
				RB75#0	7.40	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
	20 MHz	LCH	QPSK	RB1#0	7.41	Pass
				RB100#0	7.42	Pass
			16-QAM	RB1#0	7.43	Pass
				RB100#0	7.44	Pass
		HCH	QPSK	RB1#99	7.45	Pass
				RB100#0	7.46	Pass
			16-QAM	RB1#99	7.47	Pass
				RB100#0	7.48	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 26 (824-849 MHz)	MH	LCH	QPSK	RB1#0	8.1	Pass
				RB6#0	8.2	Pass
			16-QAM	RB1#0	8.3	Pass
				RB6#0	8.4	Pass
		HCH	QPSK	RB1#5	8.5	Pass
				RB6#0	8.6	Pass
			16-QAM	RB1#5	8.7	Pass
				RB6#0	8.8	Pass
	3 MHz	LCH	QPSK	RB1#0	8.9	Pass
				RB15#0	8.10	Pass
			16-QAM	RB1#0	8.11	Pass
				RB15#0	8.12	Pass
		HCH	QPSK	RB1#14	8.13	Pass
				RB15#0	8.14	Pass
			16-QAM	RB1#14	8.15	Pass
				RB15#0	8.16	Pass
	5 MHz	LCH	QPSK	RB1#0	8.17	Pass
				RB25#0	8.18	Pass
			16-QAM	RB1#0	8.19	Pass
				RB25#0	8.20	Pass
		HCH	QPSK	RB1#24	8.21	Pass
				RB25#0	8.22	Pass
			16-QAM	RB1#24	8.23	Pass
				RB25#0	8.24	Pass
	10 MHz	LCH	QPSK	RB1#0	8.25	Pass
				RB50#0	8.26	Pass
			16-QAM	RB1#0	8.27	Pass
				RB50#0	8.28	Pass
		HCH	QPSK	RB1#49	8.29	Pass
				RB50#0	8.30	Pass
			16-QAM	RB1#49	8.31	Pass
				RB50#0	8.32	Pass
15 MHz	LCH	QPSK	RB1#0	8.33	Pass	
			RB75#0	8.34	Pass	
		16-QAM	RB1#0	8.35	Pass	
			RB75#0	8.36	Pass	
	HCH	QPSK	RB1#74	8.37	Pass	
			RB75#0	8.38	Pass	
		16-QAM	RB1#74	8.39	Pass	
			RB75#0	8.40	Pass	

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 26 (814-824 MHz)	1.4 MHz	LCH	QPSK	RB1#0	9.1	Pass
				RB6#0	9.2	Pass
			16-QAM	RB1#0	9.3	Pass
				RB6#0	9.4	Pass
		HCH	QPSK	RB1#5	9.5	Pass
				RB6#0	9.6	Pass
			16-QAM	RB1#5	9.7	Pass
				RB6#0	9.8	Pass
	3 MHz	LCH	QPSK	RB1#0	9.9	Pass
				RB15#0	9.10	Pass
			16-QAM	RB1#0	9.11	Pass
				RB15#0	9.12	Pass
		HCH	QPSK	RB1#14	9.13	Pass
				RB15#0	9.14	Pass
			16-QAM	RB1#14	9.15	Pass
				RB15#0	9.16	Pass
	5 MHz	LCH	QPSK	RB1#0	9.17	Pass
				RB25#0	9.18	Pass
			16-QAM	RB1#0	9.19	Pass
				RB25#0	9.20	Pass
		HCH	QPSK	RB1#24	9.21	Pass
				RB25#0	9.22	Pass
			16-QAM	RB1#24	9.23	Pass
				RB25#0	9.24	Pass
	10 MHz	LCH	QPSK	RB1#0	9.25	Pass
				RB50#0	9.26	Pass
			16-QAM	RB1#0	9.27	Pass
				RB50#0	9.28	Pass
		HCH	QPSK	RB1#49	9.29	Pass
				RB50#0	9.30	Pass
			16-QAM	RB1#49	9.31	Pass
				RB50#0	9.32	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 66	1.4 MHz	LCH	QPSK	RB1#0	10.1	Pass
				RB6#0	10.2	Pass
			16-QAM	RB1#0	10.3	Pass
				RB6#0	10.4	Pass
		HCH	QPSK	RB1#5	10.5	Pass
				RB6#0	10.6	Pass
			16-QAM	RB1#5	10.7	Pass
				RB6#0	10.8	Pass
	3 MHz	LCH	QPSK	RB1#0	10.9	Pass
				RB15#0	10.10	Pass
			16-QAM	RB1#0	10.11	Pass
				RB15#0	10.12	Pass
		HCH	QPSK	RB1#14	10.13	Pass
				RB15#0	10.14	Pass
			16-QAM	RB1#14	10.15	Pass
				RB15#0	10.16	Pass
	5 MHz	LCH	QPSK	RB1#0	10.17	Pass
				RB25#0	10.18	Pass
			16-QAM	RB1#0	10.19	Pass
				RB25#0	10.20	Pass
		HCH	QPSK	RB1#24	10.21	Pass
				RB25#0	10.22	Pass
			16-QAM	RB1#24	10.23	Pass
				RB25#0	10.24	Pass
	10 MHz	LCH	QPSK	RB1#0	10.25	Pass
				RB50#0	10.26	Pass
			16-QAM	RB1#0	10.27	Pass
				RB50#0	10.28	Pass
		HCH	QPSK	RB1#49	10.29	Pass
				RB50#0	10.30	Pass
			16-QAM	RB1#49	10.31	Pass
				RB50#0	10.32	Pass
	15 MHz	LCH	QPSK	RB1#0	10.33	Pass
				RB75#0	10.34	Pass
			16-QAM	RB1#0	10.35	Pass
				RB75#0	10.36	Pass
		HCH	QPSK	RB1#74	10.37	Pass
				RB75#0	10.38	Pass
			16-QAM	RB1#74	10.39	Pass
				RB75#0	10.40	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
	20 MHz	LCH	QPSK	RB1#0	10.41	Pass
				RB100#0	10.42	Pass
			16-QAM	RB1#0	10.43	Pass
				RB100#0	10.44	Pass
		HCH	QPSK	RB1#99	10.45	Pass
				RB100#0	10.46	Pass
			16-QAM	RB1#99	10.47	Pass
				RB100#0	10.48	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 40 (2305-2315MHz)	5 MHz	LCH	QPSK	RB1#0	11.1	Pass
				RB25#0	11.2	Pass
			16-QAM	RB1#0	11.3	Pass
				RB25#0	11.4	Pass
		HCH	QPSK	RB1#24	11.5	Pass
				RB25#0	11.6	Pass
			16-QAM	RB1#24	11.7	Pass
				RB25#0	11.8	Pass
	10 MHz	LCH	QPSK	RB1#0	11.9	Pass
				RB50#0	11.10	Pass
			16-QAM	RB1#0	11.11	Pass
				RB50#0	11.12	Pass
		HCH	QPSK	RB1#49	11.13	Pass
				RB50#0	11.14	Pass
			16-QAM	RB1#49	11.15	Pass
				RB50#0	11.16	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band 40(2350 - 2360MHz)	5 MHz	LCH	QPSK	RB1#0	12.1	Pass
				RB25#0	12.2	Pass
			16-QAM	RB1#0	12.3	Pass
				RB25#0	12.4	Pass
		HCH	QPSK	RB1#24	12.5	Pass
				RB25#0	12.6	Pass
			16-QAM	RB1#24	12.7	Pass
				RB25#0	12.8	Pass
	10 MHz	LCH	QPSK	RB1#0	12.9	Pass
				RB50#0	12.10	Pass
			16-QAM	RB1#0	12.11	Pass
				RB50#0	12.12	Pass
		HCH	QPSK	RB1#49	12.13	Pass
				RB50#0	12.14	Pass
			16-QAM	RB1#49	12.15	Pass
				RB50#0	12.16	Pass

A.7 Field Strength of Spurious Radiation

Note 1: All modes have been tested, and only the worst case data are shown here.

Note 2: The frequencies of verdict which are marked by "N/A" should be ignored because they are UE carrier frequency.

Note 3: Test plots please refer to the document "Annex No.:BL-SZ2370302-501 Data Part 6.pdf".

Note 4: The disturbance above 26.5GHz was very low, and the above harmonics were the highest point could be found when testing, so only the worst case data displayed in this report.

LTE Mode Test Verdict


Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 2	1.4 MHz	LCH	QPSK	RB3#0	1.1	Pass
Band 4	1.4 MHz	LCH	QPSK	RB1#0	1.2	Pass
Band 5	1.4 MHz	MCH	QPSK	RB1#5	1.3	Pass
Band 18 (824-830 MHz)	5 MHz	LCH	QPSK	RB1#24	1.4	Pass
Band 18 (815-824 MHz)	5 MHz	MCH	QPSK	RB1#0	1.5	Pass
Band 19	5 MHz	LCH	QPSK	RB1#24	1.6	Pass
Band 25	5 MHz	LCH	QPSK	RB1#0	1.7	Pass
Band 26 (824-849 MHz)	3 MHz	HCH	QPSK	RB1#0	1.8	Pass
Band 26 (814-824 MHz)	3 MHz	LCH	QPSK	RB1#14	1.9	Pass
Band 66	3 MHz	HCH	QPSK	RB1#14	1.10	Pass
Band 40 (2305-2315MHz)	5 MHz	HCH	QPSK	RB1#0	1.11	Pass
Band 40 (2350-2360MHz)	5 MHz	HCH	QPSK	RB1#24	1.12	Pass

A.8 Receiver Spurious Emissions

Note: Only the worst test results were recorded in this report.

30MHz to 1GHz, ANT H


RE Test case_FCC Part 15B_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	54.008	17.73	-25.55	40.0	22.27	Peak	0.00	100	Horizontal	Pass
2	134.420	22.01	-29.96	43.5	21.49	Peak	343.00	200	Horizontal	Pass
3	246.262	22.69	-24.99	46.0	23.31	Peak	0.00	100	Horizontal	Pass
4	328.809	25.00	-22.81	46.0	21.00	Peak	170.00	100	Horizontal	Pass
5	393.992	24.33	-21.10	46.0	21.67	Peak	186.00	100	Horizontal	Pass
6	993.161	27.85	-8.40	54.0	26.15	Peak	159.00	200	Horizontal	Pass

30MHz to 1GHz, ANT V


RE Test case_FCC Part 15B_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	53.765	29.71	-25.57	40.0	10.29	Peak	56.00	100	Vertical	Pass
2	71.467	27.47	-29.91	40.0	12.53	Peak	61.00	100	Vertical	Pass
3	94.796	27.34	-27.60	43.5	16.16	Peak	91.00	100	Vertical	Pass
4	159.738	33.26	-29.59	43.5	10.24	Peak	324.00	100	Vertical	Pass
5	244.176	26.87	-25.09	46.0	19.13	Peak	222.00	100	Vertical	Pass
6	466.742	26.54	-19.51	46.0	19.46	Peak	284.00	100	Vertical	Pass

1GHz to 18GHz, ANT H


RE Test case_FCC Part 15B_FCC Part 15B Class B 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1647.600	38.94	-16.77	74.0	35.06	Peak	116.00	100	Horizontal	Pass
1**	1647.600	29.15	-16.77	54.0	24.85	AV	116.00	100	Horizontal	Pass
2	2923.100	44.95	-8.83	74.0	29.05	Peak	89.00	100	Horizontal	Pass
2**	2923.100	34.74	-8.83	54.0	19.26	AV	89.00	100	Horizontal	Pass
3	4053.750	49.32	-1.82	74.0	24.68	Peak	171.00	100	Horizontal	Pass
3**	4053.750	39.74	-1.82	54.0	14.26	AV	171.00	100	Horizontal	Pass
4	7999.500	55.70	2.88	74.0	18.30	Peak	33.00	100	Horizontal	Pass
4**	7999.500	46.62	2.88	54.0	7.38	AV	33.00	100	Horizontal	Pass
5	13833.500	56.71	5.38	74.0	17.29	Peak	198.00	100	Horizontal	Pass
5**	13833.500	47.24	5.38	54.0	6.76	AV	198.00	100	Horizontal	Pass
6	17112.500	55.14	3.55	74.0	18.86	Peak	64.00	100	Horizontal	Pass
6**	17112.500	45.73	3.55	54.0	8.27	AV	64.00	100	Horizontal	Pass

1GHz to 18GHz, ANT V

RE Test case_FCC Part 15B_FCC Part 15B Class B 1GHz-18GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1992.100	40.48	-14.60	74.0	33.52	Peak	296.00	100	Vertical	Pass
1**	1992.100	31.36	-14.60	54.0	22.64	AV	296.00	100	Vertical	Pass
2	2630.800	44.50	-10.18	74.0	29.50	Peak	42.00	100	Vertical	Pass
2**	2630.800	33.98	-10.18	54.0	20.02	AV	42.00	100	Vertical	Pass
3	4890.250	52.91	0.25	74.0	21.09	Peak	135.00	100	Vertical	Pass
3**	4890.250	42.18	0.25	54.0	11.82	AV	135.00	100	Vertical	Pass
4	7766.750	55.96	2.57	74.0	18.04	Peak	144.00	100	Vertical	Pass
4**	7766.750	45.69	2.57	54.0	8.31	AV	144.00	100	Vertical	Pass
5	13808.500	55.99	5.70	74.0	18.01	Peak	122.00	100	Vertical	Pass
5**	13808.500	47.86	5.70	54.0	6.14	AV	122.00	100	Vertical	Pass
6	17099.000	55.17	3.71	74.0	18.83	Peak	190.00	100	Vertical	Pass
6**	17099.000	45.92	3.71	54.0	8.08	AV	190.00	100	Vertical	Pass

A.9 AC Power-line Conducted Emissions

Note: Only the worst test results were recorded in this report.

L Phase


CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.270	39.82	9.79	61.12	21.30	Peak	L	Pass
1**	0.270	27.88	9.79	51.12	23.24	AV	L	Pass
2	0.512	37.43	10.10	56.00	18.57	Peak	L	Pass
2**	0.512	25.59	10.10	46.00	20.41	AV	L	Pass
3	0.910	44.08	9.96	56.00	11.92	Peak	L	Pass
3**	0.910	28.95	9.96	46.00	17.05	AV	L	Pass
4	2.228	32.39	10.19	56.00	23.61	Peak	L	Pass
4**	2.228	19.15	10.19	46.00	26.85	AV	L	Pass
5	7.172	30.02	10.21	60.00	29.98	Peak	L	Pass
5**	7.172	15.95	10.21	50.00	34.05	AV	L	Pass
6	29.930	33.09	10.93	60.00	26.91	Peak	L	Pass
6**	29.930	20.82	10.93	50.00	29.18	AV	L	Pass

N Phase

CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.330	39.13	9.74	59.45	20.32	Peak	N	Pass
1**	0.330	26.25	9.74	49.45	23.20	AV	N	Pass
2	0.392	39.40	10.28	58.02	18.62	Peak	N	Pass
2**	0.392	25.41	10.28	48.02	22.61	AV	N	Pass
3	0.916	44.20	10.07	56.00	11.80	Peak	N	Pass
3**	0.916	27.07	10.07	46.00	18.93	AV	N	Pass
4	2.130	33.67	10.32	56.00	22.33	Peak	N	Pass
4**	2.130	19.58	10.32	46.00	26.42	AV	N	Pass
5	3.184	34.28	10.05	56.00	21.72	Peak	N	Pass
5**	3.184	19.26	10.05	46.00	26.74	AV	N	Pass
6	4.692	33.17	10.22	56.00	22.83	Peak	N	Pass
6**	4.692	15.97	10.22	46.00	30.03	AV	N	Pass

ANNEX B TEST SETUP PHOTOS

Please refer to the document “BL-SZ2370302-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer to the document “BL-SZ2370302-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer to the document “BL-SZ2370302-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--