



RF MPE REPORT

Report No.: 20230717G07474X-W4

Product Name: A4 Portable THERMAL PRINTER

Model No.: JXM800R-08C

FCC ID: 2BB6H-JXM800R08C

Applicant: Xiamen Jing Xin Science and Technology Co., Ltd

Address: 2nd Floor, No, 33-35, Huli Avenue, Xiamen Area, China(Fujian) Pilot Free Trade Zone

Dates of Testing: 07/05/2023 - 07/14/2023

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product.....: A4 Portable THERMAL PRINTER
Brand Name.....: JINGXIN
Trade Name: 
Applicant.....: Xiamen Jing Xin Science and Technology Co., Ltd
Applicant Address.....: 2nd Floor, No, 33-35, Huli Avenue, Xiamen Area, China(Fujian) Pilot Free Trade Zone
Manufacturer.....: Xiamen Jing Xin Science and Technology Co., Ltd
Manufacturer Address.....: 2nd Floor, No, 33-35, Huli Avenue, Xiamen Area, China(Fujian) Pilot Free Trade Zone
Test Standards.....: 47 CFR Part 2.1091
Test Result.....: Pass

Tested by: Kim Li 2023.07.19
 Kim Li, Test Engineer

Reviewed by.....: Chris You 2023.07.19
 Chris You, Senior Engineer

Approved by.....: Yang Fan 2023.07.19
 Yang Fan, Manager



Table of Contents

1. GENERAL INFORMATION.....	5
1.1. EUT Description	5
1.2. EUT Description	6
1.3. Laboratory Facilities	6
1.4. Laboratory Location	6
2. TECHNICAL REQUIREMENTS SPECIFICATION IN CFR TITLE 47 PART 2.1091... 	7
2.1. Exposure Limits	7
2.2. Predication of MPE limit at a given distance	7
2.3. Evaluation Results	8
2.4. Conclusion	8



Change History		
Issue	Date	Reason for change
1.0	2023.07.19	First edition

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	A4 Portable THERMAL PRINTER	
Model No.	JXM800R-08C	
Hardware Version	JXM800R08_C_MAIN_V1 .0, JXM800R08C_MAIN_V5.0	
Software Version	JXM800R08_V1.4.3, JXD800R08_V1.4.4	
EUT supports Radios application	Bluetooth V4.0/ Bluetooth LE V4.0	
Frequency Range(Tx)	BT/BLE:2402MHz~2480MHz	
Modulation Type	BT	GFSK, $\pi/4$ -DQPSK, 8DPSK
	BLE	GFSK
Antenna gain	BT/BLE: 1.32dBi	
Antenna Type	Ceramic antenna	

Note 1: The IC model of the upper motherboard digit number, U4, is different. So there are two hardware and software versions.



1.2. EUT Description

EUT has been tested according to the following standards.

No.	Identity	Document Title
1	47 CFR Part 1	Practice and Procedure
2	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
3	KDB 447498 D01 General RF Exposure Guidance v06	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
4	OET Bulletin 65 Edition 97-01	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

1.3. Laboratory Facilities

FCC-Registration No.: 406086

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Sep. 30, 2023.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Sep. 30, 2023.

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.4. Laboratory Location

Company Name:	CCIC Southern Testing Co., Ltd.
Address:	Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China

2. Technical Requirements Specification in CFR Title 47 Part 2.1091

2.1. Exposure Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	< 6
3.0-30	1824/f	4.89/f	*(900/f ²)	< 6
30-300	61.4	0.163	1.0	< 6
300-1500	/	/	f/300	< 6
1500-100,000	/	/	5	< 6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	< 30
1.34-30	824/f	2.19/f	*(180/f ²)	< 30
30-300	27.5	0.073	0.2	< 30
300-1500	/	/	f/1500	< 30
1500-100,000	/	/	1.0	< 30
Note: f = frequency in MHz. * = Plane-wave equivalent power density.				

2.2. Predication of MPE limit at a given distance

Refer to formulas on page 19 of OET Bulletin 65, Edition 97-01.

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna (appropriate units, e.g., cm)



2.3. Evaluation Results

Worst-Case mode Conducted Output Power Results for BT/BLE

Band	Mode	Frequency (MHz)	Maximum Output Power (dBm)	Max Tune up power (dBm)	Max Tune up power (mW)
BT	DQPSK	2402	-5.710	-6 ± 1	0.316
BLE	GFSK	2402	-6.298	-7 ± 1	0.251

Calculation results: Worst-Case mode

Band	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm ²)	Power Density (mW/cm ²)	Ratio
BT EDR	1.32	1.36	20	0.0001	1.0	/
BLE	1.32	1.36	20	0.0001	1.0	/

2.4. Conclusion

According to the KDB 447498 D01 General RF Exposure Guidance v06 section 7.2 determine the device is exclusion from SAR test.

**** END OF REPORT ****