

# FCC RF Exposure

EUT Description: Smart Watch

Model No.: MT56

FCC ID: 2BBBT-MT56

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{(max power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

Where:

Result =  $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

Frequency (MHz)	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power (dBm/mW)	Min test separation distance (mm)	Result	Limit (mW/cm <sup>2</sup> )	SAR Test Exclusion
2441	5.81	5±1(6)	3.981	5	1.244	3.0	Pass

Note:

PK Output power = conducted power.

Conducted power see the test report HK2408094530-E, antenna gain=0.17dBi

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 1.244 which is  $\leq 3$ , RF Exposure testing is not required.

Note: Exclusion Thresholds Results =  $\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})}$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance = 5mm