

Label:

Portable Power Station	
Model: SR1KW8L-SG1-US	
HVIN: SR1KW8L-SG1-US	
Battery: 1229Wh, 51.2V $\overline{\text{---}}$	
Discharge temperature range: -20-45°C	
Charge temperature range: 0-45°C	
AC Input: 100-120V~, 50/60Hz, 12A max., 1500W max.	
Solar/Car input x1: 13-45V $\overline{\text{---}}$ 12A max., 400W max.	
AC socket x3 (Inverter Mode):100-120V~, 50/60Hz, 15A max., 1800W max.	
AC socket (Bypass Mode) x3:100-120V~, 50/60Hz, 15A max., 1800W max.	
Cigarette lighter output/DC 5521 total: 126W max.	
Cigarette lighter output: 12.6V $\overline{\text{---}}$ 10A max., 126W max.	
DC 5521 output x2: 12.6V $\overline{\text{---}}$ 3A, 40.8W max.	
USB-C1/C2 output: 5/9/12/15V $\overline{\text{---}}$ 3A, 20V $\overline{\text{---}}$ 5A, 100W max.	
USB-A1/A2 output: 5V $\overline{\text{---}}$ 3A, 9V $\overline{\text{---}}$ 2A, 12V $\overline{\text{---}}$ 1.5A, 18W max.	
USB-A3/A4 output: 5V $\overline{\text{---}}$ 2.4A, 12W max.	FCC ID: 2BBDT-1KW8
Made in China	IC: 30669-1KV8
Dongguan Hinen New Energy Technology Co., Ltd	

