

Portable Power Station

Model: SR03KWL-SG1-AU HVIN : SR03KWL-SG1-AU

Battery: 2560Wh, 51.2V

Power Input/Output: 40-58.8V 50A charge, 70A discharge [max.]

Discharge temperature range: -20-45°C

Charge temperature range: 0-45°C

AC Input: 220-240V~, 50/60Hz, 10A max., 2300W max.

Solar/Car input x2: 13-45V 12A max., 800W max.

AC socket x3 : 220-240V~, 50/60Hz, 16A max., 3000W max.

AC socket [Bypass Mode] x3 : 220-240V~, 50/60Hz, 10A max., 2300W max.

Cigarette lighter output/DC 5521 total: max. 126W

Cigarette lighter output: 12.6V 10A max., 126W max.

DC 5521 output x2: 12.6V 3A, 40.8W max.

Anderson terminal output: 12.6V 30A max., 378W max.

USB-C1/C2 output: 5/9/12/15V 3A, 20V 5A, 100W max.

USB-A1/A2 output: 5V 3A, 9V 2A, 12V 1.5A, 18W max.

USB-A3/A4 output: 5V 2.4A, 12W max.

Made in China

FCC ID: 2BBDT-3KV

IC: 30669-3KV

Portable Power Station

Model: SR03KWL-SG1-AU HVIN: SR03KWL-SG1-AU

Battery: 2560Wh, 51.2V

Power Input/Output: 40-58.8V 50A charge, 70A discharge [max.]

Discharge temperature range: -20-45°C

Charge temperature range: 0-45°C

AC Input: 220-240V~, 50/60Hz, 10A max., 2300W max.

Solar/Car input x2: 13-45V 12A max., 800W max.

AC socket x3 : 220-240V~, 50/60Hz, 16A max., 3000W max.

AC socket [Bypass Mode] x3 : 220-240V~, 50/60Hz, 10A max., 2300W max.

Cigarette lighter output/DC 5521 total: max. 126W

Cigarette lighter output: 12.6V 10A max., 126W max.

DC 5521 output x2: 12.6V 3A, 40.8W max.

Anderson terminal output: 12.6V 30A max., 378W max.

USB-C1/C2 output: 5/9/12/15V 3A, 20V 5A, 100W max.

USB-A1/A2 output: 5V 3A, 9V 2A, 12V 1.5A, 18W max.

USB-A3/A4 output: 5V 2.4A, 12W max.

Made in China

FCC ID: 2BB DT-3KV

IC: 30669-3KV

