

Test Report

Product: 4-in-1 Wireless Charger

Trade Mark: N/A

Model Number: W405

FCC ID: 2BBEH-W405

Prepared for

Jiangxi Kingtron Tech Co., Ltd.
Luoxin Tech., Industrial Park, 2nd District, Quannan Industrial
Park.Ganzhou, Jiangxi, China, 341800

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110
Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	DESCRIPTION OF EUT	5
1.2	TEST MODE.....	5
1.3	TEST SETUP	6
1.4	ANCILLARY EQUIPMENT	6
2	SUMMARY OF TEST RESULT	7
3	TEST FACILITIES AND ACCREDITATIONS	8
3.1	TEST LABORATORY	8
3.2	ENVIRONMENTAL CONDITIONS	8
3.3	MEASUREMENT UNCERTAINTY	8
3.4	TEST SOFTWARE	8
4	LIST OF TEST EQUIPMENT	9
5	TEST ITEM AND RESULTS.....	11
5.1	ANTENNA REQUIREMENT	11
5.2	CONDUCTED EMISSION.....	12
5.3	RADIATED EMISSION	16
5.4	OCCUPIED BANDWIDTH	21
6	PHOTOGRAPHS OF THE TEST SETUP.....	24
7	PHOTOGRAPHS OF THE EUT.....	26

TEST RESULT CERTIFICATION

Applicant's Name..... : Jiangxi Kingtron Tech Co., Ltd.
Address : Luoxin Tech., Industrial Park, 2nd District, Quannan Industrial
Park.Ganzhou, Jiangxi, China, 341800
Manufacturer's Name : Jiangxi Kingtron Tech Co., Ltd.
Address : Luoxin Tech., Industrial Park, 2nd District, Quannan Industrial
Park.Ganzhou, Jiangxi, China, 341800

Product description

Product name : 4-in-1 Wireless Charger
Model Number : W405


Standards : FCC Part 15C
Test procedure..... : ANSI C63.4: 2014

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.


Date of Test :
Date (s) of performance of tests..... : Aug. 28. 2023~Sept. 05. 2023
Test Result..... : **Pass**

Testing Engineer : 

(Z o e S u)

Technical Manager : 

(G a r y L u)

Authorized Signatory : 

(L e o S u)

1 General Description

1.1 Description of EUT

Product name:	4-in-1 Wireless Charger
Model name:	W405
Series Model:	N/A
Different of series model:	N/A
Operation frequency:	Watch: 326kHz Phone 1: 115kHz–205kHz Phone 2: 115kHz–205kHz Air pods: 115kHz–205kHz
Operational mode:	Wireless charging
Modulation type:	FSK
Antenna type:	Coil Antenna
Hardware version:	W405-v01
Software version:	0x0FC139C2
Power supply:	Input: DC 5V/3A, 9V/3A Wireless Output(Phone 1): 5W/7.5W/10W Wireless Output(Phone 2): 5W/7.5W/10W Wireless Output(Air pods): 3W Wireless Output(Watch): 2.5W
Adapter information:	N/A

1.2 Test Mode

Pretest Test Mode	Description of Mode
1	Wireless Output (Phone 1:10W+Phone 2:10W+Air pods:3W+Watch:2.5W)
2	Wireless Output (Phone 1:7.5W+Phone 2:7.5W+Air pods:3W+Watch:2.5W)
3	Wireless Output (Phone 1:5W+Phone 2:5W+Air pods:3W+Watch:2.5W)

Test Item	Final Test Mode
Conducted Emissions	3
Radiated Emissions	1
20dB bandwidth	1

1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Adapter	MDY-10-EH	AA61904P29 6015C	Jiangsu Chenyang Electronics Co., Ltd
Air pods	/	/	Apple Inc.
Watch	/	/	Apple Inc.
Load	YBZ1.1	/	YBZ

2 Summary of Test Result

Test procedures according to the technical standards:

FCC Part 15C				
No.	Standard Section	Test Item	Result	Remark
1	FCC Part 15.203	Antenna Requirement	Pass	
2	FCC Part 15.207	Conducted Emission	Pass	
3	FCC Part 15.209	Radiated Emission	Pass	
4	FCC Part 15.215	20dB Bandwidth	Pass	

Note:

1. "N/A" means the test case does not apply to the test object.

3 Test Facilities and Accreditations

3.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

3.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

3.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Conducted emission(150kHz~30MHz)	± 2.5 dB	
Radiated emission(30MHz~1GHz)	± 4.2 dB	
Radiated emission (above 1GHz)	± 4.7 dB	
Temperature	± 1 degree	
Humidity	± 5 %	

3.4 Test Software

Software name	Manufacturer	Model	Version
EMI Measurement	Farad	EZ-EMC	V1.1.4.2
Conducted test system	MWRF-test	MTS 8310	V2.0.0

4 List of Test Equipment

Radiation emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E001	Horn Antenna	Schwarzbeck	BBHA 9120D	02592	2022-04-02	2024-04-01
2	HB-E002	Biconical log-periodic composite antenna	Schwarzbeck	VULB 9168	01340	2022-04-06	2024-04-05
3	HB-E003	SHF-EHF Horn	Schwarzbeck	BBHA 91270	01193	2022-04-02	2024-04-01
4	HB-E004	Preamplifier	Noyetec	LAN-0910	NYCM1420101	2023-05-11	2024-05-10
5	HB-E005	Preamplifier	Noyetec	LAN-0118	NYCM1420102	2023-05-12	2024-05-11
6	HB-E006	Preamplifier	Noyetec	LAN-1840	NYCM1420103	2023-06-11	2024-06-10
7	HB-E007	EMI TEST RECEIVER	R&S	ESR7	102520	2023-05-12	2024-05-11
8	HB-E009	POSITINAL COTROLLE R	Noyetec	N/A	N/A	/	/
9	HB-E013	RF switch	Noyetec	NY-RF4	NY0CM1420204	/	/
10	HB-E066	Illuminance Tester	TASI	TA8121	N/A	2023-05-11	2024-05-10
11	HB-E075	Active loop antenna	Schwarzbeck	FMZB 1519B	1519B-245	2022-07-24	2024-07-23
Conduction emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E014	4 Path V-LISN	Schwarzbeck	NNLK 8121	00770	2023-05-12	2024-05-11
2	HB-E015	Pulse Limiter	Schwarzbeck	VTSD 9561-F	00949	2023-05-12	2024-05-11
3	HB-E016	ZN23201	Noyetec	ZN23201	N/A	2023-05-11	2024-05-10
4	HB-E059	Attenuator	Xianghua	TS2-6-1	220215166	2023-05-12	2024-05-11
5	HB-E069	EMI TEST RECEIVER	R&S	ESCI	N/A	2023-05-12	2024-05-11
RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaioq Signal Generator	Agilent	N5181A	MY47070421	2023-05-11	2024-05-10
2	HB-E042	WIDEBAND RADIO COMMUNICA	R&S	CMW500	132108	2023-05-11	2024-05-10

		TION TESTER					
3	HB-E043	MXG Anaioq Signal Generator	Agilent	N5182A	US46240335	2023-05-11	2024-05-10
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2023-05-11	2024-05-10
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	/	/
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1	N/A	/	/

Note: the calibration interval of the above test instruments is 12&24 months and the calibrations are traceable to international system unit (SI).

5 Test Item And Results

5.1 Antenna Requirement

5.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 Test Result

The EUT antenna is Coil Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2 Conducted Emission


5.2.1 Limits

Limits – Class A		
Frequency (MHz)	Limit (dBµV)	
	Quasi-Peak	Average
0.15 to 0.5	79	66
0.5 to 30	73	60
Limits – Class B		
Frequency (MHz)	Limit (dBµV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50
Note: 1. the tighter limit applies at the band edges. 2. the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.		

5.2.2 Test Procedures


- a) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d) LISN is at least 80 cm from nearest part of EUT chassis.
- e) For the actual test configuration, please refer to the related Item – photographs of the test setup.

5.2.3 Test setup




5.2.4 Test Result

EUT:	4-in-1 Wireless Charger	Model Name:	W405
Test Mode:	Mode 3	Phase :	L
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	1.131000	31.72	10.07	41.79	56.00	-14.21	QP
2	1.131000	28.39	10.07	38.46	46.00	-7.54	AVG
3	1.382900	31.58	10.05	41.63	56.00	-14.37	QP
4	1.382900	27.72	10.05	37.77	46.00	-8.23	AVG
5	2.382000	33.54	9.96	43.50	56.00	-12.50	QP
6	2.382000	29.36	9.96	39.32	46.00	-6.68	AVG
7	2.634000	32.61	9.95	42.56	56.00	-13.44	QP
8	2.634000	29.36	9.95	39.31	46.00	-6.69	AVG
9	2.881500	33.64	9.93	43.57	56.00	-12.43	QP
10 *	2.881500	30.13	9.93	40.06	46.00	-5.94	AVG
11	3.133500	33.42	9.92	43.34	56.00	-12.66	QP
12	3.133500	28.07	9.92	37.99	46.00	-8.01	AVG

EUT:	4-in-1 Wireless Charger	Model Name:	W405
Test Mode:	Mode 3	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.874500	31.63	10.06	41.69	56.00	-14.31	QP
2	0.874500	27.93	10.06	37.99	46.00	-8.01	AVG
3	1.126500	34.13	10.07	44.20	56.00	-11.80	QP
4	1.126500	27.86	10.07	37.93	46.00	-8.07	AVG
5	1.374000	30.20	10.05	40.25	56.00	-15.75	QP
6	1.374000	27.61	10.05	37.66	46.00	-8.34	AVG
7	2.116500	32.01	10.00	42.01	56.00	-13.99	QP
8	2.116500	28.03	10.00	38.03	46.00	-7.97	AVG
9	2.368500	32.74	9.97	42.71	56.00	-13.29	QP
10	2.368500	29.17	9.97	39.14	46.00	-6.86	AVG
11	2.616000	34.53	9.96	44.49	56.00	-11.51	QP
12 *	2.616000	29.94	9.96	39.90	46.00	-6.10	AVG

5.3 Radiated Emission

5.3.1 Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.3.2 Test Procedures


- a) The radiated emission tests were performed in the 3 meters.
- b) The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) If the peak mode measured value compliance with and lower than quasi peak mode limit, the EUT shall be deemed to meet QP limits and then no additional QP mode measurement performed.
- e) If the peak mode measured value compliance with and lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.
- f) For the actual test configuration, please refer to the related item – EUT test photos.

5.3.3 Test Setup

Radiated Emission Test-Up Frequency Below 30MHz




Radiated Emission Test-Up Frequency 30MHz~1GHz



5.3.4 Test Result

Frequency range (9kHz – 30MHz)


EUT:	4-in-1 Wireless Charger	Model Name:	W405
Test Mode:	Mode 1	Phase :	Coaxial
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1490	60.90	19.24	80.14	104.16	-24.02	QP
2	0.1724	56.42	19.26	75.68	102.89	-27.21	QP
3	0.3272	43.98	19.29	63.27	97.31	-34.04	QP
4	0.3756	28.54	19.29	47.83	96.11	-48.28	QP
5	0.4418	38.53	19.31	57.84	94.70	-36.86	QP
6 *	0.5196	35.11	19.34	54.45	73.29	-18.84	QP


Frequency range (30MHz – 1GHz)

EUT:	4-in-1 Wireless Charger	Model Name:	W405
Test Mode:	Mode 1	Phase :	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	32.1795	50.44	-15.41	35.03	40.00	-4.97	QP
2 !	44.1202	50.95	-14.21	36.74	40.00	-3.26	QP
3 !	46.8303	50.77	-14.33	36.44	40.00	-3.56	QP
4 !	49.0145	50.42	-14.42	36.00	40.00	-4.00	QP
5 *	87.4177	56.03	-19.13	36.90	40.00	-3.10	QP
6 !	158.6677	51.87	-13.67	38.20	43.50	-5.30	QP

EUT:	4-in-1 Wireless Charger	Model Name:	W405
Test Mode:	Mode 1	Phase :	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	76.7808	49.41	-18.01	31.40	40.00	-8.60	QP
2	87.4177	50.75	-19.13	31.62	40.00	-8.38	QP
3 *	153.7385	52.99	-13.80	39.19	43.50	-4.31	QP
4 !	157.5588	51.90	-13.70	38.20	43.50	-5.30	QP
5 !	167.2368	52.95	-14.19	38.76	43.50	-4.74	QP
6	186.4409	52.44	-15.74	36.70	43.50	-6.80	QP

5.4 Occupied Bandwidth

5.4.1 Test method

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW \geq 1% of the 20 dB bandwidth

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth and 99% occupied bandwidth of the emission.

5.4.2 Test result


Frequency (kHz)	20dB emission bandwidth (Hz)
151.34	794.20

Phone 1 Test plots as below:




Frequency (kHz)	20dB emission bandwidth (Hz)
152.44	889.10

Phone 2 Test plots as below:




Frequency (kHz)	20dB emission bandwidth (Hz)
178.33	804.20

Air pods Test plots as below:




Frequency (kHz)	20dB emission bandwidth (Hz)
326.02	884.10

Watch Test plots as below:




6 Photographs of the Test Setup


Radiated Emission Below 30MHz



Radiated Emission Above 30MHz



Conducted emission



7 Photographs of the EUT

Photo 1




Photo 2



Photo 3




Photo 4



Photo 5




Photo 6



Photo 7




Photo 8




Photo 9





Photo 10



Photo 11



***** END OF REPORT *****