

RF Exposure Evaluation Report

Report Reference No.	MTEB23060069-H
FCC ID	2BBGK-MATE
Compiled by (position+printed name+signature)...	File administrators Alisa Luo <i>Alisa</i>
Supervised by (position+printed name+signature)...	Test Engineer Sunny Deng <i>Sunny Deng</i>
Approved by (position+printed name+signature)...	Manager Yvette Zhou <i>Yvette</i>
Date of issue.....	Jun.07,2023
Representative Laboratory Name ..	Shenzhen Most Technology Service Co., Ltd.
Address	No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.
Applicant's name	Shenzhen Xincheng Times Technology Co.,Ltd
Address	104-105, Block C, Donghai Wang Building, No. 369 Bulong Road, Ma'antang Community, Bantian Street, Longgang District, Shenzhen
Test specification/ Standard	47 CFR Part 1.1307 47 CFR Part 2.1093
TRF Originator	Shenzhen Most Technology Service Co., Ltd.
Shenzhen Most Technology Service Co., Ltd. All rights reserved.	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test item description	ELECTRIC SCOOTER
Trade Mark	N/A
Model/Type reference.....	Mate
Listed Models	T4, iX3,iX4,M2
Modulation Type	GFSK
Operation Frequency.....	From 2402MHz to 2480MHz
Hardware Version.....	M0-2BLE8-V1.95-20221231
Software Version	T80.5.9 (13F0)
Rating	1:DC 48V (by Battery) 2:DC 54.6V (by Adapter)
Result.....	PASS



TEST REPORT

Equipment under Test : ELECTRIC SCOOTER

Model /Type : Mate

Listed Models : T4, iX3,iX4,M2

Remark : Difference in model names

Applicant : **Shenzhen Xincheng Times Technology Co.,Ltd**

Address : 104-105, Block C, Donghai Wang Building, No. 369 Bulong Road,
Ma'antang Community, Bantian Street, Longgang District,
Shenzhen

Manufacturer : **Shenzhen Xincheng Times Technology Co.,Ltd**

Address : 104-105, Block C, Donghai Wang Building, No. 369 Bulong Road,
Ma'antang Community, Bantian Street, Longgang District,
Shenzhen

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2023.06.07	Initial Issue	Alisa Luo

2. SAR Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \left[\sqrt{f(\text{GHz})} \right]$$
$$\leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

2.1.3 EUT RF Exposure

Measurement Data

BLE

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-2.427	-2.427 ± 1	-1.427
Middle(2440MHz)	-2.517	-2.517 ± 1	-1.517
Highest(2480MHz)	-2.293	-2.293 ± 1	-1.293

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold	SAR Test Exclusion
		(dBm)	(mW)			
Highest(2480MHz)	-2.293	-1.293	0.74	0.24	3.0	Yes

.....THE END OF REPORT.....